

Release Notes**Project Name:** PESALINK ISO 20022

Project Details

Project Name/ Jira ID	PR52
Application Name	Interbank Inbound Microservice
Project Type	Software Development
Project Version No. (If any)	release_prod_1.0
Project Start Date	15/03/2021
Project End Date	12/09/2022
VSS Tagged Version	prod_1.0
Planned Date of Release	15/09/2022
Actual Date of Release	15/09/2022
Name of Releaser	Ronald K. Cheruiyot
Mode of Delivery & Delivery Location	tar.gz & sql files
Prepared By	Ronald K. Cheruiyot

Brief Background of the Project/Release delivery

This is a release of the Pesalink inbound service that is a microservice version of the current monolithic ISO 8583 application. It works in conjunction with other microservices namely: the transaction processor and outbound microservice as part of the new ISO 20022 Pesalink ecosystem.

Delivery Details

The updated application is available via a tar.gz file named 'inbound.tar.gz'. In addition, an SQL script named 'inbound_ms_prod_1.3.sql' is provided together with the application. The SQL file must be run against the inbound ms database.

New Features in This Release

The system has been programmed to

1. Receive and process interbank account verification requests and respond asynchronously in ISO 20022 format
2. Receive and process interbank account credit transfer requests and respond asynchronously in ISO 20022 format
3. Receive interbank account verification responses and forward them to interbank outbound microservice
4. Receive interbank credit transfer responses and forward them to interbank outbound microservice

Version, Build & Deployment

Previous versions will be maintained under Azure Git Repository (Version Control Repository). The new version will be on branch name: release_prod_1.0.

Production-ready source code will be in the specified release version.

Deployment Instructions

Deploy the Archive File

1. Log in to the production server and navigate to the directory:

```
/u01/gag/plv2
```

2. Copy the tar file *inbound.tar.gz* provided to the current directory
3. Run the following command to unpack the tar file:

```
tar -xvf inbound.tar.gz
```

4. A new folder named *inbound* will be created
5. Navigate to the directory location */u01/gag/plv2/inbound/bin*

Update the keystore

1. Copy the .p12 keystores: *EQUITYBANK_transport.p12* and *EQUITYBANK_seal.p12* in to the directory ***/bin/config/certs*
2. In the ***/bin* directory, run the following commands to update the keystore:

```
jar -uf in-bound-ms-0.0.1-SNAPSHOT.jar config/certs/EQUITYBANK_transport.p12
```

```
jar -uf in-bound-ms-0.0.1-SNAPSHOT.jar config/certs/EQUITYBANK_transport.p12
```

where *EQUITYBANK_seal.p12* is the production keystore.

Edit the bootstrap.yml and bootstrap-prod.yml files

Locate *bootstrap.yml* and *bootstrap-prod.yml* files in the directory: ***/bin/config* directory

1. Edit the config property *cloud.config.uri*

```
jhipster:
  registry:
    password: admin

spring:
  application:
    name: inBoundMS
  profiles:
    # The commented value for 'active' can be replaced with valid Spring profiles to load.
    # Otherwise, it will be filled in by maven when building the JAR file
    # Either way, it can be overridden by '--spring.profiles.active' value passed in the commandline or '-Dspring.profiles.active' set in 'JAVA_OPTS'
    active: #spring.profiles.active#
  cloud:
    config:
      fail-fast: false # if not in "prod" profile, do not force to use Spring Cloud Config
      uri: http://admin:${jhipster.registry.password}@{prod-registry-ip}:8761/config
      # name of the config server's property source (file.yml) that we want to use
      name: inBoundMS
      profile: prod # profile(s) of the property source
      label: main # toggle to switch to a different version of the configuration as stored in git
      # it can be set to any label, branch or commit of the configuration source Git repository
```

uri: [http://admin:\\${jhipster.registry.password}@{prod-registry-ip}:8761/config](http://admin:${jhipster.registry.password}@{prod-registry-ip}:8761/config)

update the value [{prod-registry-ip}](#) with the correct value of the registry microservice.

Edit the application-prod.yml file

Locate the *application-prod.yml* file in the directory: ***/bin/config* directory

1. Update the config property *eureka.client.service-url.defaultZone*

```
com.equitybank.payments.interbank.processor: INFO

eureka:
  instance:
    prefer-ip-address: true
  client:
    service-url:
      defaultZone: http://admin:${jhipster.registry.password}@{prod-registry-ip}:8763/eureka/
#   defaultZone: http://admin:${jhipster.registry.password}@api-interbank-registry:8763/eureka/
```

uri: [http://admin:\\${jhipster.registry.password}@{prod-registry-ip}:8761/config](http://admin:${jhipster.registry.password}@{prod-registry-ip}:8761/config)

update the value [{prod-registry-ip}](#) with the correct value of the registry microservice.

2. Edit database configurations:

```
spring:
  datasource:
    driver-class-name: com.microsoft.sqlserver.jdbc.SQLServerDriver
    # type: com.zaxxer.hikari.HikariDataSource
    url: jdbc:sqlserver://{prod-db-host}:{port};database=inBoundMS;encrypt=true;trustServerCertificate=false;hostNameInCertificate=*.database.windows.ne
    username: {prod-db-username}
    password: {prod-db-password}
  hikari:
    poolName: Hikari
    auto-commit: false
```

- a. update the value [{prod-db-host}](#) with the correct value of the production database IP

- b. update the value `{prod-db-username}` with the correct value of the production database username
- c. update the value `{prod-db-password}` with the correct value of the production database password

3. Edit keystore configurations:

```
encrypt:
  key-store:
    alias: {prod-keystore-alias}
    location: config/certs/{prod-keystore-name}
    password: {prod-keystore-password}
```

- a. update the value `{prod-keystore-alias}` with the correct value of the production keystore alias
- b. update the value `{prod-keystore-name}` with the correct value of the production keystore file name
- c. update the value `{prod-keystore-password}` with the correct value of the production keystore password

Update the yml files

In the `**/bin` directory, run the following command to update the .yml files

- a. `jar -uf in-bound-ms-0.0.1-SNAPSHOT.jar config/bootstrap.yml`
- b. `jar -uf in-bound-ms-0.0.1-SNAPSHOT.jar config/bootstrap-prod.yml`
- c. `jar -uf in-bound-ms-0.0.1-SNAPSHOT.jar config/application.yml`
- d. `jar -uf in-bound-ms-0.0.1-SNAPSHOT.jar config/application-prod.yml`

Update the database

An SQL script named 'inbound_i_release_prod_1.3.sql' is provided. Run this script on the production instance of Inbound MS Azure MSSQL database and report any errors encountered.
Commit the changes.

Start the service

In the `**/bin` directory, run the following command to start the service:

```
./pl2-inbound start
```