

Release Notes**Project Name:** PESALINK ISO 20022

Project Details

Project Name/ Jira ID	PR52
Application Name	Interbank Transaction Processor Microservice
Project Type	Software Development
Project Version No. (If any)	release_prod_1.0
Project Start Date	15/03/2021
Project End Date	12/09/2022
VSS Tagged Version	prod_1.0
Planned Date of Release	15/09/2022
Actual Date of Release	15/09/2022
Name of Releaser	Ronald K. Cheruiyot
Mode of Delivery & Delivery Location	tar.gz & sql files
Prepared By	Ronald K. Cheruiyot

Brief Background of the Project/Release delivery

This is a release of the Pesalink tran-processor service that is a microservice version of the current monolithic ISO 8583 application. It works in conjunction with other microservices namely: the transaction processor and outbound microservice as part of the new ISO 20022 Pesalink ecosystem.

Delivery Details

The updated application is available via a tar.gz file named 'tran-processor.tar.gz'. In addition, an SQL script named 'tran-processor_ms_prod_1.3.sql' is provided together with the application. The SQL file must be run against the tran-processor ms database.

New Features in This Release

The system has been programmed to

1. Receive and process interbank account verification requests and respond synchronously to both tran-processor and Outbound Pesalink microservices
2. Receive and process interbank account credit transfer requests and respond synchronously to both tran-processor and Outbound Pesalink microservices

Version, Build & Deployment

Previous versions will be maintained under Azure Git Repository (Version Control Repository). The new version will be on branch name: release_prod_1.0.

Production-ready source code will be in the specified release version.

Deployment Instructions

Deploy the Archive File

1. Log in to the production server and navigate to the directory:

```
/u01/gag/plv2
```

2. Copy the tar file *tran-processor.tar.gz* provided to the current directory
3. Run the following command to unpack the tar file:

```
tar -xvf tran-processor.tar.gz
```

4. A new folder named *tran-processor* will be created
5. Navigate to the directory location */u01/gag/plv2/tran-processor/bin*

Edit the bootstrap.yml and bootstrap-prod.yml files

Locate *bootstrap.yml* and *bootstrap-prod.yml* files in the directory: ***/bin/config* directory

1. Edit the config property *cloud.config.uri*

```
jhipster:
  registry:
    password: admin

spring:
  application:
    name: inBoundMS
  profiles:
    # The commented value for 'active' can be replaced with valid Spring profiles to load.
    # Otherwise, it will be filled in by maven when building the JAR file
    # Either way, it can be overridden by '--spring.profiles.active' value passed in the commandline or '-Dspring.profiles.active' set in 'JAVA_OPTS'
    active: #spring.profiles.active
  cloud:
    config:
      fail-fast: false # if not in "prod" profile, do not force to use Spring Cloud Config
      uri: http://admin:${jhipster.registry.password}@{prod-registry-ip}:8761/config
      # name of the config server's property source (file.yml) that we want to use
      name: inBoundMS
      profile: prod # profile(s) of the property source
      label: main # toggle to switch to a different version of the configuration as stored in git
      # it can be set to any label, branch or commit of the configuration source Git repository
```

uri: [http://admin:\\${jhipster.registry.password}@{prod-registry-ip}:8761/config](http://admin:${jhipster.registry.password}@{prod-registry-ip}:8761/config)

update the value [{prod-registry-ip}](#) with the correct value of the registry microservice.

Edit the application-prod.yml file

Locate the *application-prod.yml* file in the directory: ***/bin/config* directory

1. Update the config property *eureka.client.service-url.defaultZone*

```
com.equitybank.payments.interbank.processor: INFO

eureka:
  instance:
    prefer-ip-address: true
  client:
    service-url:
      defaultZone: http://admin:${jhipster.registry.password}@{prod-registry-ip}:8763/eureka/
#   defaultZone: http://admin:${jhipster.registry.password}@api-interbank-registry:8763/eureka/
```

uri: [http://admin:\\${jhipster.registry.password}@{prod-registry-ip}:8761/config](http://admin:${jhipster.registry.password}@{prod-registry-ip}:8761/config)

update the value [{prod-registry-ip}](#) with the correct value of the registry microservice.

2. Edit database configurations:

```
spring:
  datasource:
    driver-class-name: com.microsoft.sqlserver.jdbc.SQLServerDriver
    # type: com.zaxxer.hikari.HikariDataSource
    url: jdbc:sqlserver://{prod-db-host}:{port};database=inBoundMS;encrypt=true;trustServerCertificate=false;hostNameInCertificate=*.database.windows.ne
    username: {prod-db-username}
    password: {prod-db-password}
  hikari:
    poolName: Hikari
    auto-commit: false
```

- a. update the value [{prod-db-host}](#) with the correct value of the production database IP
- b. update the value [{prod-db-username}](#) with the correct value of the production database username
- c. update the value [{prod-db-password}](#) with the correct value of the production database password

3. Edit keystore configurations:

```
encrypt:
  key-store:
    alias: {prod-keystore-alias}
    location: config/certs/{prod-keystore-name}
    password: {prod-keystore-password}
```

- a. update the value `{prod-keystore-alias}` with the correct value of the production keystore alias
- b. update the value `{prod-keystore-name}` with the correct value of the production keystore file name
- c. update the value `{prod-keystore-password}` with the correct value of the production keystore password

Update the yml files

In the `**/bin` directory, run the following command to update the .yml files

- a. `jar -uf tran-processor-ms-0.0.1-SNAPSHOT.jar config/bootstrap.yml`
- b. `jar -uf tran-processor-ms-0.0.1-SNAPSHOT.jar config/bootstrap-prod.yml`
- c. `jar -uf tran-processor-ms-0.0.1-SNAPSHOT.jar config/application.yml`
- d. `jar -uf tran-processor-ms-0.0.1-SNAPSHOT.jar config/application-prod.yml`

Update the ISO 8583 JPOS Multiplexer XML Files

1. Navigate to the `/u01/gag/plv2/tran-processor` folder
2. Open the `ke_channel.xml` file
3. Update the host and the port properties with the production Finacle CBC ISO8583 IP and port

```
<property name="host" value="*.*.*.*" />
<property name="port" value="45000" />
```

Update the database

An SQL script named 'tran_processor_release_prod_1.3.sql' is provided. Run this script on the production instance of the tran-processor MS Azure MSSQL database and report any errors encountered. Commit the changes.

Start the service

In the `**/bin` directory, run the following command to start the service:

```
./pl2-tran-processor start
```

