



THUNES API Documentation v2.0

Revision History

Date	Version	Author	Comments
16-09-2025	v2.0	Kennedy Gatimu	Initial document creation

Introduction	5
Discovery APIs	6
1.0 List of Services Per Country API	6
Base Endpoint	6
Request Field Description	6
Example 1: Request Example	6
Response Field Description	7
Success Response	7
Failure Response.....	7
2.0 List of All Payers API	8
Base Endpoint	8
Request Field Description	8
Behaviour Cases	8
Example Request	9
Response Fields Description	9
Success Response Body	10
Failure Response Body.....	13
3.0 Get Specific Payer Details API	13
Base Endpoint	13
Request Field Description	13
Request Body	14
Response Field Description	14
Success Response Body	15
Failure Response Body.....	17
4.0 Get Payer Rates and Transaction Limits	18
Base Endpoint	18
Request Field Description	18
Sample Request Body	18
Response Field Description	19
Sample Response - Success	19
Sample Response – Failure	20
5.0 Get List of Countries	20
Base Endpoint	20
Request Field Description	20
Sample Request Body	21
Response Field Description	21
Sample Response – Success.....	21
Sample Response – Failure	22
6.0 BIC Lookup Service	23
Base Endpoint	23
Request Field Description	23
Request Body	23
Response Field Description	24
Sample Response – Success.....	24
Sample Response – Failure	24
Credit Party APIs	25

1.0 Credit Party Information	25
Base Endpoint	25
Request Body	26
Response Field Description	26
Sample Response Example — Beneficiary (C2C / B2C)	27
Sample Response Example — Beneficiary (C2B / B2B)	28
Sample Response – Failure	28
2.0 Credit Party Verification.....	29
Base Endpoint	29
Request Body – C2C	30
Request Body – C2B	30
Response Field Description	31
Sample Response – Failure	31
Thunes Static Data APIs.....	32
1.0 Bank Account Type.....	32
Base Endpoint	32
Request Field Description	32
Example 1: Request Example.....	32
Response Field Description	33
Success Response	33
Failure Response.....	33
2.0 ID Type.....	34
Base Endpoint	34
Request Field Description	34
Example 1: Request Example.....	34
Response Field Description	35
Success Response	35
Failure Response.....	36
3.0 Purpose of Payments.....	37
Base Endpoint	37
Request Field Description	37
Example 1: Request Example.....	37
Response Field Description	38
Success Response – China Corridor	38
Success Response – Other Corridors.....	39
Failure Response.....	41
Authentication	42
Key and Certificate Setup	42
Signature Validation	42
Implementation.....	43
Canonical Text Construction	44

Introduction

This document provides details for integrating with the Thunes REST API. The service exposes the following endpoint categories:

Discovery APIs

- List of services per country
- List of all payers
- All payers for the provided serviceId
- All payers for the provided serviceId and countryCode
- All payers for the provided serviceId, countryCode, and currency
- Get specific payer details
- Get payer rates and transaction limits
- List of countries
- Bic lookup service

Credit Party APIs

- Credit party information
- Credit Party Verification

Connectivity

Assumption is made that the channel has connectivity to:

- i. GAG **UAT** server: 10.11.6.110 https port 8443
- ii. GAG **prod** server: <Prod IP> https port 8443

Discovery APIs

1.0 List of Services Per Country API

Retrieve the list of services supported for a given country.

Base Endpoint

POST /thunes/v2/outbound/money-transfer/services

Request Field Description

Field	Type	Required	Description
receiver.countryCode	String	Yes	3-letter ISO country code (e.g., GHA, KEN).
channelInfo.rrn	String	Yes	12-character unique transaction reference number.
channelInfo.bankId	String	Yes	Identifier of the originating bank.
channelInfo.channelId	String	Yes	Identifier of the originating channel (e.g., OMNI).
channelInfo.sourceSystemId	String	Yes	Identifier of the source system invoking the API.
signature	String	Yes	Digital signature string (base64-encoded, max length 1000 characters).

Example 1: Request Example

```
{
  "receiver": {
    "countryCode": "GHA"
  },
  "channelInfo": {
    "rrn": "111996657000",
    "bankId": "54",
    "channelId": "OMNI",
    "sourceSystemId": "ONMI"
  },
  "signature": "
/A2VEUvM14LEfn2jMzij1DWPzidsCkA6q7CYPPHLFIBVpevEpTNp9WTm80RWYr8oZx5jT8i4FAFMnN58kXd1/Q
HfjgMxvfkP+T3XmFg2Kv5PdF7r0F0XvsaY9u6hfy2NbnQwaSMg=="
}
```

Response Field Description

Field	Type	Description
thunesResponse[].id	Integer	Unique identifier of the service.
thunesResponse[].name	String	Name of the service (e.g., MobileWallet, BankAccount, or CashPickup).
channelStatusInfo.status	String	Status of the request (e.g., OK, FAILURE).
channelStatusInfo.code	String	Response code (e.g., 000 or 01).
channelStatusInfo.description	String	Description of the response status.

Success Response

```
{
  "thunesResponse": [
    {
      "id": 1,
      "name": "MobileWallet"
    },
    {
      "id": 2,
      "name": "BankAccount"
    },
    {
      "id": 3,
      "name": "CashPickup"
    }
  ],
  "channelStatusInfo": {
    "status": "OK",
    "code": "000",
    "description": "COMPLETED_SUCCESSFULLY."
  }
}
```

Failure Response

```
{
  "channelStatusInfo": {
    "status": "FAILURE",
    "code": "01",
    "description": "Failed: HTTP call to the url was unsuccessful. Connection
refused"
  }
}
```

2.0 List of All Payers API

Retrieve the list of available payers from Thunes. The response varies depending on which fields are supplied in the request (serviceld, countryCode, currency).

Base Endpoint

POST /thunes/v2/outbound/money-transfer/payers

Request Field Description

Field	Type	Required	Description
receiver.serviceld	String	Optional	Service ID (e.g., 1 = Mobile Wallet, 2 = Bank Account).
receiver.countryCode	String	Optional	3-letter ISO country code (e.g., KEN, UGA).
receiver.currency	String	Optional	Currency code (ISO 4217, e.g., KES, TZS).
channelInfo.rrn	String	Yes	12-character unique transaction reference.
channelInfo.bankId	String	Yes	Identifier of the originating bank.
channelInfo.channelId	String	Yes	Identifier of the originating channel (e.g., OMNI).
channelInfo.sourceSystemId	String	Yes	Identifier of the system invoking the API.
signature	String	Yes	Digital signature string (base64-encoded, max length 1000 characters).

Behaviour Cases

- **Case a:** serviceld + countryCode + currency
Returns payers matching all three filters.
- **Case b:** countryCode + currency
Returns all payers in the given country with the specified currency.
- **Case c:** serviceld + countryCode
Returns payers in the country filtered by service (currency omitted).
- **Case d:** countryCode only
Returns all payers for that country (across services/currencies).
- **Case e:** none provided
Returns the global list of all payers (multi-country).

Example Request

```
{
  "receiver": {
    "serviceId": "1",
    "countryCode": "KEN",
    "currency": "KES"
  },
  "channelInfo": {
    "rrn": "111996657000",
    "bankId": "54",
    "channelId": "OMNI",
    "sourceSystemId": "ONMI"
  },
  "signature":
  "jZzbRrd8Ycwg8xClr0dddkZchjXhNtgf6FA9gMFtCMF720S8rZPiVgtc0nPBuNXa4wLYvK+eLzapEDbxUvA+
  oiyWtPZYM+fqI/ /QHfjgMxvfKp+T3XmFg2Kv5PdF7r0F0XvsaY9u6hfy2NbnQwaSMg=="
}
```

Response Fields Description

Field	Type	Description
thunesResponse[].id	Integer	Unique identifier of the payer.
thunesResponse[].name	String	Name of the payer (e.g., M-Pesa, DIB Bank).
thunesResponse[].countryIsoCode	String	ISO country code of the payer.
thunesResponse[].currency	String	Currency supported by the payer.
thunesResponse[].service.id	Integer	Service ID (1 = Mobile Wallet, 2 = Bank Account, etc.).
thunesResponse[].service.name	String	Service type (MobileWallet, BankAccount, etc.).
thunesResponse[].transactionTypes	Object	Transaction type details (C2C, C2B, B2C, B2B).
transactionTypes*.creditPartyIdentifiersAccepted	Array	Identifiers accepted (e.g., msisdn, iban, bankAccountNumber).
transactionTypes*.maximumTransactionAmount	String	Maximum transaction amount allowed.
transactionTypes*.minimumTransactionAmount	String	Minimum transaction amount allowed.
transactionTypes*.requiredSendingEntityFields	Array	Fields required from sender (e.g., lastname, firstname, ID details).
transactionTypes*.requiredReceivingEntityFields	Array	Fields required from receiver (e.g., lastname, firstname).

channelStatusInfo.status	String	Status of the request (OK, FAILURE).
channelStatusInfo.code	String	Response code (e.g., 000 for success).
channelStatusInfo.description	String	Human-readable description of the status.

Success Response Body

```
{
  "thunesResponse": [
    {
      "countryIsoCode": "KEN",
      "currency": "KES",
      "id": 369,
      "increment": 1,
      "name": "M-Pesa",
      "precision": 0,
      "service": {
        "id": 1,
        "name": "MobileWallet"
      },
      "transactionTypes": {
        "C2C": {
          "creditPartyIdentifiersAccepted": [
            [
              "msisdn"
            ]
          ],
          "creditPartyInformation": {
            "creditPartyIdentifiersAccepted": [
              [
                "msisdn"
              ]
            ]
          },
          "creditPartyVerification": {
            "creditPartyIdentifiersAccepted": [
              [
                "msisdn"
              ]
            ],
            "requiredReceivingEntityFields": [
              []
            ]
          },
          "maximumTransactionAmount": "250000.00000000",

```

```

        "minimumTransactionAmount": "10.00000000",
        "purposeOfRemittanceValuesAccepted": [],
        "requiredDocuments": [
            []
        ],
        "requiredReceivingEntityFields": [
            [
                "lastname"
            ]
        ],
        "requiredSendingEntityFields": [
            [
                "lastname",
                "firstname"
            ],
            [
                "lastname",
                "firstname",
                "nationality_country_iso_code",
                "date_of_birth",
                "msisdn",
                "id_type",
                "id_number"
            ]
        ]
    }
},
{
    "countryIsoCode": "KEN",
    "currency": "KES",
    "id": 1466,
    "increment": 1,
    "name": "Airtel Money",
    "precision": 0,
    "service": {
        "id": 1,
        "name": "MobileWallet"
    },
    "transactionTypes": {
        "C2C": {
            "creditPartyIdentifiersAccepted": [
                [
                    "msisdn"
                ]
            ],
            "creditPartyInformation": {
                "creditPartyIdentifiersAccepted": [

```

```

        [
            "msisdn"
        ]
    ],
    "creditPartyVerification": {
        "creditPartyIdentifiersAccepted": [
            [
                "msisdn"
            ]
        ],
        "requiredReceivingEntityFields": [
            []
        ]
    },
    "maximumTransactionAmount": "250000.00000000",
    "minimumTransactionAmount": "100.00000000",
    "purposeOfRemittanceValuesAccepted": [],
    "requiredDocuments": [
        []
    ],
    "requiredReceivingEntityFields": [
        [
            "lastname"
        ]
    ],
    "requiredSendingEntityFields": [
        [
            "lastname"
        ]
    ]
    }
}
},
"channelStatusInfo": {
    "status": "OK",
    "code": "000",
    "description": "COMPLETED_SUCCESSFULLY."
}
}

```

Failure Response Body

```
{
  "channelStatusInfo": {
    "status": "FAILURE",
    "code": "01",
    "description": "Internal Error: HTTP call to the url was unsuccessful"
  }
}
```

3.0 Get Specific Payer Details API

Retrieve detailed information about a specific payer, including supported services, transaction types, limits, and required fields.

Base Endpoint

POST /thunes/v2/outbound/money-transfer/payers/details

Request Field Description

Field	Type	Required	Description
receiver.payerId	String	Yes	Numeric identifier of the payer (e.g., 1243).
channelInfo.rrn	String	Yes	12-character unique transaction reference.
channelInfo.bankId	String	Yes	Identifier of the originating bank.
channelInfo.channelId	String	Yes	Identifier of the originating channel (e.g., OMNI, APP).
channelInfo.sourceSystemId	String	Yes	Identifier of the system invoking the API.
signature	String	Yes	Digital signature string (base64-encoded, max length 1000 characters).

Request Body

```
{
  "receiver": {
    "payerId": "1243"
  },
  "channelInfo": {
    "rrn": "111996657000",
    "bankId": "54",
    "channelId": "OMNI",
    "sourceSystemId": "ONMI"
  },
  "signature": "
/A2VEUvM14LEfn2jMzij1DWPzidsCkA6q7CYPPHLFIBVpevEpTNp9WTm80RWYr8oZx5jT8i4FAFMnN58kXd1/Q
HfjgMxvfkP+T3XmFg2Kv5PdF7r0F0XvsaY9u6hfy2NbnQwaSMg=="
}
```

Response Field Description

Field	Type	Description
thunesResponse.id	Integer	Unique identifier of the payer.
thunesResponse.name	String	Name of the payer (e.g., Gcb Bank Ltd).
thunesResponse.countryIsoCode	String	Country ISO code of the payer (e.g., GHA).
thunesResponse.currency	String	Currency supported by the payer (e.g., GHS).
thunesResponse.increment	Number	Increment step for transaction amounts.
thunesResponse.precision	Integer	Decimal precision supported.
thunesResponse.service.id	Integer	Service ID (e.g., 2 = BankAccount).
thunesResponse.service.name	String	Service name (e.g., BankAccount, MobileWallet).
thunesResponse.transactionTypes	Object	Transaction type definitions (C2C, B2B, etc.).
transactionTypes.*.creditPartyIdentifiersAccepted	Array	Accepted identifiers (e.g., bankAccountNumber, iban, msisdn).

transactionTypes.*.maximumTransactionAmount	Number	Maximum allowed transaction amount.
transactionTypes.*.minimumTransactionAmount	Number	Minimum allowed transaction amount.
transactionTypes.*.requiredDocuments	Array	Required documents (e.g., invoice).
transactionTypes.*.requiredSendingEntityFields	Array	Fields required from sender (e.g., firstname, lastname, country code).
transactionTypes.*.requiredReceivingEntityFields	Array	Fields required from receiver (e.g., firstname, lastname, registered name).
transactionTypes.*.purposeOfRemittanceValuesAccepted	Array	List of accepted purpose-of-remittance codes.
channelStatusInfo.status	String	Status of the request (OK, FAILURE).
channelStatusInfo.code	String	Response code (e.g., 000 for success).
channelStatusInfo.description	String	Human-readable description of the status.

Success Response Body

```
{
  "thunesResponse": {
    "countryIsoCode": "GHA",
    "currency": "GHS",
    "id": 1243,
    "increment": 0.01,
    "name": "Gcb Bank Ltd",
    "precision": 2,
    "service": {
      "id": 2,
      "name": "BankAccount"
    },
    "transactionTypes": {
      "C2C": {
        "creditPartyIdentifiersAccepted": [
          "bank_account_number"
        ]
      }
    }
  }
}
```

```
    ],
    "creditPartyInformation": {
      "creditPartyIdentifiersAccepted": [
        [
          "bank_account_number"
        ]
      ]
    },
    "creditPartyVerification": {
      "creditPartyIdentifiersAccepted": [
        [
          "bank_account_number"
        ]
      ],
      "requiredReceivingEntityFields": [
        []
      ]
    },
    "maximumTransactionAmount": 100000,
    "minimumTransactionAmount": 0,
    "requiredDocuments": [
      []
    ],
    "requiredReceivingEntityFields": [
      [
        "lastname",
        "firstname"
      ]
    ],
    "requiredSendingEntityFields": [
      [
        "lastname",
        "firstname",
        "country_iso_code"
      ]
    ],
    "purposeOfRemittanceValuesAccepted": []
  },
  "B2B": {
    "creditPartyIdentifiersAccepted": [
      [
        "bank_account_number"
      ]
    ],
    "creditPartyInformation": {
      "creditPartyIdentifiersAccepted": [
        []
      ]
    }
  }
}
```

```

    },
    "creditPartyVerification": {
      "creditPartyIdentifiersAccepted": [
        []
      ],
      "requiredReceivingEntityFields": [
        []
      ]
    },
    "maximumTransactionAmount": 100000,
    "minimumTransactionAmount": 0,
    "requiredDocuments": [
      [
        "invoice"
      ]
    ],
    "requiredReceivingEntityFields": [
      [
        "registered_name"
      ]
    ],
    "requiredSendingEntityFields": [
      [
        "registered_name",
        "country_iso_code"
      ]
    ],
    "purposeOfRemittanceValuesAccepted": []
  }
}
},
"channelStatusInfo": {
  "status": "OK",
  "code": "000",
  "description": "COMPLETED_SUCCESSFULLY."
}
}

```

Failure Response Body

```

{
  "channelStatusInfo": {
    "status": "FAILURE",
    "code": "01",
    "description": "HTTP call to the url was unsuccessful. Connection refused"
  }
}

```

4.0 Get Payer Rates and Transaction Limits

Retrieve the FX rates and transaction limits for a specific payer. This allows you to determine applicable conversion rates (**wholesale rates**) and min/max thresholds for supported transaction types.

Base Endpoint

POST /thunes/v2/outbound/money-transfer/payers/rates

Request Field Description

Field	Type	Required	Description
receiver.payerId	String	Yes	Numeric identifier of the payer (e.g., 1243).
channelInfo.rrn	String	Yes	12-character unique transaction reference.
channelInfo.bankId	String	Yes	Identifier of the originating bank.
channelInfo.channelId	String	Yes	Identifier of the originating channel (e.g., OMNI, APP).
channelInfo.sourceSystemId	String	Yes	Identifier of the system invoking the API.
signature	String	Yes	Digital signature string (base64-encoded, max length 1000 characters).

Sample Request Body

```
{
  "receiver": {
    "payerId": "1243"
  },
  "channelInfo": {
    "rrn": "111996657000",
    "bankId": "54",
    "channelId": "OMNI",
    "sourceSystemId": "ONMI"
  },
  "signature": "
/ZCL7Rmw8u1m/A2VEUvM14LEfn2jMzij1DWPzidsCkA6q7CYPPHLFIBVpevEpTNp9WTm80RWYr8oZx5jT8i4FA
FMnN58kXd1/QHfjgMxvfkP+T3XmFg2Kv5PdF7r0F0XvsaY9u6hfy2NbnQwaSMg=="
}
```

Response Field Description

Field	Type	Description
thunesResponse.destinationCurrency	String	Destination currency code (e.g., GHS).
thunesResponse.rates	Object	Exchange rates per transaction type and source currency.
rates.<txnType>	Object	Transaction type (e.g., C2C, B2B).
rates.<txnType>.<sourceCurrency>	Array	Array of rate objects keyed by source currency (e.g., USD).
rates.<txnType>.<sourceCurrency>[].sourceAmountMin	Number	Minimum source amount applicable for the given rate.
rates.<txnType>.<sourceCurrency>[].wholesaleFxRate	Number	FX conversion rate applied to the transaction.
channelStatusInfo.status	String	Status of the request (OK, FAILED).
channelStatusInfo.code	String	Response code (e.g., 000 for success).
channelStatusInfo.description	String	Human-readable description of the response.

Sample Response - Success

```
{
  "thunesResponse": {
    "destinationCurrency": "GHS",
    "rates": {
      "B2B": {
        "USD": [
          {
            "sourceAmountMin": 0,
            "wholesaleFxRate": 12.1184142225646
          }
        ]
      },
      "C2C": {
        "USD": [
          {
            "sourceAmountMin": 0,
            "wholesaleFxRate": 12.1184142225646
          }
        ]
      }
    }
  }
}
```

```

    },
    "channelStatusInfo": {
      "status": "OK",
      "code": "000",
      "description": "COMPLETED_SUCCESSFULLY."
    }
  }
}

```

Sample Response – Failure

```

{
  "channelStatusInfo": {
    "status": "FAILURE",
    "code": "01",
    "description": "HTTP call to the url was unsuccessful. Connection refused"
  }
}

```

5.0 Get List of Countries

Retrieve the list of countries supported by Thunes for payouts. Each country record includes its ISO code and ISO name.

Base Endpoint

POST /thunes/v2/outbound/money-transfer/countries

Request Field Description

Field	Type	Required	Description
channelInfo.rrn	String	Yes	12-character unique transaction reference.
channelInfo.bankId	String	Yes	Identifier of the originating bank.
channelInfo.channelId	String	Yes	Identifier of the originating channel (e.g., OMNI, APP).
channelInfo.sourceSystemId	String	Yes	Identifier of the system invoking the API.
signature	String	Yes	Digital signature string (base64-encoded, max length 1000 characters).

Sample Request Body

```
{
  "channelInfo": {
    "rrn": "111996657000",
    "bankId": "54",
    "channelId": "OMNI",
    "sourceSystemId": "ONMI"
  },
  "signature":
  "jZzbRrd8Ycwg8xClr0dddKZchjXHnUtgf6FA9gMFtCMF720S8rZPiVgtc0nPBuNXa4WLYvK+elzapEDbxUvA+
/ZCL7Rmw8uIm/A2VEUvM14LEfn2jMzij1DWPzidsCkA6q7CYPPHLFIBVpevEpTNp9WTm80RWYr8oZx5jT8i4FA
FMnN58kXd1/QHfjgMxvfKp+T3XmFg2Kv5PdF7r0F0XvsaY9u6hfy2NbnQwaSMg=="
}
```

Response Field Description

Field	Type	Description
thunesResponse[].isoCode	String	3-letter ISO country code (e.g., KEN, GHA).
thunesResponse[].name	String	Full country name (e.g., Kenya, Ghana).
channelStatusInfo.status	String	Status of the request (OK, FAILURE).
channelStatusInfo.code	String	Response code (e.g., 000 for success).
channelStatusInfo.description	String	Human-readable description of the response.

Sample Response – Success

```
{
  "thunesResponse": [
    {
      "isoCode": "AND",
      "name": "Andorra"
    },
    {
      "isoCode": "ARE",
      "name": "United Arab Emirates"
    },
    {
      "isoCode": "AUT",
      "name": "Austria"
    },
    {
      "isoCode": "BDI",
      "name": "Burundi"
    }
  ]
}
```

```
    },  
    {  
      "isoCode": "FRA",  
      "name": "France"  
    },  
    {  
      "isoCode": "GBR",  
      "name": "United Kingdom of Great Britain and Northern Ireland"  
    },  
  ],  
  "channelStatusInfo": {  
    "status": "OK",  
    "code": "000",  
    "description": "COMPLETED_SUCCESSFULLY."  
  }  
}
```

Sample Response – Failure

```
{  
  "channelStatusInfo": {  
    "status": "FAILURE",  
    "code": "01",  
    "description": "HTTP call to the url was unsuccessful. Connection refused"  
  }  
}
```

6.0 BIC Lookup Service

Look up a payer by its Bank Identifier Code (BIC). This allows mapping a BIC to the corresponding payer ID within the Thunes network.

Base Endpoint

POST /thunes/v2/outbound/money-transfer/lookups/bic

Request Field Description

Field	Type	Required	Description
receiver.bic	String	Yes	Bank Identifier Code (BIC) of the target payer (e.g., EQBLKENAXXX).
channelInfo.rrn	String	Yes	12-character unique transaction reference.
channelInfo.bankId	String	Yes	Identifier of the originating bank.
channelInfo.channelId	String	Yes	Identifier of the originating channel (e.g., OMNI, MOBILE-APP).
channelInfo.sourceSystemId	String	Yes	Identifier of the system invoking the API.
signature	String	Yes	Digital signature string (base64-encoded, max length 1000 characters).

Request Body

```
{
  "receiver": {
    "bic": "EQBLKENAXXX"
  },
  "channelInfo": {
    "rrn": "111996657000",
    "bankId": "54",
    "channelId": "OMNI",
    "sourceSystemId": "ONMI"
  },
  "signature": "
/A2VEUvM14LEfn2jMzij1DWPzidsCkA6q7CYPPLHFBVpevEpTNp9WTm80RWYr8oZx5jT8i4FAFMnN58kXd1/Q
HfjgMxvfkP+T3XmFg2Kv5PdF7r0F0XvsaY9u6hfy2NbnQwaSMg=="
}
```

Response Field Description

Field	Type	Description
thunesResponse[].id	Integer	Unique payer ID mapped to the given BIC.
channelStatusInfo.status	String	Status of the request (OK, FAILURE).
channelStatusInfo.code	String	Response code (e.g., 000 for success).
channelStatusInfo.description	String	Human-readable description of the response.

Sample Response – Success

```
{
  "thunesResponse": [
    {
      "id": 1480
    }
  ],
  "channelStatusInfo": {
    "status": "OK",
    "code": "000",
    "description": "COMPLETED_SUCCESSFULLY."
  }
}
```

Sample Response – Failure

```
{
  "channelStatusInfo": {
    "status": "FAILURE",
    "code": "01",
    "description": "HTTP call to the url was unsuccessful. Connection refused"
  }
}
```

Credit Party APIs

1.0 Credit Party Information

Retrieve information about a specific credit party (beneficiary or business), based on service type (Mobile Wallet, Bank Account, etc.), payer, and transaction type.

- **For C2C / B2C transactions**

Returns a Beneficiary object.

- **For C2B / B2B transactions**

Returns a Receiving Business object.

Base Endpoint

POST /thunes/v2/outbound/money-transfer/credit-party-information

Request Field Description

Field	Type	Required	Description
receiver.serviceld	String	Yes	Service ID (1 = Mobile Wallet, 2 = Bank Account).
receiver.msisdn	String	Optional	Mobile number of beneficiary (required if serviceld = 1).
receiver.bankAccountNumber	String	Optional	Bank account number (required if serviceld = 2).
receiver.businessRegisteredName	String	Optional	Registered business name (for business transactions).
receiver.payerId	String	Yes	Numeric identifier of the payer.
receiver.bic	String	Optional	SWIFT BIC code of the payer bank.
receiver.transactionType	String	Yes	Transaction type (C2C, B2C, C2B, B2B).
channelInfo.rrn	String	Yes	12-character unique transaction reference.
channelInfo.bankId	String	Yes	Identifier of the originating bank.
channelInfo.channelId	String	Yes	Identifier of the originating channel (e.g., OMNI, MOBILE-APP).
channelInfo.sourceSystemId	String	Yes	Identifier of the system invoking the API.
signature	String	Yes	Digital signature string (base64-encoded, max length 1000 characters).

Request Body

```
{
  "receiver": {
    "serviceId": "1",
    "msisdn": "254101010000",
    "bankAccountNumber": "",
    "businessRegisteredName": "",
    "payerId": "9",
    "bic": "",
    "transactionType": "C2C"
  },
  "channelInfo": {
    "rrn": "111996657000",
    "bankId": "54",
    "channelId": "OMNI",
    "sourceSystemId": "ONMI"
  },
  "signature": "
/oSP0Nla3IHq/WREA40ttMPtgbQoCmp/ZCL7Rmw8uLm/A2VEUvM14LEfn2jMzij1DWPzidsCkA6q7CYPPLFIB
VpevEpTNp9WTm80RWYr8oZx5jT8i4FAFMnN58kXd1/QHfjgMxvfkP+T3XmFg2Kv5PdF7r0F0XvsaY9u6hfy2Nb
nQwaSMg=="
}
```

Response Field Description

Field	Type	Description
thunesResponse.id	Integer	Unique identifier of the credit party.
thunesResponse.beneficiary	Object	Present for C2C/B2C transactions. Contains beneficiary details.
beneficiary.firstname	String	Beneficiary's first name.
beneficiary.lastname	String	Beneficiary's last name.
beneficiary.dateOfBirth	String	Beneficiary's date of birth (YYYY-MM-DD).
thunesResponse.receivingBusiness	Object	Present for C2B/B2B transactions. Contains business details.
receivingBusiness.registeredName	String	Official registered name of the business.
receivingBusiness.tradingName	String	Trading name (if different from registered).
receivingBusiness.address	String	Business address.
receivingBusiness.city	String	Business city.
receivingBusiness.postalCode	String	Postal/ZIP code of the business.
receivingBusiness.countryIsoCode	String	ISO country code of the business.
receivingBusiness.msisdn	String	Contact mobile number.
receivingBusiness.email	String	Contact email.

receivingBusiness.dateOfIncorporation	String	Date of incorporation (YYYY-MM-DD).
receivingBusinessRepresentativeId*	String	Information about the business representative's ID.
channelStatusInfo.status	String	Status of the request (OK, FAILED).
channelStatusInfo.code	String	Response code (e.g., 000 for success).
channelStatusInfo.description	String	Human-readable description of the response.

Sample Response Example — Beneficiary (C2C / B2C)

```
{
  "thunesResponse": {
    "beneficiary": {
      "dateOfBirth": "1988-07-24",
      "firstname": "Zelda",
      "lastname": "Fitzgerald"
    },
    "id": 1139796
  },
  "channelStatusInfo": {
    "status": "OK",
    "code": "000",
    "description": "COMPLETED_SUCCESSFULLY."
  }
}
```

Sample Response Example — Beneficiary (C2B / B2B)

```
{
  "thunesResponse": {
    "receivingBusiness": {
      "registeredName": "Company ABC",
      "tradingName": "Brand name",
      "address": "12, Victoria Lane",
      "postalCode": "12345",
      "city": "Singapore",
      "countryIsoCode": "SGP",
      "msisdn": "33712345678",
      "email": "john.doe@mail.com",
      "dateOfIncorporation": "2014-10-01",
      "representativeIdCountryIsoCode": "SGP",
      "representativeIdNumber": null
    },
    "id": 113200
  },
  "channelStatusInfo": {
    "status": "OK",
    "code": "000",
    "description": "COMPLETED_SUCCESSFULLY."
  }
}
```

Sample Response – Failure

```
{
  "channelStatusInfo": {
    "status": "FAILURE",
    "code": "01",
    "description": "HTTP call to the url was unsuccessful. Connection refused"
  }
}
```

2.0 Credit Party Verification

Verify the validity of a credit party before initiating a transaction.

- **For C2C / B2C transactions**

Verifies a Beneficiary.

- **For C2B / B2B transactions**

Verifies a Receiving Business.

Base Endpoint

POST /thunes/v2/outbound/money-transfer/credit-party-verification
--

Request Field Description

Field	Type	Required	Description
receiver.serviceld	String	Yes	Service ID (1 = Mobile Wallet, 2 = Bank Account).
receiver.msisdn	String	Cond.	Mobile number (required if serviceld = 1).
receiver.bankAccountNumber	String	Cond.	Bank account number (required if serviceld = 2).
receiver.businessRegisteredName	String	Optional	Registered business name (required for business verification).
receiver.payerId	String	Yes	Payer identifier.
receiver.bic	String	Optional	SWIFT BIC code (if applicable).
receiver.transactionType	String	Yes	Transaction type (C2C, B2C, C2B, B2B).
channelInfo.rrn	String	Yes	12-character unique transaction reference.
channelInfo.bankId	String	Yes	Identifier of the originating bank.
channelInfo.channelId	String	Yes	Identifier of the originating channel.
channelInfo.sourceSystemId	String	Yes	Identifier of the invoking system.
signature	String	Yes	Digital signature string (base64-encoded, max 1000 characters).

Request Body – C2C

```
{
  "receiver": {
    "serviceId": "1",
    "msisdn": "254101010000",
    "bankAccountNumber": "",
    "businessRegisteredName": "",
    "payerId": "9",
    "bic" : "",
    "transactionType": "C2C"
  },
  "channelInfo": {
    "rrn": "111996657000",
    "bankId": "54",
    "channelId": "OMNI",
    "sourceSystemId": "ONMI"
  },
  "signature": "
/A2VEUvM14LEfn2jMzij1DWPzidsCkA6q7CYPPLHFIBVpevEpTNp9WTm80RWYr8oZx5jT8i4FAFMnN58kXd1/Q
HfjgMxvfkP+T3XmFg2Kv5PdF7r0F0XvsaY9u6hfy2NbnQwaSMg=="
}
```

Request Body – C2B

```
{
  "receiver": {
    "serviceId": "2",
    "msisdn": "",
    "bankAccountNumber": "624101010100",
    "businessRegisteredName": "Indonesia Bank",
    "payerId": "214",
    "bic" : "",
    "transactionType": "C2B"
  },
  "channelInfo": {
    "rrn": "111996657000",
    "bankId": "54",
    "channelId": "OMNI",
    "sourceSystemId": "ONMI"
  },
  "signature": "
/ZCL7Rmw8uIm/A2VEUvM14LEfn2jMzij1DWPzidsCkA6q7CYPPLHFIBVpevEpTNp9WTm80RWYr8oZx5jT8i4FA
FMnN58kXd1/QHfjgMxvfkP+T3XmFg2Kv5PdF7r0F0XvsaY9u6hfy2NbnQwaSMg=="
}
```

Response Field Description

Field	Type	Description
thunesResponse.accountStatus	String	Account availability status (AVAILABLE,).
thunesResponse.id	Integer	Unique identifier returned by Thunes for the credit party.
channelStatusInfo.status	String	Status of the request (OK, FAILURE).
channelStatusInfo.code	String	Response code (e.g., 000 for success).
channelStatusInfo.description	String	Human-readable description of the response.

Sample Response

```
{
  "thunesResponse": {
    "accountStatus": "AVAILABLE",
    "id": 2282566
  },
  "channelStatusInfo": {
    "status": "OK",
    "code": "000",
    "description": "COMPLETED_SUCCESSFULLY."
  }
}
```

Sample Response – Failure

```
{
  "channelStatusInfo": {
    "status": "FAILURE",
    "code": "01",
    "description": "HTTP call to the url was unsuccessful. Connection refused"
  }
}
```

Thunes Static Data APIs

A number of thunes resource fields will only accept a list of known values. These values are static and not subject to change.

1.0 Bank Account Type

Retrieve the list of bank account types supported for a given country.

Base Endpoint

POST /thunes/v2/outbound/money-transfer/bank-account-type

Request Field Description

Field	Type	Required	Description
receiver.countryCode	String	Yes	3-letter ISO country code (e.g., GHA, KEN).
channelInfo.rrn	String	Yes	12-character unique transaction reference number.
channelInfo.bankId	String	Yes	Identifier of the originating bank.
channelInfo.channelId	String	Yes	Identifier of the originating channel (e.g., OMNI).
channelInfo.sourceSystemId	String	Yes	Identifier of the source system invoking the API.
signature	String	Yes	Digital signature string (base64-encoded, max length 1000 characters).

Example 1: Request Example

```
{
  "receiver": {
    "countryCode": "GHA"
  },
  "channelInfo": {
    "rrn": "111996657000",
    "bankId": "54",
    "channelId": "OMNI",
    "sourceSystemId": "ONMI"
  },
  "signature": "
/A2VEUvM14LEfn2jMzij1DWPzidsCkA6q7CYPPLHFIbVpevEpTNp9WTm80RWYr8oZx5jT8i4FAFMnN58kXd1/Q
HfjgMxvfKp+T3XmFg2Kv5PdF7r0F0XvsaY9u6hfy2NbnQwaSMg=="
}
```

Response Field Description

Field	Type	Description
thunesResponse[].type	Integer	Returned bank account type value.
thunesResponse[].description	String	Description of the value
channelStatusInfo.status	String	Status of the request (e.g., OK, FAILURE).
channelStatusInfo.code	String	Response code (e.g., 000 or 01).
channelStatusInfo.description	String	Description of the response status.

Success Response

```
{
  "thunesResponse": [
    {
      "type": "CHECKING",
      "description": "Checking Account"
    },
    {
      "type": "SAVINGS",
      "description": "Savings Account"
    },
    {
      "type": "DEPOSIT",
      "description": "Deposit Account"
    },
    {
      "type": "OTHERS",
      "description": "Other type of account"
    }
  ],
  "channelStatusInfo": {
    "status": "OK",
    "code": "000",
    "description": "COMPLETED_SUCCESSFULLY."
  }
}
```

Failure Response

```
{
  "channelStatusInfo": {
    "status": "FAILURE",
    "code": "01",
    "description": "Failed: HTTP call to the url was unsuccessful. Connection refused"
  }
}
```

2.0 ID Type

Retrieve the list of identification types supported for a given country.

Base Endpoint

POST /thunes/v2/outbound/money-transfer/id-type

Request Field Description

Field	Type	Required	Description
receiver.countryCode	String	Yes	3-letter ISO country code (e.g., GHA, KEN).
channelInfo.rrn	String	Yes	12-character unique transaction reference number.
channelInfo.bankId	String	Yes	Identifier of the originating bank.
channelInfo.channelId	String	Yes	Identifier of the originating channel (e.g., OMNI).
channelInfo.sourceSystemId	String	Yes	Identifier of the source system invoking the API.
signature	String	Yes	Digital signature string (base64-encoded, max length 1000 characters).

Example 1: Request Example

```
{
  "receiver": {
    "countryCode": "GHA"
  },
  "channelInfo": {
    "rrn": "111996657000",
    "bankId": "54",
    "channelId": "OMNI",
    "sourceSystemId": "ONMI"
  },
  "signature": "
/A2VEUvM14LEfn2jMzij1DWPzidsCkA6q7CYPPLFIBVpevEpTNp9WTm80RWYr8oZx5jT8i4FAFMnN58kXd1/Q
HfjgMxvfkP+T3XmFg2Kv5PdF7r0F0XvsaY9u6hfy2NbnQwaSMg=="
}
```

Response Field Description

Field	Type	Description
thunesResponse[].type	Integer	Returned identification type value.
thunesResponse[].description	String	Description of the value
channelStatusInfo.status	String	Status of the request (e.g., OK, FAILURE).
channelStatusInfo.code	String	Response code (e.g., 000 or 01).
channelStatusInfo.description	String	Description of the response status.

Success Response

```
{
  "thunesResponse": [
    {
      "type": "PASSPORT",
      "description": "Passport"
    },
    {
      "type": "NATIONAL_ID",
      "description": "National Identification Card"
    },
    {
      "type": "DRIVING_LICENSE",
      "description": "Driving License"
    },
    {
      "type": "SOCIAL_SECURITY",
      "description": "Social Security Card/Number"
    },
    {
      "type": "TAX_ID",
      "description": "Tax Payer Identification Card/Number"
    },
    {
      "type": "SENIOR_CITIZEN_ID",
      "description": "Senior Citizen Identification Card"
    },
    {
      "type": "BIRTH_CERTIFICATE",
      "description": "Birth Certificate"
    },
    {
      "type": "VILLAGE_ELDER_ID",
      "description": "Village Elder Identification Card"
    }
  ],
  "channelStatusInfo": {
    "status": "OK",
    "code": "000",
    "description": "Success"
  }
}
```

```

        "type": "RESIDENT_CARD",
        "description": "Permanent Residency Identification Card"
    },
    {
        "type": "ALIEN_REGISTRATION",
        "description": "Alien Registration Certificate/Card"
    },
    {
        "type": "PAN_CARD",
        "description": "PAN Card"
    },
    {
        "type": "VOTERS_ID",
        "description": "Voter's Identification Card"
    },
    {
        "type": "HEALTH_CARD",
        "description": "Health Insurance Card/Number"
    },
    {
        "type": "EMPLOYER_ID",
        "description": "Employer Identification Card"
    },
    {
        "type": "OTHER",
        "description": "Others not listed"
    }
],
"channelStatusInfo": {
    "status": "OK",
    "code": "000",
    "description": "COMPLETED_SUCCESSFULLY."
}
}

```

Failure Response

```

{
    "channelStatusInfo": {
        "status": "FAILURE",
        "code": "01",
        "description": "Failed: HTTP call to the url was unsuccessful. Connection refused"
    }
}
}

```

3.0 Purpose of Payments

Retrieve the list of purpose of payments supported by Thunes.

NOTE: China has a different purpose of payment values and differs from the rest of the corridors

Base Endpoint

POST /thunes/v2/outbound/money-transfer/purpose-of-payment

Request Field Description

Field	Type	Required	Description
receiver.countryCode	String	Yes	3-letter ISO country code (e.g., GHA, KEN).
channelInfo.rrn	String	Yes	12-character unique transaction reference number.
channelInfo.bankId	String	Yes	Identifier of the originating bank.
channelInfo.channelId	String	Yes	Identifier of the originating channel (e.g., OMNI).
channelInfo.sourceSystemId	String	Yes	Identifier of the source system invoking the API.
signature	String	Yes	Digital signature string (base64-encoded, max length 1000 characters).

Example 1: Request Example

```
{
  "receiver": {
    "countryCode": "GHA"
  },
  "channelInfo": {
    "rrn": "111996657000",
    "bankId": "54",
    "channelId": "OMNI",
    "sourceSystemId": "ONMI"
  },
  "signature": "
/A2VEUvM14LEfn2jMzij1DWPzidsCkA6q7CYPPHLFIBVpevEpTNp9WTm80RWYr8oZx5jT8i4FAFMnN58kXd1/Q
HfjgMxvfkP+T3XmFg2Kv5PdF7r0F0XvsaY9u6hfy2NbnQwaSMg=="
}
```

Response Field Description

Field	Type	Description
thunesResponse[].type	Integer	Returned identification type value.
thunesResponse[].description	String	Description of the value
channelStatusInfo.status	String	Status of the request (e.g., OK, FAILURE).
channelStatusInfo.code	String	Response code (e.g., 000 or 01).
channelStatusInfo.description	String	Description of the response status.

Success Response – China Corridor

```
{
  "thunesResponse": [
    {
      "description": "Family support",
      "type": "FAMILY_SUPPORT"
    },
    {
      "description": "Liberalized remittance",
      "type": "LIBERALIZED_REMITTANCE"
    },
    {
      "description": "Construction expenses",
      "type": "CONSTRUCTION_EXPENSES"
    },
    {
      "description": "Advertising and/or public relations related expenses",
      "type": "ADVERTISING_EXPENSES"
    },
    {
      "description": "Fees for advisory or consulting service",
      "type": "ADVISORY_FEES"
    },
    {
      "description": "Payments for exported goods",
      "type": "EXPORTED_GOODS"
    },
    {
      "description": "Payment for services",
      "type": "SERVICE_CHARGES"
    },
    {
      "description": "Property rental payment",
      "type": "PROPERTY_RENTAL"
    }
  ]
}
```

```

        "description": "Tax payment",
        "type": "TAX_PAYMENT"
    },
    {
        "description": "Payment of salary",
        "type": "SALARY_PAYMENT"
    }
],
"channelStatusInfo": {
    "status": "OK",
    "code": "000",
    "description": "COMPLETED_SUCCESSFULLY."
}
}

```

Success Response – Other Corridors

```

{
    "thunesResponse": [
        {
            "description": "Broker, commitment, guarantee and other fees",
            "type": "OTHER_FEES"
        },
        {
            "description": "Residential property purchase",
            "type": "PROPERTY_PURCHASE"
        },
        {
            "description": "Small value remittance",
            "type": "SMALL_VALUE_REMITTANCE"
        },
        {
            "description": "Liberalized remittance",
            "type": "LIBERALIZED_REMITTANCE"
        },
        {
            "description": "Gift and other donations",
            "type": "GIFT_AND_DONATION"
        },
        {
            "description": "Property rental payment",
            "type": "PROPERTY_RENTAL"
        },
        {
            "description": "Investment in shares",
            "type": "SHARES_INVESTMENT"
        }
    ],
}

```

```
{
  {
    "description": "Other purposes",
    "type": "OTHER"
  },
  {
    "description": "Tax payment",
    "type": "TAX_PAYMENT"
  },
  {
    "description": "Payment of loans",
    "type": "LOAN_PAYMENT"
  },
  {
    "description": "Family support",
    "type": "FAMILY_SUPPORT"
  },
  {
    "description": "Fund investment",
    "type": "FUND_INVESTMENT"
  },
  {
    "description": "Payment of salary",
    "type": "SALARY_PAYMENT"
  },
  {
    "description": "Payment of rewards",
    "type": "REWARD_PAYMENT"
  },
  {
    "description": "Personal transfer",
    "type": "PERSONAL_TRANSFER"
  }
],
"channelStatusInfo": {
  "status": "OK",
  "code": "000",
  "description": "COMPLETED_SUCCESSFULLY."
}
}
```

Failure Response

```
{
  "channelStatusInfo": {
    "status": "FAILURE",
    "code": "01",
    "description": "Failed: HTTP call to the url was unsuccessful. Connection
refused"
  }
}
```

Authentication

The Thunes Outbound Service API exclusively relies on digital signatures to authenticate all requests. This ensures:

- **Integrity** – the payload has not been tampered with.
- **Authenticity** – the request originated from a trusted source.
- **Non-repudiation** – the sender cannot later deny sending the request..

Key and Certificate Setup

To participate in this integration:

1. Client/Channel Key Pair Generation
 - The client must generate a private key and a matching X.509 certificate.
 - The private key must be securely stored and never shared.
 - The certificate (public key) must be shared with the API provider.
2. Certificate Exchange
 - The client provides their public certificate to the service provider.
 - The service provider imports and maintains this certificate in the trust store.
 - All incoming signatures will be validated using this certificate.
3. Signing Requirement
 - The client uses their private key to digitally sign the canonical text (see next section).
 - The Base64-encoded signature is placed into the signature field of the request body.

Signature Validation

Applicable Endpoints:

- POST /thunes/v2/outbound/money-transfer/services
- POST /thunes/v2/outbound/money-transfer/payers
- POST /thunes/v2/outbound/money-transfer/payers/details

- POST /thunes/v2/outbound/money-transfer/payers/rates
- POST /thunes/v2/outbound/money-transfer/countries
- POST /thunes/v2/outbound/money-transfer/lookups/bic
- POST /thunes/v2/outbound/money-transfer/credit-party-information
- POST /thunes/v2/outbound/money-transfer/credit-party-verification
- POST /thunes/v2/outbound/money-transfer/bank-account-type
- POST /thunes/v2/outbound/money-transfer/id-type
- POST /thunes/v2/outbound/money-transfer/purpose-of-payment

Implementation

1. Canonical Text Generation

- Extract specific fields from the request body.
- Concatenate them in the exact required order.
- No separators, whitespace, or extra characters.

2. Signature Creation

- Sign the canonical text using your private key (RSA/SHA256).
- Base64-encode the signature.
- Place the result in the signature field of the request JSON.

Canonical Text Construction

Endpoint	Canonical Fields (Concatenation Order)
List of Services /services	rrn + bankId + channelId + countryCode
List of Payers /payers	rrn + bankId + channelId
Payer Rates /payers/rates	rrn + bankId + channelId + payerId
Payer Details /payers/details	rrn + bankId + channelId + payerId
List of Countries /countries	rrn + bankId + channelId
BIC Lookup /lookups/bic	rrn + bankId + channelId + bic
Credit Party Information /credit-party-information	rrn + bankId + channelId + payerId + transactionType
Credit Party Verification /credit-party-verification	rrn + bankId + channelId + payerId + transactionType
Bank Types /bank-account-type	rrn + bankId + channel + countryCode
ID Types /id-type	rrn + bankId + channel + countryCode
Purpose of Payment /purpose-of-payment	rrn + bankId + channel + countryCode