

# Endpoints

## 1. Transaction Resetting

Endpoint: `http://{hostname}/TransactionReset`

An endpoint to reset the transactions recorded for a specific UserId or TransactionId from the TransactionReset Endpoint.

Input: A POST request to `/TransactionReset` with raw JSON input in one of the two formats:

```
{  
  "UserId": <integer>  
}
```

Or

```
{  
  "TransactionId": <integer>  
}
```

Output: Returns success if data was successfully reset.

```
{"Success":true}
```

## 2. Leaderboard Score Resetting

Endpoint: `http://{hostname}/ScorePostReset`

An endpoint to reset the scores posted for a specific UserId or LeaderboardId from the ScorePostReset Endpoint.

Input: A POST request to `/ScorePostReset` with raw JSON input in one of the two formats:

```
{
```

```
    "UserId": <integer>
  }
  Or
  {
    "LeaderboardId": <integer>
  }
```

Output: Returns success if data was successfully resetted.

```
{"Success":true}
```

### 3. User Reset

Endpoint: `http://{hostname}/UserReset`

An endpoint to reset the data posted for a specific UserId from the UserResetEndpoint.

Input: A POST request to `/UserReset` with raw JSON input in the format:

```
{
  "UserId": <integer>
}
```

Output: Returns success if data was successfully resetted.

```
{"Success":true}
```