

[illegible]

E.D. Estimating	(22) INTERNAL WALLS			
Description	Qty	Unit	Rate	Amount
<u>(22) INTERNAL WALLS</u>				
CONCRETE WORK				
PRECAST CONCRETE				
<u>Precast concrete units; bedding in gauged mortar; minimum bearing 200mm both sides</u>				
<u>Lintels</u>				
100mm wide x 65mm thick	5	m	9.35	46.75
<u>Sundries</u>				
Fireback, fire gatherer, flue	1	item	600.00	600.00
BRICKWORK AND BLOCKWORK				
BLOCKWORK				
<u>Solid concrete blocks; I.S.20; size 440 x 215 x 100mm; compressive strength 7.5N/mm2; stretcher bond; in cement lime and sand mortar (1:1:6) type III as Engineers specification; pointing details to be agreed with architect onsite following sample details</u>				
<u>Walls</u>				
100mm thick	67	m2	23.00	1,541.00
450mm thick in chimneys	7	m2		EXCL
<u>FLOOR, WALL AND CEILING FINISHES</u>				
STUD PARTITIONS				
<u>44 x 100mm timber studs grade C16 at 400mm centres; faced both side with single layer 12.5mm Standard plasterboard; 3mm skim both sides; Rockwool insulation between joists 100mm thick</u>				
<u>Partitions</u>				
2450mm high	26	m	169.81	4,415.06
<u>extra over for door opes</u>	6	nr	40.00	240.00
<u>extra over for moisture resistant board</u>	20	m2	3.00	60.00
<u>extra over for abutments, angles, T-junctions, fair ends, etc</u>	1	item	100.00	100.00
			To Collection €	7,002.81