



Qty Description Lnr Mrk

005 W1 1 ND NTech Villa Fixed frame w/sash

Construction 105/80, 113 mm frame incl. 8 mm alum.

U-value product: No performance declared

Weight 173 kg Mrk: W1

Without ventilator

Outward opening topswing reversible sash

Lam Low E 2s WES/Ar

Construction 6,38ES+16G+4+16G+ES6,38

Aluminium cladded

Product Unspecified colour

Surface finishing

Product Unspecified colour

Details:

Wallside frame finished No sub frame groove No fixing holes

Details (sash):

b.: Hoppe handle brushed aluminium (S)

Note (only for customer):

max height

Bar:

64 = Solid transom/mullion

010 W2 1 ND NTech Villa Fixed frame

NOBB 47543466

Construction 105/80, 113 mm frame incl. 8 mm alum.

U-value product: 0,79W/m²K

Weight 67 kg Mrk: W2

Without ventilator

Lam Low E 2s WES/Ar

Construction 6,38ES+16G+4+16G+ES6,38

Aluminium cladded

Product Unspecified colour

Surface finishing


Product Unspecified colour

Details:


Wallside frame finished No sub frame groove No fixing holes

Width× Height

2248 ×1788mm



673 ×2273mm





Lnr Mrk Qty Description

015 W3 1 ND NTech Villa Topswing reversible

NOBB 47546974

Construction 105/80, 113 mm frame incl. 8 mm alum.

U-value product: 0,99W/m²K

Weight 27 kg Mrk: W3

Without ventilator

Outward opening topswing reversible sash

Low E 2s WES/Ar

Construction 4ES+16G+4+16G+ES4

Aluminium cladded

Product Unspecified colour

Surface finishing

Product Unspecified colour

Details:

Wallside frame finished No sub frame groove No fixing holes

Hoppe handle brushed aluminium (S)

020 D2 1 ND NTech Villa Balcony door (security)

NOBB 47547057

Construction 105/80, 113 mm frame incl. 8 mm alum.

U-value product: 0,87W/m²K

Weight 107 kg Mrk: D2

Left hinge

Without ventilator

Outward opening sidehinged door leaf

Lam Low E 2s WES/Ar

Construction 6,38ES+16G+4+16G+ES6,38

Threshold 25 mm

Panel height 136 mm

Aluminium cladded

Product Unspecified colour

Surface finishing

Product Unspecified colour


Details:

Wallside frame finished No sub frame groove


No fixing holes

Hoppe with external cylinder Casementstay (FIX 150) (door) Width× Height

673 ×998mm



0.40 -- 0.400-----





Lnr Mrk Qty Description

025 D2

1 ND NTech Villa Topswing reversible

NOBB 47546974

Construction 105/80, 113 mm frame incl. 8 mm alum.

U-value product: 1,07W/m²K

Weight 24 kg Mrk: D2

Without ventilator

Outward opening topswing reversible sash

Lam Low E 2s WES/Ar

Construction 6,38ES+16G+4+16G+ES6,38

Aluminium cladded

Product Unspecified colour

Surface finishing

Product Unspecified colour

Details:

Wallside frame finished No sub frame groove No fixing holes

Hoppe handle brushed aluminium (S)

Note (only for customer):

W4

026 D2 1 Coupling

S: Mounted on building site

Aluminium cladded

Product Unspecified colour


Surface finishing

Product Unspecified colour

Width× Height 498 ×998mm



1448 ×2498mm





Lnr Mrk Qty Description

030 W5 1 ND NTech Villa Fixed frame

NOBB 47543466

Construction 105/80, 113 mm frame incl. 8 mm alum.

U-value product: 0,72W/m²K

Weight 103 kg Mrk: W5

Without ventilator Lam Low E 2s WES/Ar

Construction 6,38ES+16G+4+16G+ES6,38

Aluminium cladded

Product Unspecified colour

Surface finishing

Product Unspecified colour

Details:

Wallside frame finished No sub frame groove No fixing holes

NOBB 47547076

Construction 105/80, 172 mm frame incl. 8

mm alum.

U-value product: 0,79W/m²K

Weight 292 kg Mrk: D03

Right door leaf primary Without ventilator Lifting sliding door leaf Toughened LowE 2s WES/Ar

Construction 4ES#+16G+4+16G+#ES4

Threshold 25 mm

Panel height 136 mm

Aluminium cladded

Product Unspecified colour

Surface finishing

Product Unspecified colour


Details:

Wallside frame finished No sub frame groove No fixing holes

Patio door: Glass sent loose Hoppe with external cylinder Width× Height 1198 ×1998mm



3178 ×2498mm







Lnr Mrk Qty Description

040 W6 1 ND NTech Villa Fixed frame w/sash

Construction 105/80, 113 mm frame incl. 8 mm alum.

U-value product: No performance declared

Weight 56 kg Mrk: W6

Without ventilator

Outward opening topswing reversible sash

Low E WES/Ar

Construction 6+16G+ES4

Aluminium cladded

Product Unspecified colour

Surface finishing

Product Unspecified colour

Details:

Wallside frame finished No sub frame groove No fixing holes

Details (sash):

a.: Hoppe handle brushed aluminium (S)

Bar:

64 = Solid transom/mullion

045 W7 1 ND NTech Villa Fixed frame w/sash

Construction 105/80, 113 mm frame incl. 8 mm alum.

U-value product: No performance declared

Weight 42 kg Mrk: W7

Without ventilator

Outward opening topswing reversible sash

Low E 2s WES/Ar

Construction 4ES+16G+4+16G+ES4

Aluminium cladded

Product Unspecified colour

Surface finishing

Product Unspecified colour

Details:

Wallside frame finished No sub frame groove No fixing holes

Details (sash):


a.: Hoppe handle brushed aluminium (S)


Bar:

64 = Solid transom/mullion

Width× Height

1738 ×998mm









Lnr Mrk Qty Description

050 W8 1 ND NTech Villa Fixed frame w/sash

Construction 105/80, 113 mm frame incl. 8 mm alum.

U-value product: No performance declared

Weight 83 kg Mrk: W8

Without ventilator

Outward opening topswing reversible sash

Low E 2s WES/Ar

Construction 4ES+16G+4+16G+ES4

Aluminium cladded

Product Unspecified colour

Surface finishing

Product Unspecified colour

Details:

Wallside frame finished No sub frame groove No fixing holes

Details (sash):

a.: Hoppe handle brushed aluminium (S)c.: Hoppe handle brushed aluminium (S)

Bar:

64 = Solid transom/mullion

055 W9 2 ND NTech Villa Fixed frame

NOBB 47543466

Construction 105/80, 113 mm frame incl. 8 mm alum.

U-value product: 0,86W/m²K

Weight 24 kg Mrk: W9

Without ventilator Low E 2s WES/Ar

Construction 4ES+16G+4+16G+ES4

Aluminium cladded

Product Unspecified colour

Surface finishing

Product Unspecified colour


Details:

Wallside frame finished No sub frame groove No fixing holes


Note (only for customer):

W10

Width× Height



673 ×998mm





Qty Description Lnr Mrk

060 W11

1 ND NTech Villa Fixed frame w/sash

Construction 105/80, 113 mm frame incl. 8 mm alum.

U-value product: No performance declared

Weight 88 kg Mrk: W11

Without ventilator

Outward opening topswing reversible sash

Low E 2s WES/Ar

Construction 4ES+16G+4+16G+ES4

Aluminium cladded

Product Unspecified colour

Surface finishing

Product Unspecified colour

Details:

Wallside frame finished No sub frame groove No fixing holes

Details (sash):

a.: Hoppe handle brushed aluminium (S)

64 = Solid transom/mullion

065 W12

2 ND NTech Villa Topswing reversible

NOBB 47546974

Construction 105/80, 113 mm frame incl. 8 mm alum.

U-value product: 0,89W/m²K

Weight 46 kg Mrk: W12

Without ventilator

Outward opening topswing reversible sash

Matelux w/Low E 2s WES/Ar

Construction 4ES+16G+4#+16G+ES4

Aluminium cladded

Product Unspecified colour

Surface finishing

Product Unspecified colour

Details:

Wallside frame finished No sub frame groove

No fixing holes


Hoppe handle brushed aluminium (S)

Note (only for customer):


W14

Width× Height

1798 ×1398mm



898 ×1398mm





Lnr Mrk Qty Description

070 W13 1 ND NTech Villa Fixed frame

NOBB 47543466

Construction 105/80, 113 mm frame incl. 8 mm alum.

U-value product: 0,81W/m²K

Weight 55 kg Mrk: W13

Without ventilator Lam Low E 2s WES/Ar

Construction 6,38ES+16G+4+16G+ES6,38

Aluminium cladded

Product Unspecified colour

Surface finishing

Product Unspecified colour

Details:

Wallside frame finished No sub frame groove No fixing holes

075 W15 1 ND NTech Villa Fixed frame w/sash

Construction 105/80, 113 mm frame incl. 8 mm alum.

U-value product: No performance declared

Weight 74 kg Mrk: W15

Without ventilator

Outward opening topswing reversible sash

Low E 2s WES/Ar

Construction 4ES+16G+4+16G+ES4

Aluminium cladded

Product Unspecified colour

Surface finishing

Product Unspecified colour

Details:

Wallside frame finished No sub frame groove No fixing holes

Details (sash):

a.: Hoppe handle brushed aluminium (S)

Bar:


64 = Solid transom/mullion

Width× Height

673×1843mm



1498 ×1398mm







Lnr Mrk Qty Description

080 W16 2 ND NTech Villa Fixed frame w/sash

Construction 105/80, 113 mm frame incl. 8 mm alum.

U-value product: No performance declared

Weight 67 kg Mrk: W16

Without ventilator

Outward opening topswing reversible sash

Low E 2s WES/Ar

Construction 4ES+16G+4+16G+ES4

Aluminium cladded

Product Unspecified colour

Surface finishing

Product Unspecified colour

Details:

Wallside frame finished No sub frame groove No fixing holes

Details (sash):

a.: Hoppe handle brushed aluminium (S)

Note (only for customer):

W17

Bar:

64 = Solid transom/mullion


120 RAS 7 Article RAS5407

Surface finishing

Product Unspecified colour

992 1 Non standard finishing

Width× Height



6000mm



Averaged U-value: 0,82W/m²K

Products where shown "no performance declared" are not included in the overall averaged U-value.

Calculation of U-value in accordance to NS-EN ISO 10077-1, 10077-2 and the programme "Therm". Centre U-value of glass is calculated in accordance to NS-EN 673.

The calculation methodology is independently quality assured by SINTEF Building and Infrastructure.