


# POINT-OF-INTEREST RECOMMENDATION IN LOCATION-BASED SOCIAL NETWORKS

Ludovico Boratto

<https://www.ludovicoboratto.com>

# LOCATION-BASED SOCIAL NETWORKS

- Sharp increase of smart phones led to the massive use of online location-based social networks (LBSNs)
  - E.g., Foursquare, Facebook Places, and Yelp
- LBSNs collect users' check-in information
  - visited locations' geographical information (latitude and longitude)
  - users' tips at the location
- LBSNs also allow users to make friends and share information



# POINT-OF-INTEREST RECOMENDATION

- Point-of-interest (POI) recommendation suggests new places for users to visit
- One of the most important tasks in LBSNs
  - It helps users discover new interesting locations in the LBSNs
- POI recommendation mines:
  - users' check-in records
  - venue information such as categories
  - users' social relationships
- POI recommendation is a branch of recommendation systems
  - It borrows ideas for this task from conventional recommendation systems (e.g., collaborative filtering)

# CHALLENGES FOR POI RECOMMENDATION


- Physical constraints [2,5,11,12,25,34,39]
  - users in LBSNs check-in at geographically constrained areas (shops open at given times)
  - Physical constraints make the check-in activity in LBSN exhibit significantly spatial and temporal properties
- Complex relations
  - For online social media services such as Twitter and Facebook, location is a new object
  - It creates new relations between locations [41], between users and locations [10,27,37], and between users [28,29]
- Heterogeneous information [19,20,23,26,30,32,31,43,48]
  - LBSNs go beyond check-in records
  - Geographical information of locations
  - Venue descriptions
  - Users' social relation information and media information (e.g., user comments and tweets)




# PROBLEM DEFINITION

- **Definition 1 (Check-in)** A check-in is denoted as a triple  $\langle u, l, t \rangle$  that depicts a user  $u$  visiting POI  $l$  at time  $t$ .
- **Definition 2 (Check-in sequence)** A check-in sequence is a set of check-ins of user  $u$ , denoted as  $S_u = \{\langle l_1, t_1 \rangle, \dots, \langle l_n, t_n \rangle\}$ , where  $t_i$  is the check-in time stamp. For simplicity, we denote  $S_u = \{l_1, \dots, l_n\}$ .
- **Problem 1 (POI recommendation)** Given all users' check-in sequences  $S$ , POI recommendation aims to recommend a POI list  $S_N$  for each user  $u$ .

# POI RECOMMENDATION






# INFLUENTIAL FACTORS

---

# INFLUENTIAL FACTORS

- Check-in activity is a synthesized decision from a variety of factors




# GEOGRAPHICAL INFLUENCE

- It's an important factor that distinguishes the POI recommendation from traditional item recommendation
  - Check-in behavior depends on locations' geographical features
  - A user acts in geographically constrained areas and prefers to visiting POIs nearby those where the user has checked-in
- We can employ the geographical influence to improve POI recommendation systems  
[3,17,22,36,42,44,45,50]

# GEOGRAPHICAL INFLUENCE

- Three main models:
  - Power law distribution [35,36]






# GEOGRAPHICAL INFLUENCE

- Three main models:
  - Power law distribution [35,36]
  - Gaussian distribution [3,6]



# GEOGRAPHICAL INFLUENCE

- Three main models:
  - Power law distribution [35,36]
  - Gaussian distribution [3,6]
  - Kernel density estimation (KDE) [44]



# SOCIAL INFLUENCE

- Intuition: friends in LBSNs share more common interests than non-friends [3,10,11,13,35,33,45,47]

- Friend-based Collaborative Filtering (FCF) [35]: preference  $r_{ij}$  of user  $u_i$  for  $I_j$

$$r_{ij} = \frac{\sum_{u_k \in F_i} r_{kj} w_{ik}}{\sum_{u_k \in F_i} r_{kj}}$$

- where  $F_i$  is the set of friends with top-n similarity,  $w_{ik}$  is similarity weight between  $u_i$  and  $u_k$
- FCF enhances the efficiency by reducing the computation cost of finding top similar users
  - However, it overlooks the non-friends who share many common check-ins with the target user

Result: very limited improvements over user-based POI recommendation in terms of precision

# SOCIAL INFLUENCE


- Cheng et al. [3] apply the probabilistic matrix factorization with social regularization (PMFSR)

$$\arg \min_{U, L} \sum_{i=1}^{|U|} \sum_{j=1}^{|L|} I_{ij} (g(c_{ij}) - g(U_i^T L_j))^2 + \lambda_1 \|U\|_F^2 + \lambda_2 \|V\|_F^2 + \beta \sum_{i=1}^N \sum_{u_f \in F_i} sim(i, f) \|U_i - U_f\|^2$$

- Social influence is incorporated by the social constraints that ensure latent features of friends keep in close distance at the latent subspace



# SOCIAL INFLUENCE

- Also in this case, limited improvements w.r.t. classic POI recommendation
- Users in LBSNs make friends online without any limitation;
  - The check-in activity requires physical interactions between users and POIs
- Friends in LBSNs may share common interest but may not visit common locations
  - Friends in favor of Italian food from different cities will visit their own local Italian food restaurants



# TEMPORAL INFLUENCE

- Physical constraints on the check-in activity result in specific temporal patterns
- Three main aspects: periodicity, consecutiveness, and non-uniformness
- **Periodicity:** users' check-in behaviors in LBSNs exhibit periodic pattern [6,8,42,46]




# TEMPORAL INFLUENCE


- Physical constraints on the check-in activity result in specific temporal patterns
- Three main aspects: periodicity, consecutiveness, and non-uniformness
- **Consecutiveness:** Successive check-ins are usually correlated [4,7,14,24,47,28]
  - Users may have fun in a nightclub after diner in a restaurant
  - The nightclub and the restaurant are geographically adjacent and correlated from the perspective of venue function

# TEMPORAL INFLUENCE

- Physical constraints on the check-in activity result in specific temporal patterns
- Three main aspects: periodicity, consecutiveness, and non-uniformness
- **Consecutiveness:** Successive check-ins are usually correlated [4,7,14,24,47,28]



CCDF of intervals in check-ins




CCDF of distances in successive check-ins

- 40%-60% successive check-in behaviors happen in less than 4 hours since last check-in in Foursquare and Gowalla
- 90% successive check-ins happen in less than 32 kilometers (half an hour driving distance) in Foursquare and Gowalla

# TEMPORAL INFLUENCE

- Physical constraints on the check-in activity result in specific temporal patterns
- Three main aspects: periodicity, consecutiveness, and non-uniformness
- **Non-uniformness:** a user's check-in preference variance at different hours of a day, or at different months of a year, or at different days of a week [8]
  - a user's check-in preference changes at different hours of a day
  - The most frequent checked-in POI alters at different hours




# TEMPORAL INFLUENCE

- Physical constraints on the check-in activity result in specific temporal patterns
- Three main aspects: periodicity, consecutiveness, and non-uniformness
- These distinct temporal characteristics mentioned above make the previous temporal models unsatisfactory for POI recommendation
- A variety of systems are proposed to enhance POI recommendation performance [4,8,23,51]

# CONTENT INDICATION

- In LBSNs, users generate contents including tips and ratings for POIs and also photos about the POIs [9,21,30,33,38]
  - They can be used to enhance the POI recommendation
- Comments provide extra information from the shared tips beyond the check-in behavior
- Yang et al. [33] propose a sentiment-enhanced location recommendation method



User  $u$  at Venue  $v$  ( $ss = 0.3$ )

Good place in center New York, I went there last Sunday night and had great spaghetti with reasonable price. But I had a very long waiting time , almost one hour just for appetizer !!!



Great spaghetti  
Reasonable price  
Good place


Center New York  
Last Sunday night  
Appetizer

Long waiting time

Sentiment Score	Preference Measure
[-1, -0.05]	1
(-0.05, -0.01]	2
(-0.01, 0.01)	3
[0.01, 0.05)	4
[0.05, 1]	5

- $\hat{C}_{i,j}$  measures the preference of user  $u_i$  at a POI  $I_j$
- Traditional matrix factorization method can be employed to recommend POIs through the following objective

$$\arg \min_{U,L} \sum_{(i,j) \in \Omega} (\hat{C}_{i,j} - U_i L_j^T)^2 + \alpha \|U\|_F^2 + \beta \|L\|_F^2$$



# METHODOLOGY

---

# METHODOLOGY

- We discussed four general influential factors for POI recommendation
- A POI recommendation system requires to construct a model incorporating those influential factors
- The **fused model** fuses recommended results from collaborative filtering and recommended results from models capturing geographical influence, social influence, and temporal influence [3,36,45]
- The **joint model** establishes a joint model to learn the user preference and the influential factors together [8,9,15,17,18,22,33,40]

# FUSED MODEL

- It establishes **a model for each influential factor** and combines their recommended results with **suggestions from the collaborative filtering model**
- Social influence provides limited improvements in POI recommendation and user comments are usually missing in users' check-ins
- Geographical influence and temporal influence constitute two important factors for POI recommendation
- In [5], Cheng et al. employ probabilistic matrix factorization (PMF) and probabilistic factor model (PFM) to learn user preference for recommending POIs

$$P_{ul} = P(F_{ul}) \cdot P(l|C_u)$$


- $P(F_{ul})$  encodes a users preference on a location
- $P(l|C_u)$  is calculated via the Multi-center Gaussian Model


# JOINT MODEL

- The joint model learns several influential factors together, and then recommends POIs from the jointly learned model
- The check-in behavior as a synchronized decision influenced by several factors together
- Two types of joint models:
  - **Incorporating factors** (e.g., geographical influence and temporal influence) into traditional collaborative filtering, like matrix factorization [8,9,17,22,33]
  - **Generating a graphical model** according to the check-ins and extra influences like geographical information [18,15,40]

# JOINT MODEL

- In [17], Lian et al. propose the GeoMF model to incorporate geographical influence into a weighted regularized matrix factorization model (WRMF)





# TASKS


---

# TASKS

- We categorize the POI recommendation task in two ways
- **General POI recommendation:** it recommends the top-N POIs for users, similar to movie recommendation task in Netflix competition [8,16,18,36]
- **Successive POI recommendation:** it generates to list sensitive to their recent check-ins [3,7,49,51]
  - It takes advantage of the recent check-in information → recall improves

# SUCCESSIVE POI RECOMMENDATION

- POI recommendation provides satisfied recommendations promptly based on users most recent checked-in location
- It requires not only the preference modeling from users but also the accurate correlation analysis between POIs
- In [51], Zhao et al. propose the STELLAR system, which aims to provide time-aware successive POI recommendations
- Rank the POIs via a score function  $f: U \times L \times T \times L \rightarrow R$
- The score function  $f(u, l_q, t, l_c)$  that represents the “successive check-in possibility”, is defined for user  $u$  to a candidate POI  $l_c$  at the time stamp  $t$  given the user’s last check-in as a query POI  $l_q$



# EVALUATION

Data source  
Metrics

# DATA SOURCE

- Gowalla, Brightkite, and Foursquare are famous benchmark datasets available for evaluating a POI recommendation model

Name	Statistics
Brightkite [6]	4,491,143 check-ins from 58,228 users
Gowalla 1 [6]	6,442,890 check-ins from 196,591 users
Gowalla 2 [3]	4,128,714 check-ins from 53,944 users
Foursquare 1 [10]	2,073,740 check-ins from 18,107 users
Foursquare 2 [11]	1,385,223 check-ins from 11,326 users
Foursquare 3 [1]	325,606 check-ins from 80,606 users
Foursquare (NYC restaurants) [52]	27,149 check-ins and 10377 tips from 3,112 users
Foursquare (NYC and Tokio) [53]	227,428 check-ins in New York city and 573,703 check-ins in Tokyo
Foursquare (Global scale) [54]	33,278,683 check-ins by 266,909 users
Foursquare (Global scale + Social network) [55]	22,809,624 checkins by 114,324 users

# METRICS

- Most of POI recommendation systems utilize metrics of *precision* and *recall*
  - F-score is also introduced in some work
- The precision and recall in the top-N recommendation system are denoted as P@N and R@N
- P@N measures the ratio of recovered POIs to the N recommended POIs
- R@N is the ratio of recovered POIs to the set of POIs in the testing data

- $L_u^T$  denotes the set of POIs visited by user  $u$  in the test data
- $L_u^R$  denotes the set of POIs recommended to user  $u$

$$P@N = \frac{1}{|U|} \sum_{u \in N} \frac{|L_u^R \cap L_u^T|}{N}$$

$$R@N = \frac{1}{|U|} \sum_{u \in N} \frac{|L_u^R \cap L_u^T|}{|L_u^T|}$$

$$F-score@N = \frac{2 * P@N * R@N}{P@N + R@N}$$


# METRICS

- Relative precision@N and recall@N ( $r - P@N$  and  $r - R@N$ ) have been introduced in [18,35]
- Let  $L_u^C$  denote the candidate POIs for each user  $u$ , namely POIs the user has not checked-in
- Precision of a random recommender would be  $\frac{|L_u^T|}{|L_u^C|}$
- Recall of a random recommender would be  $\frac{|N|}{|L_u^C|}$

- Then:

$$r - P@N = \frac{P@N}{|L_u^T| / |L_u^C|}$$

$$r - R@N = \frac{R@N}{|N| / |L_u^C|}$$



# TRENDS AND NEW DIRECTIONS

# RANKING-BASED MODELS

- Most of previous methods generally attempt to estimate the user check-in probability over POIs
- We do not really care about the predicted check-in possibility value but the preference order
- Recent advances in recommender systems who optimize for ranking quality may be applied to POI recommendation:
  - Bayesian personalized ranking (BPR)
  - Weighted approximate rank pairwise (WARP)

# ONLINE RECOMMENDATION


- The existing approaches work with pre-trained offline methods
- This suffers two problems:
  - **Cold start:** the offline model performs not satisfying for new users or users who have only a few check-ins
  - **User behavior variance:** the offline model may perform awfully if a user's behavior changes since it learns user behavior according to history records
- No work using online model for POI recommendation exists

# USER PRIVACY AND DATA SOURCES

- Due to recent scandals and recent regulations (GDPR) collecting real data is becoming more and more challenging
- However, algorithms are becoming more and more thirsty for data (e.g., Deep Learning approaches)
- Balancing these two challenges is not trivial

# BIASES AND DISCRIMINATION

- Recommendation algorithms learn patterns from data
- But no perfect data exists!
- Several biases affect the data (popularity, gender unbalance)
- This is very likely to lead to **biased recommendations!**
  - Only popular venues get recommended (places get too crowded, owners of unpopular venues are affected)
  - Minorities get systematically worse recommendations, thus affecting their experience



## REFERENCES

---

- [1] Jie Bao, Yu Zheng, and Mohamed F. Mokbel. Location-based and preference-aware recommendation using sparse geo-social networking data. In Proceedings of the 21st ACM SIGSPATIAL International Conference on Advances in Geographic Information Systems, pages 199–208, 2012.
- [2] Preeti Bhargava, Thomas Phan, Jiayu Zhou, and Juhan Lee. Who, what, when, and where: Multi-dimensional collaborative recommendations using tensor factorization on sparse user-generated data. In Proceedings of the 24th International Conference on World Wide Web, pages 130–140. ACM, 2015.
- [3] Chen Cheng, Haiqin Yang, Irwin King, and Michael R Lyu. Fused matrix factorization with geographical and social influence in location-based social networks. In Proceedings of the Twenty-Sixth AAAI Conference on Artificial Intelligence, pages 17–23. AAAI Press, 2012.
- [4] Chen Cheng, Haiqin Yang, Michael R Lyu, and Irwin King. Where you like to go next: successive point-of-interest recommendation. In Proceedings of the Twenty-Third international joint conference on Artificial Intelligence, pages 2605–2611. AAAI Press, 2013.
- [5] Zhiyuan Cheng, James Caverlee, Kyumin Lee, and Daniel Z Sui. Exploring millions of footprints in location sharing services. In Fifth International AAAI Conference on Weblogs and Social Media, pages 81–88. AAAI, 2011.

- [6] Eunjoon Cho, Seth A Myers, and Jure Leskovec. Friendship and mobility: user movement in location-based social networks. In Proceedings of the 17th ACM SIGKDD international conference on Knowledge discovery and data mining, pages 1082–1090. ACM, 2011.
- [7] Shanshan Feng, Xutao Li, Yifeng Zeng, Gao Cong, Yeow Meng Chee, and Quan Yuan. Personalized ranking metric embedding for next new poi recommendation. In Proceedings of the 24th International Conference on Artificial Intelligence, pages 2069–2075. AAAI Press, 2015.
- [8] Huiji Gao, Jiliang Tang, Xia Hu, and Huan Liu. Exploring temporal effects for location recommendation on location-based social networks. In Proceedings of the 7th ACM conference on Recommender systems, pages 93–100. ACM, 2013.
- [9] Huiji Gao, Jiliang Tang, Xia Hu, and Huan Liu. Content-aware point of interest recommendation on location-based social networks. In Proceedings of the Twenty-Ninth AAAI Conference on Artificial Intelligence, pages 1721–1727. AAAI Press, 2015.
- [10] Huiji Gao, Jiliang Tang, and Huan Liu. Exploring social-historical ties on location-based social networks. In Sixth International AAAI Conference on Weblogs and Social Media. AAAI, 2012.

- [11] Huiji Gao, Jiliang Tang, and Huan Liu. gscorr: modeling geo-social correlations for new check-ins on location-based social networks. In Proceedings of the 21st ACM international conference on Information and knowledge management, pages 1582–1586. ACM, 2012.
- [12] Huiji Gao, Jiliang Tang, and Huan Liu. Addressing the cold-start problem in location recommendation using geo-social correlations. *Data Mining & Knowledge Discovery*, 29(2):299–323, 2015.
- [13] Yong Ge, Huayu Li, and Hengshu Zhu. Point-of-interest recommendations: Learning potential check-ins from friends. 2016.
- [14] Jing He, Xin Li, Lejian Liao, Dandan Song, and William K Cheung. Inferring a personalized next point-of-interest recommendation model with latent behavior patterns. In Thirtieth AAAI Conference on Artificial Intelligence, 2016. [21] Bo Hu and Martin Ester. Social topic modeling for point-of-interest recommendation in location-based social networks. In 2014 IEEE International Conference on Data Mining, pages 845–850. IEEE, 2014.
- [15] Takeshi Kurashima, Tomoharu Iwata, Takahide Hoshide, Noriko Takaya, and Ko Fujimura. Geo topic model: joint modeling of user’s activity area and interests for location recommendation. In Proceedings of the sixth ACM international conference on Web search and data mining, pages 375–384. ACM, 2013.

- [16] Xutao Li, Gao Cong, Xiao-Li Li, Tuan-Anh Nguyen Pham, and Shonali Krishnaswamy. Rankgeofm: A ranking based geographical factorization method for point of interest recommendation. In Proceedings of the 38th International ACM SIGIR Conference on Research and Development in Information Retrieval, pages 433–442. ACM, 2015.
- [17] Defu Lian, Cong Zhao, Xing Xie, Guangzhong Sun, Enhong Chen, and Yong Rui. Ge- oMF: Joint geographical modeling and matrix factorization for point-of-interest recom- mendation. In ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, pages 831–840. ACM, 2014.
- [18] Bin Liu, Yanjie Fu, Zijun Yao, and Hui Xiong. Learning geographical preferences for point-of-interest recommendation. In Proceedings of the 19th ACM SIGKDD interna- tional conference on Knowledge discovery and data mining, pages 1043–1051. ACM, 2013.
- [19] Bin Liu and Hui Xiong. Point-of-Interest recommendation in location based social networks with topic and location awareness. In Siam International Conference on Data Mining, pages 396–404. SIAM, 2013.
- [20] Bin Liu, Hui Xiong, Spiros Papadimitriou, Yanjie Fu, and Zijun Yao. A general geo- graphical probabilistic factor model for point of interest recommendation. IEEE Trans- actions on Knowledge and Data Engineering, 27(5):1167–1179, 2015.

- [21] Yanchi Liu, Chuanren Liu, Bin Liu, Meng Qu, and Hui Xiong. Unified point-of-interest recommendation with temporal interval assessment. 2016.
- [22] Yong Liu, Wei Wei, Aixin Sun, and Chunyan Miao. Exploiting geographical neighbor-hood characteristics for location recommendation. In ACM International Conference on Conference on Information and Knowledge Management, pages 739–748, 2014.
- [23] Anastasios Noulas, Salvatore Scellato, Neal Lathia, and Cecilia Mascolo. Mining user mobility features for next place prediction in location-based services. In 2012 IEEE 12th International Conference on Data Mining, pages 1038–1043. IEEE, 2012.
- [24] Steffen Rendle, Christoph Freudenthaler, and Lars Schmidt-Thieme. Factorizing per- sonalized markov chains for next-basket recommendation. In Proceedings of the 19th international conference on World wide web, pages 811–820. ACM, 2010.
- [25] Injong Rhee, Minsu Shin, Seongik Hong, Kyunghan Lee, Seong Joon Kim, and Song Chong. On the levy-walk nature of human mobility. IEEE/ACM transactions on networking (TON), 19(3):630–643, 2011.

- [26] Jitao Sang, Tao Mei, and Changsheng Xu. Activity sensor: Check-in usage mining for local recommendation. *ACM Transactions on Intelligent Systems and Technology (TIST)*, 6(3):41, 2015.
- [27] Masoud Sattari, Murat Manguoglu, Ismail H Toroslu, Panagiotis Symeonidis, Pinar Senkul, and Yannis Manolopoulos. Geo-activity recommendations by using improved feature combination. In *Proceedings of the 2012 ACM Conference on Ubiquitous Computing*, pages 996–1003. ACM, 2012.
- [28] Salvatore Scellato, Cecilia Mascolo, Mirco Musolesi, and Vito Latora. Distance matters: geo-social metrics for online social networks. In *Wonference on Online Social Networks*, pages 8–8, 2010.
- [29] Salvatore Scellato, Anastasios Noulas, and Cecilia Mascolo. Exploiting place features in link prediction on location-based social networks. In *ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, San Diego, Ca, Usa, August, pages 1046–1054, 2011.
- [30] Xiangyu Wang, Yi-Liang Zhao, Liqiang Nie, Yue Gao, Weizhi Nie, Zheng-Jun Zha, and Tat-Seng Chua. Semantic-based location recommendation with multimodal venue semantics. *IEEE Transactions on Multimedia*, 17(3):409–419, 2015.

- [31] Yingzi Wang, Nicholas Jing Yuan, Defu Lian, Linli Xu, Xing Xie, Enhong Chen, and Yong Rui. Regularity and conformity: Location prediction using heterogeneous mobility data. In ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, pages 1275–1284, 2015.
- [32] Zih-Syuan Wang, Jing-Fu Juang, and Wei-Guang Teng. Predicting poi visits with a het- erogeneous information network. In 2015 Conference on Technologies and Applications of Artificial Intelligence (TAAI), pages 388–395. IEEE, 2015.
- [33] Dingqi Yang, Daqing Zhang, Zhiyong Yu, and Zhu Wang. A sentiment-enhanced per- sonalized location recommendation system. In Proceedings of the 24th ACM Conference on Hypertext and Social Media, pages 119–128. ACM, 2013.
- [34] Dingqi Yang, Daqing Zhang, Vincent W Zheng, and Zhiyong Yu. Modeling user ac- tivity preference by leveraging user spatial temporal characteristics in lbsns. IEEE Transactions on Systems, Man, and Cybernetics: Systems, 45(1):129–142, 2015.
- [35] Mao Ye, Peifeng Yin, and Wang-Chien Lee. Location recommendation for location-based social networks. In Proceedings of the 18th SIGSPATIAL international conference on advances in geographic information systems, pages 458–461. ACM, 2010.

- [36] Mao Ye, Peifeng Yin, Wang-Chien Lee, and Dik-Lun Lee. Exploiting geographical influence for collaborative point-of-interest recommendation. In Proceedings of the 34th international ACM SIGIR conference on Research and development in Information Retrieval, pages 325–334. ACM, 2011.
- [37] Hongzhi Yin, Bin Cui, Ling Chen, Zhiting Hu, and Xiaofang Zhou. Dynamic user modeling in social media systems. ACM Transactions on Information Systems (TOIS), 33(3):10, 2015.
- [38] Hongzhi Yin, Bin Cui, Yizhou Sun, Zhiting Hu, and Ling Chen. Lcars: A spatial item recommender system. ACM Transactions on Information Systems (TOIS), 32(3):11, 2014.
- [39] Hongzhi Yin, Zhiting Hu, Xiaofang Zhou, Hao Wang, Kai Zheng, Quoc Viet Hung Nguyen, and Shazia Sadiq. Discovering interpretable geo-social communities for user behavior prediction. In The 32nd IEEE International Conference on Data Engineering, 2016.
- [40] Hongzhi Yin, Yizhou Sun, Bin Cui, Zhiting Hu, and Ling Chen. Lcars: A location-content-aware recommender system. In ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, pages 221–229, 2013.

- [41] Jing Yuan, Yu Zheng, and Xing Xie. Discovering regions of different functions in a city using human mobility and pois. In Proceedings of the 18th ACM SIGKDD international conference on Knowledge discovery and data mining, pages 186–194. ACM, 2012.
- [42] Quan Yuan, Gao Cong, Zongyang Ma, Aixin Sun, and Nadia Magnenat Thalmann. Time-aware point-of-interest recommendation. In Proceedings of the 36th international ACM SIGIR conference on Research and development in information retrieval, pages 363–372. ACM, 2013.
- [43] Quan Yuan, Gao Cong, and Aixin Sun. Graph-based point-of-interest recommendation with geographical and temporal influences. In Proceedings of the 23rd ACM International Conference on Conference on Information and Knowledge Management, pages 659–668. ACM, 2014.
- [44] Jia-Dong Zhang and Chi-Yin Chow. igslr: personalized geo-social location recommendation: a kernel density estimation approach. In Proceedings of the 21st ACM SIGSPATIAL International Conference on Advances in Geographic Information Systems, pages 334–343. ACM, 2013.
- [45] Jia-Dong Zhang and Chi-Yin Chow. Geosoca: Exploiting geographical, social and categorical correlations for point-of-interest recommendations. In Proceedings of the 38th International ACM SIGIR Conference on Research and Development in Information Retrieval, pages 443–452. ACM, 2015.

- [46] Jia Dong Zhang and Chi Yin Chow. Ticrec: A probabilistic framework to utilize temporal influence correlations for time-aware location recommendations. *IEEE Transactions on Services Computing*, (1):1–1, 2015.
- [47] Jia-Dong Zhang, Chi-Yin Chow, and Yanhua Li. Lore: exploiting sequential influence for location recommendations. In *Proceedings of the 22nd ACM SIGSPATIAL International Conference on Advances in Geographic Information Systems*, pages 103–112. ACM, 2014.
- [48] Jiawei Zhang, Xiangnan Kong, and Philip S. Yu. Transferring heterogeneous links across location-based social networks. In *ACM International Conference on Web Search and Data Mining*, pages 303–312, 2014.
- [49] Wei Zhang and Jianyong Wang. Location and time aware social collaborative retrieval for new successive point-of-interest recommendation. In *Proceedings of the 24th ACM International Conference on Information and Knowledge Management*, pages 1221–1230. ACM, 2015.
- [50] Shenglin Zhao, Irwin King, and Michael R Lyu. Capturing geographical influence in poi recommendations. In *International Conference on Neural Information Processing*, pages 530–537. Springer, 2013.

- [51] Shenglin Zhao, Tong Zhao, Haiqin Yang, Michael R Lyu, and Irwin King. Stellar: Spatial-temporal latent ranking for successive point-of-interest recommendation. In Thirtieth AAAI Conference on Artificial Intelligence, 2016.
- [52] Dingqi Yang, Daqing Zhang, Zhiyong Yu and Zhiwen Yu, Fine-Grained Preference-Aware Location Search Leveraging Crowdsourced Digital Footprints from LBSNs. In Proceeding of the 2013 ACM International Joint Conference on Pervasive and Ubiquitous Computing (UbiComp 2013), September 8-12, 2013, in Zurich, Switzerland.
- [53] Dingqi Yang, Daqing Zhang, Vincent W. Zheng, Zhiyong Yu. Modeling User Activity Preference by Leveraging User Spatial Temporal Characteristics in LBSNs. IEEE Trans. on Systems, Man, and Cybernetics: Systems, (TSMC), 45(1), 129-142, 2015.
- [54] Dingqi Yang, Daqing Zhang, Bingqing Qu. Participatory Cultural Mapping Based on Collective Behavior Data in Location Based Social Networks. ACM Trans. on Intelligent Systems and Technology (TIST), 2015.
- [55] Dingqi Yang, Bingqing Qu, Jie Yang, Philippe Cudre-Mauroux, Revisiting User Mobility and Social Relationships in LBSNs: A Hypergraph Embedding Approach, In Proc. of The Web Conference (WWW'19). May. 2019, San Francisco, USA.[50] Shenglin Zhao, Irwin King, and Michael R Lyu. Capturing geographical influence in poi recommendations. In International Conference on Neural Information Processing, pages 530–537. Springer, 2013.