

11 December 2015

TO:           Ranadu documentation  
FROM:        Al Cooper  
SUBJECT:     Ranadu manual and tutorial

## 1 Introduction

This manual describes an R package named “Ranadu” (R-based analysis for aircraft data users), which is intended to facilitate use of the data archives produced by the data systems on the NSF/NCAR/EOL/RAF research aircraft. (NSF=National Science Foundation; NCAR=National Center for Atmospheric Research; EOL=Earth Observing Laboratory; RAF=Research Aviation Facility) All the recent data files are in netCDF format, so that is the format emphasized here. Those files contain measurements made in field campaigns that use the NSF research aircraft operated by NCAR, presently consisting of a C-130 and a Gulfstream V. A list of recent projects is available at this EOL web page, and data requests can be made via links on that page.

The standard data archives consist of netCDF files that contain a set of measurements each second during a flight. Special archives may be available at higher rate, usually 25 Hz. The Ranadu functions produce R data.frames containing subsets of those measurements and then facilitate plotting and analyses using those data.frames. The table in the Appendix contains an alphabetical list of the functions, brief descriptions, and references where additional information can be found.

There are several groups of functions that serve different purposes. Some examples are listed below. For a complete list, see the Appendix.

### 1. *Functions for data access:*

- (a) `getNetCDF()` for reading netCDF files to R data.frames
- (b) `standardVariables()` to define common variables for (a)
- (c) `setVariableList()` to provide a GUI interface to variable selection
- (d) `TimeRoutines()` including `setRange()`, `getIndex()`, `getStartEnd()`

### 2. *Functions that implement calculation algorithms for derived measurements:*

- (a) `TrueAirspeed()`
- (b) `WindProcessor()` to calculate wind from basic measurements
- (c) `AirTemperature()` to calculate ambient temperature
- (d) `DPfromE()` to get the dew point temperature from the water vapor pressure
- (e) `PCorFunction()` to correct pressure measurements for the static defect
- (f) and others

3. *Convenience functions for plots:*

- (a) `plotTrack()` for a simple flight track
- (b) `plotWAC()` and `lineWAC()` to generate plots
- (c) `skewT()` to construct a skew-T thermodynamic diagram

4. *Utilities for handling and examining data:*

- (a) `makeNetCDF()` to make a new netCDF file from a data.frame
- (b) `TellAbout()` to list characteristics of variables
- (c) `ValueOf()` to look up values from the data.frame
- (d) `getAttributes()` to see the original netCDF attributes

5. *Miscellaneous functions for analysis:*

- (a) `DemingFit()` to minimize the perpendicular distance of points from a line
- (b) `LagrangeInterpolation()`
- (c) `binStats()` to aid in constructing error-bar or bar-and-whisker plots

6. *Functions to improve measurements:*

- (a) `CorrectPitch()`, `CorrectRoll()` to improve measurements of pitch and roll
- (b) `CorrectHeading()` to improve measurements of heading

When data.frames are created, global attributes in the netCDF file become attributes of the generated data.frame and variable attributes in the netCDF file are associated with column variables in the data.frame. Other information in the netCDF file is also stored with the data.frame, so the data.frame becomes a full representation of the netCDF file and complete netCDF files can be re-generated from the data.frames. However, usually data.frames are generated with only subsets of the data needed for particular analysis routines. They therefore can be small and suitable for archiving with analysis projects to document the data as used for the project.

Because these functions are assembled into an R package, they each have associated usage information. This wiki is intended to provide additional information regarding the basis for the algorithms used, the limitations of the functions, and more general documentation. Some of the functions (will) have their own pages for this information.

This manual includes an introductory set of sections that discuss R and how to use it for data analysis. This is intended to be tutorial information, focused on the applications to aircraft data, and some of the information is also specific to uses on NCAR/EOL computers, so Sections\_2–4 can be skipped by those who already are comfortable with R. Section 5 is the central discussion of Ranadu. Section 6 is mostly advocacy for using these routines and other capabilities of R to make analyses reproducible by others, and Sect. 7 presents a brief discussion of how these routines can be used for data-quality review during field projects.

## 2 Introduction to R

The very limited intent here is to provide a brief context in R for using the Ranadu package. There are many books, tutorials, and web resources that provide complete information on R, including the manuals available via R itself. Therefore, this and the following few chapters are provided only to get a reader started with R and to illustrate some of the analysis tasks that are possible.

### 2.1 Getting access: Some recommended set-up work

This section will guide you through obtaining R (if necessary), RStudio (which I recommend but which isn't essential), and the Ranadu package itself. I'm going to use `tikal.eol.ucar.edu`, a linux machine, for these illustrations. R and RStudio are available on `tikal`, so if you have access to that machine these are already installed and maintained. However, you may also want them on your own machines or laptop.

The central repository for R is CRAN (`CRAN`)<http://cran.r-project.org/>, the Comprehensive R Archive Network. That page has links for downloading versions for Windows, Mac, and linux. For RStudio, you can download from <http://www.rstudio.com/products/RStudio/>. Or submit a support request to EOL/SIG to have R and RStudio installed. To run R (without RStudio) on `tikal` or any linux machine where it is installed, just type "R" into a terminal window<sup>1</sup> and you get the classic command-line interface that has been in use since at least 1998. To start an RStudio session on `tikal`, point a web browser to `tikal.eol.ucar.edu`. You must be inside the UCAR firewall, or use VPN, and you will have to sign in using your EOL name and password.

My suggestion for getting started is this:

1. Make a new directory "RStudio" in your EOL workspace or on the machine you will use, named '~/.RStudio'. You can do this using a terminal or using the RStudio interface; for the latter,
  - (a) click the 'Files' tab in the lower right pane
  - (b) use the 'New Folder' item just below that tab to create the new folder named 'RStudio' under your home directory.
2. On `tikal`, if that is where you will be running, Ranadu is already installed, so you can save some set-up steps by copying this line into a file named `.Renvirom` in your home directory on that system:  
`R_LIBS=~/.cooperw/R/x86_64-redhat-linux-gnu-library/3.2"`  
This provides access to the Ranadu package. Subsection XXX below describes how to download your own copy, and that may be preferable to using the above link because it will be more straightforward to maintain and update your own copy.

---

<sup>1</sup>To exit, type "quit()"; reply 'n' to 'save workspace' for now.

3. Start RStudio; for tikal, you can use the link above; otherwise just type “rstudio”.
4. Go to Tools -> Global Options -> R General
  - (a) enter ‘~/RStudio’ (without quotes) in the line that says “Default Working Directory”
5. Go to Sweave under the same window
  - (a) in the top where it says “Weave Rnw files using:”, select ‘knitr’. You may get a message saying knitr is not available if you are not on tikal; in that case, knitr will be added to the available packages when you follow the steps in subsection XXX.
6. Go to “Git/SVN” under the same window
  - (a) check “Enable version control”. This is very useful and will be the best way to stay current with the Ranadu package, which is installed and maintained there.
7. For other options, the defaults are probably reasonable to start, so click “OK” to save the options.
8. Optionally, make a new project called RSessions for the purpose of this tutorial:
  - (a) Go to the ‘File’ menu and select ‘New Project’
  - (b) Select ‘Version Control’
  - (c) Select ‘Git’
  - (d) Use this repository name: <https://github.com/WilliamCooper/RSessions.git> .
  - (e) Give the project the name ‘RSessions’ and create it as a subdirectory of ‘~/RStudio’
  - (f) At this point, RStudio will switch to windows that apply to this new project and copy from the repository into your new project.
9. If you are preparing your personal machine, you may eventually want  $\text{\LaTeX}$ , and you may need to install git, although it seems to be standard on linux and Mac machines. These are both available on tikal. If you are installing on another machine that doesn’t have them try these links: For  $\text{\LaTeX}$ , <http://miktex.org/> and for git <http://git-scm.com>.

## 2.2 A quick tour of the RStudio window panes:

If you haven’t already done this, start RStudio on your machine so you can see the windows, panes, and functions described here. You have seen the ‘Files’ window before if you followed the steps in the preceding section; click on that to see the files in RStudio/RSessions. Then, if you have followed step 8 above, click on ‘RSessionsDataFrame.Rnw’ to have something to look at. It will appear in the top left window. Don’t worry about the details of what is there just yet; we’ll get back to that. First, notice that there are four panes visible. At start-up, you will usually see these panes:

1. Top left: The source editor, where a working file (or many working files in tabs) are displayed.
2. Bottom left: The console, where you can enter R commands just as you would in the command-line mode that you would use without RStudio. Try it now: Click where the '>' prompt is displayed, type `2+2` [enter]. I use this frequently as a very capable calculator, because the math functions and R functions are all available here. Try `'pi'`, `'rnorm(5, 3.5, 0.5)'`, `plot(0:360, sin(0:360 * pi / 180), type='l')`, and `'Ranadu::WetEquivalentPotentialTemperature(P=800., AT=25., E=Ranadu::MurphyKoop (DP=20., P=800))'`.
3. Top right: This pane has several functions.
  - (a) The 'History' tab displays the history of what you have entered in the console, along with options to transfer lines either to the source editor or to the console for re-execution, possibly with editing (although that function is available more conveniently from the console using the up and down arrows to move through the history).
  - (b) Another tab will show the environment, where defined variables for your workspace are shown. [Try `X = 5` in the console and see what appears here.] There is also a useful tab for importing a data set from either a web location or a text file.
  - (c) This pane also has a 'git' tab if you have set up the project as recommended above, where you can monitor the status of what has changed since you last saved to your local repository and where you can commit back to your local repository. You can also "pull" from the github repository where appropriate (e.g., to get Ranadu updates).
4. Bottom right: Again, there are several functions.
  - (a) Plot: If you tried the examples in item 2 above, you will have noticed this pane switch to 'Plots' and display the latest plot. RStudio also maintains a history of the plots that have been generated, and you can skip back through that history, which seems endless in my experience so far. The 'export' function in the 'Plot' tab allows you to save the plot externally to either png or pdf format.
  - (b) Files: This displays the files in the working directory, which for now should be the project directory. There are a few functions for dealing with those files.
  - (c) Help: Requests for help are displayed in this window. If you click on the 'Home' button, you are taken to a page that shows links to some of the basic manuals and also a definitive definition of the R language, along with other more specialized manuals. If you want to know how a particular function works, you can enter your search phrase into the console as, for example, `?atan2` to see information on the arctangent function, or you can enter this into the entry line on the help window, which has the advantage that it displays auto-completion options as you type. [Try 'plot' to see this in action.] There are many cross-references among the help pages that are quite useful. If you click on the left drop-down menu you will see a history of the help topics you have consulted.

- (d) Viewer: I'm going to postpone discussion of this until later; you won't need the viewer for a while.
- (e) Packages: This displays the packages that are available for your use, either in the system-wide repository or in your personal repository. To test if you have access to Ranadu, look for 'Ranadu' in the list of packages. If it is there, let your mouse linger over it and its location will be displayed. You could try this for other packages also; check, for example, ggplot2, a very useful and standard plotting package not yet part of the EOL repository. The check boxes indicate which packages will be available in your session without special loading; if unchecked, you can either check the box or include a statement similar to `require(Ranadu)` in your session (or when you use these functions, use the form `Ranadu::routine_you_want`). The 'install' and 'update' functions at the top of the 'Packages' pane provide easy access to the 'CRAN' archive of packages or to packages you may have from other sources that you want to load for use. There is a very extensive set of packages available via CRAN. If you need something new, check there to see if someone has already provided a package for the task you need.

## 2.3 Getting the 'Ranadu' package

For use on `tikal.eol.ucar.edu`, a procedure suggested in the first section of this memo should provide access to my package of routines for use with RAF netCDF files. Here are steps for obtaining that package on other systems.

You may first need to install some packages on which it depends. Ranadu uses these packages: R (version  $\geq 2.10$ ), `ncdf4`, `maps`, `ggplot2`, `ggthemes`, `grid`, `tcltk`, `nleqslv`, `reshape2`, `zoo`, `fields`, `stats`, and `signal`. You will also want `knitr` if you want to combine text and R code in files that generate documents, as described in a later section. If any of these are missing, they can be installed by clicking 'Install' at the top of the 'Packages' pane of RStudio, selecting 'repository (CRAN)' in the first drop-down menu, and entering a list of packages that you are missing in the second line labeled 'Packages'. The default location for local libraries on the last line should be kept, and the check-box labelled 'Install dependencies' should be checked. Click 'Install' and those packages should be downloaded from the CRAN repository, compiled where necessary, and added to your list of packages.

Then to get the package 'Ranadu', follow these steps:

1. Within RStudio, select 'File' -> 'New Project' -> 'Version Control' -> 'Git' (clone a repository)
2. For the package URL, enter '`https://github.com/WilliamCooper/Ranadu.git`' (without the quote marks). Use the package name 'Ranadu' and make the directory for it a subdirectory under 'RStudio'.
3. Click 'Create Project' and RStudio will download the files and change the working project to Ranadu.

4. Go to the 'Build' window in the top-right pane and click 'Build & Reload'. You may get an error listing missing dependencies if any required packages are unavailable. In that case, return to the above description of how to install packages and install the missing dependencies.
5. The package 'Ranadu' should appear in your list of packages.

## 3 R objects, with focus on the data.frame

### 3.1 Some basic objects

#### vector

The fundamental objects we will deal with the most is the vector. This is an indexed set of quantities, which can be numeric (double, integer), logical, character, or some other less common types. Vectors are 'atomic' if they consist all of the same type; 'generic' vectors can have mixed types, but I won't deal much with them. Vectors can have only one element, which would be called a scalar in other languages, but scalars in R are just vectors with one element. Vectors have a length property [try `length(x)`] but not a dimension property: Try the following:

The '`<-`' operator above is the R assignment operator. It is mostly equivalent to the '=' operator from other languages, and '=' can usually be used in place of this operator, but it does have the clarity of indicating that the variable on the left is assigned the value of the quantity on the right. The operator '`->`' can also be used, but usually will result in rather confusing code.

#### list

A list resembles an atomic vector but can have mixed types. Lists also have additional ways of selecting elements, e.g., by character name. Lists are generic vectors, but when I talk about vectors I'll almost always be talking about atomic vectors.

#### array

A special vector-like object is the array or matrix. These are like vectors but with an assigned dimension so that, in the two-dimensional or matrix case, the vector is a vector of columns in a matrix. The dimension can be single-valued, but more often there are at least two dimensions. R convention is column-major format (like FORTRAN but opposite to C); i.e., the row index represents adjacent values in the underlying vector (items that lie vertically in the conventional display of a matrix) so that for example `z[1,1]` and `z[2,1]` are adjacent in the underlying vector and aligned vertically in a display of the matrix. The first index in a two-dimensional array can be thought of as specifying the row and the second the column; all rows in a particular column

appear together. You can construct an array from a vector by assigning it a dimension via `'dim(x) <- c(dim1, dim2)'` as in the following example,<sup>2</sup> which also illustrates the column-major structure and the effect of transposing the array using `t()`:

(Note that `'#'` indicates the the remainder of the line is a comment.) This works well for arrays constructed from our netCDF files because the time index can be thought of as the row index and each column represents a vector of measurements of a particular variable.

## data.frame

A `data.frame` is a named list of vectors and resembles a matrix or a spreadsheet. For example, it may consists of columns each representing a variable and rows that are the time sequence of observations of that variable. Applied to RAF data files, it may have a structure like this:

Time	ATX	PSXC	WDC	WSC	...
15:00:00	-25.1	410.8	275.4	25.4	...
15:00:01	-25.1	410.9	275.2	25.6	...
15:00:02	-25.2	411.1	275.4	25.5	...
15:00:03	-25.1	411.1	275.1	25.7	...
15:00:04	-25.0	411.2	275.3	25.3	...
...	...	...	...	...	...

All columns must be of the same length, but they may contain different types of variables (Time, character, numeric, logical). Like a spreadsheet, the columns can be assigned names like the header in this table. Rows can also be assigned names, but in the absence of special assignment they will default to the character names `'1'`, `'2'`, `'3'`, `'4'`, ... and can be addressed by an index that is the first in a two-index specification; i.e., `D[500, 10]` represents the 10th variable as measured at the 500-th time in the dataframe.

Let's get an example. Included with Ranadu is a sample `data.frame` named `RAFdata` that contains a short sample of measurements from a research flight.

```
require(Ranadu, quietly = TRUE, warn.conflicts = FALSE)
names (RAFdata)

## [1] "Time" "ATTACK" "SSLIP" "GGVEW" "GGVNS" "GGVSPD" "VEW"
## [8] "VNS" "ATX" "DPXC" "THDG" "ROLL" "PITCH" "PSXC"
## [15] "QCXC" "EWX" "RTH1" "RTH2" "ADIFR" "BDIFR" "TASX"
## [22] "GGALT" "LATC" "LONC" "PLWC" "CONCD" "WDC" "WSC"

Ranadu::getStartEnd (RAFdata)

## [1] 201000 201500
```

<sup>2</sup>Want your original vector back? Use `x <- as.vector(x)`



`names()` is a standard R function that lists the names associated with an object, so here it lists the names of the variables in the `data.frame`. `getStartEnd()` is a Ranadu function that returns the start and end times in the `data.frame`. The leading `'Ranadu: '` is not necessary here because the package is loaded, but these notes will tend to include that superfluous header to highlight which parts of the code refer to the Ranadu package. The lines above starting with `'##'` are the output from the R code in the listing. The first few rows and first few columns in the `data.frame` `'RAFdata'` look like this:

```
##           Time  ATTACK      SSLIP  GGVIEW  GGVNS
## 9721 2013-10-01 20:10:00 1.999224 -0.1875578 53.44360 226.5322
## 9722 2013-10-01 20:10:01 1.943987 -0.1734225 53.57179 226.9628
## 9723 2013-10-01 20:10:02 1.981951 -0.1649992 53.69322 227.4117
## 9724 2013-10-01 20:10:03 1.993126 -0.1854287 53.81462 227.8630
## 9725 2013-10-01 20:10:04 1.996357 -0.1891418 53.94920 228.2795
## 9726 2013-10-01 20:10:05 1.987496 -0.1899927 54.07005 228.7055
## 9727 2013-10-01 20:10:06 1.996506 -0.1594946 54.18315 229.1384
## 9728 2013-10-01 20:10:07 1.989084 -0.1842116 54.26129 229.5390
## 9729 2013-10-01 20:10:08 1.994024 -0.1646231 54.33908 229.9423
## 9730 2013-10-01 20:10:09 1.989765 -0.1765334 54.41174 230.3561
```

The `'Time'` variable is a special-format variable in POSIX format, discussed later when the Ranadu access functions are described. The first item in each row is the row name, seldom used but here a remnant from the index in the original `data.frame` from which this subset was extracted. Having the time variable in this format is particularly convenient when examining time series of measurements, as will be described later.

## 3.2 Working with data.frames

### Addressing elements of a data.frame

You can address particular elements in many ways, using syntax like the following:

```
RAFdata$ATX[5]

## [1] -36.71588

RAFdata[5, 2]           # note the [row,column] syntax

## [1] 1.996357

RAFdata[5, ]
```

```
##           Time   ATTACK   SSLIP   GGVIEW   GGVNS   GGVSPD
## 9725 2013-10-01 20:10:04 1.996357 -0.1891418 53.9492 228.2795 -0.58602
##           VEW     VNS      ATX      DPXC      THDG      ROLL      PITCH
## 9725 54.11258 228.2388 -36.71588 -50.19225 2.978105 0.3509116 1.760113
##           PSXC    QCXC      EWX      RTH1      RTH2      ADIFR      BDIFR
## 9725 301.8117 126.1786 0.06180029 -12.34667 -12.4678 -13.82708 -0.7944382
##           TASX    GGALT    LATC    LONC    PLWC CONCD      WDC      WSC
## 9725 223.3128 9424.435 44.99973 -101.271 8.453611      0 262.9346 42.98902

RAFdata[5, "ATX"]           # using " or ' to surround text is usually equivalent

## [1] -36.71588

RAFdata$ATX[1:10]

## [1] -36.77266 -36.77094 -36.75904 -36.73860 -36.71588 -36.70886 -36.69385
## [8] -36.68116 -36.71080 -36.72738

RAFdata$ATX[Ranadu::getIndex(RAFdata, 201105)]

## [1] -36.58235

RAFdata$ATX[RAFdata$Time == as.POSIXct("2013-10-01 20:11:05", tz='UTC')]

## [1] -36.58235
```

(`getIndex()`) is part of Ranadu and provides a convenient way to determine the data.frame index that corresponds to a specified time.)

## Creating subsets of a data.frame

New data.frames that contain subsets of original data.frames can be created using logical vectors. For example:

```
RAFdata[RAFdata$TASX < 213, "TASX"]

## [1] 212.9421 212.9741 212.9477

RAFdata[Ranadu::setRange(RAFdata, 201210, 201215), c(1, 6:10)]
```

```
##           Time      GGVSPD      VEW      VNS      ATX      DPXC
## 9851 2013-10-01 20:12:10 -10.78104 57.81869 243.1800 -33.63138 -54.88298
## 9852 2013-10-01 20:12:11 -10.80652 57.80622 243.0562 -33.50258 -54.90860
## 9853 2013-10-01 20:12:12 -10.88169 57.78197 242.9372 -33.42321 -54.71121
## 9854 2013-10-01 20:12:13 -10.89062 57.74649 242.8225 -33.37087 -55.01767
## 9855 2013-10-01 20:12:14 -10.89485 57.71845 242.7063 -33.28124 -54.75344
## 9856 2013-10-01 20:12:15 -10.81118 57.69278 242.5950 -33.20294 -54.59950
```

Another useful subset is that omitting all missing-variable rows from the data.frame:

```
RAFdataNoNA <- na.omit(RAFdata)
```

However, be careful using this and other subsetting commands because if the time sequence has gaps some functions like 'setRange()' won't work, although plots will just skip the missing values. When it is necessary to omit missing values (e.g., for filtering), it is best to do other subsetting before using the na.omit() function.

### Adding or changing variables in a data.frame

You can operate on variables in the data.frame, changing values, and you can add new variables to the data.frame as follows:

```
# wind component from the east:
RAFdata$UEW <- RAFdata$WSC * sin (RAFdata$WDC * pi / 180)
summary (RAFdata$UEW)


##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
## -44.64  -43.67  -42.66  -41.73  -38.79  -38.01
```

A few comments on this example may be useful. The function summary() provides a quick indication of the range of a variable and also includes an indication of the number of missing elements (having the R value NA). The assignment equivalently could have been made to RAFdata['UEW']. The standard math functions in R include the 'sin()' function used here, but it takes an argument in radians so the wind direction is multiplied by pi/180 to convert from the wind direction WDC in degrees. "pi" is always available, and R makes no distinction between the numerical values "180." and "180" so the decimal point that would be used in many other languages is superfluous here.

### Simple plots


Let's plot something, using 'plotWAC()' from Ranadu for convenience, although you can try the standard 'plot ()' function from R base routines to see what changes I have made:

```
Ranadu::plotWAC(RAFdata$Time, RAFdata$GGVSPD, ylab='rate of climb [m/s]')
```



It is also useful to define special data.frames for constructing plots, especially when using the more advanced plotting capabilities provided by 'ggplot2'. To see a simple scatterplot, you can use the following:

```
D <- RAFdata[, c("ATX", "GGALT")]
plot(D, pch=20)           # pch=20 plots small solid dots
## equivalent to:
plot(RAFdata[, c("ATX", "GGALT")], pch=20)
```



```
## or to  
plot (subset (RAFdata, , c(ATX, GGALT)), pch=20)
```

You may find the last form attractive because it avoids the need to type the quote marks in the second form, and those quote marks can seem tiresome in extended strings. Exercise: See what happens if you instead include three variables in the preceding plot, e.g., by adding DPXC.

## Exporting to Excel

If you have the `xlsx` package available, you can create an Excel spreadsheet with the data:

This can be very convenient for those who are comfortable working with the features of Excel spreadsheets, and this is also a convenient way to examine `data.frames`.

## 4 Some basic operations in R

### 4.1 Using the RStudio console as a calculator

The standard R interface or the console pane in RStudio (the lower left pane) can be used as a convenient calculator, and it is possible to do some simple programming interactively. As a simple example, let's find the roll angle for a 3-min turn (i.e., a turn through  $360^\circ$  in 3 minutes). If the airspeed is  $v$ , the radius of the turn is  $r$ , the acceleration of gravity is  $g$ , the time taken for a turn through  $2\pi$  radians is  $T$ , and the roll angle is  $\phi$ , then

$$\frac{v^2}{r} = g \tan \phi$$

is the required horizontal acceleration and the distance flown around the turn is

$$2\pi r = vT$$

so

$$\phi = \arctan\left(\frac{2\pi v}{gT}\right)$$

Here is an evaluation in R:

```
v <- 220          ## do the calculation for a flight speed of 220 m/s
g <- 9.8          ## acceleration of gravity in m/s^2
T <- 3 * 60
phi <- atan (2 * pi * v / (g * T)) * (180 / pi) ## convert to degrees
print (sprintf ("required roll angle is %.1f degrees", phi))

## [1] "required roll angle is 38.1 degrees"
```

The console is often very useful for exploring aspects of data. For example, after running R scripts, the R objects remain available in the working environment and can be examined, plotted, or otherwise used in exploratory analysis.

### 4.2 Some math conventions

Here the focus is on what might seem different to those experienced in other programming languages.

## Operator precedence

- `::` `$` `[ ]` `PEU:MDAS`  
`::` references a package and has highest precedence  
`$` references a column of a `data.frame` (for example)  
`[ ]` are used for subsetting operations  
`P` denotes parentheses  
`E` denotes exponentiation (see below)  
`U` denotes the unary operators `'-'` and `'+'` when used to indicate signs  
`:` is an operator that generates sequences  
`%%` operators include the modulus operator and some others like `%/%`  
`M,D` denote multiplication and division and have equal precedence so are evaluated in order  
`A,S` denote addition and subtraction and are equal in precedence.
- Here are some special cases to note:  
 In `"1:5 * 2"`, `:` has precedence so you get `c(2,4,6,8,10)` not `c(1,2,3,4,5,6,7,8,9,10)`  
 The precedence of logical operators is `!` (`& &&`) (`| ||`) `xor` . Note that `&` has precedence over `|`, so for example the result of `TRUE | FALSE & FALSE` is `TRUE`.

## Operators to note:

- The exponentiation operator is `'^'`, although `'**'` is usually accepted.
- `&` and `|` are vectorized while `&&` and `||` return a single logical result.
- `%%` is the modulus operator; i.e., `8 %% 3` is 2. `%/%` gives integer division; e.g., `16 %/% 3` gives 5.
- `%in%` tests if an element is present in a vector; e.g., `"TASX" %in% names(RAFdata)`
- The function `c()` combines its arguments, usually to form a vector; e.g., `A <- c(1, 3, 6)`
- The test for equality is `'=='`, not `'='`; the latter will result in assignment.
- R does not accept operators like `'+='`, `'++'`, etc.
- The preferred values to use for the status of logical operations are `TRUE` and `FALSE`. R does not recognize `True` or `False`. It does accept `T` and `F`, but these are dangerous to use and should be avoided because you may inadvertently use `T` or `F` for variable names.

## 4.3 Vector operations

Almost everything can be accomplished using vectorized operators, and loops are seldom needed. Vectorized functions are almost always significantly faster than equivalent loops, so it is worthwhile to take advantage of vector capabilities. Here are a few examples, which you should try:

```

AT <- 2 * (RAFdata$ATX - 1)      ## for each element, subtracts 1,
                                ## then multiplies by 2
length (AT)                     ## shows that AT is a vector with 301 elements

## [1] 301

ROCsq <- RAFdata$GGVSPD^2
MACH <- Ranadu::MachNumber (RAFdata$PSXC, RAFdata$QCXC)
str (MACH)                      ## str() shows the structure of a variable

##  num [1:301] 0.719 0.72 0.722 0.723 0.724 ...

```

Here are some comments about vectorized operations:

1. Almost all Ranadu functions are vectorized, with a few exceptions (esp. where fits are required that depend on R functions that are not vectorized).
2. If vectors are supplied that have different lengths, the shorter one is recycled; this makes it possible, for example, to use calls like `MachNumber (500, RAFdata$QCXC)`.
3. Vectorized logical operators can be particularly useful for selecting subsets of data:
  - (a) To create a new data.frame that excludes periods where the airspeed is less than some limit `MinTAS`:  
`D <- Data[Data$TASX < MinTAS, ]` Note the comma; this keeps all columns but only includes rows where `TASX` exceeds the limit.
  - (b) More complex selection tests can be made by combining logical arrays; for example  
`Valid <- (Data$TASX > MinTAS) & (abs (Data$ROLL) < 4) & (Data$GGVSPD > 2)`  
`Data[!Valid, c("WDC", "WSC")] <- NA`
  - (c) Consider also the 'subset' command, for which the second argument is a logical test and the third specifies the variables to include in the subset (see `?subset` for more information):

```

D <- subset (RAFdata, RAFdata$GGVSPD > 0, c(Time, ATX, GGVSPD))
str (D)

## 'data.frame': 29 obs. of 3 variables:
## $ Time : POSIXct, format: "2013-10-01 20:10:10" "2013-10-01 20:10:11" ...
## $ ATX : num -36.7 -36.7 -36.6 -36.7 -36.6 ...
## $ GGVSPD: num 0.0557 0.0586 0.0251 0.0359 0.0864 ...

```



## 4.4 R packages

A strength of R is the extensive set of packages available to help with analysis tasks. The standard repository is called “CRAN”, although there are many packages available on GitHub also. To see the packages available on CRAN, check this URL. Most of what has been discussed to this point is in the ‘base’ package, including the math functions. Some additional frequently used functions, like ‘plot()’, are in other standard packages (in this case, ‘graphics’) and are usually available without special actions. However, others require special action like loading via the ‘require()’ or ‘library()’ functions, or access via statements like ‘packageName::function()’. A few of the packages used by Ranadu routines, and some others that have proven especially useful, are discussed in this subsection to provide some context for what capabilities they provide.

These are some of the packages referenced by Ranadu:

1. ncdf: basic netCDF functions. This package is used for access to the netCDF data files archived by NCAR/EOL/RAF.
2. ggplot2 and ggthemes: These are alternatives to the standard graphics package that provide particularly aesthetic plots.
3. stats and signal: used for interpolation and filtering of signals
4. nleqslv: solve non-linear equations (used e.g. by DPfromE())
5. maps: provides state or national boundaries for maps
6. fields: used by the skewT-generating program to average measurements in bins
7. zoo: used to replace missing values by interpolation
8. grid and reshape2: used to customize the ggplot theme

Two other packages that are particularly useful for the purposes of this manual are knitr and devtools. The former provides the ability to intermix text-generating code with R code, and so provides an important route to making analyses reproducible, as discussed later. ‘devtools’ is useful for checking and building packages and may be useful if you want to add components to a package like Ranadu.

## 5 Using the Ranadu package

### 5.1 Getting help

All functions will provide information regarding their usage in response to a ?FunctionName query in the console or the RStudio help window. (Example: ‘?getNetCDF’) In addition, in most cases

that help window provides an example that uses the 'RAFdata' data.frame and shows how results should look. These help displays should be considered the definitive information because they are more likely to remain up-to-date than is this manual.

## 5.2 The data.frame containing measurements

### Using getNetCDF

Ranadu is based on data.frames that contain subsets of data representing measurements in the NCAR/EOL/RAF netCDF data archives. The starting point therefore is to construct those data.frames. These routines assist in that task:

- `Data <- getNetCDF ( )`: loads a data.frame named Data with requested variables
- `standardVariables ( )`: defines a common set of variables for input to `getNetCDF()`
- `DataDirectory ( )`: This is system dependent and is intended to aid in portability by providing the usual location of the netCDF data files.
- `getIndex ( )`: finds the index for a specified time
- `setRange ( )`: sets a range of indices covering a specified time interval
- `TellAbout (V)`: lists some characteristics of variable V
- `Z <- getAttributes (V)`: lists the original netCDF attributes associated with V (either a data.frame or a variable in a data.frame)

The starting point will usually be `getNetCDF()`. Here is an example of how this might be used:

```
require (Ranadu, quietly=TRUE)
## try ?getNetCDF
Data <- getNetCDF (sprintf ("%s/extdata/RAFdata.nc",
                           path.package ("Ranadu")), "ALL")
dim (Data)           ## the length in seconds and the number of variables

## [1] 301  28

names (Data)         ## see the variables in Data

## [1] "Time"   "ATTACK" "SSLIP"  "GGVEW"  "GGVNS"  "GGVSPD" "VEW"
## [8] "VNS"    "ATX"    "DPXC"   "THDG"   "ROLL"   "PITCH"  "PSXC"
## [15] "QCXC"   "EWX"    "RTH1"   "RTH2"   "ADIFR"  "BDIFR"  "TASX"
## [22] "GGALT"  "LATC"   "LONC"   "PLWC"   "CONCD"  "WDC"    "WSC"
```

```
getStartEnd (Data)      ## the start and end times

## [1] 201000 201500

## try TellAbout (Data)
Z <- getAttributes (Data$ATX)

## [1] "attributes for variable"
## [1] "units: deg_C"
## [1] "_FillValue: -32767"
## [1] "long_name: Ambient Temperature, Reference"
## [1] "standard_name: air_temperature"
## [1] "Category: Atmos. State"
## [1] "DataQuality: Preliminary"
## [1] "Dependencies: 1 ATHR1"

## try str(Data)
```

If you have Ranadu installed, these and other segments of R commands should work as they do in these examples. Where there are comments that start with `## try`, you should type the command that follows, but the output is usually too large to include here.

These comment elaborate on the code in the preceding code block:

1. Using `Ranadu::DataDirectory()`: In the case shown above the path to the example netCDF data file provided with Ranadu is special and `path.package()` is used to find the file. Usually you will not load the data from this path. The function `DataDirectory()` is provided to help make routines portable among systems where the data files might be loaded in different locations. That function tries a set of possibilities and sets the returned directory to the first found. The possibilities are: `$DATA_DIR`, `"/scr/raf_data/"`, `"/home/data/"`, `"/home/Data/"`, `"/Data/"`, and  `"~/Data/"`. You may want to set your environment variable `$DATA_DIR` appropriately if one of these doesn't match your system. A typical use of `DataDirectory()` is shown in the code block that follows.
2. Using `Ranadu::standardVariables()`: In the code block shown above, "ALL" is used to load all the variables in the data file. Usually this will result in data.frames that are very large and will slow processing, and if this is done for a high-rate file you may exceed available memory, so it is better to list only the variables that you want. "`standardVariables()`" provides a basic set, and an argument to `standardVariables` like `c("VAR1", "VAR2")` can be used to add more variables. Alternately, you can just provide a list of variables that you want, as illustrated in the code block that follows.

3. Ranadu::getAttributes(): The data.frames produced by `getNetCDF()` have assigned attributes that match those in the original netCDF file, and this can be retrieved via `getAttributes()`.<sup>3</sup> The result of that call is a printed listing of attributes and creation of a list (here in Z) that contains the attributes, so it is usually preferable to assign the returned value to something to avoid the double listing that would be produced otherwise.
4. Ranadu::TellAbout() and `str()` provide some details about the characteristics of variables.

A more typical starting block of code would look like the following, listed here but not executed:

```
require (Ranadu)
Project <- "DEEPWAVE"
Flight <- "rf15"
fname <- sprintf ("%s%s/%s%s.nc", DataDirectory(), Project, Project, Flight)
## or you can provide the name via
## fname <- "/scr/raf_data/DEEPWAVE/DEEPWAVErf15.nc"
VarList <- standardVariables (c("ADIFR", "BDIFR", "CONCU_"))
## try 'standardVariables()' to see the standard list
Data <- getNetCDF (fname, VarList)
## try ?getNetCDF to see additional optional arguments to getNetCDF()
```

Some additional comments on `getNetCDF`:

1. The variable name “CONCD\_” is not a standard name, but this structure is provided to avoid the need to know the full names. Variables from probes like the UHSAS or CDP have suffixes that indicate where the probe was located on the aircraft (e.g., \_RWO for right wing outboard pylon). If a variable name is provided that ends in ‘\_’, a matching variable with a location index will be provided. The full name (e.g., “CONCU\_RWO”) can be provided if there is possibility of ambiguity, but usually this avoids the need to lookup where a probe was installed for a particular experiment.
2. The “Time” variable needs special discussion. In NCAR/EOL/RAF data files, time (except for some very old projects) is provided as an integer representing seconds after a reference time, usually 0:0:0 UTC on the day the flight started. The “units” attribute is listed as, for example, “seconds since 2014-06-06 00:00:00 +0000”. For files at rates higher than 1 Hz, the time remains integer seconds but variables are provided with additional dimensions that represent the measurements within that second. The Ranadu function `getNetCDF()` always provides “Time” as the first variable, but this is converted into POSIXct format (see `?POSIXct` in R) which is the number of seconds since the start of 1970 (UTC). Fractional values are used in cases of data rates higher than 1 Hz, giving a “flat” file. This format has the advantage that plot routines interpret times appropriately and produce appropriate labels

---

<sup>3</sup>Subsetting will often lose some attributes so special steps are needed to preserve them if that is desired.

in terms of time. To see the date and time in conventional format, use “as.POSIXlt ()” with a POSIXct-format time. This also returns a named list with names like “hour”, “min”, “sec” that you can use to create different-format representations of the time or date.

3. The optional getNetCDF argument “F” can be used to preserve the flight number, by for example providing F=15 for flight 15. This results in the addition of a new variable called “RF” to the data.frame. This is provided for cases where multiple data.frames are combined in order to facilitate analysis tasks using data that span more than one flight. If data.frames have exactly the same variables, then can be combined using the ‘rbind()’ function:

```
DataM <- rbind (Data1, Data2)
```

If flight numbers have been added, the individual flights can be retrieved by subsetting; e.g.,

```
D1 <- DataM[RF == 1, ]
```

This may be useful, for example, when finding radome sensitivity coefficients for an entire project, to check if individual flights provide outlier measurements.

4. In the netCDF files, missing values are usually indicated by the value -32767. getNetCDF converts such values to NA, the R value for missing values. is.na() will test for such values.

## Examining the measurements

Ranadu provides some functions intended for examination of the measurements. Some, “getStartEnd()”, “TellAbout()” and “getAttributes()”, were discussed above. Others include:

1. Ranadu::getIndex(Data, HHMMSS): For data.frame Data, getIndex() returns the index corresponding to the time provided by HHMMSS, which should be a time like 201213 (without : separators). Data[i, ] will then contain all the measurements at the time corresponding to HHMMSS. See the examples below.
2. Ranadu::setRange(Data, Start, End): This function returns a sequence of inclusive indices covering the period from “Start” to “End” (both provided in HHMMSS format). Data[setRange(Data, Start, End), ] will then be a subset data.frame containing all the measurements in Data for the specified period.
3. Ranadu::ValueOf(Data, V, HHMMSS): This will return the value of variable V in data.frame Data at time HHMMSS.
4. Ranadu::ValueOfAll(Data, HHMMSS): This is like “ValueOf()” but returns the values of all the measurements at the specified time.

```
RAFdata[getIndex (RAFdata, 201213), "ATX"]
```

```
## [1] -33.37087
```

```
RAFdata[getIndex (RAFdata, 201213), ]
```

```
##           Time  ATTACK      SSLIP  GGVEW  GGVNS  GGVSPD
## 9854 2013-10-01 20:12:13 1.698893 -0.1679749 57.76046 242.881 -10.89062
##           VEW      VNS      ATX      DPXC      THDG      ROLL      PITCH
## 9854 57.74649 242.8225 -33.37087 -55.01767 3.345159 -0.2978565 -1.002424
##           PSXC      QCXC      EWX      RTH1      RTH2      ADIFR      BDIFR
## 9854 320.1704 149.8021 0.03480845 -6.05707 -6.13966 -18.06383 -0.7949235
##           TASX      GGALT      LATC      LONC      PLWC  CONCD      WDC      WSC
## 9854 236.3266 9000.719 45.28072 -101.1768 8.39129      0 260.7146 44.72694
```

```
RAFdata[setRange (RAFdata, 201200, 201210), "TASX"]
```

```
## [1] 239.9797 239.5875 239.3123 239.0751 238.8636 238.4475 238.0735
## [8] 237.7671 237.5088 237.1420 237.0540
```

```
ValueOf (RAFdata, GGALT, 201200)
```

```
## [1] 9140.305
```

```
Z <- ValueOfAll (RAFdata, 201200)
```


```
##           Time  ATTACK      SSLIP  GGVEW  GGVNS  GGVSPD
## 9841 2013-10-01 20:12:00 1.666395 -0.1723428 58.18249 244.6779 -10.72564
##           VEW      VNS      ATX      DPXC      THDG      ROLL      PITCH
## 9841 58.17815 244.6206 -34.50745 -54.7943 3.396143 -0.1813508 -0.9280989
##           PSXC      QCXC      EWX      RTH1      RTH2      ADIFR      BDIFR
## 9841 313.9382 152.9558 0.03578181 -6.334847 -6.429331 -18.57253 -0.8421018
##           TASX      GGALT      LATC      LONC      PLWC  CONCD      WDC      WSC
## 9841 239.9797 9140.305 45.25227 -101.1864 8.307867      0 263.08 44.49925
```

## 5.3 Constructing plots


### Ranadu standard plot routines

Plots can always be constructed using the base graphics routines in R rather than Ranadu routines. Try the following example, which compares a standard plot to those generated by `Ranadu::plotWAC()` and `Ranadu::ggplotWAC()`. The second simply calls `plot()` with some changes in plot parameters: inward ticks, ticks duplicated on opposing axes, different time labels, etc. The third uses the “grammar of graphics” package `ggplot2` with a special theme. You can tailor any of these to meet your needs. The follow-up function `Ranadu::lineWAC()` will add lines to a previously constructed plot, but it does not modify the axis limits or add a legend so there are advantages to constructing plots using single calls to `plotWAC()` or `ggplotWAC()`.

```
plot(RAFdata[, c("Time", "GGALT")], type='l')
```




```
plotWAC(RAFdata[, c("Time", "GGALT")])
```



```
## try plotWAC (subset (RAFdata,, c(Time, GGALT))) ##note absence of " marks
```

```
ggplotWAC (RAFdata[, c("Time", "GGALT")])
```






### Other manipulations for plots

1. The `Ranadu::setRange()` function can be used to plot a limited range in time.
2. Legends are added automatically by `Ranadu::plotWAC()` and `Ranadu::ggplotWAC()`. See `?legend` for information on how to add or modify legends.
3. Many additional parameters can be used as arguments to these plotting routines, for example `"lwd=2"` or `"lty=2"` to set the line width or type. You can explore the possibilities by starting with `?par`
4. Missing values are handled in special ways in plots, as illustrated in the next code block:
  - (a) If a measurement is missing in the data.frame, plotted lines will show a gap.
  - (b) If the index itself is missing, plotted lines will connect across the gap. A subset constructed as is `R2` below omits the entire row of values when `R1$ATX` is `NA`, so the plotted blue line just connects the remaining points and shows no indication of the gap.

```
R1 <- RAFdata
R1$ATX[setRange (R1, 201100,201120)] <- NA
R2 <- RAFdata[!is.na (R1$ATX), ]
```

```
plotWAC (R2[, c("Time", "ATX")])  
lineWAC (R1$Time, R1$ATX+0.5, col='red') ## note 0.5 offset
```




## Flight tracks

The routine `Ranadu::plotTrack()` is provided to plot flight tracks on a background that shows geographic boundaries. In its simplest form it is called with a single argument of a data.frame that contains at least latitude and longitude in variables named `LATC` and `LONC`. This routine also has an option to plot the track in a reference frame that drifts with the wind. See `?plotTrack` for more information on options.

## Skew-T thermodynamic diagram

`Ranadu::SkewTsounding()` provides the capability of plotting measurements on a skew-T diagram. The diagram itself has been constructed using modern reference values for the water vapor pressure, adiabatic ascent, and air and water properties and represents a project in itself (documented in this repository). The usual usage is to average measurements of temperature and dewpoint in pressure intervals and then superimpose those measurements on the previously generated background. It is also possible to add multiple soundings to a single plot. See `?SkewTSounding` for more information. An example using the short flight segment “RAFdata” is shown below:

```
SkewTSounding (RAFdata$PSXC, RAFdata$ATX, RAFdata$DPXC)
```



## 5.4 Implementing processing algorithms

Many of the algorithms used for calculation of the variables in the netCDF data archives are available as Ranadu functions. These may be useful during data analysis for checking how values might change with different algorithms or to apply the algorithms to new measurements. The processing algorithms are documented in a Technical Note available at this URL. The Appendix lists the Ranadu functions and, under references, notes those that represent descriptions in that technical note.

A few will benefit from additional description, but these are only a select set of the algorithm routines:

1. Two functions, `CorrectPitch()` and `CorrectHeading()`, provide corrections to the measurements of pitch, roll, and heading. They are based on detection of the errors in INS measurements that result in discrepancies between those measurements and measurements from

GPS. These are the basis for a manuscript that is accessible from this GitHub repository. For example, an error in pitch results in the acceleration of gravity being rotated into a false component of horizontal acceleration, and this causes a false derivative in the INS-provided ground speed components. This can be detected by comparing to the GPS-provided measurements, so a correction is possible. Similarly, an error in heading results in the accelerations measured in the aircraft reference frame being transformed erroneously into Earth-relative accelerations, so again comparison to GPS can provide an estimate of this error. These two Ranadu functions provide estimates of those errors and can be used to improve the measurements. These are not part of standard NCAR/EOL/RAF data processing.

2. The function `MurphyKoop()` provides the water vapor pressure in equilibrium at a specified temperature. `MurphyKoopIce()` provides the equilibrium water vapor pressure relative to a plane ice surface. References are provided in the technical note.
3. Equivalent potential temperature can be calculated via three different formulas:
  - (a) `RossbyEquivalentPotentialTemperature()`: The original Rossby formulation
  - (b) `BoltonEquivalentPotentialTemperature()`: The Bolton revision, used in many earlier data archives and still retained as the variable THETA\_E
  - (c) `EquivalentPotentialTemperature()`: The Davies-Jones formula, leading to the variable THETA\_P (for pseudo-adiabatic equivalent potential temperature) now in standard archives. This is now the favored calculation. It uses the Murphy-Koop values for equilibrium water vapor pressure and otherwise represents the favored equation for analysis, as discussed in the technical note.
4. `WindProcessor()` replicates the code for calculation of wind that is represented in RAF Bulletin 23 (except for the omission of a small term representing the motion of the INS relative to the aircraft during turns). It can be used to calculate wind from new sets of measurements, as for example is needed for new sensors of the relative wind or for corrected attitude angles resulting from the first item above.
5. `XformLA()` transforms a vector as measured in the aircraft coordinate system to one in an Earth-relative coordinate system, or vice versa.
6. `KingProbe()` calculates the liquid water content measured by a CSIRO (King) sensor with drift removed by reference to a cloud-droplet spectrometer like a Cloud Droplet Probe. This duplicates the algorithm used for data processing. It is useful because it may be preferable to change the characteristics of the updating and the relationship between Nusselt number and Reynolds number used in this processing.
7. `PCorFunction()` provides the correction for static defect developed in this reference. That has led to significant improvement in the measurements of pressure, airspeed, and temperature, as described in that reference.

8. `StandardConstant()`, `Gravity()` and `SpecificHeats()` return the values of various constants used in processing, as listed in the section on defined constants in the technical note. For example, some of the constants available are the molecular weights of water and of air, the universal gas constant, the angular rotation rate of the Earth, and Avogadro's constant, among others.

## 5.5 Some Ranadu utilities

Some of the Ranadu functions that are provided to implement tasks that may be useful are described here:

1. `binStats()` is intended to bin measurements and then compute averages and standard deviations in bins, as might be needed for constructing error-bar plots or soundings vs. height or pressure.
2. `SmoothInterp()` interpolates to fill regions with missing values and then filters the result to obtain a smoothed variable.
3. `ShiftInTime()` moves variables forward or backward in time to support shifting variables that are sampled at different times.
4. `makeNetCDF()` makes a netCDF file from a data.frame, provided it has the required characteristics (dimensions, attributes, etc.) If a data.frame is constructed by `getNetCDF()`, it is usually possible to construct the corresponding netCDF file that will have the originally selected subset of variables from the original file.
5. `LagrangeInterpolate()` implements standard Lagrange interpolation.
6. `DemingFit()` provides a fit that minimizes the perpendicular distance from points to a line, as is appropriate when comparing measurements when neither is known to be a standard.

## 6 Using R for reproducible data analysis

### 6.1 Key steps toward reproducibility

There is a growing and beneficial trend toward documentation of research and analysis in ways that permit others to check, duplicate, and extend the work. In R, the package 'knitr' has made a substantial contribution toward that goal by making it possible to blend the text of a document with the R code that generates the results, as discussed in the next subsection. A minimum set of actions toward reproducibility might include these steps:

1. Use of data from public repositories where the data files are assigned DOI numbers and where there is a commitment to long-term preservation and public access.

2. Use of programs, similarly archived and associated with a DOI number where possible. When these programs generate the final document while containing the R code and accessing the original data, they will be reproducible by others.
3. A workflow and/or provenance document describing the steps taken in the analysis project. This goes beyond what is in the code, and it should help those trying to understand the code by providing context and intent for various steps. For example, how were the data collected and by whom, how were they processed before being used in this analysis, what approaches were tried and rejected or abandoned, how does control flow through the program and through any subprograms, how was the final document reviewed and archived, and who are the appropriate contacts for the data, analysis, and interpretation? A good workflow document can be of great aid to someone who wants to repeat the analysis, because snippets of code can be difficult to understand and the reasons for the steps in a program are often obscure.

As an example of one attempt, see the work-in-progress that is contained in this GitHub repository: <https://github.com/WilliamCooper/AMTD-AAC>.

These principles can also be applied to smaller analysis projects that might need to be repeated. For an example of the latter, the following will describe one use of R and Ranadu to determine appropriate empirical coefficients relating the pressure difference measured between radome ports to the flow angle perpendicular to those ports. This is a common task needed for the measurement of vertical or horizontal wind, and the empirical coefficients may change, for example when the radome is replaced or even re-installed after removal or when sensors are placed in locations that might affect the airflow around the aircraft. The document is this memo giving the recommended empirical coefficients, and it was generated by this program file which combines the R code and  $\text{\LaTeX}$  commands that produced the memo. At the end of the memo there is an appended section called “Reproducibility” that contains these entries:

Reproducibility:	
PROJECT:	WI-HIPPO1
ARCHIVE PACKAGE:	WI-HIPPO1.zip
CONTAINS:	attachment list below
PROGRAM:	AKRDforHIPPO1.Rnw
THIS DOCUMENT:	AKRDforHIPPO1.pdf
WORKFLOW::	WorkflowFindAKRDcal.pdf
ORIGINAL DATA:	/scr/raf_data/HIPPO/HIPPO-1rf01.nc etc
DATA ARCHIVE:	NCAR HPSS (not github)
GIT:	<a href="https://github.com/WilliamCooper/Reprocessing.git">https://github.com/WilliamCooper/Reprocessing.git</a>
Attachments:	AKRDforHIPPO1.Rnw
	AKRDforCSET.pdf
	WorkflowFindAKRDcal.pdf
	SessionInfo

The content of some of these items is as follows:

- Archive package: The content of this package is given by the attachment list, and it is located in the repository listed as the last item. The actual address is this URL.
- Program: The listed program produces the document and contains the R code. It uses 'knitr' as discussed in the next subsection.
- Workflow: In this case the workflow description is a general description of the task, with some discussion of the application to the HIPPO-1 project.
- Original data and Data archive: In this case the original data are in temporary files on EOL computer systems. The reprocessing task to which this document contributes was underway at the time this was written, and those files may change or change location. Therefore a separate archive was constructed that consists of the data.frames used in this analysis. Those are saved on the NCAR HPSS. (They tend to be larger than seems appropriate to place on github.) At this time, these datasets have not been assigned DOI numbers, but the underlying data archive eventually will meet this requirement.
- Attachments: A "SessionInfo" section is included. This is the result of the R command 'sessionInfo()' and includes information like the R version, platform, operating system, packages used, etc.

## 6.2 Using knitr

As for R itself, this manual will only give very sketchy information regarding the use of knitr, but this may help readers of the 'Rnw' files. This manual itself is constructed from the file 'Ranadu-Manual.Rnw' in which the R examples and the descriptive code are merged. The file is basically a  $\text{\LaTeX}$  file into which segments of R code called 'chunks' have been inserted. There is also an alternate format, 'Rmd', in which the text is html (markdown) instead of  $\text{\LaTeX}$ . In that format, the chunks have a different but similar format. In the Rnw format, chunks are set apart from other  $\text{\LaTeX}$  prose by headers and trailers that have this format:

```
<<chunk-name, chunk options>>=
[R code]
@
```

Results contained in R variables can be referenced in the  $\text{\LaTeX}$  part of the document using the 'Sexpr{ }' command, and plots can be referenced by a label corresponding to the chunk-name and will be placed in the document at an appropriate location. In the case of this manual, the first chunk has this content:

```
<<initialization,echo=FALSE,include=FALSE>>=
library(knitr)
opts_chunk$set(echo=FALSE, include=FALSE, fig.lp="fig:")
opts_chunk$set(fig.width=6, fig.height=5, fig.pos="center",
               digits=4)
thisFileName <- "RanaduManual"
require(Ranadu, quietly = TRUE, warn.conflicts=FALSE)
@
```

This loads the knitr library, sets some options, and loads the Ranadu package. Here is a small example of how R calculations and text can be merged:

```
<<knitr-example-1, echo=FALSE, include=TRUE>>=
meanTemperature <- mean (RAFdata$ATX)
sdTemperature <- sd (RAFdata$ATX)
@
```

The mean and standard deviation of temperature is  $-31.33 \pm 4.98$ , placed here using the command `\Sexpr{meanTemperature}` where the first number appears and `\Sexpr{sdTemperature}` for the second.


For more information on using knitr, see the resources at the end of this manual.

## 7 An example: Data quality review

During field projects, monitoring data quality is essential so that problems can be found and corrected to minimize data loss. One approach to this has been to set up an R script that constructs plots of key measurements that can be reviewed quickly after flights. These plots are constructed from the preliminary netCDF files produced in the field, and in recent projects they have been stored in the field catalog for projects where they are available to all personnel in the project as well as for documentation after the project.

A flowchart for the Review() program, constructed using the 'DiagrammeR' package for R, is shown below:





1. Project preparation: This only needs to be done once at the start of a project:

- (a) Data files by convention are in a directory with the project name and have names beginning with the project name, so “Project” should be set appropriately.
- (b) There is a ‘Configuration.R’ file that is read by Review(), and it has sections for each project. A new section should be added that provides the variables used by the various plots. A template from recent projects can be a good starting point. If runs terminate with messages that variables are not present in the data files, the project configuration should be modified to omit those variables. There is a list of what is plotted by each plot function in the program, so that can help determine what variables are appropriate for the different entries in ‘Configuration.R’.
- (c) The plot functions used by Review() are located in the directory ‘PlotFunctions’ and have names like RPlot15.R. There is a model in that directory, named RPlotModel.R, that can be used as a starting point for adding new plots, and the existing plots also can be used as starting points for new plots. Usually no new plots will be needed, and it may be best to get started with the available plots and add others as needed.
- (d) The default list of plots for the project also should be defined. It may be useful to skip some plots, e.g., to skip the display of CDP size distributions in cases where no CDP is used in the project.

2. Initialization: This may involve interactive entry of information or entry via the ‘Rscript’ method of running Review(). See the comments near the start of the program for information on optional methods for running and providing the needed information.

- (a) Each run processes an individual flight, so the flight number must be provided.
- (b) An individual-run set of plots can be provided, or the default set can be accepted.

- (c) The program will read the appropriate section of 'Configuration.R' for the project and construct a list of the variables needed.
  - (d) The data file is then read and the needed variables are returned in a data.frame.
3. pdf-format and html-format plots: The program produces plots in two formats, a PDF format that can be magnified without loss of resolution and an html format that is much smaller and faster to read and transfer. For each, it loops through the plot routines, loading them from 'PlotFunctions' if they are needed then running them with appropriate variables. The result will be two files named PROJECTrfixPlots.pdf and PROJECTrfixPlots.html.

## 8 Additional resources

These are some resources that have proven useful in constructing and using the Ranadu package. Almost all of the analyses reported here were performed using R (R Core Team [2013]), with RStudio (RStudio [2009]) and knitr (Xie [2013, 2014]). The "ggplot2" package (Wickham [2009]) was used for some figures. The effort to make these results reproducible benefited greatly from the work represented in these analysis tools, especially that provided by Y. Xie. The book by C. Gandrud (Gandrud [2014]) and material and presentations related to the "Geoscience Paper of the Future" (<http://www.ontosoft.org/gpf/>) also had a strong influence on the approach to this work. For those wanting more advanced information about R, consider Wickham [2014].

## References

- C. Gandrud. *Reproducible Research with R and RStudio*. CRC Press, Boca Raton, FL, USA, 2014. ISBN 13:978-1-4665-7284-3.
- R Core Team. *R: A language and environment for statistical computing*. R Foundation for Statistical Computing, Vienna, Austria, 2013. URL <http://www.R-project.org>.
- RStudio. *RStudio: Integrated development environment for R (Version 0.98.879)*, 2009. URL <http://www.rstudio.org>.
- H. Wickham. *ggplot2: elegant graphics for data analysis*. Springer New York, 2009. ISBN 978-0-387-98140-6. URL <http://had.co.nz/ggplot2/book>.
- H. Wickham. *Advanced R*. Chapman & Hall/CRC The R Series. Taylor & Francis, 2014. ISBN 9781466586963. URL <https://books.google.com/books?id=PFHFNAEACAAJ>.
- Y. Xie. *Dynamic Documents with R and knitr*. Chapman and Hall/CRC, Boca Raton, Florida, 2013. URL <http://yihui.name/knitr/>. ISBN 978-1482203530.

Y. Xie. *knitr: A general-purpose package for dynamic report generation in R*, 2014. URL <http://yihui.name/knitr/>. R package version 1.6.

– End of Memo –

## Appendix

name	purpose	reference <sup>4</sup>
AdiabaticT-andLWC	For adiabatic ascent, calculates the temperature and liquid water content at specified levels	
AirTemperature	Implements the algorithm for calculating ambient air temperature from measurements, with inclusion of the correction for dynamic heating	[a] Section 4.4
binStats	A convenience function for binning measurements of one variable in bins of another, then calculating means and standard deviations for the bins. Useful for constructing error-bar plots.	
BoltonEquivalent-PotentialTemperature	Calculates equivalent potential temperature using the Bolton equation	[a] Sect. 4.6
calcAttack	A function that returns the angle of attack that would be present in the absence of vertical wind. Useful for determining sensitivity coefficients for the angle of attack	[b] Sect.
ComplementaryFilter	A duplication of the filter used in original processing that combined low-pass measurements from GPS and high-pass measurements from an inertial system to provide a representation of wind that has the long-term stability of GPS combined with the fast response of an inertial system	[a] Sect. 3.4; [b] Sect.
CorrectHeading	Estimate the error in measured heading based on comparison of accelerations in the body frame and Earth reference frame, the latter measured by GPS.	[c] Sect.
CorrectPitch	Estimates the error in measured pitch based on the Schuler oscillation as represented by the difference between ground speeds measured by GPS and by the inertial system providing the measurement of pitch.	cf. this presentation,; [b] Sect.; [c] Sect.
DPfromE	Given the water vapor pressure, calculates the dew point. Uses the Murphy-Koop representation of equilibrium water vapor pressure as a function of temperature.	[a] Sect. 4.5
DataDirectory	A convenience function providing the directory in which data reside on different systems, so that code can be written that is portable among systems. (May need modification for new systems.)	

<b>name</b>	<b>purpose</b>	<b>reference<sup>5</sup></b>
DemingFit	Implements a fit that minimizes the distance between points and a fitted line, treating pairs of measurements equally in the fit (in contrast to standard regression, treating one as a function of the other)	special ref.
Equivalent-PotentialTemperature	An implementation of the Davies-Jones (2009) formula for pseudo-adiabatic equivalent potential temperature, the THETAP variable in RAF netCDF files	[a] Sect.4.6
getAttributes	List the attributes of a data.frame or a column in a data.frame. These duplicate the attributes present in the original netCDF file.	
getIndex	Determine the index (row number) in the data.frame that corresponds to a specific time	
getNetCDF	The starting point for all these functions. Provides a data.frame consisting of specified variables and times from the original netCDF file.	
getRAFDData	A specialized routine for transfer of data using NCAR/EOL storage and ftp; not useful except for those with an NCAR/EOL computer account.	[special use]
getStartEnd	Provides the start and end times for a data.frame	
ggplotWAC	An incomplete early try at using ggplot for plots in ways similar to those provided for plotWAC below. CAVEAT: work in progress.	[special use]
GV_AOA-fromRadome	Calculates the angle of attack on the GV aircraft given the pressure measurements on the radome	[a] Sect. 4.7.1
GV_Yaw-FromRadome	Calculates the sideslip angle on the GV aircraft given the pressure measurements on the radome	[a] Sect. 4.7.1
Gravity	A representation of the acceleration of gravity as a function of latitude and altitude	[a] Section 1.3
KingProbe	Calculates the liquid water content sensed by a CSIRO (King) sensor, with correction for the power required in clear air	[a] Sect. 5.1
Lagrange-Interpolate	Standard implementation of Lagrange interpolation	
lineWAC	Following plotWAC(), lineWAC() can be used to add additional lines to the plot.	
MachNumber	From pressure, dynamic pressure, and humidity, calculate the Mach number representing the flight speed	[a] Sect. 4.7.1

<b>name</b>	<b>purpose</b>	<b>reference<sup>5</sup></b>
makeNetCDF	From a data.frame generated by getNetCDF, construct a netCDF file containing the measurements in that data.frame	
MixingRatio	Calculation of water vapor mixing ratio as implemented in the original processing	[a] Sect. 4.5
MurphyKoop	A function that provides the equilibrium water vapor pressure as a function of temperature, following the formulation of Murphy and Koop (2005), with optional "enhancement factor" arising from the ambient pressure	[a] Sect. 4.5
MurphyKoopIce	Similar to MurphyKoop but for equilibrium over ice	[a] Sect. 4.5
ncsubset	Simple subsetting routine for netCDF files. Uses ncks, and ncks could be used directly to do the same thing.	[special use]
PCorFunction	The pressure-correction functions applied to NCAR aircraft to account for the static defect in measured pressure and dynamic pressure	[a] Sect. 4.3
plotTrack	Plot a flight track on a simple representation of geographic boundaries, with an option to plot the track in a coordinate frame drifting with the wind. (Better looking flight tracks can be constructed using the .kml files provided by EOL/RAF.)	
plotWAC	A convenience function that calls base-R plot() with some tailoring of the parameters of the call. See also lineWAC.	
PotentialTemperature	Standard calculation of potential temperature, with an option to apply a correction for moist air properties	[a] Sect. 4.6
PressureAltitude	Standard formula for pressure altitude, International Standard Atmosphere	[a] Sect. 3.3
RecoveryFactor	The formulas used to correct temperature sensors for the effect of dynamic heating.	[a] Sect. 4.4
RosbyEquivalent-PotentialTemperature	Implementation of the original Rossby formula for equivalent potential temperature. See also BoltonEquivalentPotentialTemperature and EquivalentPotentialTemperature for other representations.	[a] Sect. 4.6
setRange	Generate a sequence of indices that spans a specified time range, for constructing plots that cover specified periods	

<b>name</b>	<b>purpose</b>	<b>reference<sup>5</sup></b>
setVariableList	Displays a GUI with variables from a netCDF file, displaying those selected for inclusion in a data.frame and allowing interactive addition and subtraction of variables	[special use]
ShiftInTime	Shifts a variable forward or backward in time to improve timing matches among measurements	
SkewTSounding	Plot measurements of temperature and humidity on a skew-T background. The background was generated by code outside this package, and plots are superimposed on that background. It was generated with modern representation of equilibrium water vapor pressure (Murphy and Koop, 2005) and using full entropy-preserving trajectories with specific heats and gas constant dependent on humidity, and was checked by comparison to the formula of Davies-Jones (2009), so the plot may differ in minor ways from standard plots. A separate github repository, WilliamCooper/SkewT.git, contains the code that generated the background.	
SmoothInterp	Interpolate to fill missing values and smooth via a Savitzky-Golay filter	
SpecificHeats	A representation of the specific heats and gas constant for moist air	[a] Sect. 4.4, pp. 37–38
StandardConstant	Returns a value or set of values as used in processing data from research aircraft	[a] Sect. 1.3
standardVariables	A standard set of variables that can be included in a call to getNetCDF, with optional addition of more variables	
TellAbout	Simple functions to describe R objects and attributes of measurements.	
theme_WAC	A ggplot2 theme used by WAC; others may prefer the standard theme for most uses.	[special use]
TrueAirspeed	The standard equation for true airspeed in terms of Mach number and temperature	[a] Sect. 4.7
ValueOf	Quick look-up of values in the data.frame	
ValueOfAll	Like ValueOf but for all measurements in the data.frame at a specified time	
VirtualTemperature	Standard calculation of virtual temperature	[a] Sect. 4.6
Virtual-PotentialTemperature	Standard calculation of virtual potential temperature, with optional adjustment of the specific heats and gas constant for moist air.	[a] Sect. 4.6

<b>name</b>	<b>purpose</b>	<b>reference<sup>5</sup></b>
WetEquivalent-PotentialTemperature	The wet-equivalent potential temperature as defined by Paluch (1978); see also Emanual (1994).	[a] Sect. 4.6
WindProcessor	An implementation of the calculation of wind from basic measurements, incorporating transformations among reference frames and combination of the relative wind and the ground track to obtain wind with reference to the Earth coordinate system	RAF Bulletin 23
XformLA	Transform a vector from the aircraft reference frame to the local Earth-relative (ENU) frame, or v.v.	

## Reproducibility:

**PROJECT:** RanaduManual  
**ARCHIVE PACKAGE:** RanaduManual.zip  
**CONTAINS:** attachment list below  
**PROGRAM:** RanaduManual.Rnw  
**ORIGINAL DATA:** /scr/raf\_data/  
**WORKFLOW:** WorkflowRanaduManual.pdf  
**GIT:** <https://github.com/WilliamCooper/Ranadu.git>

**Attachments:** RanaduManual.Rnw  
RanaduManual.pdf  
SessionInfo