

ON THE GROUND 1-6

- ☐ **1 Ground:** the house number, then a wide shot of each of the 4 sides.
- ☐ **2 Window screens + AC fins** (dents or tears show hail and its direction).
- ☐ **3 Soft metals:** vents, flashing, gutter straps.
- ☐ **4 Gutters/downspouts:** round dings; granules inside the gutter.
- ☐ **5 Siding, storm side first.** Vinyl: cracks, chips, round holes. Fiber cement: chipped paint and hairline cracks (look closely).
- ☐ **6 Chalk-circle every hit BEFORE the photo.**

! SAFETY

BEFORE YOU CLIMB

- ◆ 3-point contact
- ◆ Never wet, icy or windy roofs
- ◆ A harness above ~6:12
- ◆ Tell someone before you climb and when you're down

LADDER + ROOF 7-10

- ☐ **7 Ladder:** level ground, 3-point contact, extending ~3 ft above the roofline.
- ☐ **8 Roof:** check pitch and wetness first. Harness above ~6:12; skip if wet, icy, mossy or windy.
- ☐ **9 One 10×10 ft test square per slope,** away from trees; circle and count the hits (~8+ per square on 2+ slopes is often treated as damage, but it varies by insurer: **record the count, not a verdict**).
- ☐ **10 Photo each square:** wide (with slope label) → medium → close-up with a coin or tape for scale.

HAIL VS NOT HAIL

HAIL Random round hits, soft bruise, granules knocked off in a crater.

BLISTERING Small bubbles spread evenly, no bruise, from heat/age.

WEAR / MECHANICAL Linear scuffs near valleys, vents and foot paths.

VINYL Needs ~1"+ hail; the cracks are sharp, unlike wavy age cracks.

FIBER CEMENT Needs ~1.5"+ hail; match it with dents on metal on the same side.

DESDE EL SUELO 1-6

- ☐ **1 Suelo:** el número de la casa, luego una foto amplia de cada uno de los 4 lados.
- ☐ **2 Mallas de ventana + aletas del aire acondicionado** (las abolladuras o rasgaduras muestran el granizo y de qué lado vino).
- ☐ **3 Metales blandos:** ventilas, flashing (tapajuntas), ganchos de las canaletas.
- ☐ **4 Canaletas/bajantes:** golpes redondos; gránulos de las tejas dentro de la canaleta.
- ☐ **5 Siding, primero el lado de la tormenta.** Vinyl: grietas, despostilladas, hoyos redondos. Fibrocemento: pintura saltada y grietas finitas (mira de cerca).
- ☐ **6 Marca cada golpe con un círculo de gis ANTES de la foto.**



SEGURIDAD

ANTES DE SUBIR

- ◆ 3 puntos de apoyo
- ◆ Nunca en techos mojados, con hielo o con viento
- ◆ Arnés arriba de ~6:12
- ◆ Avísale a alguien antes de subir y cuando ya bajaste

ESCALERA + TECHO 7-10

- ☐ **7 Escalera:** piso parejo, 3 puntos de apoyo, que sobresalga ~3 pies arriba de la orilla del techo.
- ☐ **8 Techo:** primero revisa la inclinación y si está mojado. Arnés arriba de ~6:12; no subas si está mojado, con hielo, con musgo o con viento.
- ☐ **9 Un cuadro de prueba de 10×10 pies por cada agua del techo,** lejos de los árboles; encierra y cuenta los golpes (~8+ por cuadro en 2+ aguas muchas veces se toma como daño, pero cambia según la aseguradora: **anota el número, no un veredicto**).
- ☐ **10 Foto de cada cuadro:** amplia (con el nombre del agua) → mediana → de cerca con una moneda o cinta métrica para la escala.

GRANIZO O NO

GRANIZO

Golpes redondos al azar, moretón suave, gránulos arrancados en forma de cráter.

AMPOLLAS

Burbujitas repartidas parejo, sin moretón; por el calor o la edad.

DESGASTE / MECÁNICO

Raspones en línea cerca de los valles, las ventilas y por donde se camina.

VINIL

Necesita granizo de ~1"+; las grietas son limpias, no onduladas