

# The Long Short Term Memory (LSTM) layer

The "vanilla" Recurrent Neural Network (RNN) layer that we introduced was powerful but somewhat limited

- It suffered from gradients that vanished or exploded
- It's memory tended to be short-term
- Unable to capture dependencies that were too far separated in time

Researchers developed advanced Recurrent Network layer types to address these specific issues.

The *Long Short Term Memory* (LSTM) layer is one such example.

# The importance of selectively forgetting

An RNN layer, at time step  $t$

- Takes input element  $\mathbf{x}_{(t)}$
- Updates latent state  $\mathbf{h}_{(t)}$
- Optionally outputs  $\mathbf{y}_{(t)}$

according to the equations

$$\begin{aligned}\mathbf{h}_{(t)} &= \phi(\mathbf{W}_{xh}\mathbf{x}_{(t)} + \mathbf{W}_{hh}\mathbf{h}_{(t-1)} + \mathbf{b}_h) \\ \mathbf{y}_{(t)} &= \mathbf{W}_{hy}\mathbf{h}_{(t)} + \mathbf{b}_y\end{aligned}$$

where

- $\phi$  is an activation function (usually  $\tanh$ )
- $\mathbf{W}$  are the weights of the RNN layer
  - partitioned into  $\mathbf{W}_{xh}$ ,  $\mathbf{W}_{hh}$ ,  $\mathbf{W}_{hy}$
  - $\mathbf{W}_{xh}$ : weights that update  $\mathbf{h}_{(t)}$  based on  $\mathbf{x}_{(t)}$
  - $\mathbf{W}_{hh}$ : weights that update  $\mathbf{h}_{(t)}$  based on  $\mathbf{h}_{(t-1)}$
  - $\mathbf{W}_{hy}$ : weights that update  $\mathbf{y}_{(t)}$  based on  $\mathbf{h}_{(t)}$

RNN

Latent state  $h_{(t)}$  is

- A *fixed length* encoding of the variable length input sequence  $[\mathbf{x}_{(1)} \dots \mathbf{x}_{(t)}]$
- All essential information about the prefix of  $\mathbf{x}$  ending at step  $t$  is recorded in  $\mathbf{h}_{(t)}$

$\mathbf{h}_{(t)}$  is charged with several tasks

- Determining the time  $t$  output  $\mathbf{y}_{(t)}$  (for a many to many RNN)
- Determining the next latent state  $\mathbf{h}_{(t+1)}$

But is each and every element  $\mathbf{x}_{(t')}$  needed for both these tasks?

Probably not.



Consider sequence  $\mathbf{x}$  as frames in a movie.

- Is every detail of the early scenes of a movie
- Relevant to the final scene ?

It would be very powerful

- To be able to "forget" synthetic features that are **no longer** relevant
- And *selectively* update **immediately relevant** features
- While leaving unchanged those features needed **far in the future**

This is where the "gates" ( if , switch/case ) of Neural Programming are relevant.

They will be used in an LSTM

- To determine ("gate") when an individual feature in latent state  $\mathbf{h}_{(t)}$  "forgets" (reset)
- To determine which individual features in latent state  $\mathbf{h}_{(t)}$  get updated at step  $t$

# Conclusion

The LSTM is an advanced Recurrent Neural Network (RNN) layer type.

The "gating" mechanism of Neural Programming will be key.

It will endow the LSTM with

- The ability to forget a feature
- Selectively update other features

This will allow the LSTM to mitigate the drawbacks of "vanilla" RNN layers

- Short term memory
- Vanishing/Exploding gradients

In [2]: `print("Done")`

Done