

Using Principal Components to understand a Neural Network

Principal Components Analysis (PCA) is a *dimension reduction* technique

- Transforms an example with many, correlated features
- Into an example with fewer, independent features

A feature map of a Convolutional Neural Networks (CNN) is big

- Single feature in a map
- But at *many* spatial locations
- Which may be highly correlated

The advantage of PCA is

- Its ability to be able to express the data in smaller dimension
- Ordering of the synthetic features it creates (the components)

It is common to apply PCA to layer 0: the input \mathbf{x} .

This can be used to find clusters of examples that have common input properties.

But one can apply PCA to *any* layer, where the synthetic properties may be more complex.

PCA will be used to find *clusters* of examples

- That produce a similar feature map k at layer l

We will reduce the large spatial dimension

- To a smaller dimension
- Retaining only the "most important" locations

If we can identify a property that is common to all examples in the cluster

- We can interpret feature map k of layer l as implementing the feature

"Is the property present in the input?"

PCA of Feature Maps

It is hard to find clusters when objects are of high dimension

- With so many dimensions
- Any distance measurement tends to be large even for similar objects
- Because the number of *irrelevant* elements
- May be larger than the number of relevant elements

Consider a feature map $\mathbf{y}_{(l), \dots, k}$ with spatial dimension (1000×1000)

- A typical image size
- Two examples have a dog in the center
- Surrounded by much different backgrounds

If the number of spatial locations in the background is much larger than the region containing the dog

- Then these two similar examples
- Have large distance
- Due to the different, but irrelevant, backgrounds

We can use *dimensionality* reduction techniques of Classical Machine Learning.

One such technique is Principal Components Analysis

- Find a small number of synthetic features
- That express commonalities of many examples
- Represent an example in a synthetic feature space
- Of reduced dimensions

In this case: we are reducing the number of spatial locations

Here is a two layer Neural Network that we built to classify digits in the MNIST dataset

MNIST CNN

We perform PCA on the representations produced by the first Convolutional Layer (dark vertical line)

- Plotting each example
- Using the two most important synthetic features (components) as coordinates in the plot

MNIST CNN Conv1 PCA

Clusters are starting to appear.

Do these clusters give us a clue as to the property that the layer is representing ?

- Left to right: strong vertical ("1", "7") to less vertical ?
- Bottom to top: digits *without* "curved tops" to those with tops ?

Let's perform the same analysis on the representations of the second Convolutional layer

MNIST CNN Conv1 PCA

The clusters become "more pure".

So the deeper representation

- May be finding *combinations* of input features
- That cluster similar digits

So we might be able to interpret what the first two Convolutional Layers are representing

- Without necessarily understanding what the second layer is doing in isolation

In [4]: `print("Done")`

Done