

## 1. The Generic Swapper (The Basics)

**Goal:** Create a utility method that can swap the values of two variables of any type.

- **Task:** Write a static class Utils with a generic method Swap<T>.
- **Requirement:** The method should take two parameters by reference (ref) and swap their values.
- **Test Case:** Try swapping two int values, then two string values.

## 2. The Simple Box (Constraints)

**Goal:** Build a container that only holds "Reference Types" (classes), not "Value Types" (like int or structs).

- **Task:** Create a class `Box<T>`.
- **Constraint:** Use the `where T : class` constraint.
- **Challenge:** Add a method `void PrintType()` that prints the name of the type `T` to the console. Why does `Box<int>` fail to compile?

### 3. Circular Buffer (Data Structures)

**Goal:** Implement a fixed-size Circular Buffer (or Ring Buffer) using generics.

- **Task:** Create a class `CircularBuffer<T>` with a private array of size `N`.
- **Logic:** \* `Push(T item)`: Adds an item. If the buffer is full, it overwrites the oldest item.
  - `T Pop()`: Returns and removes the oldest item.
- **Constraint:** Ensure the class handles any data type.

#### 4. The Result Wrapper (Real-world API Design)

**Goal:** Create a standardized way for methods to return either a success value or an error message.

- **Task:** Create a class `Result<T>`.
- **Properties:**
  - `T Data`: The actual value returned on success.
  - `bool IsSuccess`: Whether the operation worked.
  - `string ErrorMessage`: Detailed info if it failed.
- **Logic:** Add two static methods: `Result<T>.Success(T data)` and `Result<T>.Failure(string message)`.

## 5. Generic Repository Pattern (Advanced)

**Goal:** Simulate a database repository that works with any entity that has an Id.

- **Task:** 1. Define an interface IEntity with a property int Id. 2. Create a class Repository<T> where T must implement IEntity and have a parameterless constructor (new()).
- **Methods:** \* void Add(T entity)
  - T GetById(int id) (Use a List<T> internally to store items).
- **Constraint:** where T : class, IEntity, new()

## Quick Syntax Refresher

- If you get stuck on the syntax for constraints, remember the pattern:

C#



```
public class MyGenericClass<T> where T : IEnumerable, new()
{
    // T must be a collection AND have a public parameterless constructor
}
```