
Spock Workshop



© 2020 D2iQ, Inc. All Rights Reserved.



Ken Sipe

Distribute Application
Engineer

Apache Mesos Contributor

Apache and CNCF Committer, Open DCOS

Developer: Embedded, C++, Java, Groovy, Grails, Scala,
GoLang, Python

 @KenSipe

© 2020 D2iQ, Inc. All Rights Reserved.

2



Spock

First Officer and Science Officer

Vulcan Nerve Pinch, Mind Meld, “imperturbable,
logical, intelligent, and had pointed ears”

 @cmndrspock

 @spockframework

© 2020 D2iQ, Inc. All Rights Reserved.

3

Agenda

- Testing
- Spock Basics
- Spock Mocking
- Advanced Spock

Code Intensive Talk

<https://github.com/kensipe/spock-workshop>



Spock Intro



Spock is...

testing framework...

based on Groovy

fully compatible with JUnit

result of learnings from

- RSpec, BDD, JUnit

JUnit


JUnit 5

© 2020 D2iQ, Inc. All Rights Reserved.

Taxonomy of JUnit

```
public class SimpleInterestCalculatorJUnitTest extends TestCase {  
    InterestCalculator interestCalculator;  
  
    protected void setUp() throws Exception {  
        interestCalculator = new SimpleInterestCalculator();  
        interestCalculator.setRate(0.05);  
    }  
  
    public void testCalculate() {  
        double interest = interestCalculator.calculate(10000, 2);  
        assertEquals(interest, 1000.0);  
    }  
  
    public void testIllegalCalculate() {  
        try {  
            interestCalculator.calculate(-10000, 2);  
            fail("No exception on illegal argument");  
        } catch (IllegalArgumentException e) {  
        }  
    }  
}
```

Pain Points?



Verbose!!!

There was a time when I only survived because I made myself write out three pages of words in the morning. Pen to paper: no coming up for air until there were three full pages, and don't you dare read them, no. No re-reading until at least a month has gone by. The whole idea came from Julie Cameron and her Artist's Way book. I never really got past the first or second chapter, but they sure served me well. Well that survival may have been mostly just an emotional one, but still, I survived. I was the wreck of the Titanic. My grandma taught me that phrase. I should call her. Some days I pull out those old survival pages and re-read them. I laugh at myself. I say, "hmmmm." I say, "I'm glad I made myself articulate those days." And then I stuff them back into the old manila envelope where I stack them, three pages by three. And I wonder, where were those words before I wrote them all down? Maybe they were crouched behind wells of tears, or hiding behind walls of jealousy. Maybe they were shaking hands with old memories, and trying to teach them some rather unimpressive breakdance moves. I'm not certain. But it always felt better to write them down. Some days it had the effect of standing on the edge of an oceanic cliff and screaming for ten minutes. Other days I could hardly see through my tears, and snotted all over the page. Some days I had to write, "blah blah blah I don't know what to write about this morning" for six lines before I realized I had six pages of things to dislodge in my mind. I have friends who don't care for words. And I have friends who are enamored by them. I have friends who treat them cheaply. I have friends who don't know how well they play with them. And I have friends who have so many words locked up in them. I think that there is a lot more most of us need to say. But we're not sure if there's enough time to let the children out to play. We're not sure if our neighbor is safe enough to watch them, yet. Maybe tomorrow, we say. I think a wise old man once said that there is time for words and there is a time for silence, or something like that. A time for war and a time and for peace, a time to embrace and a time to refrain. I think that's the one. I like that in the beginning, there was the Word. I think I underestimate how much of a wordsmith God really is.

Repetitive and Repetitive



Refactoring Nightmare



THAT IS ENTIRELY

ILLOGICAL

GROOVY

Taxonomy of GroovyTest Case

```
class SimpleInterestCalculatorGTest extends GroovyTestCase {

    def interestCalculator;

    protected void setUp() throws Exception {
        interestCalculator = new SimpleInterestCalculator(rate: 0.05)
    }

    public void testCalculate() {
        double interest = interestCalculator.calculate(10000, 2)
        assertEquals interest, 1000.0
    }

    public void testIllegalCalculate() {
        shouldFail {
            interestCalculator.calculate(-10000, 2)
        }
    }
}
```

Groovy Power Assert

Condition not satisfied:

```
interest == calc.calculate(amt, year)
      |   | |
      25.0 | |    20.0 100 4
            | com.math.SimpleInterestCalculator@606e1dec
            false
```

Groovy Power Assert

Condition not satisfied:

```
interest == calc.calculate(amt, years)
      |   | |
  25.0 | | 20.0 100 4
        | com.math.SimpleInterest
        false
```



Groovy Improvements

- Concise, Clear and Readable
- Promote “user” thinking
 - context
 - stimulus
 - expectations
- Productivity

Spock

Spock

- Programmers Environment
 - Groovy
- Promotes Clarity
 - structural blocks
 - removes noise

Why use Spock?

- Expressive testing language
- Easy to learn
- Usable from unit to end-to-end
- Leverages Groovy
- Runs with JUnit Runner
 - IDE
 - CI

Taxonomy of a Spec

First Spec

```
import spock.lang.Specification

class MyFirstSpec extends Specification {

    //fields
    //fixture methods
    // feature methods
    // helper methods
}
```

Terms

Specification

- compare to TestCase or GroovyTestCase
- Instructs JUnit to run with **Sputnik** (JUnit runner)

Fields

- initialized for each “test”
- think “setup”
- not shared between feature methods

More Fields

```
@Shared res = new VeryExpensiveResource()
```

- Shared
 - Setup once
 - think setupSpec()
- statics
 - only use for constants

Fixture Methods

```
//fixture methods
def setup() {}           // run before every feature method
def cleanup() {}         // run after every feature method
def setupSpec() {}       // run before the first feature method
def cleanupSpec() {}     // run after the last feature method
```

- before / after a feature
- before / after a spec
- optional

Feature Methods

- “heart” of spec
- four phases
 - setup the features fixture
 - provide stimulus to system
 - describes the response
 - clean up

```
// feature methods
def "pushing an element on the stack"() {
    // blocks go here
}
```

Blocks

given:	preconditions, data fixtures
when:	actions that trigger some outcome
then:	makes assertions about outcome
expect:	short alt to when & then
where:	applies varied inputs
and:	sub-divides other blocks
setup:	alias for given
cleanup:	post-conditions, housekeeping

Blocks

- setup

- must be first
- must be the only
- no special semantics
- label is optional
- label given: is an alias

```
setup:  
def stack = new Stack()  
def elem = "push me"
```

```
given: "setup and initialization of ..."  
def stack = new Stack()  
def elem = "push me"
```

When / Then Blocks

- used together
 - possible to have many per feature
- then restrictions
 - conditions
 - exception conditions
 - automatic asserts
 - interactions
 - variable defs

```
when: // stimulus
stack.push(elem)

then: // response
!stack.empty
stack.size() == 1
stack.peek() == elem
```

Conditions

when:
stack.pop()

then:
thrown(EmptyStackException)
stack.empty

when:
stack.pop()

then:
EmptyStackException e = thrown()
e.cause == null

- checking for exceptions

Throwing an Exception NOT!

```
def "HashMap accepts null key"() {  
    setup:  
        def map = new HashMap()  
  
    when:  
        map.put(null, "elem")  
  
    then:  
        notThrown(NullPointerException)  
}
```

Mocks and Expectations

```
def "events are published to all subscribers"() {
    def subscriber1 = Mock(Subscriber)
    def subscriber2 = Mock(Subscriber)
    def publisher = new Publisher()
    publisher.add(subscriber1)
    publisher.add(subscriber2)

    when:
    publisher.fire("event")

    then:
    1 * subscriber1.receive("event")
    1 * subscriber2.receive("event")
}
```

Cleanup on Feature X

- cleanup block
 - only followed by a where block
 - no repeats

```
def "setup and cleanup example"() {  
    setup:  
        def file = new File("/some/path")  
        file.createNewFile()  
  
        // ...  
  
    cleanup:  
        file.delete()  
}
```

Where Blocks

- last in a method
- no repeats
- used for data-driven features

```
def "computing the maximum of two numbers"() {  
    expect:  
        Math.max(a, b) == c  
  
    where:  
        a << [5, 3]  
        b << [1, 9]  
        c << [5, 9]  
}
```

Helper Methods

- either return a boolean
- or
- assert

```
def "offered PC matches preferred configuration"() {  
    when:  
        def pc = shop.buyPc()  
  
    then:  
        matchesPreferredConfiguration(pc)  
    }  
  
    // helper methods  
    def matchesPreferredConfiguration(pc) {  
        pc.vendor == "Sunny" && pc.clockRate >= 2333  
    }  
  
    void matchesPreferredConfiguration(pc) {  
        assert pc.vendor == "Sunny"  
        assert pc.clockRate >= 2333  
    }  
}
```

Demo Basics

Specification Functions

- and Spock.lang.*

- old()
- thrown() / notThrown
- with {}

Spock.lang.* Documentation

@Title
@Narrative
@Issue
@See
@Subject

Spock.lang.* Ignoring Stuff

@Requires
@IgnoreIf
@Ignore
@IgnoreRest

Built-in Extensions: AutoCleanup


```
@AutoCleanup  
@AutoCleanup('dispose')  
@AutoCleanup(quite=true)
```

Built-in Extensions: Timeout

```
@Timeout  
@Timeout(10)  
@Timeout(value=10,  
unit=TimeUnit.MILLISECONDS)
```

Mocking with Spock

Mocks Aren't Stubs



The screenshot shows a web browser displaying Martin Fowler's website. The title bar reads "Mocks Aren't Stubs". The page header features a black banner with "MARTIN FOWLER" in white. Below the banner is a navigation menu with links to "Intro", "Design", "Agile", "Refactoring", "NoSQL", "DSL", "Delivery", "About Me", "ThoughtWorks", and social media icons for RSS and Twitter. The main content area has a dark background with a landscape image. The title "Mocks Aren't Stubs" is prominently displayed in large, bold, purple letters. A descriptive paragraph follows, explaining the concept of mock objects. Below the paragraph is a horizontal line. To the left of the line, there is a sidebar with author information: "02 January 2007", "Martin Fowler", "Translations: French Italian Spanish Portuguese", and "Tags: popular · testing". To the right of the line is a "Contents" section listing various article topics. At the bottom of the page, a paragraph discusses the author's personal history with mock objects. On the right side of the page, there is a portrait photo of Martin Fowler, a man with a beard, smiling.

MARTIN FOWLER

Intro Design Agile Refactoring NoSQL DSL Delivery About Me ThoughtWorks [RSS](#) [Twitter](#)

Mocks Aren't Stubs

The term 'Mock Objects' has become a popular one to describe special case objects that mimic real objects for testing. Most language environments now have frameworks that make it easy to create mock objects. What's often not realized, however, is that mock objects are but one form of special case test object, one that enables a different style of testing. In this article I'll explain how mock objects work, how they encourage testing based on behavior verification, and how the community around them uses them to develop a different style of testing.

02 January 2007

Martin Fowler

Translations: French Italian Spanish Portuguese

Tags: popular · testing


Contents

- Regular Tests
- Tests with Mock Objects
 - Using EasyMock
- The Difference Between Mocks and Stubs
- Classical and Mockist Testing
- Choosing Between the Differences
 - Driving TDD
 - Fixture Setup
 - Test Isolation
 - Coupling Tests to Implementations
 - Design Style
- So should I be a classicist or a mockist?
- Final Thoughts

I first came across the term "mock object" a few years ago in the XP community. Since then I've run into mock objects more and more. Partly this is because many of the leading developers of mock objects have been colleagues of mine at ThoughtWorks at various times. Partly it's because I see them more and more in the XP-influenced testing



Mocks Aren't Stubs



All Rights Reserved.

Dummy

- Objects passed around
- you don't care about them
- but they are required
(parameters lists, etc.)



Fake

- Working implementations with built-in short-cuts
 - not production
 - in-memory database



All Rights Reserved.

Stub

- Objects with “canned” answers
- Some times record interactions



Rights Reserved.

Mocks

- Objects with **pre-programmed** expectations
- Testing for behavior instead of state



Solutions

Type	Tool Options
Dummy	<ul style="list-style-type: none">- developer only- objenesis
Fake	<ul style="list-style-type: none">- db options- hibernate
Stubs	
Mocks	

- Classical TDD
- Mockist TDD
- Behavior Driven Development
 - off-shoot of mockist

Faking it with Spock

Spock Mock

- Response with:
 - zero
 - null
- **is verified**

```
/**  
 * A mock object whose method calls are verified, which instantiates class-based mock objects with Objenesis,  
 * and whose strategy for responding to unexpected method calls is {@link ZeroOrNullResponse}.  
 */  
MOCK(true, true, ZeroOrNullResponse.INSTANCE),
```

Spock Stub

- Response with:
 - Empty
 - Dummy object
- is **not** verified

```
/**  
 * A mock object whose method calls are not verified, which instantiates class-based mock objects with  
 * Objenesis,  
 * and whose strategy for responding to unexpected method calls is {@link EmptyOrDummyResponse}.  
 */  
STUB(false, true, EmptyOrDummyResponse.INSTANCE),
```

Spock Spy

- Response with:
 - Delegated calls to real object
 - unless programmed to do otherwise
- is **verified**

```
/**  
 * A mock object whose method calls are verified, which instantiates class-based mock objects by calling a  
 * real constructor, and whose strategy for responding to unexpected method calls is {@link  
 CallRealMethodResponse}.  
 */  
SPY(true, false, CallRealMethodResponse.INSTANCE);
```

JMock vs. EasyMock vs. Spock

Mocking with Spock

Pick a way to Mock

```
def catalogService = Mock(CatalogService)
```

```
CatalogService catalogService = Mock()
```

```
void "test interaction scoping"() {
    given:"create mock CatalogService"
        CatalogService service = Mock()
        controller.catalogService = service
    and: "make sure it can file books"
        service.isAvailable(_ as Book) >> true

    when:"we verify isdn"
        params.isdn = book.isdn
        def result = controller.verifyISDN()

    then:"verify the book was filed"
        1 * service.inquired(_)
        result == true
}
```

```
void "test interaction scoping"() {
    given:"create mock CatalogService"
        CatalogService service = Mock()
        controller.catalogService = service
    and: "make sure it can file books"
        service.isAvailable(_ as Book) >> true
    when:"we verify isdn"
        params.isdn = book.isdn
        def result = controller.verifyISDN()
    then:"verify the book was filed"
        1 * service.inquired(_)
        result == true
}
```

Global

```
void "test interaction scoping"() {  
    given:"create mock CatalogService"  
        CatalogService service = Mock()  
        controller.catalogService = service  
    and: "make sure it can file books"  
        service.isAvailable(_ as Book) >> true  
  
    when:"we verify isdn"  
        params.isdn = book.isdn  
        def result = controller.verifyISDN()  
  
    then:"verify the book was filed"  
        1 * service.inquired(_)  
        result == true  
}
```

Local

```
void "test interaction scoping"() {  
    given:"create mock CatalogService"  
        CatalogService service = Mock()  
        controller.catalogService = service  
    and: "make sure it can file books"  
        service.isAvailable(_ as Book) >> true  
  
    when:"we verify isdn"  
        params.isdn = book.isdn  
        def result = controller.verifyISDN()  
  
    then:"verify the book was filed"  
        1 * service.inquired(_)  
        result == true  
}
```

Required

```
void "test interaction scoping"() {  
    given:"create mock CatalogService"  
        CatalogService service = Mock()  
        controller.catalogService = service  
    and: "make sure it can file books"  
        service.isAvailable(_ as Book) >> true  
  
    when:"we verify isdn"  
        params.isdn = book.isdn  
        def result = controller.verifyISDN()  
  
    then:"verify the book was filed"  
        1 * service.inquired(_)  
        result == true  
}
```

Optional

```
1 * catalogService.file(book, library) >> 'FILED'  
└─ Carnality
```

```
(0..3) * catalogService.file(book, library) >> 'FILED'
```



Carnality

```
(3.._) * catalogService.file(book, library) >> 'FILED'
```



Carnality

```
(_..3) * catalogService.file(book, library) >> 'FILED'
```



Carnality

TooFewInvocationsError

TooManyInvocationsError

```
(_..3) * catalogService.file(book, library) >> 'FILED'
```



Target Constraint

```
(_..3) * _.file(book, library) >> 'FILED'
```



Target Constraint

```
(_..3) * catalogService.file(book, library) >> 'FILED'
```



Method Constraints

```
(_..3) * catalogService./f.*/(book, library) >> 'FILED'
```



```
(_..3) * catalogService._(book, library) >> 'FILED'
```




```
(_..3) * catalogService.file(book, library) >>  
'FILED'
```



Argument List Constraint

```
(_.3) * catalogService.file(_, _) >> 'FILED'
```



Argument List Constraint

```
(_..3) * catalogService.file(*_) >> 'FILED'
```



```
(_..3) * catalogService.file(_ as Book, _) >> 'FILED'
```



Argument List Constraint

```
(_..3) * catalogService.file(_ as Book, !null) >> 'FILED'
```



Argument List Constraint

```
(_..3) * catalogService.file({it.isdn > 1}, !null) >> 'FILED'
```



Argument List Constraint

```
1 * catalogService.file(book, library) >> 'FILED'
```

Return Values



```
3 * catalogService.file(book, library) >>> ['FILED', 'ERROR']
```

Return Values



```
3 * catalogService.file(book, library) >> {  
    book.status = FILED  
    return book  
}
```

Return Values



```
3 * catalogService.file(book, library) >> {
    throw new TimeoutException()
}
```

Return Values



$(\underline{\quad} \cdot \underline{\quad}) * \underline{\quad} \cdot \underline{(\ast \underline{\quad})}$

Order Is NOT enforced

```
void "test ordered interactions"() {  
    . . .  
  
    then:"verify the book was filed"  
        1 * service.inquired(_)  
        2 * service.notifyLibrarian(*_)  
        result == true  
}
```

Order is enforced

```
void "test ordered interactions"() {  
    . . .  
  
    then:"verify an inquiry was add to the book"  
        1 * service.inquired(_)  
    then:"verify that all librarians are notified "  
        2 * service.notifyLibrarian(*_)  
        result == true  
}
```

Mocking Summary

● Creating

```
def sub = Mock(Subscriber)  
Subscriber sub = Mock()
```

● Mocking

```
1 * sub.receive("msg")  
(1..3) * sub.receive(_)  
(1.._) * sub.receive(_ as String)  
1 * sub.receive(!null)  
1 * sub.receive({it.contains("m")})  
1 * _./rec.*/("msg")
```

Interactions Summary

- Stubbing


```
sub.receive(_) >> "ok"
sub.receive(_) >>> ["ok", "ok", "fail"]
sub.receive(_) >>> { msg -> msg.size() > 3 ? "ok" : "fail" }
```

- Mocking and Stubbing

```
3 * sub.receive(_) >>> ["ok", "ok", "fail"]
```

References

- Getting Spock
 - <http://code.google.com/p/spock/>
- Source from Presentation
 - <https://github.com/kensipe/spock-workshop>



Thanks!

- @kensipe
- kensipe@gmail.com
- slack.k8s.io

