DAEKYUNG BEND
CO., LTD.

INSPECTION CERTIFICATE

(EN10204 3.1)

115, Eosil-ro, Yangsan-Si,
Gyeongsangnam-Do, Korea
TEL : 82-055-364-1800
FAX : 82-055-362-7074

Customer	(주)태양밴드	**Certificate. No.**	**YR-26-07015**
P.O. No.	**A202610150**	**Date of Issue**	**2026-10-19**
Hull No.(Project No.)	**N/A**	**Dimension & VI**	**GOOD**
Spec. for Material	**ASTM A312 TP316L**	**Spec. for Inspection**	**KS B1543 STS316L-W**

1. ITEM DESCRIPTION

DKB LOT No	Item No	Heat No	Description	Q'TY	Starting Material	NDE(RESULT)
JCQ4366	1	SD34285	R(C) S/10S 32A * 15A B.W	2	WELDED PIPE	N/A

*** Heat Treatment Condition : 1040℃ Solution Annealing & Water Quenching**

2. CHEMICAL COMPOSITION(%)

Heat No.	Spec	C	Si	Mn	P	S	Ni	Cr	Mo
	Max	0.030	1.00	2.00	0.045	0.030	14.00	18.00	3.00
	Min	-	-	-	-	-	10.00	16.00	2.00
SD34285	L	0.017	0.6	1.06	0.029	0.002	10.03	16.16	2.07

* L : Ladle Analysis P : Product Analysis

3. MECHANICAL PROPERTIES

Heat No	Unit	TENSILE TEST			HARDNESS TEST	CHARPY-V IMPACT TEST (Test Temp : ℃)		
		Y.S(0.2%)	T.S	E.L		ABSORBED ENERGY (Unit:J)		LATERAL EXP.
		MPa	MPa	%	HB	Min	AVR	Min (mm)
Spec Min		170	485	35	-	-	-	-
SD34285	L,B	285	594	50	-	-	-	-
					-	-	-	-
					-	-	-	-
					-	-	-	-
					-	-	-	-
					-	-	-	-

* L : Longitudinal, T : Transvers, B : Base Metal, W : Weld Metal

Heat No	PMI	FLATTENING	CORROSION TEST	HYDROSTATIC TEST	FERRITE	GRAIN SIZE
SD34285	GOOD	N/A	N/A	N/A	N/A	N/A

REMARK:

We certify this material has been manufactured and examined in accordance with
all requirements of the specification and the results of all examination are acceptable

HEAD OF QUALITY MANAGEMENT