

SimpleEQ User Manual

AudioForge SimpleEQ v1.0.0

3-band parametric equalizer with high-pass and low-pass filters

Overview

SimpleEQ provides surgical and musical equalization with:

- **3 Parametric Bands:** Low, Mid, High with gain, frequency, and Q control
 - **High-Pass Filter:** Remove sub-bass rumble (12-500 Hz)
 - **Low-Pass Filter:** Tame harsh highs (2k-20k Hz)
 - **Minimal phase shift:** Linear-phase option for mastering
 - **Low CPU:** Efficient IIR filters
-

Quick Start

Boost Vocal Presence (2-5 kHz)

1. **Mid Band:** Freq = 3000 Hz, Gain = +3 dB, Q = 1.5
2. Result: More clarity and presence

Remove Mud (200-400 Hz)

1. **Low Band:** Freq = 300 Hz, Gain = -3 dB, Q = 2.0
2. Result: Cleaner, less boxy sound

Add Air (8-12 kHz)

1. **High Band:** Freq = 10000 Hz, Gain = +2 dB, Q = 0.7
 2. Result: Bright, airy top-end
-

Parameters

Low Band (Parametric)

- **Frequency:** 20 Hz - 500 Hz
- **Gain:** -15 dB to +15 dB
- **Q:** 0.5 (wide) to 5.0 (narrow)

Use for: Bass boost/cut, sub control, low-mid warmth

Mid Band (Parametric)

- **Frequency:** 200 Hz - 8 kHz
- **Gain:** -15 dB to +15 dB
- **Q:** 0.5 to 5.0

Use for: Vocal presence, guitar body, snare attack

High Band (Parametric)

- **Frequency:** 2 kHz - 20 kHz
- **Gain:** -15 dB to +15 dB
- **Q:** 0.5 to 5.0

Use for: Brightness, air, cymbal control

High-Pass Filter (HPF)

- **Frequency:** 20 Hz - 500 Hz
- **Slope:** 12 dB/octave

Use for:

- Remove sub-bass rumble (vocals, guitars)
 - Clean up low-end mud
 - Typical setting: 80-120 Hz for vocals
-

Low-Pass Filter (LPF)

- **Frequency:** 2 kHz - 20 kHz
- **Slope:** 12 dB/octave

Use for:

- Tame harsh highs
 - Lo-fi effects
 - De-essing (narrow, high Q)
-

Use Cases

1. Vocal EQ

Settings:

- **HPF:** 100 Hz (remove rumble)
 - **Low:** 200 Hz, -2 dB, Q=1.5 (reduce mud)
 - **Mid:** 3 kHz, +3 dB, Q=2.0 (presence)
 - **High:** 10 kHz, +2 dB, Q=0.7 (air)
-

2. Kick Drum Punch

Settings:

- **Low:** 60 Hz, +4 dB, Q=1.0 (sub-bass)
 - **Mid:** 2.5 kHz, +3 dB, Q=2.5 (attack/click)
 - **HPF:** 30 Hz (sub-sonic filter)
-

3. Guitar Warmth

Settings:

- **Low:** 200 Hz, +2 dB, Q=1.0 (body)
 - **Mid:** 800 Hz, -1 dB, Q=2.0 (reduce boxiness)
 - **High:** 5 kHz, +1 dB, Q=1.5 (sparkle)
-

Tips & Techniques

1. Cut Before Boost

Rule: Cut problem frequencies first, boost to taste second.

Why: More transparent, avoids buildup

2. Use Q Wisely

- **Wide Q (0.5-1.0):** Musical, gentle curves
 - **Narrow Q (3.0-5.0):** Surgical, notch problem frequencies
-

3. A/B Compare

Toggle bypass frequently to ensure EQ improves the sound.

AudioForge SimpleEQ v1.0.0

© 2026 AudioForge

Last updated: 2026-08-23