

CSE 3302/5307 Programming Language Concepts

Homework 13 - Fall 2025

Due Date: Nov. 17, 2025, 9:00PM Central Time

Please include your source code file and a screenshot of execution result for each program problem in your submit.

Problem 1 - 40%

Use Ada¹ language to implement a max heap (of int type) data type by array, it should have following methods:

- empty:whether it is an empty heap
- size:return the size of the heap
- push:add a element into heap
- pop:remove the top element from heap
- top:access to the top element in heap

For testing:

- 1.push 3
- 2.push 1
- 3.push 2
- 4.call size(), print size
- 5.call top(), print result
- 6.call pop()
- 7.repeat 5
- 8.call empty()
- 9.repeat 4

¹You can use this online website: https://www.tutorialspoint.com/compile_ada_online.php

Problem 2 - 60%

Suppose we have two strings: $x = CTACCG$ and $y = TACATG$. After an alignment, we have:

1	2	3	4	5	6	7
C	T	A	C	C	$-$	G
$-$	T	A	C	A	T	G

Here “-” means empty. In order to compare the distance between two strings, we usually use edit distance. There are two kind of penalties in edit distance.

- Gap: If in alignment, we match a character with empty (such as position 1 and 6), there will be a gap penalty.
- Mismatch: If in alignment, we match a character with a different character (such as position 5), there will be a mismatch penalty.

The alignment cost C is define as:

$$C = \sum_{\text{gap pair}} \text{Gap Penalty} + \sum_{\text{mismatch pair}} \text{Mismatch Penalty}$$

Suppose in this case, the gap penalty is a and the mismatch penalty is b , then the cost for this alignment is:

$$C = 2a + b$$

In **String Similarity** problem, we want to find the minimum alignment and its cost for two strings. We can use dynamic programming to solve this problem in $O(mn)$ space and $O(mn)$ time, where m and n are the length of the string. Actually there is a better algorithm called **Hirschberg Algorithm** which can solve this problem in $O(m + n)$ space and $O(mn)$ time.

The idea of Hirschberg Algorithm is we can combine divide and conquer with dynamic programming. Suppose we have two strings: $x_{1,\dots,n}$ and $y_{1,\dots,m}$. First we divide string x into two sub strings: $x_{\text{left}} = x_{1,\dots,n/2}$ and $x_{\text{right}} = x_{n/2+1,\dots,n}$. Then we divide string y at position k into two sub strings: $y_{\text{left}} = y_{1,\dots,k}$ and $y_{\text{right}} = y_{k+1,\dots,m}$. We calculate the costs for $(x_{\text{left}}, y_{\text{left}})$ and $(x_{\text{right}}, y_{\text{right}})$ by divide and conquer.

$$C_k = C(x_{\text{left}}, y_{\text{left}}) + C(x_{\text{right}}, y_{\text{right}})$$

We traverse k from 0 to m to find the optimal k_{opt} which leads to the minimum cost.

$$k_{\text{opt}} = \min_{k=0,\dots,m} C_k$$

In this problem, you are to find the lowest alignment cost between 2 string sequences. There are only uppercase letters in strings. The mismatch penalty of two letters are the distance between their order in ASCII. For example, $\text{Distance}(A, E) = 4$. The gap penalty is fixed as 7.

- a) Implement a Hirschberg Algorithm to solve this problem with Smalltalk².
- b) Test your program with following inputs:

$$\begin{aligned}x &= CTACPG \\ y &= TACATG\end{aligned}$$

Your program should print the lowest cost and the aligned strings(add "—" into the strings to represent empty)

²You can use this online website: https://www.tutorialspoint.com/execute_smalltalk_online.php