

# Lecture 3: Challenges in Machine Learning

## DD2421

Atsuto Maki

Autumn, 2020

How should we select/determine the right model  $f$  from data?

Basic idea for classification:

Given training data

$$\mathcal{D} = \{(\mathbf{x}_1, y_1), \dots, (\mathbf{x}_N, y_N)\}$$

of inputs  $\mathbf{x}_i \in \mathbb{R}^d$  and their labels  $y_i$ .

How should we select/determine the right model  $f$  from data?

Basic idea for classification:

Given training data

$$\mathcal{D} = \{(\mathbf{x}_1, y_1), \dots, (\mathbf{x}_N, y_N)\}$$

of inputs  $\mathbf{x}_i \in \mathbb{R}^d$  and their labels  $y_i$ .

Compute the misclassification rate on  $\mathcal{D}$

$$err(f, \mathcal{D}) = \frac{1}{N} \sum_{i=1}^N \text{Ind}(f(\mathbf{x}_i) \neq y_i)$$

**Note:**  $\text{Ind}(x) = 1$  if  $x = \text{TRUE}$  otherwise  $\text{Ind}(x) = 0$

- 1 Overfitting
- 2 Cross-Validation
- 3 The Curse of Dimensionality
- 4 The Bias-Variance Trade-off
  - Concept of prediction errors
  - Decomposition of the MSE
  - Bias and variance

# Overfitting

Visited in Lecture 2 using decision tree.

# Overfitting

Visited in Lecture 2 using decision tree.

Good results on training data, but generalizes poorly.

This occurs due to

- Non-representative sample
- Noisy examples

# Overfitting

Visited in Lecture 2 using decision tree.


Good results on training data, but generalizes poorly.

This occurs due to

- Non-representative sample
- Noisy examples

## Overfitting


When the learned models are overly specialized for the training samples.



(T. Hastie et al, The Elements of Statistical Learning)




## Example: Polynomial Curve Fitting (regression to sinusoidal)



$$y(x, \mathbf{w}) = w_0 + w_1x + w_2x^2 + \dots + w_Mx^M = \sum_{j=0}^M w_jx^j$$

(C. Bishop, Pattern Recognition and Machine Learning)

## $K$ -fold cross validation (schematic for $K = 5$ )



(K. Murphy, Machine Learning – A probabilistic perspective)

- **Training set**  $T$ : to fit the models
- **Validation set**  $V$ : to estimate prediction error for model selection (i.e. to determine *hyperparameters*)

If we are in a data-rich situation:

→ partition the data into three sets, *Training set*, *Validation set*, and *Test set* for assessment of the generalization error of the final chosen model.

# Curse of Dimensionality

# Curse of Dimensionality



Imagine: inputs represented by 30 features but some of them are less relevant to target function. Will you use all of them?

# Curse of Dimensionality

Imagine: inputs represented by 30 features but some of them are less relevant to target function. Will you use all of them?



- Easy problems in low-dimensions are harder in high-dimensions
  - training more complex model with limited sample data
- In high-dimensions everything is far from everything else
  - issues in Nearest Neighbours
- Any method that attempts to produce locally varying functions in small isotropic neighbourhoods will run into problems in high dimensions.

Example 1: Normal random numbers in 1-d and 2-d  
(both plots for 100 inputs)



Too few data to represent the probability density function in 2-d.

Example 2: A subcubical neighbourhood for uniform data in a unit cube.



(T. Hastie et al, The Elements of Statistical Learning)

Graph: The side-length of the subcube needed to capture a fraction of the volume of the data (for different dimensions  $p$ ).



Intuitions in low-dimensions do not apply in high-dimensions

Intuitions in low-dimensions do not apply in high-dimensions  
Real world is in 3-d, but we deal with data for instance in 1000-d

- Uniform distribution on hypercube
- Volume of hypersphere

Intuitions in low-dimensions do not apply in high-dimensions  
Real world is in 3-d, but we deal with data for instance in 1000-d

- Uniform distribution on hypercube
- Volume of hypersphere

Techniques for dimensionality reduction / feature selection exist.

# The Bias-Variance Trade-off


# Concepts of prediction errors

Let us imagine we could **repeat** the modeling for many times – each time by gathering new set of training samples,  $\mathcal{D}$ .

The resulting models will have a **range of predictions** due to randomness in the underlying data set.

- Error due to **Bias**: the difference between the average (expected) prediction of our model and the correct value.
- Error due to **Variance**: the variability of a model prediction for a given data point between different realizations of the model.

# Graphical illustration of bias and variance



(figure source: <http://scott.fortmann-roe.com/docs/BiasVariance.html>)

# The bias-variance decomposition

Let us consider

$f(\mathbf{x})$  : true function

$\hat{f}_{\mathcal{D}}(\mathbf{x})$  : prediction function (= model) estimated with  $\mathcal{D}$

# The bias-variance decomposition

Let us consider

$f(\mathbf{x})$  : true function

$\hat{f}_{\mathcal{D}}(\mathbf{x})$  : prediction function (= model) estimated with  $\mathcal{D}$

and a conceptual tool:

$E_{\mathcal{D}}[\hat{f}_{\mathcal{D}}(\mathbf{x})]$  : average of models due to different sample sets  
(NOTE: it's shown simply as  $E[\hat{f}_{\mathcal{D}}(\mathbf{x})]$  in the sequel)



# The bias-variance decomposition

Let us consider

$f(\mathbf{x})$  : true function

$\hat{f}_{\mathcal{D}}(\mathbf{x})$  : prediction function (= model) estimated with  $\mathcal{D}$

and a conceptual tool:

$E_{\mathcal{D}}[\hat{f}_{\mathcal{D}}(\mathbf{x})]$  : average of models due to different sample sets  
(NOTE: it's shown simply as  $E[\hat{f}_{\mathcal{D}}(\mathbf{x})]$  in the sequel)

The mean square error (MSE) for estimating  $f(\mathbf{x})$

$$\begin{aligned} E_{\mathcal{D}}[(\hat{f}_{\mathcal{D}}(\mathbf{x}) - f(\mathbf{x}))^2] &= E_{\mathcal{D}}[(\hat{f}_{\mathcal{D}}(\mathbf{x}) - E[\hat{f}_{\mathcal{D}}(\mathbf{x})])^2] + (E[\hat{f}_{\mathcal{D}}(\mathbf{x})] - f(\mathbf{x}))^2 \\ &= \mathbf{Variance} + (\mathbf{Bias})^2 \end{aligned}$$

# The bias-variance decomposition

Let us consider

$f(\mathbf{x})$  : true function

$\hat{f}_{\mathcal{D}}(\mathbf{x})$  : prediction function (= model) estimated with  $\mathcal{D}$

and a conceptual tool:

$E_{\mathcal{D}}[\hat{f}_{\mathcal{D}}(\mathbf{x})]$  : average of models due to different sample sets  
(NOTE: it's shown simply as  $E[\hat{f}_{\mathcal{D}}(\mathbf{x})]$  in the sequel)

The mean square error (MSE) for estimating  $f(\mathbf{x})$

$$\begin{aligned} E_{\mathcal{D}}[(\hat{f}_{\mathcal{D}}(\mathbf{x}) - f(\mathbf{x}))^2] &= E_{\mathcal{D}}[(\hat{f}_{\mathcal{D}}(\mathbf{x}) - E[\hat{f}_{\mathcal{D}}(\mathbf{x})])^2] + (E[\hat{f}_{\mathcal{D}}(\mathbf{x})] - f(\mathbf{x}))^2 \\ &= \mathbf{Variance} + (\mathbf{Bias})^2 \end{aligned}$$

To complete, we compute:  $E_{\mathbf{x}}[E_{\mathcal{D}}[(\hat{f}_{\mathcal{D}}(\mathbf{x}) - f(\mathbf{x}))^2]]$

The mean square error (MSE) for estimating  $f(\mathbf{x})$  is **two-fold**.

The mean square error (MSE) for estimating  $f(\mathbf{x})$  is **two-fold**.  
(derivation of decomposition at the lecture)

$$\begin{aligned}(\hat{f}_{\mathcal{D}}(\mathbf{x}) - f(\mathbf{x}))^2 &= (\hat{f}_{\mathcal{D}}(\mathbf{x}) - E[\hat{f}_{\mathcal{D}}(\mathbf{x})] + E[\hat{f}_{\mathcal{D}}(\mathbf{x})] - f(\mathbf{x}))^2 \\&= (\hat{f}_{\mathcal{D}}(\mathbf{x}) - E[\hat{f}_{\mathcal{D}}(\mathbf{x})])^2 + (E[\hat{f}_{\mathcal{D}}(\mathbf{x})] - f(\mathbf{x}))^2 \\&\quad + 2(\hat{f}_{\mathcal{D}}(\mathbf{x}) - E[\hat{f}_{\mathcal{D}}(\mathbf{x})])(E[\hat{f}_{\mathcal{D}}(\mathbf{x})] - f(\mathbf{x}))\end{aligned}$$

The mean square error (MSE) for estimating  $f(\mathbf{x})$  is **two-fold**.  
(derivation of decomposition at the lecture)


$$\begin{aligned}(\hat{f}_{\mathcal{D}}(\mathbf{x}) - f(\mathbf{x}))^2 &= (\hat{f}_{\mathcal{D}}(\mathbf{x}) - E[\hat{f}_{\mathcal{D}}(\mathbf{x})] + E[\hat{f}_{\mathcal{D}}(\mathbf{x})] - f(\mathbf{x}))^2 \\&= (\hat{f}_{\mathcal{D}}(\mathbf{x}) - E[\hat{f}_{\mathcal{D}}(\mathbf{x})])^2 + (E[\hat{f}_{\mathcal{D}}(\mathbf{x})] - f(\mathbf{x}))^2 \\&\quad + 2(\hat{f}_{\mathcal{D}}(\mathbf{x}) - E[\hat{f}_{\mathcal{D}}(\mathbf{x})])(E[\hat{f}_{\mathcal{D}}(\mathbf{x})] - f(\mathbf{x}))\end{aligned}$$

Taking  $E_{\mathcal{D}}[ \dots ]$  for both sides, the cross term disappears (!)  
while the second term stays the same.


## Characterization of a classifier: Bias

**Bias of a classifier** is the discrepancy between its averaged estimated and true function

$$E[\hat{f}_{\mathcal{D}}(\mathbf{x})] - f(\mathbf{x})$$



**High-bias classifier**



**Low-bias classifier**

Low model complexity (small # of d.o.f.)  $\implies$  High-bias

High model complexity (large # of d.o.f.)  $\implies$  Low-bias

## Characterization of a classifier: Variance

**Variance of a classifier** is the expected divergence of the estimated prediction function from its average value:

$$E_{\mathcal{D}}[(\hat{f}_{\mathcal{D}}(\mathbf{x}) - E[\hat{f}_{\mathcal{D}}(\mathbf{x})])^2]$$

This measures how dependent the classifier is on the random sampling made in the training set.

# Characterization of a classifier: Variance

**Variance of a classifier** is the expected divergence of the estimated prediction function from its average value:

$$E_{\mathcal{D}}[(\hat{f}_{\mathcal{D}}(\mathbf{x}) - E[\hat{f}_{\mathcal{D}}(\mathbf{x})])^2]$$

This measures how dependent the classifier is on the random sampling made in the training set.

Low model complexity (small # of d.o.f.)  $\implies$  Low-variance  
High model complexity (large # of d.o.f.)  $\implies$  High-variance



**High variance** classifiers produce differing decision boundaries which are highly dependent on the training data.

Also called “flexible”.

Examples:

1. *decision trees*

The depth of the tree determines the variance. How?

2. *k Nearest-Neighbour*

$k$  determines the variance. How?

Our intuition may tell:

- The presence of bias indicates something basically wrong with the model and algorithm...
- Variance is also bad, but a model with high variance could at least predict well on average...

Our intuition may tell:

- The presence of bias indicates something basically wrong with the model and algorithm...
- Variance is also bad, but a model with high variance could at least predict well on average...

So the model should minimize bias even at the expense of variance??

Our intuition may tell:

- The presence of bias indicates something basically wrong with the model and algorithm...
- Variance is also bad, but a model with high variance could at least predict well on average...

So the model should minimize bias even at the expense of variance??

Not really!

Bias and variance are **equally important** as we are always dealing with a single realization of the data set.

Take home message: Match the model complexity to the **data resources**, not to the target complexity