

Kubernetec Cluster 3 Master

```
fish
# Run Master1
curl -sfL https://get.k3s.io | INSTALL_K3S_EXEC="--cluster-init --node-ip
192.168.56.10 --advertise-address 192.168.56.10 --tls-san 192.168.56.10 --
tls-san 192.168.56.11 --tls-san 192.168.56.12 --node-taint
CriticalAddonsOnly=true:NoExecute" sh -

sudo kubectl get node
sudo kubectl get node -o wide

sudo cat /var/lib/rancher/k3s/server/node-token

# Master2
curl -sfL https://get.k3s.io | INSTALL_K3S_EXEC="server --server
https://192.168.56.10:6443 --token
K1003f49ef9ef06a935efa3b41268b75202e356248eee5e5bcfd4d1556c3ae5e028::server
:d159e523a86e6396ab8ff6e95a9b2015 --node-ip 192.168.56.11 --advertise-
address 192.168.56.11 --tls-san 192.168.56.10 --tls-san 192.168.56.11 --
tls-san 192.168.56.12 --node-taint CriticalAddonsOnly=true:NoExecute" sh -

# Master3
curl -sfL https://get.k3s.io | INSTALL_K3S_EXEC="server --server
https://192.168.56.10:6443 --token
K1003f49ef9ef06a935efa3b41268b75202e356248eee5e5bcfd4d1556c3ae5e028::server
:d159e523a86e6396ab8ff6e95a9b2015 --node-ip 192.168.56.12 --advertise-
address 192.168.56.12 --tls-san 192.168.56.10 --tls-san 192.168.56.11 --
tls-san 192.168.56.12 --node-taint CriticalAddonsOnly=true:NoExecute" sh -
```