

Opti 45

TRAILER - CAR HAULER - TWO AXLES WITH OVERRUN BRAKE

VERSION: **Galvanized**



STANDARD EQUIPMENT

- Hot-dip galvanised construction
- Aluminium ramp
- Slide-in aluminium loading ramps (retractable under the platform - 1,5 m long)
- Gas springs gravity tilting ramp
- KNOTT hand winch
- Supporting wheel
- Wheel chocks
- LED lights

OPTIONAL ACCESSORIES		SPECIFICATION	
Powder-coated elements		Permissible maximum weight[kg]	2700 3000 3500
Aluminium infill		Maximum cargo capacity [kg]	2020 2300 2720
Tool box		Cargo area dimensions length x width (mm)	4500x2100
Automatic supporting wheel		Tare weight [kg]	680 700 780
AL-KO hand winch		Exterior dimensions length x width x height (mm)	6110 X 2100 X 679
Electric winch		Number and type of axle	2 BRAKED
Shock absorbers		Type of wheels	10" (13" for 3500 kg)
Single-acting hydraulic pump		Load angle	8°
Double-acting hydraulic pump			
Aluminium rear gate			
Tail lights with dynamic indicator			
Slide-in aluminium loading ramps (retractable under the platform - 2 m)			

