

# Prefix Sum

---

Arnar Bjarni Arnarson

September 21, 2025

School of Computer Science

Reykjavík University

## Range queries

- We have an array  $A$  of size  $n$ .

# Range queries

- We have an array  $A$  of size  $n$ .
- Given  $i, j$ , we want to answer:

# Range queries

- We have an array  $A$  of size  $n$ .
- Given  $i, j$ , we want to answer:
  - $\max(A[i], A[i + 1], \dots, A[j - 1], A[j])$

# Range queries

- We have an array  $A$  of size  $n$ .
- Given  $i, j$ , we want to answer:
  - $\max(A[i], A[i + 1], \dots, A[j - 1], A[j])$
  - $\min(A[i], A[i + 1], \dots, A[j - 1], A[j])$

# Range queries

- We have an array  $A$  of size  $n$ .
- Given  $i, j$ , we want to answer:
  - $\max(A[i], A[i + 1], \dots, A[j - 1], A[j])$
  - $\min(A[i], A[i + 1], \dots, A[j - 1], A[j])$
  - $\text{sum}(A[i], A[i + 1], \dots, A[j - 1], A[j])$

# Range queries

- We have an array  $A$  of size  $n$ .
- Given  $i, j$ , we want to answer:
  - $\max(A[i], A[i + 1], \dots, A[j - 1], A[j])$
  - $\min(A[i], A[i + 1], \dots, A[j - 1], A[j])$
  - $\text{sum}(A[i], A[i + 1], \dots, A[j - 1], A[j])$
- We want to answer these queries efficiently, or in other words, without looking through all elements.

# Range queries

- We have an array  $A$  of size  $n$ .
- Given  $i, j$ , we want to answer:
  - $\max(A[i], A[i + 1], \dots, A[j - 1], A[j])$
  - $\min(A[i], A[i + 1], \dots, A[j - 1], A[j])$
  - $\text{sum}(A[i], A[i + 1], \dots, A[j - 1], A[j])$
- We want to answer these queries efficiently, or in other words, without looking through all elements.
- Sometimes we also want to update elements.



## Range sum on constant array

- Let's look at range sums on a constant array

## Range sum on constant array

- Let's look at range sums on a constant array
- How do we support these queries efficiently?

## Range sum on constant array

- Let's look at range sums on a constant array
- How do we support these queries efficiently?
- Simplification: only support queries of the form  $\text{sum}(0, j)$

## Range sum on constant array

- Let's look at range sums on a constant array
- How do we support these queries efficiently?
- Simplification: only support queries of the form  $\text{sum}(0, j)$
- Notice that  $\text{sum}(i, j) = \text{sum}(0, j) - \text{sum}(0, i - 1)$

## Range sum on constant array

- So we're only interested in prefix sums

## Range sum on constant array

- So we're only interested in prefix sums
- But there are only  $n$  of them...

## Range sum on constant array

- So we're only interested in prefix sums
- But there are only  $n$  of them...
- Just compute them all once in the beginning

## Range sum on constant array

- So we're only interested in prefix sums
- But there are only  $n$  of them...
- Just compute them all once in the beginning

1	0	7	8	5	9	3



## Range sum on constant array

- So we're only interested in prefix sums
- But there are only  $n$  of them...
- Just compute them all once in the beginning

1	0	7	8	5	9	3
1						

## Range sum on constant array

- So we're only interested in prefix sums
- But there are only  $n$  of them...
- Just compute them all once in the beginning

1	0	7	8	5	9	3
1	1					

## Range sum on constant array

- So we're only interested in prefix sums
- But there are only  $n$  of them...
- Just compute them all once in the beginning

1	0	7	8	5	9	3
1	1	8				

## Range sum on constant array

- So we're only interested in prefix sums
- But there are only  $n$  of them...
- Just compute them all once in the beginning

1	0	7	8	5	9	3
1	1	8	16			

## Range sum on constant array

- So we're only interested in prefix sums
- But there are only  $n$  of them...
- Just compute them all once in the beginning

1	0	7	8	5	9	3
1	1	8	16	21		

## Range sum on constant array

- So we're only interested in prefix sums
- But there are only  $n$  of them...
- Just compute them all once in the beginning

1	0	7	8	5	9	3
1	1	8	16	21	30	

## Range sum on constant array

- So we're only interested in prefix sums
- But there are only  $n$  of them...
- Just compute them all once in the beginning

1	0	7	8	5	9	3
1	1	8	16	21	30	33

## Range sum on constant array

- So we're only interested in prefix sums
- But there are only  $n$  of them...
- Just compute them all once in the beginning

1	0	7	8	5	9	3
1	1	8	16	21	30	33

- $O(n)$  time to preprocess



## Range sum on constant array

- So we're only interested in prefix sums
- But there are only  $n$  of them...
- Just compute them all once in the beginning

1	0	7	8	5	9	3
1	1	8	16	21	30	33

- $O(n)$  time to preprocess
- $O(1)$  time each query

## Range sum on constant array

- So we're only interested in prefix sums
- But there are only  $n$  of them...
- Just compute them all once in the beginning

1	0	7	8	5	9	3
1	1	8	16	21	30	33

- $O(n)$  time to preprocess
- $O(1)$  time each query
- Can we support updating efficiently?

## Range sum on constant array

- So we're only interested in prefix sums
- But there are only  $n$  of them...
- Just compute them all once in the beginning

1	0	7	8	5	9	3
1	1	8	16	21	30	33

- $O(n)$  time to preprocess
- $O(1)$  time each query
- Can we support updating efficiently? No, at least not without modification

## Generalizing

- This works on any invertible function.

## Generalizing

- This works on any invertible function.
- If we want the product we can store the products and use  $\text{mul}(i, j) = \text{mul}(0, j) / \text{mul}(0, i - 1)$ .

# Generalizing

- This works on any invertible function.
- If we want the product we can store the products and use  $\text{mul}(i, j) = \text{mul}(0, j) / \text{mul}(0, i - 1)$ .
- This also works for multidimensional arrays, but the math is more involved.

# Generalizing

- This works on any invertible function.
- If we want the product we can store the products and use  $\text{mul}(i, j) = \text{mul}(0, j) / \text{mul}(0, i - 1)$ .
- This also works for multidimensional arrays, but the math is more involved.
- We let  $\text{sum}(x_i, x_j, y_i, y_j)$  denote the query for the sum from  $x_i$  to  $x_j$  along the  $x$ -dimension, and the same for  $y$ .


# Generalizing

- This works on any invertible function.
- If we want the product we can store the products and use  $\text{mul}(i, j) = \text{mul}(0, j) / \text{mul}(0, i - 1)$ .
- This also works for multidimensional arrays, but the math is more involved.
- We let  $\text{sum}(x_i, x_j, y_i, y_j)$  denote the query for the sum from  $x_i$  to  $x_j$  along the  $x$ -dimension, and the same for  $y$ .
- Then the formula becomes

$$\begin{aligned}\text{sum}(x_i, x_j, y_i, y_j) &= \text{sum}(0, x_j, 0, y_j) \\ &\quad - \text{sum}(0, x_{i-1}, 0, y_j) \\ &\quad - \text{sum}(0, x_j, 0, y_{i-1}) \\ &\quad + \text{sum}(0, x_{i-1}, 0, y_{i-1})\end{aligned}$$




## 2D sum



`query(1, 3, 3, 4)`


## 2D sum



`query(1, 3, 3, 4)`

`query(0, 3, 0, 4)`

## 2D sum




query(1, 3, 3, 4)

query(0, 3, 0, 4)

query(0, 4, 0, 2)

## 2D sum




query(1, 3, 3, 4)

query(0, 3, 0, 4)

query(0, 4, 0, 2)

query(0, 0, 0, 4)

## 2D sum



query(1, 3, 3, 4)

query(0, 3, 0, 4)

query(0, 4, 0, 2)

query(0, 0, 0, 4)

query(0, 0, 0, 2)