

Square Root Decomposition

Arnar Bjarni Arnarson

September 21, 2025

School of Computer Science

Reykjavík University

Range queries

- We have an array A of size n .

Range queries

- We have an array A of size n .
- Given i, j , we want to answer:

Range queries

- We have an array A of size n .
- Given i, j , we want to answer:
 - $\max(A[i], A[i + 1], \dots, A[j - 1], A[j])$

Range queries

- We have an array A of size n .
- Given i, j , we want to answer:
 - $\max(A[i], A[i + 1], \dots, A[j - 1], A[j])$
 - $\min(A[i], A[i + 1], \dots, A[j - 1], A[j])$

Range queries

- We have an array A of size n .
- Given i, j , we want to answer:
 - $\max(A[i], A[i + 1], \dots, A[j - 1], A[j])$
 - $\min(A[i], A[i + 1], \dots, A[j - 1], A[j])$
 - $\text{sum}(A[i], A[i + 1], \dots, A[j - 1], A[j])$

Range queries

- We have an array A of size n .
- Given i, j , we want to answer:
 - $\max(A[i], A[i + 1], \dots, A[j - 1], A[j])$
 - $\min(A[i], A[i + 1], \dots, A[j - 1], A[j])$
 - $\text{sum}(A[i], A[i + 1], \dots, A[j - 1], A[j])$
- We want to answer these queries efficiently, or in other words, without looking through all elements.

Range queries

- We have an array A of size n .
- Given i, j , we want to answer:
 - $\max(A[i], A[i + 1], \dots, A[j - 1], A[j])$
 - $\min(A[i], A[i + 1], \dots, A[j - 1], A[j])$
 - $\text{sum}(A[i], A[i + 1], \dots, A[j - 1], A[j])$
- We want to answer these queries efficiently, or in other words, without looking through all elements.
- Sometimes we also want to update elements.

Bucketing

- Group values into buckets of size k and store result of each bucket

Bucketing

- Group values into buckets of size k and store result of each bucket
- Updating is easy:

Bucketing

- Group values into buckets of size k and store result of each bucket
- Updating is easy:
 - change the array element

Bucketing

- Group values into buckets of size k and store result of each bucket
- Updating is easy:
 - change the array element
 - recompute corresponding bucket

Bucketing

- Group values into buckets of size k and store result of each bucket
- Updating is easy:
 - change the array element
 - recompute corresponding bucket
- Time complexity: $O(k)$

Bucketing

- Group values into buckets of size k and store result of each bucket
- Updating is easy:
 - change the array element
 - recompute corresponding bucket
- Time complexity: $O(k)$
- Again we want to query over a range

Bucketing

- Group values into buckets of size k and store result of each bucket
- Updating is easy:
 - change the array element
 - recompute corresponding bucket
- Time complexity: $O(k)$
- Again we want to query over a range
 - When a bucket is contained in the range, use the stored sum for the bucket

Bucketing

- Group values into buckets of size k and store result of each bucket
- Updating is easy:
 - change the array element
 - recompute corresponding bucket
- Time complexity: $O(k)$
- Again we want to query over a range
 - When a bucket is contained in the range, use the stored sum for the bucket
 - This (sometimes) allows us to “jump” over intervals of size k

Bucketing

- Group values into buckets of size k and store result of each bucket
- Updating is easy:
 - change the array element
 - recompute corresponding bucket
- Time complexity: $O(k)$
- Again we want to query over a range
 - When a bucket is contained in the range, use the stored sum for the bucket
 - This (sometimes) allows us to “jump” over intervals of size k
 - Only have to go inside at most two buckets (each end)

Bucketing

- Group values into buckets of size k and store result of each bucket
- Updating is easy:
 - change the array element
 - recompute corresponding bucket
- Time complexity: $O(k)$
- Again we want to query over a range
 - When a bucket is contained in the range, use the stored sum for the bucket
 - This (sometimes) allows us to “jump” over intervals of size k
 - Only have to go inside at most two buckets (each end)
 - Have to consider at most n/k buckets and 2 buckets of size k

Bucketing

- Group values into buckets of size k and store result of each bucket
- Updating is easy:
 - change the array element
 - recompute corresponding bucket
- Time complexity: $O(k)$
- Again we want to query over a range
 - When a bucket is contained in the range, use the stored sum for the bucket
 - This (sometimes) allows us to “jump” over intervals of size k
 - Only have to go inside at most two buckets (each end)
 - Have to consider at most n/k buckets and 2 buckets of size k
- Time complexity: $O(n/k + k)$

Choosing number of buckets

- Now we have a data structure that supports:
 - Querying in $O(n/k + k)$

Choosing number of buckets

- Now we have a data structure that supports:
 - Updating in $O(k)$
 - Querying in $O(n/k + k)$

Choosing number of buckets

- Now we have a data structure that supports:
 - Updating in $O(k)$
 - Querying in $O(n/k + k)$
- What k to pick?

Choosing number of buckets

- Now we have a data structure that supports:
 - Updating in $O(k)$
 - Querying in $O(n/k + k)$
- What k to pick?
- Time complexity is minimized for $k = \sqrt{n}$:

Choosing number of buckets

- Now we have a data structure that supports:
 - Updating in $O(k)$
 - Querying in $O(n/k + k)$
- What k to pick?
- Time complexity is minimized for $k = \sqrt{n}$:
 - Updating in $O(\sqrt{n})$

Choosing number of buckets

- Now we have a data structure that supports:
 - Updating in $O(k)$
 - Querying in $O(n/k + k)$
- What k to pick?
- Time complexity is minimized for $k = \sqrt{n}$:
 - Updating in $O(\sqrt{n})$
 - Querying in $O(n/\sqrt{n} + \sqrt{n}) = O(\sqrt{n})$

Choosing number of buckets

- Now we have a data structure that supports:
 - Updating in $O(k)$
 - Querying in $O(n/k + k)$
- What k to pick?
- Time complexity is minimized for $k = \sqrt{n}$:
 - Updating in $O(\sqrt{n})$
 - Querying in $O(n/\sqrt{n} + \sqrt{n}) = O(\sqrt{n})$
- Also known as square root decomposition, and is a very powerful technique

Example problem: Supercomputer

- <https://open.kattis.com/problems/supercomputer>

Mo's Algorithm