


H01: likely S-1200B45 LDO. Nominal 4.5 V is a candidate, not a measured rail.



User: RA3/R14, RA4/R15, RA5/R16, RC0/R11, RC6/R13, RC2 -> TP3; R80 -> TP16 / Q2; VREF tie withdrawn, RC1 -> R18 via V053-V070



User: PIC15/RC4 -> INA pin2; PIC16/RC5 -> INB pin3. Motor output polarity remains inferred.



U5 alternative: DRV8212PDSGR. Different package/pins; redesign required.

Q1: R1A -> FMOS3401A PMOS candidate, Battery+ at D3; post-Q1 supply at S2; G1 via R44

H06c S1 pairs and RC debounce inferred.

H07: C14R Inverter candidate. C6 parallels C5 by photo: Q8 source rail still inferred.




V113/V115: Q8 centre pin5 GND. V114 is U2 pin2 GND, not Q8 pin2.

C6 parallels C5 on H_RF_VDD/GND (photo-supported). Q8 F-P 10 ohm path still qualified

H10-H12: working topology around photographed 120k feedback resistors. Filters, bias, and interstage routes inferred.

Q7: 11.2 kohm V064-V070 fits R18+R19. Supply-switch topology Inferred; RC1 drives R18 via V053-V070.

H_RX_ENABLE_CTL



D2: R-C20 lower; L-ANT2/R46 upper; S-R46 lower, R46 empty; 4P identity unknown

U3 alternatives: MCP6002-1/SN: same pin roles, electrical suitability to verify

Use: U3 pin5 / V079 / V080 = VREF (1 ohm); TP6 remains separate across C18.

H13: 2H devices are probably PHP BJTs (MMBTA55 family; P8SS5140T is an alternative). Capacitor values unknown.



Local three-capacitor junctions retained. Hidden links from these midpoints to antenna remain unknown.

Q3/Q4/Q5/Q6/Q11: PNP E-at-GND assignment and RF switching role PROVISIONAL: verify one cell.

H14—H15: C2N supports S-812C33AMC 3.3V LDO. C/R3 ground supported by resistance

VSD



U6A: DNP alternative regulator; stock symbol does not identify the original part.

U6A: DNP alternative regulator; stock symbol does not identify the original part.

One sheet. Functional wiring is proposed; this is not a verified production circuit.

H.* is inferred inter-block net. Other net names do not imply measurement.

? on a part value or pin function means an estimate or candidate identity.

Library pin numbers are mapped to photo pads in *evidence/pin_crosswalk.json*.

THESE DOCUMENTS ARE THE PROPERTY OF THE NATIONAL ARCHIVES. ANY REPRODUCTION OR DISTRIBUTION OF THESE DOCUMENTS WITHOUT THE WRITTEN PERMISSION OF THE NATIONAL ARCHIVES IS PROHIBITED.

BIC nodes have local paths; some forward routes remain unresolved

DNP = unpopulated. An open pin means unresolved, not a certified no-connect

The ungrouped means are not yet given; 22 represents its increase.

See also RECONSTRUCTION and for evidence, alternatives, and conclusions.

v0.9.31 | KiCad 10.0.5 | 2026-10-06

Power declarations added: physical net partitions unchanged.

KiCad 10 libraries + four datasheet symbols | MCP authoring

Sheet: /

File: PetSafe_1001339.kicad_sch

Title: PetSafe 100-1339 R03 A | single-sheet reconstruction

Size: A2	Date: 2026-10-09
----------	------------------

KiCad E.D.A. 10.0.5

Rev: 0.9.31