
Impulse-Momentum Questions

Q1: Find the force exerted by the water jet on the object



$V' = (V-u) = 20-5 = 15 m/s$ (relative velocity)


$Q' = V'.A = 15 \times \frac{\pi \times 0.1^2}{4} = 0.1178 m^3/s$ (relative discharge)

$\vec{\Sigma} F_x = 0 = \rho Q'V' - \rho Q'V'.\cos 60° - Rx$

$1 \times (0.1178) \times 15 - 1 \times (0.1178) \times 15 \times \cos 60° = 0.8835 kN = 883.5 N = Rx$

$\uparrow \Sigma F_y = 0 = \rho Q'V' \sin 60° - Ry \quad Ry = 1.531 kN = 1530 N \quad R = \sqrt{0.8835^2 + 1.53^2} = 1.7674 kN$

Q2: The speed of the water jet observed in the figure is 20m/s and it's diameter is 50mm. It effects the blade of a wheel turbine. Find the force acting on this turbine wheel. (kanatçığa etkiyen kuvvet)



$Q = V.A = 30 \times \frac{\pi \times 0.05^2}{4} = 0.0589 m^3/s$

$V' = (V-u) = 30-6 = 24 m/s$

$\vec{\Sigma} F_x = 0 = \rho Q'V' - \rho Q'V' \cos 30° - Rx \Rightarrow Rx = 0.1196 kN = 119 N$

$\uparrow \Sigma F_y = 0 = \rho Q'V' \sin 30° - Ry \Rightarrow Ry = 0.7063 kN = 706.3 N$

$R = \sqrt{0.119^2 + 0.706^2} = 0.732 kN$

Dimensional Analysis

Prob.1- Obtain an expression for pressure gradient in a circular pipe flow.

$f_1(\Delta p, L, \rho, V, D, \mu, \varepsilon) = 0$ — Δp: N/m^2; L: m; ρ: kg/m^3 (dynamic viscosity); V: m/s; D: m; μ: $N.s/m^2$ (effective roughness); ε: m

variables

$\tau = \mu \frac{du(m/s)}{dy(m)}$ (N/m^2) $N: kg.m/s^2$

* Önce hepsini 3 boyutta aynı birimlerle yaz (kütle, uzunluk, zaman: kg, m, s)

n: number of variables

m: number of main dimensions

} number of dimensionless parameters: $n-m = 7-3 = 4$ pi terms (pi terms)

$n \rightarrow Re, k/D$

$\frac{\Delta p}{\rho V^2} = \frac{L}{D} . f(\Pi_3, \Pi_4) = \frac{\Delta p}{\rho g} = \frac{LV^2}{gD}$

$\Delta h_L = \lambda \frac{L}{D} \frac{V^2}{2g}$ — Sınır olu buruşuş kaldır Yüzeyinin yüzeyi

repeating variables should be chosen — repeating variables

Fluid (ρ; μ)

Flow (V)

Flow geometry (D; L)

$f_1(\Delta p, L, \rho, V, D, \mu, \varepsilon)$

$f_2(\Pi_1, \Pi_2, \Pi_3, \Pi_4)$

dimensions (x,y,z)

$\Pi_1 = \rho^{x_1} . D^{y_1} . V^{z_1} . \Delta p = M^0 L^0 T^0 = (M.L^{-3})^{x_1} . (L)^{y_1} . (L.T^{-1})^{z_1} . (M.L^{-1}.T^{-2})$ — mass, length, time

$\Pi_2 = \rho^{x_2} . D^{y_2} . V^{z_2} . L$

$\Pi_3 = \rho^{x_3} . D^{y_3} . V^{z_3} . \varepsilon$

$\Pi_4 = \rho^{x_4} . D^{y_4} . V^{z_4} . \mu$

for M: $x_1 + 1 = 0 \Rightarrow x_1 = -1$

for L: $-3x_1 + y_1 + z_1 - 1 = 0 \Rightarrow y_1 + z_1 = -2$

for T: $-z_1 - 2 = 0 \Rightarrow z_1 = -2$, $y_1 = 0$

→ apply these steps for the remaining pi terms

$\Pi_1 = \rho^{-1} . V^{-2} . \Delta p = \frac{\Delta p}{\rho . V^2}$

$\Pi_2 = D^{-1} . L = L/D$

$\Pi_3 = \varepsilon/D$

$\Pi_4 = \rho^{-1} . D^{-1} . V^{-1} . \mu = \mu/\rho DV = \nu/DV = 1/Re$ (Reynold's number)

$\rho = kg/m^3 = M.L^{-3}$

$D = m = L$

$V = m/s = L.T^{-1}$

Q2: Determine the resistance force expression of the D diameter.

$f_1(F, D, V, \rho, \mu)$ — F: $M.L.T^{-2}$; D: L; V: $L.T^{-1}$; ρ: $M.L^{-3}$

$n = 5$, $m = 3$, # pi terms $= n-m = 2$

$\Pi_1 = D^{x_1} . \rho^{y_1} . V^{z_1} . F \rightarrow M^0 L^0 T^0 = (L)^{x_1} . (M.L^{-3})^{y_1} . (L.T^{-1})^{z_1} . (M.L.T^{-2})$

for M: $y_1 + 1 = 0$, $y_1 = -1$

for T: $-z_1 - 2 = 0$, $z_1 = -2$

for L: $x_1 - 3y_1 + z_1 + 1 = 0$, $x_1 = -2$

$\Pi_1 = D^{-2} . \rho^{-1} . V^{-2} . F = F/\rho D^2 V^2$

$\Pi_2 = D^{x_2} . \rho^{y_2} . V^{z_2} . \mu \rightarrow M^0 L^0 T^0 = (L)^{x_2} . (M.L^{-3})^{y_2} . (L.T^{-1})^{z_2} . (M.L^{-1}.T^{-1})$