



Team 10229

FLORA BYTE

Ahmed Anwar

Asser Hatem

Kyrollois Youssef

Yousef Reda

STEM High School for Boys - 6th of October

Grade 11 - Semester 2 - 2025-2026

Table of Contents

Abstract:	3
Introduction:	4
Materials and Methods.....	6
Materials	6
Test Plan	9
Results	10
Negative results	10
Positive results	11
Analysis.....	12
Structural Engineering.....	13
Soil-Water Dynamics:.....	15
Conclusions:	21
Recommendation	22
Real-Life Application:	22
Drip Irrigation System	23
Semiconductor LED Chips.....	24
Literature Cited	24
Acknowledgement	26

Abstract:

The rapid population growth in Egypt necessitates innovative, sustainable approaches to increase the national agricultural base. The purpose of the study is to expand agricultural regions into desert-like conditions. As the population increased to 119 million, the corresponding per capita consumption rate created enormous demand that bears no resemblance to local crop production. Evidently, Egypt cultivates approximately $4,058 \times 10^3$ hectares; Egypt secures 37th place in Africa. Narrowing the scope to the 6th October city, it is a city with a population that is estimated at more than 670 thousand people. Despite this high population, it is coupled with desert-like conditions: soil moisture is 1%, and high temperatures. Furthermore, they consume more than 0.5 million acres. Thus, the problem is addressed via an even-span smart greenhouse. This project aims to ensure an optimal, sustainable environment for crops such as orchids and coriander. The small-scale prototype is constructed in an area that doesn't exceed 0.25 m^2 , with a feedback system hosted by ESP-32. The system gathers readings for the soil moisture, light intensity, and temperature; meanwhile, they are synchronized. It then compares these real-time metrics against conditions needed for selected crops individually, automatically compensating for any disturbance. This prototype can work for 6 continuous hours over 5 consecutive days, optimizing the environmental conditions.

It can effectively operate, as indicated by measured results: 22.85 °C temperature, 1733.52 soil moisture, 57.08% humidity, and 785.24 LDR.

Introduction:

The significant agricultural deficit in Egypt is driven by a rapid population growth crisis. This imbalance between the domestic production and food demand is especially prominent in Egyptian crop imports, which reach approximately 23–25 million tons annually (United States Department of Agriculture, 2025). Another major contributor is the scarcity of arable land in




Figure 1: demonstrates the average arable land

Egypt (nearly 3.1%), which stands below the global average of around 14.3% (Figure 1) (World Bank Open Data, 2022). These issues are coupled with the limited recycling infrastructure; Egypt secures the 7th place on the plastic mismanagement list (Simpson, 2024). This further exacerbates soil pollution. These constraints particularly appear in the city of 6th October, a desert-like region. Evidently, the average temperature is 36 °C, with low precipitation of 0.1 mm. Despite the harshness, it has more than 600,000 residents. This enormous population

consumes about 150-200 ft² per capita (**Lisa, 2025**). At the same time, the city of 6th October produces a tiny percentage of its crop consumption.

Similar issues were addressed via solutions such as Azahir Farm, which relies heavily on recycled, old components in its construction. This project is effective as it utilizes an adaptive mechanism that effectively prevents sudden environmental fluctuations; however, it poses some power issues. Furthermore, the Jain Irrigation system, which implements micro-irrigation. This approach drives water directly into plant roots through small tubes and emitters, minimizing waste of water. Nevertheless, it has limited repair flexibility. In order to obtain the best results, the even-span smart greenhouse monitors three parameters: soil moisture, light intensity, and temperature. The greenhouse adopts an even-span structure, consisting of two roofs with equal slope and length. The structure ensures efficient sunlight distribution and proper air circulation, which regulates the internal temperature. Moreover, it provides fresh carbon dioxide for plants. The small-scale prototype should be constructed in an area that doesn't exceed 0.25 m², corresponding to dimensions of 0.4 m × 0.6 m. The entire system is an ESP-32-based closed-loop feedback control system. The system synchronizes the sensors' readings. It then compares the real-time metric against conditions needed for coriander and orchid cultivation. It automatically compensates for any disturbance during the 6-hour continuous operation, fulfilling the design requirements.

Materials and Methods

Materials

Table 1: Materials Utilized in Prototype.

Materials	ESP 32	LDR Sensor	DHT-22 Sensor	Soil moisture sensor	Recycled-Bottles	Relays
Description	The controller board that used for controlling Feedback system	used to detect the light and gives feedback for ESP 32	used to measure temprature and Humidity	Used to measure the humidity of Soil	Used a transparent cover to allow sunlight passing	Used to control the operation of Actuator
Quantity	1	1	1	1	30	1
Image						
Materials	Beech Wood	Fans	Nails	White Pumps 5V	Power Supply	Jumper wires
Description	to construct the frame of our Prototype	to cool weather condition around plant	to connect the frame of prototype	to pump water inside prototype	to emerge power inside the circuit	used to connctet components of circuit
Quantity	8 meters	3	50	2	1	60
Image						

Methods

1. **Prototype design and sketching:** The project started with visualization and selecting the dimensions to make a 3D model using SolidWorks, as shown in **Figure 2.**




Figure2: 3D Design

2. Electronic System Integration:

The control system was built using an ESP32 microcontroller mounted on a breadboard, including relay modules to safely handle high voltage components, alongside a 12V power supply to operate actuators. All components were




Figure 3: Electronic System

interconnected with ESP32, as shown in **Figure 3**, ensuring a robust electronic architecture for the automated operations.

3. Sensors and actuators integration:

A DHT22 sensor was connected to monitor temperature; the ESP was programmed to activate a cooling fan when temperature threshold was exceeded. Regarding the soil moisture



Figure 4: Sensors & Actuators

sensor, it was utilized to activate a secondary water pump until soil took the required water as shown in **Figure 4**. Also, Light Dependent Resistor (LDR) was used to monitor light intensity to control a 220V to provide artificial lighting, while a DC motor driven by an H-bridge module was implemented to operate a shading system.

4. Programming system:

A ESP32 code was programmed using Arduino IDE to control sensors and actuators as shown in **Figure 5**. The system continuously reads data and activates corresponding actuators to

```
#include <WiFi.h>
#include <WebServer.h>
#include <DHT.h>
#include <Wire.h>
#include <LiquidCrystal_I2C.h>

const char* ssid = "Ahmed";
const char* password = "123456788";

#define LDR_PIN 35
#define SOIL_PIN 32
#define DHT_PIN 4
#define RELAY_LAMP 26
#define RELAY_PUMP1 19
#define RELAY_PUMP2 18
#define RELAY_FAN 25
#define MOTOR_IN1 33
#define MOTOR_IN2 23
```

Figure 5: Programming

maintain optimal environmental conditions without human intervention.

5. System testing and calibration:

To ensure the accuracy of the data collected from sensors, the calibration was conducted. The temperature data from the DHT22 sensor was validated by comparing the reading against an external digital thermometer. For the soil moisture sensor, readings were recorded in both completely dry and fully saturated soil to handle the water pump. This physical calibration ensured that the logic responded accurately to actual environmental conditions.

6. Web-Based Monitoring and Control:

A web-based interface was integrated and connected to the ESP32 via Wi-Fi. This website allows real-time monitoring of parameters and data, and allows manual



Figure 6: Website control

control of the system components, which provides flexibility with automated operation and emergency cases, as shown in **Figure 6**

7. **Assembly of the whole prototype:** A wooden frame was constructed using a combination of fabricated and recycled materials to form a box structure as a container for soil as shown in **Figure 7**. Also, recycled plastic bottles were flattened to serve as a cover.



Figure 7: Final Assembly

Test Plan

A comprehensive set of criteria of testing was established to ensure the feasibility of the prototype to meet design requirements:

1. The prototype was tested to ensure continuous operation for at least 6 hours without human intervention. The structure was verified to be assembled from recycled components.

2. The parameters were monitored to ensure accurate sensor readings with defined range. Sensors were calibrated using standard methods to ensure that accuracy does not exceed the $\pm 5\%$.
3. The ESP32 controller was tested to ensure the correct implementation of programming logic like IF-THEN rules and the system was tested under different conditions to evaluate its ability to detect changes.
4. The system was tested to ensure stable power, voltage, and reliable performance. Also, the complete documentation including circuit diagrams was tested.

Results

Negative results

Initially, the system had noticeable delay and unstable behavior in the circuit, such as vibration-like fluctuations. After testing, the issue was caused by the water pump because it was connected with 12 volt instead of 5 volt. The issue was solved by adding the voltage regulator to reduce the voltage to 5 volt.

The project was implemented using Arduino Uno as controller. After connecting the circuits components, it became clear that the system required data monitoring on a website to make it easier for user. So, the issue solved by using an ESP32 instead of Arduino Uno to allow integration with Wi-Fi.

Positive results




Figure 8: Soil Variation across Time




Figure 9: Light Variation across Time




Figure 10: Light Variation across Time




Figure 11: Humidity Variation across Time

Table 2: Parameters average value across each day for 5 consecutive days

Day Number	Temp	Humidity	soil	Light	Time
Day 1	18.7	69.1	1713	4095	04:00:00 AM
	25	52.5	1671	36	10:00:00 AM
	22.2	65.7	1723	205	05:30:00 PM
Day 2	18.2	68.5	1713	4095	04:00:00 AM
	24.9	50.1	1671	36	10:00:00 AM
	22	60	1723	205	05:30:00 PM
Day 3	17.9	68.8	1718	4095	04:00:00 AM
	24	52.2	1617	110	10:00:00 AM
	20.5	50	1733	205	05:30:00 PM
Day 4	18.9	69.1	1713	4095	04:00:00 AM
	25.2	53.2	1671	32	10:00:00 AM
	22.2	65.7	1723	205	05:30:00 PM
Day 5	19	67	1728	4095	04:00:00 AM
	25	52.5	1671	36	10:00:00 AM
	23	65.7	1723	205	05:30:00 PM

Analysis

After constructing the small-scale prototype, a test plan was conducted to verify that the prototype satisfies the design requirements. These criteria included cultivation area, which was measured to ensure that it does not exceed 0.25 m^2 , corresponding to dimensions of $0.4 \text{ m} \times 0.6 \text{ m}$. Moreover, the system's endurance was evaluated through continuous operation for 6 hours per day over 5 consecutive

days to emphasize its reliability. This performance resulted from an integration of electric and mechanical concepts.

Structural Engineering

The primary purpose of this investigation is to validate the system's capacity to sustain an optimal agricultural microclimate amidst the harsh, desert-like conditions of the 6th of October City. To achieve this purpose, the project's performance is evaluated across several interdisciplinary aspects:

At the outset, the extreme environmental loads of the region—elevated temperature (approximately 36.0 °C)—dictate strict architectural constraints. That is why the structure must




Figure 12: Even-Span Greenhouse Structure (Kwon et al., 2015)

satisfy two critical criteria: passive air circulation and climate optimization. In response to these constraints, the **even-span greenhouse configuration** emerges as the optimum solution, **as illustrated in Figure (12)**. It is a greenhouse structure composed of two equal roof slopes that accommodates two to three rows of plant benches.

Under desert-like conditions, the even span relies on several approaches that enable it to gradually decrease the temperatures:

First of all, the number of spans enhances the microclimate by regulating the air temperatures via smooth air paths. The 30° angle of inclination based on Bernoulli's principle:

Equation 1: Bernoulli's Principle

$$P_1 + \rho gh_1 + \frac{1}{2}\rho v_1^2 = P_2 + \rho gh_2 + \frac{1}{2}\rho v_2^2$$

To validate the aerodynamic efficiency of the structure, based on the average air velocity of the city of 6th October, which is estimated at 6.0 m/s (***Simulated Historical Climate & Weather Data for 6th of October City - Meteoblue, n.d.***). Determining the structural geometry at a 30° roof and applying Bernoulli's principle resulted in a negative static pressure zone of 11.5 pascals. This pressure differential acts as a natural extraction system; air naturally flows from regions of higher pressure to regions of lower pressure. In light of these considerations, the quantified Air Changes per Hour (ACH), which was modeled utilizing:

Equation 2: Air Changes per Hour (ACH)

$$ACH = \frac{Q_{hourly}}{V}$$

Where Q is defined as hourly airflow capacity per structural volume (V). This equation determines ventilation efficiency; the calculated airflow corresponds to 1.388 Air Changes per Hour.

Furthermore, the small-scale prototype has been constructed with a scale of 1:4.6 to the standard dimensions (*Ponce et al., 2015*); a width of 0.6 m, and a length of 0.4 m. Even more, the symmetric structure demonstrated in **Figure 12** assists in distributing the load across the structural frame, which resulted in enhancing the structure's resistance to wind (ideal yearlong utilization) (*Admin, 2025*). This behavior arises from the symmetrical roof, which redistributes the aerodynamic loads via the configuration of pressure along the entire foundation. Thereby, it prevents localizing the stress, enhancing the overall structural stability.

Soil-Water Dynamics:

This study addresses the limited soil quality for sustainable cultivation in a hyper-arid soil profile. The city of 6th October is characterized by extremely low soil moisture (approximately 1%); meanwhile, the coriander and orchid require high, consistent moisture for survival. To verify this criterion, some quantitative analysis is conducted.

Primarily, the particle density is considered, with an average value of 2.66 g/cm³. This corresponds to a bulk density estimated at 1.4 – 1.8 g/cm³ (*University of Nebraska, 2026*). These parameters will be utilized to calculate the total soil porosity (Φ), according to the following formula that was established by **Shreeja (2016)**

(Equation 3):

Equation 3: Soil Porosity

$$\Phi = \left(1 - \frac{\rho_b}{\rho_p} \right) \times 100$$

Where ρ_b is bulk density, and ρ_p is particle density. This equation determines the porosity of soil; it corresponds to a range between 32.3 and 52.6%, depending on soil compaction. This indicates a relatively high concentration of macro-pores, which can rapidly percolate water.

Within this project, the coriander typically occupies a shallow root zone of approximately 0.01-0.02 m, particularly in sandy soils, allowing roots to absorb water (*Modhavadia et al., 2025*). Thus, the amount of water that would be pumped via the prototype's environmental optimization system is calculated utilizing the following mathematical model (**Equation 4**):

Equation 4 : Volume of water required for soil

$$V_w = A \times Z \times (\theta_{FC} - \theta_i)$$

Where V_w is the total required water, Z indicates the effective root zone depth, and A is the prototype area. Furthermore, θ_{FC} and θ_i are the volumetric water content and the initial water content, respectively. The irrigation demand corresponds to approximately 0.5 L of water per irrigation cycle.

Feedback system

The observed stability in the prototype results is explained by principles of thermodynamic equilibrium and hydrological balancing in the system. The smart greenhouse uses a feedback system

dependent on the ESP32 microcontroller to monitor environmental variable within defined conditions against external action perturbations, which describe in schematic diagram as shown in Figure 13.

Thermodynamically, the system prevents thermal runaway by controlling the heat rate inside the greenhouse. When the DHT22 sensor detects the temperature exceeding the set threshold, the system alters the heat accumulation as shown in

Equation 5:

Equation 5: Net Thermal Accumulation Model

$$q_{net} = q_{solar} - q_{conv}$$

where q_{net} is the net heat transfer rate inside the greenhouse required to represent the thermal gain or loss of the system, q_{solar} is the incoming solar heat load, which represents the energy gain from solar radiation, q_{conv} is the heat removed from the system due to the cooling fan. The actuation of the DC motor to move the shade




Figure 13: The schematic diagram

reduces the value of q_{solar} . Additionally, the cooling fan maximizes q_{conv} , which is represented by Newton's Law of Cooling (**Equation 6**):

Equation 6: Newton's Law of Cooling

$$q_{conv} = h \cdot A \cdot (T_{internal} - T_{ambient})$$

where h is the convective heat transfer coefficient established by the fan's airflow, A is the effective internal surface area, and T represents the respective internal and ambient temperature. Hydrologically, the stability of soil moisture is analyzed through the conservation of mass principle. The soil moisture sensor triggers the water pump to compensate for evaporative losses, described by the following moisture balance **equation 7**:

Equation 7: Differential mass balance equation

$$\frac{d(\theta \cdot V)}{dt} = Q_{pump} - E_{rate}$$

where θ is the volumetric water content of the soil (m^3/m^3), V is the control volume, Q_{pump} is the volumetric flow rate provided by the pump, and E_{rate} represents the evaporative losses rate from the system (m^3/s). Furthermore, low-light conditions are corrected through an LDR sensor that activates a lamp, ensuring sufficient flux to maintain the baseline illuminance level for plant growth

The implementation of this active feedback control system is justified as it provides continuous real-time error correction compared to passive cooling or static timer-based irrigation systems, which cannot adapt effectively to dynamic environmental variables. By regulating q_{net} toward zero or negative values during peak thermal loads and adjusting the rate of change of $\frac{d(\theta.V)}{dt}$, the system reduces environmental fluctuations. This closed-loop regulating mechanism helps explain the empirical results obtained, where the prototype maintained internal temperature within the target range of 15C to 25C and kept soil moisture within the optimal range of 40% to 50% under test conditions.

Table 3: Learning outcomes

Learning Outcome	Utilization
ME.2.07	This topic shows how the Law of Conservation of Momentum explains collisions by linking force, time, and change in motion (impulse), and is used to study and predict real-life impacts like car crashes.
PH.2.09	Energy storage and control in circuits Energy storage and control in circuits RL circuits and inductors show how energy is stored in magnetic fields and released over time, which is used in devices like power supplies, electric motors, and timing circuits in electronics.
PH.2.10	Studying diodes and transistors explains how devices like chargers, computers, and smartphones control current flow, convert AC to DC, and amplify signals—forming the basis of all digital technology.
Bi.2.10	Understanding Natural Selection helps explain how organisms adapt to their environment over time. In real life, this connects to biodiversity and conservation, as studying fossils and evolution allows us to understand how species survive environmental changes and how to protect them from extinction.
CH.2.11	The studying of the hydrocarbons and cracking explains how fuels are produced and used to heat a greenhouse. This helps you choose efficient fuels, control gas levels for plant growth, and select suitable polymer materials to build a strong and effective greenhouse system.
CH.2.09	The smart greenhouse system operates using an external power supply that provides electrical energy to sensors, controllers, and actuators. Although no batteries are used, the system still depends on electric current flow from the power supply, which is based on electron movement in circuits.
PH.2.12	The smart greenhouse uses Sensors, a microcontroller (ESP32 / Arduino), a fan, a pump, an LED light, and a power supply (AC → DC adapter); all of these depend on electrical circuits and power behavior. So consequently, it is a must to analyze the prototype efficiency running system, using this LO. □
PH.2.15	The system likely includes: Power regulation circuits, Protection components (diodes), Conversion from AC to DC (adapter). Which are included in this LO.
MA.2.06	There are some changes in the conditions which are sudden, like the (pump ON/OFF, fan switching), and the change can be smooth over time, like (temperature, humidity), such that changes can be studied and analyzed by the limits and continuity graphs and functions.
ME.2.06	The center of mass concept is relevant to ensuring stability of the greenhouse structure, especially when adding components like water tanks or mounted sensors, to prevent tipping or imbalance.

Conclusions:

In light of these considerations, one major contributor to environmental pollution is the limited implementation of recycling, exacerbated by increasing population density, hindering Egypt's progress. These significant issues particularly appear in the city of 6th October, resulting in elevated temperature levels of 36 °C. Thus, the proposed solution represents an even-span smart greenhouse. This design ensures good ventilation, with even temperature distribution for orchid and coriander cultivation. Taken together, the highlighted results of three environmental parameters (soil moisture, light intensity, and temperature) include: 22.2 °C temperature, 1733.52 soil moisture, 57.08% humidity, and 785.24 LDR. All data were collected via an ESP-32-based monitoring system. The small-scale prototype was also designed more cost-effectively compared with the prior solution such as Bluehouse, which involves high operational costs.

Recommendation

Real-Life Application:

The even-span greenhouse structure is constructed in the 6th of October City, Egypt, due to severe water scarcity and low soil quality for sustainable cultivation. As



Figure 24: 6th October City (Proposed Location)

illustrated in Figure 1, the desert-

like conditions are characterized by high temperature levels (approximately 36°C) and extremely low soil moisture (1%). Furthermore, the city experiences low precipitation (nearly 0.1 mm/day); meanwhile, the average is estimated at 7.5 mm/day.

The implementation of the **even-span** structure would emphasize air circulation and ensure uniform temperature distribution. This is primarily via the utilization of two symmetrical spans, identical slopes with equal lengths. The structure is proposed to be constructed with galvanized steel covered with fiberglass (*ACF Greenhouses Buying Guide - Help Choosing a Greenhouse, n.d.*) due to its durability and UV resistance. The structure is designed with dimensions of 44.0 × 7.0 m along height of 2.0 m (*Kwon et al., 2015*).

Drip Irrigation System

It is recommended to use drip irrigation systems due to their high efficiency in delivering water directly to the plant root zone in a controlled and precise manner. This method significantly improves the efficiency of water usage by reducing evaporation, surface runoff, and unnecessary water distribution, making it highly appropriate for arid environments such as 6th of October City, where water conservation is important, due to a lack of water sources. The system operates through a network of small tubes and emitters that release water drop by drop, which relies on programmed control signals from the loop circuit, which can be integrated with soil moisture, through which the sensor detects the level of the soil moisture, and then sends signals for the loop to allow the work of the system if it is required. This closed feedback mechanism helps maintain optimal soil moisture levels, enhancing plant growth stability and reducing stress caused by overwatering or underwatering. However, it is hard to apply this to the idea of the project because of the highly complex tubing infrastructure, precise clog-free maintenance, and stable, continuous water pressure.

Semiconductor LED Chips

It is recommended to use the Semiconductor LED Chips, due to their importance in providing the appropriate spectrum wavelengths according to the three phases of plant live, which are 1-seedling phase, 2-vegetative phase, 3-flowering phase, and it is a strong edit due to the enhancement leaf and stem development, improving flowering and fruiting efficiency, reducing wasted energy compared to normal white light, and allowing plants to grow in optimized, controlled environments regardless of natural sunlight. The loop circuit is preprogrammed with inputs for the plant's phases and properties, and these inputs provide a signal to the current, and finally to the semiconductor LED material, such as Gallium Nitride, to emit the desired wavelength for each phase. Finally, it can't be applied in the prototype's enclosed system, because of the high cost that ranges between 10000 - 25000 pounds for the small scale of the prototypes.

Literature Cited

1. Benzine, H., Labrim, H., Aouni, I. E., Bouali, K., Achour, Y., Saad, A., Zejli, D., & Bouayadi, R. E. (2026). Integrated Passive Cooling Techniques for Energy-Efficient Greenhouses in Hot–Arid Environments: Evidence from a Systematic Review. *Water*,

- 18(4), 463. <https://doi.org/10.3390/w18040463>
2. *Simulated historical climate & weather data for 6th of October City - meteoblue.* (n.d.).
Meteoblue.
https://www.meteoblue.com/en/weather/historyclimate/climatemodelled/6th-of-october-city_egypt_353219
3. Admin. (2025, June 18). *What is an Even-Span Greenhouse? Advantages, disadvantages, and diagram - INSONGREEN.* INSONGREEN.
<https://www.insongreen.com/what-is-even-span-greenhouse/>
4. Kwon, K., Kim, D., Kim, R., Ha, T., & Lee, I. (2015). Evaluation of wind pressure coefficients of single-span greenhouses built on reclaimed coastal land using a large-sized wind tunnel. *Biosystems Engineering*, 141, 58–81.
<https://doi.org/10.1016/j.biosystemseng.2015.11.007>
5. *Particle Density | Soils - Part 2: Physical Properties of Soil and Soil Water - passel.* (n.d.). <https://passel2.unl.edu/view/lesson/0cff7943f577/5>
6. *Home | Soils - Part 2: Physical Properties of Soil and Soil Water - passel.*

(n.d.). <https://passel2.unl.edu/view/lesson/0cff7943f577>

7. D, S. (2016, July 20). *Calculation of soil moisture (With example)*. Soil

Management India. <https://www.soilmanagementindia.com/soil->

[water/calculation-of-soil-moisture-with-example/1815](https://www.soilmanagementindia.com/soil-water/calculation-of-soil-moisture-with-example/1815)

8. Modhavadia, R., Odedra, K. N., Bamaniya, J., & Jadeja, B. A. (2025). Soil-

Specific Optimal sowing depth for coriander: Effects on seed

germination and early growth. *Annals of Arid Zone*, 64(3), 413–424.

<https://doi.org/10.56093/aaz.v64i3.165757>

9. *17.2 combined conduction and convection*. (n.d.).

[https://web.mit.edu/16.unified/www/FALL/thermodynamics/notes/node123.](https://web.mit.edu/16.unified/www/FALL/thermodynamics/notes/node123.html)

[html](https://web.mit.edu/16.unified/www/FALL/thermodynamics/notes/node123.html)

Acknowledgement

First, many thanks to Allah for enabling us to complete this project and fulfill all the design requirements, and secondly, many thanks to our capstone manager, who is Mr. Mohamed Ali Bekheet, our capstone leader. Mrs. Ninet Rifat, and finally, thanks to our capstone teacher. Mrs. Reham for their help in our project.