

STONE POLYMER COMPOSITE
SKIRTING BOARD

Elite 100

Interior skirting profile engineered for clean wall-floor transitions, concealed cable routing, water resistance and fast finishing in residential and commercial spaces.

Made in Türkiye

Stone Polymer Composite

Soft Flexible Edges

Concealed Cable Channel

100 mm

nominal height



19 mm

nominal depth

1.8

g/cm³ declared density

Class B

reaction to fire class

<0.3%

water absorption by volume

Soft edge seal

Flexible co-extruded lips help mask minor irregularities at the wall and floor joint.

Cable channel

Rear concealment area for organized low-voltage or power cable routing, subject to local electrical rules.

Matt surface

Low-gloss surface appearance for modern, understated interior detailing.

Pb-free

Stone Polymer Composite construction declared Pb-free and suitable for responsible recycling streams.

PRODUCT CONSTRUCTION

Three-layer composite profile with flexible contact edges.



The profile combines a rigid Stone Polymer Composite body with a co-extruded surface and soft edge lips for clean contact at the wall and floor junction. The rigid body supports everyday interior finishing durability.

100 mm height

19 mm depth

Soft edge lips

Cable channel

Matt surface

DECLARED TECHNICAL SPECIFICATIONS

Property	Reference / method	Declared value
Product model	Internal designation	Elite 100
Profile type	Product category	Stone Polymer Composite Skirting Board
Nominal height	Profile dimension	100 mm
Nominal depth	Profile dimension	19 mm
Chemical structure	Material declaration	Stone Polymer Composite
Density	Declared performance	1.8 g/cm ³
Indentation under pressure	Declared performance	0.3 mm
Vicat softening temperature	TS EN 13245-1	68.3 °C
Tensile-impact strength	TS EN ISO 8256	179 kJ/m ²
Heat-assisted forming	Installation method	Can be heat-formed for curved walls
Water absorption - full immersion	Declared performance	< 0.3% by volume
Moisture from air	Declared performance	< 0.04%
Reaction to fire class	EN 13501-1	B
Dimensional change at heat	+80 ± 2 °C	Max. 2%
Lead content	Material note	Pb-free

FEATURE SYSTEM

Technical benefits for fast, clean interior finishing.



100% waterproof

Waterproof + humidity resistant profile with very low absorption.



Multiple colors

Color options for coordinated flooring and wall finishes.



Cable concealment

Rear channel for TV/ electric cable routing, subject to local rules.



Clean saw cuts

45° cuts without burn marks or darkening.



Modern profile

Straight, minimal visual line for contemporary interiors.



Aluminum-like hardness

Rigid composite core supports impact resistance.



Matt surface

Low-gloss surface for a refined, non-shiny appearance.



Easy installation

Install-friendly profile for fast site finishing.



Anti-bacterial

Surface supports clean, controlled interior maintenance.



Flexible edges

Co-extruded soft lips adapt to minor unevenness.

Application areas

Designed as an interior skirting profile for common floor finishes and wall-floor transitions.

Ceramic

Carpet

Vinyl

Parquet

SPC / LVT

Accessories and finishing

For a complete system, plan color-matched corners, end caps and connectors where applicable. Use accurate 45° mitre cuts when accessories are not used or where the design requires a continuous visual line.

EN 13245-2

Declared performance references EN 13245-2:2008 for intended use and key specification basis.

AVCP System 4

Evaluation and verification of constancy of performance is declared under AVCP System 4.

Fire class B

Reaction to fire class: B, referenced to EN 13501-1 in the source technical document.

Product description

Kermit Elite 100 is a high-performance composite skirting profile with a durable surface, a rigid composite core and flexible lips for clean contact with the wall and floor.

Sustainability note

The product is declared Pb-free and recyclable. This sheet avoids broad environmental claims unless supported by the relevant declaration or certification for the specific product batch.

INSTALLATION GUIDE

Clean substrate, accurate cuts, correct fixing.

Condition

01

Store profiles in the installation area before fitting. Keep them flat and away from heat sources.

Prepare

02

Substrate should be clean, dry, stable, dust-free and as flat as practical along the wall-floor junction.

Cut

03

Cut profiles with a suitable mitre saw. Use 45° cuts or compatible accessories for neat inside/outside corners.

Fix

04

Use compatible adhesive or mechanical fixing according to project conditions. Press firmly so soft lips close the gap.

Recommended practice

- **Plan accessories:** corners, end caps and connectors should match the profile and color.
- **Heat-assisted bending:** warm the profile and form it to curved walls; a key product advantage.
- **Use neutral cleaning:** wipe with a soft cloth and pH-neutral cleaner.
- **Test on sample:** verify adhesive or cleaning agents before large-area application.

Avoid

- Do not fix to wet, dusty, oily or loose substrates; clean and dry the bonding area first.
- Do not use abrasive pads, aggressive solvents or high-alkaline cleaners.
- Do not expose stored profiles to direct sunlight, deformation loads or high heat.

Storage

Store horizontally in original packaging, protected from dust, direct sun and excessive temperature variation.

Maintenance

Routine cleaning requires only damp wiping. Remove dirt before it hardens around the soft edges and joints.

Limitations

Interior finishing profile only. It is not structural and should not be used where load-bearing performance is required.

DOCUMENT CONTROL

MANUFACTURER

Kermit Plastik San. ve Tic.
A.Ş.

PRODUCT MODEL

Elite 100

DOCUMENT

TDS-SK-ELITE100-EN

REVISION DATE

05.06.2026

This technical data sheet summarizes declared product information and installation guidance. Project specifications, local regulations, electrical rules, fire classification requirements and the latest installation guide take precedence where applicable.