

## Technical Specifications

### COMPOSITE SKIRTING BOARD

#### GENERAL DESCRIPTION OF THE PRODUCT:

Kermi Composite Skirting Profile is an eco-friendly, high-performance baseboard system composed of three integrated layers. Its unique structural design incorporates a concealed cable duct for organized wiring, flexible silicone edges for seamless wall and floor contact, and a co-extruded coated surface that ensures superior durability, moisture resistance, and long-lasting color stability. The composite core provides excellent impact resistance while maintaining a lightweight and easy-to-install form.

**PRODUCER** : KERMIT PLASTİK SANAYİ VE TİCARET ANONİM ŞİRKETİ

**Address** : Cumhuriyet Mah. Cihan Sok.No:4/1  
Çayırova – KOCAELİ – TÜRKİYE



**PRODUCT MODEL** : *Alpha 140*

#### TECHNICAL SPECIFICATIONS:

|                                                   |                         |
|---------------------------------------------------|-------------------------|
| Height : 140 mm                                   | Width : 16 mm           |
| Chemical Structure                                | : PVC, Stone Composite  |
| Density                                           | : 1,8g/cm <sup>3</sup>  |
| Absolute Strength Under Pressure                  | : 0,3mm                 |
| Vicat Softening Temperature TS EN 13245-1         | : 68,3 °C               |
| Tensile-Impact Strength TS EN ISO 8256            | : 179 kJ/m <sup>2</sup> |
| D 30mm                                            | : Not flexible          |
| Water Absorption During Continuous Full Immersion | : by volume <%0,3       |
| Moisture from the Air                             | : <%0,04                |
| Reaction to Fire Class TS EN 11925:2020-07        | : D                     |
| Size Change Rate at +80,-2 C Temperature %        | : Max 2                 |


## PRODUCT DESCRIPTION:

- Kermit skirting is easy to assemble and disassemble with its unique click system.
- It has a soft silicone edge and provides a perfect joint by camouflaging the wall and floor squares in wall and floor joints.
- Water resistant
- Paintable
- Concealment area with cable duct, TV or electric cable (max. 230V)
- Kermit Skirtings are environmentally friendly, renewable, recyclable and do not contain Pb.

## APPLICATION AREAS:

It acts as a skirting in all kinds of Ceramic, Carpet, Vinyl and Parquet floor applications.

- *Declared Performance - Key specification EN13245-2:2008*
- *System or systems of evaluation and verification of the constancy of performance of the construction product: AVCP – System4*
- *Intended use or uses of the building material according to the relevant harmonized technical specification stipulated by the manufacturer EN13245-2:2008*




100%  
WATERPROOF



MULTIPLE COLORS



3 WAY  
SYSTEM




MITRE  
SAW



MODERN  
DESIGN



IMPACT  
RESISTANT



MATT  
MATT  
SURFACE



SMART  
INSTALLATION



DUST & DIRT  
BARRIER



FLEXIBLE  
EDGES

*This declaration of performance has been prepared by KERMIT PLASTİK SAN.TİC.A.Ş. regulated under the sole responsibility of the manufacturer.*