

Technical Specifications

COMPOSITE SKIRTING BOARD

GENERAL DESCRIPTION OF THE PRODUCT:

Kermi Composite Skirting Profile is an eco-friendly, high-performance baseboard system composed of three integrated layers. Its unique structural design incorporates a concealed cable duct for organized wiring, flexible silicone edges for seamless wall and floor contact, and a co-extruded coated surface that ensures superior durability, moisture resistance, and long-lasting color stability. The composite core provides excellent impact resistance while maintaining a lightweight and easy-to-install form.

PRODUCER : KERMİT PLASTİK SANAYİ VE TİCARET ANONİM ŞİRKETİ

Address : Cumhuriyet Mah. Cihan Sok.No:4/1
Çayırova – KOCAELİ – TÜRKİYE



PRODUCT MODEL : *Berlin 100*

TECHNICAL SPECIFICATIONS:

Height : 100 mm	Thickness : 22mm
Chemical Structure	: PVC, Stone Composite
Density	: 1,8g/cm ³
Absolute Strength Under Pressure	: 0,3mm
Vicat Softening Temperature TS EN 13245-1	: 68,3 °C
Tensile-Impact Strength TS EN ISO 8256	: 179 kJ/m ²
D 30mm	: Not flexible
Water Absorption During Continuous Full Immersion	: by volume <0,3%
Moisture from the Air	: <0,04%
Reaction to Fire Class TS EN 11925:2020-07	: D
Size Change Rate at +80,-2 C Temperature %	: Max 2


PRODUCT DESCRIPTION:

- Kermit skirting is easy to assemble and disassemble with its unique click system.
- It has a soft silicone edge and provides a perfect joint by camouflaging the wall and floor squares in wall and floor joints.
- Water resistant
- Paintable
- Concealment area with cable duct, TV or electric cable (max. 230V)
- Kermit Skirtings are environmentally friendly, renewable, recyclable and do not contain Pb.

APPLICATION AREAS:

It acts as a skirting in all kinds of Ceramic, Carpet, Vinyl and Parquet floor applications.

- *Declared Performance - Key specification EN13245-2:2008*
- *System or systems of evaluation and verification of the constancy of performance of the construction product: AVCP – System4*
- *Intended use or uses of the building material according to the relevant harmonized technical specification stipulated by the manufacturer EN13245-2:2008*




**%100
WATERPROOF**



MULTIPLE COLORS



**3 WAY
SYSTEM**




**MITRE
SAW**



**MODERN
DESIGN**



**IMPACT
RESISTANT**



**MATT
MATT
SURFACE**



**SMART
INSTALLATION**



**DUST & DIRT
BARRIER**



**FLEXIBLE
EDGES**

This declaration of performance has been prepared by KERMIT PLASTİK SAN.TİC.A.Ş. regulated under the sole responsibility of the manufacturer.