



Manual de Usuario
Instalación de MySQL en Kali Linux
26-10-2025 Versión 1.0


```
css@css: ~  
(css@css)-[~]  
$ sudo apt install default-libmysqlclient-dev default-mysql-client default-mysql-client-core default-mysql-server default-mysql-server-core mysql-common  
default-libmysqlclient-dev is already the newest version (1.1.1).  
default-mysql-client is already the newest version (1.1.1).  
default-mysql-client-core is already the newest version (1.1.1).  
default-mysql-server is already the newest version (1.1.1).  
default-mysql-server-core is already the newest version (1.1.1).  
mysql-common is already the newest version (5.8+1.1.1).  
Summary:  
Upgrading: 0, Installing: 0, Removing: 0, Not Upgrading: 0  
(css@css)-[~]  
$
```

Figura 3. Comando para instalar los quetes necesarios para MySQL

Posteriormente tienes que verificar el estado del servicio MySQL y para eso debes usar el comando: `service mysql status` ó con `sudo systemctl status mysql`. A continuación verás la salida de ambos comandos:

```
css@css: ~  
(css@css)-[~]  
$ sudo systemctl status mysql  
○ mariadb.service - MariaDB 11.8.3 database server  
   Loaded: loaded (/usr/lib/systemd/system/mariadb.service; disabled; preset: disabled)  
   Active: inactive (dead)  
     Docs: man:mariadb(8)  
           https://mariadb.com/kb/en/library/systemd/  
(css@css)-[~]  
$ service mysql status  
○ mariadb.service - MariaDB 11.8.3 database server  
   Loaded: loaded (/usr/lib/systemd/system/mariadb.service; disabled; preset: disabled)  
   Active: inactive (dead)  
     Docs: man:mariadb(8)  
           https://mariadb.com/kb/en/library/systemd/
```

Figura 4. Comandos para consultar estado del servicio

Ahora se tiene que activar el servicio MySQL con el comando: `service mysql start` ó `sudo systemctl start mysql`

```
css@css: ~  
(css@css)-[~]  
$ systemctl start mysql  
(css@css)-[~]  
$ systemctl status mysql  
● mariadb.service - MariaDB 11.8.3 database server  
   Loaded: loaded (/usr/lib/systemd/system/mariadb.service; disabled; preset: disabled)  
   Active: active (running) since Sun 2025-10-26 03:04:01 CST; 3min 13s ago  
 Invocation: fba2b73d2d75462cb60e3fadac5ced62  
     Docs: man:mariadb(8)  
           https://mariadb.com/kb/en/library/systemd/  
 Process: 2743436 ExecStartPre=/usr/bin/install -m 755 -o mysql -g root -d /var/run/mysqld (code=exited, >  
 Process: 2743438 ExecStartPre=/bin/sh -c [ ! -e /usr/bin/galera_recovery ] && VAR= || VAR=/usr/bin/ga>  
 Process: 2743504 ExecStartPost=/bin/rm -f /run/mysqld/wsrep-start-position (code=exited, status=0/SUCCESS>  
 Process: 2743506 ExecStartPost=/etc/mysql/debian-start (code=exited, status=0/SUCCESS)  
 Main PID: 2743490 (mariadb)  
   Status: "Taking your SQL requests now..."  
    Tasks: 10 (limit: 186590)  
  Memory: 122.5M (peak: 128.5M)  
     CPU: 556ms  
    CGroup: /system.slice/mariadb.service  
            └─2743490 /usr/sbin/mariadb
```

Figura 5. Comando para consultar estado y posteriormente activar el servicio

```
(css@css)-[~]
$ sudo systemctl start mysql
[sudo] password for css:

(css@css)-[~]
$ sudo systemctl status mysql
● mariadb.service - MariaDB 11.8.3 database server
   Loaded: loaded (/usr/lib/systemd/system/mariadb.service; disabled; preset: disabled)
   Active: active (running) since Mon 2025-10-27 10:52:40 CST; 3s ago
 Invocation: 0ba32828c4ef41fa811dd265fb4682f2
    Docs: man:mariabdb(8)
          https://mariadb.com/kb/en/library/systemd/
   Process: 5998 ExecStartPre=/usr/bin/install -m 755 -o mysql -g root -d /var/run/mysql (code=exited, >
   Process: 6000 ExecStartPre=/bin/sh -c [ ! -e /usr/bin/galera_recovery ] && VAR= || VAR=/usr/bin/ga>
   Process: 6066 ExecStartPost=/bin/rm -f /run/mysql/wsrep-start-position (code=exited, status=0/SUCCE>
   Process: 6068 ExecStartPost=/etc/mysql/debian-start (code=exited, status=0/SUCCESS)
  Main PID: 6053 (mariabdb)
    Status: "Taking your SQL requests now..."
     Tasks: 14 (limit: 186561)
  Memory: 152.3M (peak: 157.6M)
     CPU: 1.464s
    CGroup: /system.slice/mariadb.service
            └─6053 /usr/sbin/mariabdb

Oct 27 10:52:39 css mariabdb[6053]: 2025-10-27 10:52:39 0 [Note] InnoDB: Loading buffer pool(s) from /var>
Oct 27 10:52:39 css mariabdb[6053]: 2025-10-27 10:52:39 0 [Note] InnoDB: Buffer pool(s) load completed at>
Oct 27 10:52:40 css mariabdb[6053]: 2025-10-27 10:52:40 0 [Note] Server socket created on IP: '127.0.0.1'>
Oct 27 10:52:40 css mariabdb[6053]: 2025-10-27 10:52:40 0 [Note] mariabdb: Event Scheduler: Loaded 0 even>
Oct 27 10:52:40 css mariabdb[6053]: 2025-10-27 10:52:40 0 [Note] /usr/sbin/mariabdb: ready for connection>
Oct 27 10:52:40 css mariabdb[6053]: Version: '11.8.3-MariaDB-1+b1 from Debian' socket: '/run/mysql/mysq>
Oct 27 10:52:40 css systemd[1]: Started mariadb.service - MariaDB 11.8.3 database server.
Oct 27 10:52:40 css mariabdb[6053]: 2025-10-27 10:52:40 3 [Warning] Access denied for user 'root'@'localh>
Oct 27 10:52:40 css mariabdb[6053]: 2025-10-27 10:52:40 4 [Warning] Access denied for user 'root'@'localh>
Oct 27 10:52:40 css debian-start[6083]: ERROR 1045 (28000): Access denied for user 'root'@'localhost' (us>
lines 1-28/28 (END)
```

Figura 6. Comando alternativo para consultar estado y posteriormente activar el servicio

Ahora se tiene que cambiar la clave del usuario que viene por defecto, MySQL tiene un usuario por defecto llamado “root”, para proceder a cambiar la clave se tiene que iniciar sesión en MySQL.

```
(css@css)-[~]
$ sudo mysql -u root -p
Enter password:
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 10
Server version: 11.8.3-MariaDB-1+b1 from Debian -- Please help get to 10k stars at https://github.com/MariaDB/Server

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]> |
```

Figura 7. Se inicia sesión en MySQL

Nota: al meter el comando `sudo mysql -u root -p` se pide una contraseña, esa clave es la del usuario que tienes configurado en Linux.

Para cambiar la clave y el usuario se mete el comando: `ALTER USER 'root'@'localhost' IDENTIFIED BY 'javafx123456';`


```
css@css: ~  
MariaDB [(none)]> ALTER USER 'root'@'localhost' IDENTIFIED BY 'javafx123456';  
Query OK, 0 rows affected (0.016 sec)  
  
MariaDB [(none)]> |
```

Figura 8. Se cambia la clave del usuario root

La clave del usuario root ahora es javafx123456, esto es así porque se devuelve un mensaje “Query OK” lo que confirma que el cambio de clave fue exitoso.

El proyecto construye la base de datos mediante un script llamado: \$HOME/DashBoard-Soporte-Tecnico/DashBoard/src/main/resources/sql_scripts/db_tech_support.sql. El cual podrás ejecutar desde consola: source db_tech_support.sql;

```
css@css: ~  
MariaDB [(none)]> ALTER USER 'root'@'localhost' IDENTIFIED BY 'javafx123456';  
Query OK, 0 rows affected (0.016 sec)  
  
MariaDB [(none)]> source /home/css/javafx/DashBoard-Soporte-Tecnico/DashBoard/src/main/resources/sql_scripts/  
db_tech_support.sql;  
Query OK, 1 row affected (0.001 sec)  
  
Database changed  
Query OK, 0 rows affected (0.006 sec)  
  
Query OK, 1 row affected (0.002 sec)  
  
Query OK, 1 row affected (0.000 sec)  
  
MariaDB [db_tech_support]> |
```

Figura 9. Comando para crear la base de datos mediante un script SQL

Para verificar si la base de datos se creó o no, se usa el comando: show databases

```
MariaDB [db_tech_support]> show databases;  
+-----+  
| Database |  
+-----+  
| db tech support |  
| dbpeliculas |  
| information_schema |  
| mysql |  
| performance_schema |  
| sys |  
+-----+  
6 rows in set (0.001 sec)
```

Figura 10. Comando para verificar si la base de datos se creó

Al completar todos los pasos en el orden especificado, el proyecto se podrá ejecutar para su uso, en caso de anomalías o problemas relacionados con la instalación, favor enviar un mensaje al correo manuel.cruz.sanchez@estudiante.uacm.edu.mx y te responderé en breve.

Manual creado por Manuel Cruz Sánchez