



Java is a trademark of Sun Microsystems, Inc.



JavaOneSM

The Collections Connection Gala Tenth (!) Edition

Joshua Bloch
Martin Buchholz
Kevin Bourrillion
Google Inc.

Goal of Talk

Find true happiness

Achieve world domination with the
Java™ Collections Framework

Outline

I. What's coming in Java 7?

II. Google Collections

III. Q & A

Pearls of wisdom from the assembled multitudes

I. What's coming in Java 7?

- > Strangely, we don't exactly know
- > Hopefully: Collection literals and array-like access
- > Probably: core of Doug Lea's Fork-Join Framework
- > Probably: **Phaser**, **TransferQueue** (JSR-166y)
- > Hopefully: a few goodies from Google Collections
- > Improved **sort** *implementation*
- > Improved **ConcurrentLinkedQueue** *implementation*

Collection Literals

Submitted to Project Coin by Josh Bloch

```
List<String> list = ["a", "b", "c"];  
String firstElement = list[0];  
Map<Integer, String> map = {1 : "One"};
```

Indexing syntax for Lists and Maps

Submitted to Project Coin by Shams Mahmood Imam

```
List<String> list = ...;  
String firstElement = list[0];  
Map<Integer, String> map = ...;  
map[1] = "One";
```

Fork-Join Framework (Doug Lea)

- > Framework for a style of fine-grained parallel programming in which problems are solved by (recursively) splitting them into subtasks that are solved in parallel, waiting for them to complete, and then composing results.
- > A talk unto itself
 - (Which Doug gave, but not at JavaOne)


TransferQueue

- > When **ThreadPoolExecutor** is below core size, it creates a new thread when request comes in, even if there is a waiting worker thread
- > What is needed (internally): **tryTransfer(Task)**

Collections/Arrays.sort Will Use TimSort

- > Adapted from Tim Peter's Python list sort
- > A stable, adaptive, iterative mergesort that requires far fewer than $n \lg(n)$ comparisons when running on partially sorted arrays, while offering performance comparable to a traditional mergesort when run on random arrays (**i.e., magic!**)
- > Systematically exploits any order
- > Space performance also much better than current

ConcurrentLinkedQueue Improvements



II. Google Collections

- > An open-source (Apache 2) library
- > Complements Java Collections Framework
 - Parts of GC will eventually migrate into JCF
 - Requires JDK 1.5
- > Status: 1.0-rc2 (release candidate 2) **today**
- > Widely used in production at Google
- > Developers: Kevin Bourrillion & a cast of thousands

Google Collections Overview

- > 1. Immutable Collections
- > 2. Multisets, Multimaps
- > 3. **MapMaker**
- > Other cool interfaces, implementations, algorithms

1. Immutable Collections

- > JDK has `collections.unmodifiableFoo` wrappers
- > *Unmodifiable* - you can't change it
- > *Immutable* - it can never change, no matter what
- > Immutability is tasty!
 - See *Effective Java* Item 15 for some of the many reasons

Immutable Collections (2)

- > We provide
 - `ImmutableList`
 - `ImmutableSet`
 - `ImmutableSortedSet`
 - `ImmutableMap`
 - `ImmutableSortedMap` (as of today!)
- > Brand-new, standalone implementations

Immutable vs. unmodifiable

- > JDK wrappers still useful for unmodifiable views of changing data. But for most purposes, use ours:
 - Immutability guaranteed!
 - Very easy to use
 - Slightly faster
 - Use less memory
 - Sometimes far less (ImmutableSet, factor of 2-3x)

Constant sets: Before, v1

```
public static final Set<Integer> LUCKY_NUMBERS;  
static {  
    Set<Integer> set = new LinkedHashSet<Integer>();  
    set.add(4);  
    set.add(8);  
    set.add(15);  
    set.add(16);  
    set.add(23);  
    set.add(42);  
    LUCKY_NUMBERS = Collections.unmodifiableSet(set);  
}
```


Constant sets: Before, v2

```
> public static final Set<Integer> LUCKY_NUMBERS  
    = Collections.unmodifiableSet(  
        new LinkedHashSet<Integer>(  
            Arrays.asList(4, 8, 15, 16, 23, 42)));
```

- A little nicer.
- But uses four different classes! Something's weird.

Constant sets: After

- >

```
public static final ImmutableSet<Integer> LUCKY_NUMBERS  
    = ImmutableSet.of(4, 8, 15, 16, 23, 42);
```
- > Now we just say exactly what we mean.
- > And get performance benefits as well!
- > We're using just one class (it implements `Set`)
- > `of()` method name inspired by `java.util.EnumSet`

Constant maps: Before

```
public static final Map<String, Integer> ENGLISH_TO_INT;  
static {  
    Map<String, Integer> map  
        = new LinkedHashMap<String, Integer>();  
    map.put("four", 4);  
    map.put("eight", 8);  
    map.put("fifteen", 15);  
    map.put("sixteen", 16);  
    map.put("twenty-three", 23);  
    map.put("forty-two", 42);  
    ENGLISH_TO_INT = Collections.unmodifiableMap(map);  
}
```

Constant maps: After

```
public static final ImmutableMap<String, Integer>
    ENGLISH_TO_INT =
        new ImmutableMap.Builder<String, Integer>()
            .put("four", 4)
            .put("eight", 8)
            .put("fifteen", 15)
            .put("sixteen", 16)
            .put("twenty-three", 23)
            .put("forty-two", 42)
            .build();
```

2. Multisets and Multimaps

- > A multiset is a set that permits multiple instances
 - Set: {spam, baked-beans, sausage}
 - Multiset: [spam x 42, baked beans x 1, sausage x 1]
- > A multimap is a multi-valued map
 - Map: {a=1, a=2, b=3, c=4, c=5, c=6}
 - Multimap: {a=[1, 2], b=[3], c=[4, 5, 6]}

Historically, Multimaps and Multisets Emulated Atop Maps

```
public class Freq {  
    public static void main(String[] args) {  
        Map<String, Integer> m =  
            new TreeMap<String, Integer>();  
        for (String word : args) {  
            Integer freq = m.get(word);  
            m.put(word, (freq == null ? 1 : freq + 1));  
        }  
        System.out.println(m);  
    }  
}
```

- A bit verbose
- Bug-prone
- Uses wrong abstraction

With Multiset

```
public class Freq {  
    public static void main(String[] args) {  
        Multiset<String> m =  
            TreeMultiset.create(Arrays.asList(args));  
        System.out.println(m);  
    }  
}
```

- Speaks for itself!

3. MapMaker (Bob Lee)

- > A **ConcurrentMap** builder, providing any combination of these features:
 - Soft or weak keys
 - Soft or weak values
 - Timed expiration
 - On-demand computation of values
- > Far more powerful, easy to use than **WeakHashMap**
- > Concurrent on-demand computation is **really** hard

Mapmaker Example

```
ConcurrentMap<Key, Graph> graphs = new MapMaker()  
    .concurrencyLevel(32)  
    .softKeys()  
    .weakValues()  
    .expiration(30, TimeUnit.MINUTES)  
    .makeComputingMap(  
        new Function<Key, Graph>() {  
            public Graph apply(Key key) {  
                return createExpensiveGraph(key);  
            }  
        })  
    );
```

MapMaker Makes it Easy to Do Hard Stuff

```
public static Comparator<Object> arbitraryOrder() {
    return new Comparator<Object>() {
        private Map<Object, Integer> uids;

        public int compare(Object left, Object right) {
            if (left == right) return 0;
            int leftCode = System.identityHashCode(left);
            int rightCode = System.identityHashCode(right);
            if (leftCode != rightCode)
                return leftCode < rightCode ? -1 : 1;

            // We have an identityHashCode collision (rare)
            synchronized (this) {
                if (uids == null)
                    final AtomicInteger counter = new AtomicInteger(0);
                    uids = new MapMaker().weakKeys().makeComputingMap(
                        new Function<Object, Integer>() {
                            public Integer apply(Object from) {
                                return counter.getAndIncrement();
                            }
                        });
            }
            return uids.get(left).compareTo(uids.get(right));
        }
    };
}
```

Useful URLs

> Java Collections

- <http://java.sun.com/javase/6/docs/technotes/guides/collections/index.html>

> Google Collections

- <http://google-collections.googlecode.com>


> Fork-Join Framework

- <http://g.oswego.edu/>

> TimSort

- <http://svn.python.org/projects/python/trunk/Objects/listsort.txt>

Obligatory Graphic





JavaOneSM

Thank You

jjb@google.com
martinrb@google.com
kevinb@google.com