kernoid

Kernoid: One Sovereign Core for Email, Identity and Storage

Whitepaper v0.2 (draft) · October 2026

Executive Summary

Email and identity are the core of every organisation's IT – and the core of its dependency. Whoever runs an organisation's mailboxes and its accounts also runs the logins to every other service, the calendars, the contacts and, usually, the files. Many organisations have handed that core to Microsoft or Google – universities in the United States, the United Kingdom and the Netherlands largely, those in Germany, France, Austria and Switzerland far less[1]. Switching away is hard not because good free software is missing, but because the free building blocks are separate systems: one for mail, one for identity, one for files – each with its own users, its own administration and its own operations.

Kernoid is one system for that core. Kernoid is a self-hostable cloud application, written in Rust, that combines an email and collaboration server with an identity provider and storage – as one program with one data model:

- **one identity** – an account is created once and is at the same time the mailbox, the login for single sign-on and the owner of files; nothing has to be synchronised;
- **one administration** – users, groups, domains and policies are managed in one place;
- **one operation** – one application to deploy, update and monitor, built for containers and Kubernetes, with PostgreSQL for data and S3-compatible object storage for messages and files.

Built on proven free software. Kernoid does not start from zero. It takes over what it can from two mature projects under the GNU AGPL-3.0: from **Stalwart**, a mail and collaboration server written in Rust (SMTP, IMAP, JMAP, CalDAV, CardDAV, WebDAV)[2], and from **Zitadel**, an identity provider with OpenID Connect, SAML 2.0, SCIM 2.0 and passkeys[3]. Kernoid reuses Stalwart's AGPL-licensed code where it fits and carries Zitadel's concepts and protocol logic over to Rust – with the attribution both licences require.

Everything included, for everyone. Kernoid is free software under the GNU AGPL-3.0, and the free release is the full product: single sign-on, provisioning, multi-tenancy and clustering are part of it – the very features that other projects reserve for a paid edition; Stalwart, for example, lists SCIM provisioning and multi-tenancy with per-tenant identity backends as enterprise features[4]. Kernoid collects no telemetry.

[1] Fiebig et al., "Heads in the Clouds? Measuring Universities' Migration to Public Clouds", Proceedings on Privacy Enhancing Technologies 2023(2) (MX records of universities), checked 2026-10-22: https://arxiv.org/abs/2104.09462

[2] Stalwart, README of `stalwartlabs/stalwart` (AGPL-3.0 and SELv2), checked 2026-10-22: https://github.com/stalwartlabs/stalwart

[3] Zitadel, README of `zitadel/zitadel` (AGPL-3.0), checked 2026-10-22: https://github.com/zitadel/zitadel

[4] Stalwart Enterprise, feature list, checked 2026-10-22: https://stalw.art/enterprise/

A falkOSS project. Kernoid is published by falkOSS, a non-profit company for free software in formation in Falkensee near Berlin **[OPEN: status of the incorporation and of the non-profit recognition at publication]**. falkOSS holds the name and funds the development; the technical direction lies with the project. As soon as Kernoid is stable, falkOSS will run its own email on it.

The Problem

Whoever runs the core holds the keys

Every other service of an organisation hangs on two things: the **login**, which single sign-on hands out for all applications, and the **email address**, to which every account outside single sign-on sends its password resets. Whoever operates mail and identity can let people in and lock them out – everywhere at once.

That is not a theoretical risk. Providers based in the United States must hand over data on request "regardless of whether such communication, record, or other information is located within or outside of the United States"[5] – a European data centre does not change that. And in May 2025 the chief prosecutor of the International Criminal Court lost access to his Microsoft email after the US sanctioned the court; Microsoft states that it never stopped its services to the court itself[6]. Whatever happened in detail: an organisation that does not run its core itself does not decide alone who keeps access to it.

Free building blocks, separate systems

There is good free software for every part of the core – mail servers, identity providers, file services. But each is its own system with its own accounts. A self-hosted setup typically connects them: the mail server reads its users from a directory over LDAP, accepts logins from an identity provider over OpenID Connect, or has its accounts created and removed by that identity provider over SCIM. Stalwart, for example, offers all three ways next to its internal directory[7].

Connected systems are not one system:

- **An account exists several times** – in the identity provider, in the mail server, in the file service – and every copy has to be created, changed and removed. If one connection fails, a person who left keeps a working mailbox, or a new colleague has none.
- **Rights live in several places.** Who may read a shared mailbox, who may open a folder, who is administrator: each system answers that itself.
- **Operation multiplies:** several administration interfaces, several update cycles, several backups, several sets of logs to look at when something goes wrong.

That is not a weakness of the individual projects. It follows from building the core out of separate systems.

The connecting parts cost extra

Many free projects finance themselves through a paid edition – a legitimate model. But what moves into the paid edition is often exactly what connects systems or serves many organisations at once:

- Stalwart lists SCIM provisioning and multi-tenancy with per-tenant identity backends as enterprise features[8].

[5] 18 U.S.C. § 2713, added by the CLOUD Act (Pub. L. 115–141, div. V, 2018), checked 2026-10-22: https://www.law.cornell.edu/uscode/text/18/2713

[6] heise online, "Criminal Court: Microsoft's email block a wake-up call for digital sovereignty", 19 May 2025: https://heise.de/-10387383; heise online, "Microsoft denies mail blockade at the International Criminal Court", 5 June 2025, checked 2026-10-22: https://heise.de/-10429628

[7] Stalwart documentation, authentication backends (internal; external LDAP, SQL, OIDC; SCIM provisioning), checked 2026-10-22: https://stalw.art/docs/auth/backend/overview

– authentik reserves provisioning to Google Workspace and Microsoft Entra ID, among others, for its enterprise edition[9].

An organisation that wants to run its core seriously ends up paying in several places – or living without these features.

Mail has to arrive

A mail server can be configured perfectly and its messages still land in the spam folder. The large mailbox providers set the rules: since February 2024 Google requires SPF or DKIM, valid reverse DNS and TLS from every sender, and from bulk senders also DMARC and one-click unsubscribe[10]; Microsoft applies similar rules to domains that send 5,000 or more messages to Outlook.com[11]. Beyond those rules, a new server's address has no sending history – and reputation cannot be configured.

Kernoid makes the configurable part the default and checks it: it shows when SPF, DKIM, DMARC, reverse DNS or MTA-STS are missing or wrong. Reputation it cannot create – but a new installation can send through a relay of the operator's choice until its own address has built a history.

Positioning

What Kernoid is

Kernoid is **one application** for an organisation's core services:

Area	Scope
Email	SMTP (in and out), IMAP, JMAP; spam and phishing filtering; SPF, DKIM, DMARC, MTA-STS, DANE
Collaboration	calendars and contacts (CalDAV, CardDAV, JMAP), sharing
Storage	files with sync, sharing and versions – Kernoid's own storage, with first-party apps (see below)
Identity	accounts, groups, roles; OpenID Connect, OAuth 2.0, SAML 2.0, SCIM 2.0, LDAP; MFA and passkeys
Administration	one interface and one API for all of the above, multi-tenancy
Operation	self-hosted on Docker or Kubernetes; needs only PostgreSQL and S3-compatible object storage

Mailbox, login and file owner are **the same object**. That is the difference to running a mail server and an identity provider side by side and connecting them.

Everything included

The free release is the full product. Single sign-on, provisioning, multi-tenancy, clustering, audit logs – everything an organisation needs to run its core seriously – is part of every Kernoid release, for everyone. There is one edition, and it is free.

Kernoid is funded through falkOSS – by donations, grants and the service providers who build on it – not by holding features back (see Governance and Funding).

[8] Stalwart Enterprise, feature list, checked 2026-10-22: https://stalw.art/enterprise/
[9] authentik documentation, enterprise features, checked 2026-10-22: https://docs.goauthentik.io/enterprise/enterprise-features/
[10] Google Workspace Admin Help, "Email sender guidelines", checked 2026-10-22: https://support.google.com/a/answer/81126
[11] Microsoft Support, "Fix NDR error 550 5.7.515 in Outlook.com", checked 2026-10-22: https://support.microsoft.com/en-us/outlook/fix-ndr-error-550-5-7-515-in-outlook-com

Apps and protocol

Kernoid comes with **first-party apps** for files, and over time for mail, calendars and contacts – first on the web, then on the desktop, then on mobile **[OPEN: evaluation of a cross-platform framework, e.g. Flutter]**. They speak an **open, documented protocol**; anyone can write their own apps and clients against it, and existing clients keep working through the standard protocols (IMAP, JMAP, CalDAV, CardDAV, WebDAV).

For file sync, Kernoid either adopts an existing open protocol that meets its needs or defines its own **[OPEN: evaluation – JMAP for files (IETF draft, already implemented by Stalwart) would give Kernoid one protocol family for mail, calendars, contacts and files; other candidates to be assessed]**.

The licences are split on purpose:

Part	Licence	Why
Server (Kernoid)	GNU AGPL-3.0-or-later; code taken over from Stalwart and Zitadel stays AGPL-3.0-only	whoever offers Kernoid as a service must share their changes
First-party apps and client libraries	MIT	apps can be distributed through app stores; anyone can build on them
Protocol specification	CC BY 4.0, freely implementable	no client depends on Kernoid's own apps

The apps are decoupled from the server: they share no AGPL code with it, only the protocol. Code taken over from Stalwart or Zitadel therefore stays in the server.

No lock-in, not even to Kernoid

Kernoid speaks the open standards in both directions: mail over IMAP and JMAP, calendars and contacts over CalDAV and CardDAV, files over WebDAV, accounts over SCIM and LDAP. The same protocols that bring an organisation's data into Kernoid take it out again. An organisation that leaves Kernoid takes its data with it, in standard formats.

Where it comes from

Kernoid stands on the work of others and says so: it takes over **Stalwart**'s AGPL code for mail and collaboration and carries **Zitadel**'s concepts and logic for identity over to Rust – see Building on Stalwart and Zitadel.

What Kernoid is not

- **Not an integration layer** on top of separate servers – it is one system.
- **Not an office suite.** Kernoid builds where integration is the problem – the core – and connects where integration already works: documents, video and chat come from proven free software that logs in through Kernoid (see Integrations).
- **Not a hosting company.** Kernoid is software that anyone can run. Managed hosting is offered by others: by providers of the operator's choice, and planned by a separate company **[OPEN: name, timing]**. falkOSS itself hosts Kernoid only for non-profit purposes.

Why Rust

Kernoid handles the most sensitive data an organisation has: its mail and its accounts. Rust removes whole classes of memory-safety bugs, delivers the performance needed to serve many tenants from few machines, and lets Kernoid build directly on Stalwart's existing Rust code.

DRAFT

Architecture

One data model

Kernoid is built around a few objects that every part of the system shares:

- A **tenant** is an organisation: its domains, its policies, its administrators. One installation serves one or many tenants.
- An **account** belongs to a tenant and is at the same time a login, a mailbox, the owner of calendars and contacts and the owner of files.
- A **group** collects accounts and is at the same time a mailing list and the owner of shared folders and calendars – one object instead of three.
- A **shared mailbox** has an address but no person behind it (info@, support@); roles decide who works with it.
- A **resource** – a room, a device – has an address and a calendar and can be booked.
- A **service account** belongs to a machine or an application and uses keys instead of a login.
- **Roles** say what an account or a group may do – one rights model for mailboxes, calendars, folders and administration.
- **Applications** are the other services of a tenant that log in through Kernoid over OpenID Connect or SAML.

Because these objects exist once, there is nothing to synchronise inside Kernoid: an account that is disabled can no longer log in, receive mail or open files – in one step.

Components

Component	Does	Protocols
Identity and auth	accounts, groups, roles, login, MFA and passkeys, single sign-on for other applications	OpenID Connect, OAuth 2.0, SAML 2.0, SCIM 2.0, LDAP
Mail	receiving, filtering, storing and sending mail	SMTP, IMAP, JMAP
Collaboration	calendars, contacts, sharing	CalDAV, CardDAV, JMAP
Storage and sync	files, folders, versions, sharing, sync with the apps	WebDAV; sync protocol **[OPEN: see Apps and protocol]**
Administration	one interface and one API for all of the above	REST (described with OpenAPI) and GraphQL, over HTTPS with JSON

All components are parts of one program, not separate services: they use the same objects and the same rights model directly.

Modules

The core – identity, mail, collaboration, storage – is always there. Everything that connects Kernoid to a particular outside service is a **module**: the Jitsi module, the WOPI module for office software, SCIM connections to specific services, and further modules as integrations are added (see Integrations).

- Modules are **off by default** and are switched on where they are needed – per installation, and per tenant.
- A module that is off does nothing: it opens no ports and runs no background jobs.
- Modules are part of the same free release. They are not add-ons that cost extra – *everything included* applies to them as well.

DRAFT

[OPEN: whether modules are compiled into the one image and switched on in the configuration, or loaded separately]

Data

Kernoid needs **PostgreSQL** and **S3-compatible object storage** – nothing else:

- **Identity and administration** are stored as events, following Zitadel, which is built on the event-sourcing pattern and gets its audit trail from it[12]. Every change to an account, a role or a policy is an event; the current state is derived from them. The audit log is not an extra feature, it is the data.
- **Mail, calendars and contacts:** structure and metadata in PostgreSQL, message bodies and attachments in object storage.
- **Files:** folders, versions and rights in PostgreSQL, content in object storage.
- **Search and coordination** between instances run on PostgreSQL as well; an external search index can be added later as an option for large installations, but is never required.

Operation

Kernoid ships as **one container image**. Configuration decides which roles a process takes on: in a small installation one process does everything; in a large one, receiving mail, IMAP and JMAP, the web interface and API, and background jobs run as separate, independently scaled groups of processes. The processes keep no state of their own – everything lives in PostgreSQL and object storage – so they can be added, removed and updated one after another.

Kernoid comes with **Docker Compose** files for small installations and a **Kubernetes operator** for large ones, which also takes care of upgrades and backups **[OPEN: upgrade policy and supported versions]**.

Security

- **Memory safety:** written in Rust, see Why Rust.
- **In transit:** TLS for every protocol, MTA-STS and DANE for mail between servers.
- **At rest:** Kernoid encrypts message and file content itself, with a key per tenant, before it goes to object storage – the storage provider only ever sees ciphertext. PostgreSQL is encrypted by the storage layer below it. The tenant keys are protected by a main key from the configuration **[OPEN: rotation, optional external key management]**.
- **Login:** MFA and passkeys for every account; policies per tenant.
- **Traceability:** every change to identity and administration is an event (see Data).
- **End-to-end encryption** for selected folders is a goal for after 1.0; it has no date yet.
- **Review:** an external security audit takes place before 1.0, and its results are published **[OPEN: funding of the audit]**.

Building on Stalwart and Zitadel

Kernoid does not start from zero. Two mature free projects have solved large parts of what it needs: Stalwart for mail and collaboration, Zitadel for identity. This chapter says what Kernoid takes from them, under which rules, and how it deals with both projects.

[12] Zitadel documentation, "Event store", checked 2026-10-22: https://zitadel.com/docs/concepts/eventstore/overview

Stalwart: code

Stalwart is a mail and collaboration server written in Rust[13]. Kernoid takes over Stalwart code where it fits – above all the protocols (SMTP, IMAP, JMAP, CalDAV, CardDAV, WebDAV) and mail filtering. Kernoid copies the selected parts **once** into its own repository, removes everything under the enterprise licence and adapts the code to its own data model; it does not merge Stalwart's later changes **[OPEN: the exact selection of crates]**.

Stalwart is published under two licences, and every source file says which applies[14]:

Files (Rust, `main`, 2026-10-22)	Licence	Kernoid
907	`AGPL-3.0-only OR LicenseRef-SEL` – free choice	takes them under the AGPL-3.0
102	`LicenseRef-SEL` only (Stalwart Enterprise License)	takes nothing – among them all of SCIM
52 of the 907	contain sections marked `SPDX-SnippetBegin` … `SPDX-SnippetEnd` under `LicenseRef-SEL`	removes these sections

What Stalwart reserves for its enterprise edition – SCIM provisioning, parts of multi-tenancy – Kernoid writes itself. An automated check keeps the rule: no file and no section under `LicenseRef-SEL` ever enters Kernoid's repository – every change is checked for it automatically before it is merged.

Zitadel: concepts and logic

Zitadel is an identity provider written in Go, under AGPL-3.0-only; some parts are under Apache-2.0 (API definitions, documentation) or MIT (the login application, client packages)[15]. Kernoid carries over Zitadel's event model, its multi-tenancy and the logic of its protocols – OpenID Connect, OAuth 2.0, SAML 2.0 **[OPEN: further scope]** – and rewrites them in Rust.

A translation from Go to Rust is still a derivative work. Kernoid therefore draws a clear line: **code written while reading Zitadel's source is marked as derived from Zitadel** and keeps its licence and copyright notice. What Kernoid builds only from specifications and documentation is its own code.

[OPEN: whether Zitadel's MIT-licensed login application can serve as a starting point for Kernoid's login]

Licences in one repository

- **Kernoid's own code** is under the AGPL-3.0-or-later.
- **Code taken over** from Stalwart or derived from Zitadel keeps the AGPL-3.0-only, its copyright notice and a note of its origin.
- **The server as a whole** is therefore distributed under the AGPL-3.0. A move to a later version of the AGPL would only be possible once the taken-over code is replaced.
- **The apps are not affected:** they share no code with the server (see Apps and protocol).

Every file names its licence and its authors in SPDX headers; a credits file lists both projects and what Kernoid took from them. Kernoid follows the REUSE specification, so every file's licence and copyright can be checked by machine[16].

[13] Stalwart, README of `stalwartlabs/stalwart` (AGPL-3.0 and SELv2), checked 2026-10-22: https://github.com/stalwartlabs/stalwart

[14] Own count of the `SPDX-License-Identifier` lines in the `.rs` files of `stalwartlabs/stalwart`, branch `main`, commit `aa47d8e`, 2026-10-22; licence texts in `LICENSES/`: https://github.com/stalwartlabs/stalwart/tree/main/LICENSES

[15] Zitadel, `LICENSING.md`, checked 2026-10-22: https://github.com/zitadel/zitadel/blob/main/LICENSING.md

[16] REUSE Specification, Free Software Foundation Europe, checked 2026-10-22: https://reuse.software/spec/

Working with the upstreams

Kernoid is not a fork that follows Stalwart or Zitadel release by release. Code that Kernoid takes over becomes part of Kernoid and develops on its own. Fixes found along the way go back where the projects accept them:

- **Zitadel** accepts contributions under Apache-2.0[17].
- **Stalwart** currently accepts only bug fixes and translations, only from contributors it has vouched for, only under its Fiduciary Contributor License Agreement, and no AI-generated code[18]. Kernoid reports what it finds and offers fixes within these rules.

Security fixes in both projects concern Kernoid as well: Kernoid follows the security advisories of both and checks every fix against the code it took over. **[OPEN: contact with both projects before publication]**

Integrations

Kernoid builds the core and leaves the rest to free software that already works: documents, video and chat. These services do not become part of Kernoid; the operator runs them next to it, and they connect to Kernoid through open standards. Where a service needs more than a standard, Kernoid has an optional module for it (see Modules) – an organisation that uses no video conferencing never has to think about Jitsi.

How services connect

Need	Standard	Kernoid's part
Login	OpenID Connect, SAML 2.0	identity provider: one login for every connected service
Accounts in other services	SCIM 2.0	accepts accounts from outside, and creates and removes accounts in connected services – leaving the organisation ends access everywhere in one step
Directory for older software	LDAP	directory that such software can read
Editing files in place	WOPI	file host that office software opens and saves files on

Any service that supports one of these standards can use Kernoid without changes to either side.

Planned integrations

- **Documents:** Collabora Online and ONLYOFFICE Docs open and save files on a file host over WOPI[19]. Kernoid's storage acts as that host, so documents are edited where they are stored, with Kernoid's rights. This WOPI module is the first extension planned after 1.0.
- **Video:** Jitsi Meet authenticates users internally, over LDAP or with signed tokens (JWT); its documentation names no OpenID Connect[20]. Kernoid's Jitsi module issues these tokens for logged-in accounts – no extra service is needed.
- **Chat:** for Matrix, the Matrix Authentication Service accepts an upstream OpenID Connect provider, but no SAML[21]. Kernoid is that provider.

[17] Zitadel, `LICENSING.md`, checked 2026-10-22: https://github.com/zitadel/zitadel/blob/main/LICENSING.md

[18] Stalwart, `CONTRIBUTING.md`, checked 2026-10-22: https://github.com/stalwartlabs/stalwart/blob/main/CONTRIBUTING.md

[19] Collabora Online, `README.md` (integration with a host via a WOPI URL; MPL-2.0): https://github.com/CollaboraOnline/online.mirror/blob/main/README.md; ONLYOFFICE Docs API, "WOPI REST API", checked 2026-10-22: https://api.onlyoffice.com/docs/docs-api/using-wopi/wopi-rest-api/

[20] Jitsi Meet Handbook, "Self-Hosting Guide – Docker", section Authentication, checked 2026-10-22: https://jitsi.github.io/handbook/docs/devops-guide/devops-guide-docker/

Further integrations follow when someone needs them and tests them.

What an integration means

An integration is listed when it has been tested against a released version of Kernoid and its setup is documented. There is no certification and no partner programme behind it; the setup guides are part of Kernoid's documentation.

Governance and Funding

A falkOSS project

Kernoid is published by **falkOSS – Falcon Lake Open Source Software gUG (haftungsbeschränkt)**, a non-profit company for free software in Falkensee near Berlin, currently in formation **[OPEN: state of incorporation and of the non-profit recognition at publication]**. falkOSS holds Kernoid's name, logo, domains and GitHub organisation and funds its development. Kernoid keeps its own identity; falkOSS appears as its publisher.

The technical direction lies with the project. A small group of maintainers decides; larger changes – to the protocol, the data model or the licences – are first published as a proposal (RFC) and discussed in the open. Whoever contributes well over time can become a maintainer.

Principles

Two principles of falkOSS apply to every falkOSS project and are part of its articles of association **[OPEN: until notarisation, a draft]**:

- **Everything included.** The free release is the whole product: one edition, no enterprise or pro edition, no licence keys, no subscriptions, no features released later for paying customers. Money is earned for work – operation, support, development – never for unlocking.
- **No telemetry.** Kernoid sends no usage data anywhere. Exceptions are only what is technically necessary, what the user starts themselves, and what an operator explicitly opts into.

Licences

Part	Licence
Server	GNU AGPL-3.0-or-later; code taken over from Stalwart and Zitadel AGPL-3.0-only (see Building on Stalwart and Zitadel)
First-party apps and client libraries	MIT
Protocol specification	CC BY 4.0
Documentation and this whitepaper	CC BY-SA 4.0
Name and logo	not covered by the licences; held by falkOSS, which registers "Kernoid" as a word mark once it is incorporated

Contributions are accepted under the Developer Certificate of Origin (`git commit -s`) – there is no contributor licence agreement, and nobody gets rights to the code that others do not have.

[21] Matrix Authentication Service documentation, "Single sign-on", checked 2026-10-22: https://element-hq.github.io/matrix-authentication-service/setup/sso.html

Funding

Kernoid is funded through falkOSS, by:

- **donations** – tax-deductible once falkOSS is recognised as non-profit;
- **grants** for open digital infrastructure, such as those of the Sovereign Tech Agency[22] or NLnet's NGI Zero funds[23] **[OPEN: which programmes fit and accept a project at Kernoid's stage]**;
- **work** for organisations that build on Kernoid: support, development of features they need – which then go into the one free release.

The roadmap assumes two to three full-time developers (see Roadmap); budgets are part of the individual grant applications.

Managed service

falkOSS does not sell Kernoid as a service. A **separate company** is planned to offer managed hosting **[OPEN: name, timing]**; any other provider can do the same. That company runs the same software under the same licence and has no rights that other providers lack.

falkOSS itself hosts Kernoid only for non-profit purposes – and runs its own email on Kernoid as soon as it is stable.

Roadmap

The order is fixed; the time windows are rough. They count from the **start of funded development** and assume a team of **two to three full-time developers** – with fewer people or less money, every window grows **[OPEN: start of funded development]**.

Milestone	Window (from start)	Content
Alpha	12–18 months	identity and mail
Beta	further 9–12 months (21–30)	collaboration, storage and sync, first app
1.0	further 6–12 months (27–42)	stable for production

Before the start

- publish this whitepaper and the repositories
- talk to Stalwart and Zitadel (see Working with the upstreams)
- apply for funding (see Funding)
- write down the data model and the event model in detail; evaluate the sync protocol

Alpha – identity and mail

Identity comes first: it is the larger part of the work and the foundation of everything else. Much of the mail part can build on Stalwart.

- tenants, accounts, groups, roles – as events, with the audit log
- login with MFA and passkeys; OpenID Connect and OAuth 2.0 for other applications
- mail: SMTP in and out, IMAP, JMAP, spam filtering, SPF, DKIM and DMARC
- administration interface and API
- one container image with Docker Compose, PostgreSQL and object storage

[22] Sovereign Tech Agency, checked 2026-10-22: https://www.sovereign.tech
[23] NLnet, "Propose a project", checked 2026-10-22: https://nlnet.nl/propose/

DRAFT

The alpha is for testing, not for production data.

Beta – collaboration and files

- calendars and contacts (CalDAV, CardDAV, JMAP)
- SAML 2.0, SCIM 2.0 (accepting and pushing accounts) and LDAP
- files: storage, versions, sharing, WebDAV and the sync protocol
- the first first-party app: files on the web
- running in separate roles across several instances, with the Kubernetes operator

1.0 – ready for production

- stable data formats and a documented upgrade path between versions
- documentation for operators, including migration from other systems
- external security audit, results published
- falkOSS moves its own email to Kernoid

After 1.0

First comes editing documents in place over WOPI. After that, without dates and in no fixed order: end-to-end encryption for selected folders, the desktop and mobile apps, further integrations, an optional external search index.

Get Involved

Kernoid is at its beginning. This is the moment when help shapes the most.

Developers

Kernoid needs people who know or want to learn:

- **Rust** – async, networking, systems programming
- **identity protocols** – OpenID Connect, OAuth 2.0, SAML, SCIM, WebAuthn
- **mail and groupware protocols** – SMTP, IMAP, JMAP, CalDAV, CardDAV
- **distributed systems** – PostgreSQL, object storage, event sourcing
- **apps** – desktop, mobile and web clients
- **operation** – containers, Kubernetes, security

Every contribution is welcome – code, review, documentation, translations, testing. Contributions are accepted under the Developer Certificate of Origin.

Organisations

- **Try it:** test the alpha and the beta and tell us what is missing for your organisation.
- **Fund it:** donations and grants pay for development; commissioned work goes into the one free release.
- **Offer it:** run Kernoid for your customers – the software is the same for everyone.

Public sector and funders

Kernoid is free software for a core every administration needs. Public bodies can fund its development, test it in pilots and ask for open standards in procurement.

DRAFT

Contact

- **GitHub:** https://github.com/kernoid **[OPEN: organisation not yet created]**
- **Website, email, chat: [OPEN: domains not yet registered]**
- **Publisher:** falkOSS – https://falkoss.org

Questions and corrections to this whitepaper are welcome as issues or pull requests in its repository **[OPEN: link once public]**.

DRAFT