

Segment Tree With Graph :

```

#define L node*2+1
#define R node*2+2
#define mid ((l+r)/2)
const int N = 1e5+1 ;
int id ;
int seg [2][4*N] ;
vvp adj (8*N);
void build (int l , int r , int node){
    if(l==r){
        seg[0][node] = 1 ;
        seg[1][node] = 1 ;
        return ;
    }
    seg[0][node] = id++;
    seg[1][node] = id++;
    build(l,mid,L);
    build(mid+1,r,R);
    adj[seg[0][node]].push_back({seg[0][L],0});
    adj[seg[0][node]].push_back({seg[0][R],0});
    adj[seg[1][L]].push_back({seg[1][node],0});
    adj[seg[1][R]].push_back({seg[1][node],0});
}
void connect (int l , int r , int node , int lx , int rx , int tp ,int u , int w){
    if(r<lx || rx<l) return ;
    if(l>=lx&&r<=rx){
        if(tp==0){
            adj[u].push_back({seg[0][node],w});
        }else{
            adj[seg[1][node]].push_back({u,w});
        }
        return ;
    }
    connect (l , mid , L , lx , rx , tp , u , w);
    connect (mid+1 , r , R , lx , rx , tp , u , w);
}
int n , q , s ;
void solve(){
    cin>>n>>q>>s ;
    id = n ;
    build(0,n-1,0);

    while (q--){
        {
            int t ; cin>>t ;
            if(t==1){
                int u , v , w ; cin>>u>>v>>w ;
                u--;v--;
                adj[u].push_back({v,w});
            }
        }
    }
}

```

```

    }else if (t==2){
        int v , l , r , w ; cin>>v>>l>>r>>w;
        l--;r--;v--;
        conect(0,n-1,0,l,r,0,v,w);

    }else{
        int v , l , r , w ; cin>>v>>l>>r>>w;
        l--;r--;v--;
        conect(0,n-1,0,l,r,1,v,w);
    }
}
vi dis (8*N,-1);
vi vis (8*N);
priority_queue<pair<int,int>,vp,greater<>>pq;
pq.push({0,s-1});

while (!pq.empty())
{
    int w = pq.top().first ;
    int node = pq.top().second ;
    pq.pop();
    if(vis[node])continue;
    vis[node]++;
    dis[node]=w ;
    for(auto f : adj[node]){
        if(!vis[f.first]){
            pq.push({f.second +w,f.first });
        }
    }
}

lp(i,n){
    cout<<dis[i]<<" " ;
}
cout ln ;
}

```

Max Subarray Sum SegTree :

```

struct Segtree
{
    #define L 2*node+1
    #define R 2*node+2
    #define mid ((l+r)/2)
    struct nod
    {
        int mx ;
        int sum ;
        int perf ;
    }
}

```

```

    int suf ;
};

vector<nod> seg ;
int sz; nod skip ;

nod merge (nod a ,nod b){
    nod ans ;
    ans.sum = a.sum+b.sum ;
    ans.perf = max(a.perf , a.sum+b.perf);
    ans.suf = max(b.suf , b.sum+a.suf);
    ans.mx = max({a.mx,b.mx,a.suf+b.perf,0ll});
    return ans ;
}

void build (int l , int r , int node , vector<int> & arr){
    if(l==r){
        if(l<arr.size()){
            seg[node].sum += arr[l];
            seg[node].mx = max(arr[l],0ll);
            seg[node].perf = max(arr[l],0ll);
            seg[node].suf = max(arr[l],0ll);
        }
        return;
    }
    build(l,mid,L,arr);
    build(mid+1,r,R,arr);
    seg[node] = merge (seg[L],seg[R]);
}

nod query (int l , int r , int node ,int lx , int rx){
    if(r<lx || rx<l)return skip ;
    if(l>=lx&&r<=rx) return seg[node];
    nod left = query (l , mid ,L , lx , rx);
    nod right= query (mid+1,r,R , lx,rx);
    return merge(left,right);
}

void update (int l , int r , int node , int indx , int val){
    if(l==r){
        seg[node].sum=val;
        seg[node].mx = max(val,0ll);
        seg[node].perf=val;
        seg[node].suf = max(val,0ll);
        return ;
    }
    if(indx<=mid){
        update(l,mid,L,indx,val);
    }
    else{
        update(mid+1,r,R,indx,val);
    }
    seg[node] = merge (seg[L],seg[R]);
}

Segtree(vector<int>&v){
    int n = v.size();

```

```

    sz = 1 ;
    nod x ;
    x.mx = 0 ; x.sum = 0 , x.perf = 0, x.suf = 0;
    skip = x ;
    while (sz < n) sz *= 2 ;
    seg = vector<nod> (sz*2 , skip);
    build(0,sz-1,0,v);
}

nod queryCall(int l , int r){
    return query(0,sz-1,0,l,r);
}

void updateCall(int val , int indx){
    update(0,sz-1,0,indx,val);
}

};

```

C. First element at least X

time limit per test: 1 second
memory limit per test: 1024 megabytes

In this task, you need to add to the segment tree the operation of finding the minimum index j such that $a[j] \geq x$.

Input

The first line contains two integers n and m ($1 \leq n, m \leq 100000$), the size of the array and the number of operations. The next line contains n numbers a_i , the initial state of the array ($0 \leq a_i \leq 10^9$). The following lines contain the description of the operations. The description of each operation is as follows:

- 1 i v : change the item with index i to v ($0 \leq i < n, 0 \leq v \leq 10^9$).
- 2 x : find the minimum index j such that $a[j] \geq x$. If there is no such element, print -1 . Indices start from 0.

Output

For each operation of the second type, print the answer for the query.

```

struct Segtree
{
    #define L 2*node+1
    #define R 2*node+2
    #define mid ((l+r)/2)
    struct nod
    {
        int val ;
        int ind ;
    };
    vector<nod> seg ;
    int sz; nod skip ;
    nod merge (nod a , nod b){
        nod res ;
        res.val = max(a.val,b.val);
        res.ind = max(a.val,b.val); // not important ;
        return res ;
    }
}

```

```

nod query (int l , int r , int node ,int lx , int rx , int x ){
    if(seg[node].val<x){
        nod temp ;
        temp.val = x , temp.ind = -1 ;
        return temp ;
    }
    if(l==r)return seg[node];
    if(seg[L].val>=x){
        return query(l , mid, L,lx,rx,x);
    }else{
        return query(mid+1, r, R,lx,rx,x);
    }
}

void update (int l , int r, int node , int indx , int val){
    if(l==r){
        seg[node].val = val;
        seg[node].ind = indx ;
        return ;
    }
    if(indx<=mid){
        update(l,mid,L,indx,val);
    }
    else{
        update(mid+1,r,R,indx,val);
    }
    seg[node] = merge (seg[L],seg[R]);
}

Segtree(int szz){
    int n = szz;
    sz = 1 ;
    nod x ; x.ind = 0 ; x.val = 0 ;
    skip = x ;
    while (sz<n) sz*=2 ;
    seg = vector<nod> (sz*2 , skip);
}

int queryCall(int l , int r , int x){
    return query(0,sz-1,0,l,r ,x).ind;
}

void updateCall(int val , int indx){
    update(0,sz-1,0,indx,val);
}

#undef L
#undef R
#undef mid
};

```

D. First element at least X - 2

time limit per test: 1 second

memory limit per test: 1024 megabytes

In this task, you need to add to the segment tree the operation of finding for the given x and l the minimum index j such that $j \geq l$ and $a[j] \geq x$.

Input

The first line contains two integers n and m ($1 \leq n, m \leq 100000$), the size of the array and the number of operations. The next line contains n numbers a_i , the initial state of the array ($0 \leq a_i \leq 10^9$). The following lines contain the description of the operations. The description of each operation is as follows:

- 1 i v : change the item with index i to v ($0 \leq i < n$, $0 \leq v \leq 10^9$).
- 2 x l : find the minimum index j such that $j \geq l$ and $a[j] \geq x$ ($0 \leq x \leq 10^9$, $0 \leq l < n$). If there is no such element, print -1 . Indices start from 0.

Output

For each operation of the second type, print the answer for the query.

```
struct Segtree
{
    #define L 2*node+1
    #define R 2*node+2
    #define mid ((l+r)/2)
    struct nod
    {
        int val ;
        int ind ;
    };

    vector<nod> seg ;
    int sz; nod skip ;
    nod temp ;

    nod merge (nod a ,nod b){
        nod res ;
        res.val = max(a.val,b.val);
        if(a.val>b.val){
            res.ind = a.ind;
        }else{
            res.ind = b.ind;
        }
        return res;
    }

    nod query (int l , int r , int node ,int lx , int rx , int x ){
        if(seg[node].val<x || r<lx){
            return temp ;
        }
        if(l==r)return seg[node];
        nod left ;

        left = query(l,mid,L,lx,rx,x);
        if(left.ind!=1e14){
            return left;
        }
    }
}
```

```

    return query(mid+1, r, R,lx,rx,x) ;
}

void update (int l , int r, int node , int indx , int val){
    if(l==r){
        seg[node].val = val;
        seg[node].ind = indx ;
        return ;
    }
    if(indx<=mid){
        update(l,mid,L,indx,val);
    }
    else{
        update(mid+1,r,R,indx,val);
    }
    seg[node] = merge (seg[L],seg[R]);
}

Segtree(int sz){
    int n = sz;
    sz = 1 ;
    nod x ; x.ind = 0 ; x.val = 0 ;
    temp.val = 1e9 , temp.ind = 1e14 ;
    skip = x ;
    while (sz<n) sz*=2 ;
    seg = vector<nod> (sz*2 , skip);
}

int queryCall(int l , int r , int x){
    return query(0,sz-1,0,l,r ,x).ind;
}

void updateCall(int val , int indx){
    update(0,sz-1,0,indx,val);
}

};

```

DSU Without Small to Larg :

```

struct Dsu
{
    vector<int> par , sz , pos;
    Dsu (int n){
        for (int i = 0; i <= n; i++)
        {
            sz.push_back(1);
            par.push_back(i);
            pos.push_back(0) ;
        }
    }
    int find(int u) {

```

```

        if (par[u] == u) return u;
        int p = find(par[u]);
        pos[u] += pos[par[u]];
        return par[u] = p;
    }
    bool merge (int u , int v){
        u = find(u) ;
        v = find(v) ;
        if(u==v)return false ;
        par[u] = v ;
        pos[u] = pos[v]+1;
        sz[u]+=sz[v];
        return true ;
    }
};

```

DP Problem For GCD = 1 :

```

#include <bits/stdc++.h>
using namespace std;

const int N = 3e5 + 7;
const int MOD = 1e9 + 7;

int n;
int countDiv[N];      // countDiv[i] = number of elements divisible by i
int factorial[N];     // factorial[i] = i!
int inverse[N];       // inverse[i] = modular inverse of factorial[i]
int dp[20][N];        // dp[k][i] = number of groups of size k with GCD = i

// Fast exponentiation to compute a^b % MOD
int fast_pow(int a, int b) {
    int result = 1;
    while (b) {
        if (b & 1) result = 1LL * result * a % MOD;
        a = 1LL * a * a % MOD;
        b >>= 1;
    }
    return result;
}

// Compute n choose r modulo MOD
int nCr(int a, int b) {
    if (b < 0 || a < b) return 0;
    return 1LL * factorial[a] * inverse[b] % MOD * inverse[a - b] % MOD;
}

// Subtract under modulo
void mod_subtract(int &a, int b) {

```



```
a -= b;
if (a < 0) a += MOD;
}

int main() {
    ios::sync_with_stdio(false);
    cin.tie(nullptr);

    // Precompute factorials and their modular inverses
    factorial[0] = 1;
    for (int i = 1; i < N; ++i)
        factorial[i] = 1LL * factorial[i - 1] * i % MOD;

    inverse[N - 1] = fast_pow(factorial[N - 1], MOD - 2);
    for (int i = N - 1; i >= 1; --i)
        inverse[i - 1] = 1LL * inverse[i] * i % MOD;

    // Read input and count frequencies
    cin >> n;
    for (int i = 0; i < n; ++i) {
        int a;
        cin >> a;
        countDiv[a]++;
    }

    // For each i, accumulate counts of all its multiples
    for (int i = 1; i < N; ++i)
        for (int j = i * 2; j < N; j += i)
            countDiv[i] += countDiv[j];

    // Try group sizes from 1 to 19
    for (int groupSize = 1; groupSize < 20; ++groupSize) {
        for (int i = N - 1; i >= 1; --i) {
            // Total ways to choose groupSize elements from numbers divisible by i
            dp[groupSize][i] = nCr(countDiv[i], groupSize);

            // Subtract counts for all multiples of i (Inclusion-Exclusion)
            for (int j = i * 2; j < N; j += i)
                mod_subtract(dp[groupSize][i], dp[groupSize][j]);
        }

        // If there exists at least one group of this size with GCD = 1
        if (dp[groupSize][1] > 0) {
            cout << groupSize << '\n';
            return 0;
        }
    }

    // No valid group found
    cout << -1 << '\n';
    return 0;
}
```

parall Binary Search 1:

```

struct BIT {
    int n;
    vector<int> bit;

    BIT(int _n) {
        n = _n;
        bit.assign(n + 1, 0); // عشان نقدر نوصل لـ n+1 بنخلي الحجم
    }

    // أضيف قيمة عند موقع i
    void add(int i, int val) {
        ++i; // داخليًا فقط -based نحوله لـ 1
        while (i <= n) {
            bit[i] += val;
            i += i & -i;
        }
    }

    // مجموع [0, i]
    int prefixQuery(int i) {
        ++i;
        int res = 0;
        while (i > 0) {
            res += bit[i];
            i -= i & -i;
        }
        return res;
    }

    // rangeAdd (بعد مجموع في موقع واحد)
    int pointQuery(int i) {
        return prefixQuery(i);
    }

    // أضيف قيمة لمدى [l, r]
    void rangeAdd(int l, int r, int val) {
        add(l, val);
        add(r + 1, -val);
    }
};

void solve(){
    int n , q ; cin>>n>>q;
    BIT t1 (n+1);
    vvi adj(n+1) , anc(20,vi(n+1));
    int timer = 0 ;
    vp arr ;
    vi in(n+1) , out(n+1) , dis(n+1) , ans(q);

```

```

lp(i,n){
    int a ; cin>>a;
    arr.push_back({a,i});
}
sort(all(arr)) ;
for (int i = 0; i < n-1; i++)
{
    int a , b ; cin>>a>>b;
    adj[a].push_back(b);
    adj[b].push_back(a);
}

function<void(int,int)>dfs=[&](int u , int p){
    anc[0][u] = p ;
    in[u] = timer++;
    for(auto f : adj[u]){
        if(f!=p){
            dis[f] = dis[u]+1;
            dfs(f,u);
        }
    }
    out[u] = timer-1;
};
dfs(1,0);
for (int mask = 1; mask < anc.size(); mask++)
{
    for (int u = 1; u <= n; u++)
    {
        anc[mask][u] = anc[mask-1][anc[mask-1][u]];
    }
}
auto getLCA=[&](int u, int v)
{
    if (dis[v] > dis[u]) swap(u, v);

    int diff = dis[u] - dis[v];
    for (int i = 0; diff > 0; ++i) {
        if (diff & 1)
            u = anc[i][u];

        diff >>= 1;
    }

    if (u == v) return u;

    for (int i = anc.size() - 1; i >= 0; --i) {
        if (anc[i][u] != anc[i][v]) {
            u = anc[i][u];
            v = anc[i][v];
        }
    }
    return anc[0][u];
};

```

```

int ind = -1 ;

vector<array<int,5>>qi ;
for (int i = 0; i < q; i++)
{
    int u , v , k ; cin>>u>>v>>k;
    qi.push_back({k,u,v,getLCA(u,v),i});
}
sort(all(qi)) ;
function<void(int,int,vector<int>)>ParallelBS=[&](int l ,int r ,
vector<int>curQ){
    if(l>r||curQ.empty())return ;
    if(l==r){
        for(auto indxQuery : curQ){
            ans[qi[indxQuery][4]] = arr[l].first ;
        }
        return;
    }
    int mid = (l+r)/2 ;
    while (ind<mid)
    {
        ind++;
        int node = arr[ind].second+1 ;
        t1.rangeAdd(in[node],out[node],1);
    }
    while (ind>mid)
    {
        int node = arr[ind].second+1 ;
        t1.rangeAdd(in[node],out[node],-1);
        ind--;
    }
    vector<int>lf , ri ;
    for(auto indxQuery : curQ){
        auto [k , u , v , lc , iQ] = qi[indxQuery];
        int sum = t1.pointQuery(in[u])+t1.pointQuery(in[v])-
t1.pointQuery(in[lc]);
        if(lc!=1)sum-=t1.pointQuery(in[anc[0][lc]]);

        if(sum<k)ri.push_back(indxQuery);
        else lf.push_back(indxQuery);
    }
    ParallelBS(l , mid , lf);
    ParallelBS(mid+1 , r , ri);
};
vector<int>tmpQ(q);
for (int i = 0; i < q; i++)
{
    tmpQ[i] = i ;
}
ParallelBS(0,n-1,tmpQ) ;
for (int i = 0; i < q; i++)
{
    cout<<ans[i] ln ;
}

```

```
}
```

parall Binary Search 2:

```
int MXN = 1e6+100;
vector<bool>prim(MXN+1,true);
vector<int> allprimes ;
void sev(){
    for (int i = 2; i <= MXN; i++)
    {
        if(prim[i]){
            allprimes.push_back(i);
            for (int j = i*i; j <= MXN; j+=i)
            {
                prim[j] = false ;
            }
        }
    }
}

struct BIT {
int n;
vector<int> bit;
BIT(int _n) {
    n = _n;
    bit.assign(n + 1, 0);
}

void add(int i, int val) {
    ++i;
    while (i <= n) {
        bit[i] += val;
        i += i & -i;
    }
}

int prefixQuery(int i) {
    ++i;
    int res = 0;
    while (i > 0) {
        res += bit[i];
        i -= i & -i;
    }
    return res;
}

int pointQuery(int i) {
    return prefixQuery(i);
}
```

```

}

void rangeAdd(int l, int r, int val) {
    add(l, val);
    add(r + 1, -val);
}
};

void solve(){
    int n , q , timer = 0 ; cin>>n ;
    vector<vector<int>>>adj(n+1) , anc(20,vector<int>(n+1));
    vector<array<int,4>>>qi ;
    vector<int>in(n+1),out(n+1),dis(n+1) ;
    map<int,vector<int>>>mp;
    for (int i = 0; i < n; i++)
    {
        int a ; cin>>a ; mp[a].push_back(i+1);
    }
    for (int i = 0; i < n-1; i++)
    {
        int a , b ; cin>>a>>b;
        adj[a].push_back(b) ;
        adj[b].push_back(a) ;
    }
    cin>>q ;
    function<void(int,int)>dfs = [&](int u , int p){
        in[u] = timer++;
        anc[0][u] = p ;
        for(auto f : adj[u]){
            if(f!=p){
                dis[f] = dis[u]+1;
                dfs(f,u);
            }
        }
        out[u] = timer-1;
    };
    dfs(1,0);

    for (int mask = 1; mask < 18; mask++)
    {
        for (int u = 1; u <= n; u++)
        {
            anc[mask][u] = anc[mask-1][anc[mask-1][u]];
        }
    }
    auto getLCA = [&](int u, int v)
    {
        if (dis[v] > dis[u]) swap(u, v);
        int diff = dis[u] - dis[v];
        for (int i = 0; diff > 0; ++i) {
            if (diff & 1)
                u = anc[i][u];
        }
    }
}

```

```

        diff >>= 1;
    }

    if (u == v) return u;

    for (int i = anc.size() - 1; i >= 0; --i) {
        if (anc[i][u] != anc[i][v]) {
            u = anc[i][u];
            v = anc[i][v];
        }
    }
    return anc[0][u];
};

for (int i = 0; i < q; i++)
{
    int u , v ; cin>>u>>v ;
    qi.push_back({u,v,getLCA(u,v),i});
}
BIT t1 = BIT(n+1) ;
vector<int>ans(q);
int ind = -1 ;
function<void(int,int,vector<int>)>parallBS=[&](int l , int r ,
vector<int>cur){
    if(l>r||cur.empty())return ;
    if(l==r){
        for(auto indxQury : cur){
            ans[qi[indxQury][3]] = allprimes[l] ;
        }
        return;
    }
    int mid = (l+r)/2 ;
    while (mid>ind)
    {
        ind++;
        for(auto ix : mp[allprimes[ind]]){
            t1.rangeAdd(in[ix],out[ix],1);
        }
    }
    while (mid<ind)
    {
        for(auto ix : mp[allprimes[ind]]){
            t1.rangeAdd(in[ix],out[ix],-1);
        }
        ind--;
    }
    vector<int> lf , ri ;

    for(auto qx : cur){
        auto [u , v , lc , iq] = qi[qx];
        int sum = t1.pointQuery(in[u])+t1.pointQuery(in[v])-
t1.pointQuery(in[lc]);
        if(lc!=1)sum -= t1.pointQuery(in[anc[0][lc]]);
        if(sum<=ind){
            lf.push_back(qx);

```

```

        }else{
            ri.push_back(qx);
        }
    }
    parallBS(l , mid , lf);
    parallBS(mid+1 , r , ri);
};
vector<int>tmp(q) ;
iota(all(tmp),0);
parallBS(0 , n+5, tmp);

for (int i = 0; i < q; i++)
{
    cout<<ans[i] ln ;
}
}
int32_t main()
{
    sev();
    KERO
    tc
    solve();
    return 0;
}

```

Binary Search For In , Out :

```

void solve(){
    int n ; cin>>n ;
    vvi adj(n+1) , anc(20 , vi(n+1));
    vvi distarrin(n+1) ;

    vi dis(n+1),in(n+1) , out(n+1);
    int timer = 0 ;
    for (int i = 0; i < n; i++)
    {
        int a; cin>>a;
        adj[a].push_back(i+1);
        adj[i+1].push_back(a);
    }
    function<void(int,int)>dfs=[&](int u , int p){
        anc[0][u] = p ;
        in[u] = timer++;
        for(auto f : adj[u]){
            if(f!=p){
                dis[f] = dis[u]+1;

                dfs(f,u);
            }
        }
    }
}

```



```

    }
    out[u] = timer-1;
};
dfs(0,0);
for (int mask = 1; mask < 20; mask++)
{
    for (int u = 1; u <= n; u++)
    {
        anc[mask][u] = anc[mask-1][anc[mask-1][u]];
    }
}
auto get_kth_ancestor=[&](int u, int k) {
for (int i = 0; i < 20; ++i) {
    if (k & (1 << i)) {
        u = anc[i][u];
        if (u == 0) break;
    }
}
return u;
};
for (int i = 1; i <= n; i++)
{
    distarrin[dis[i]].emplace_back(in[i]);
}
for (int i = 0; i <= n; i++)
{
    sort(all(distarrin[i]));
}

int m ;cin>>m;
while (m--)
{
    int a , b ;cin>>a>>b;
    if(b>=dis[a]){cout<<0<<" " ; continue;}
    int lc = get_kth_ancestor(a,b);
    int d = dis[a];
    if(lc==0){cout<<0<<" " ; continue;}
    int l = in[lc], r = out[lc];
    int L = lower_bound(distarrin[d].begin(), distarrin[d].end(), l) -
distarrin[d].begin();
    int R = upper_bound(distarrin[d].begin(), distarrin[d].end(), r) -
distarrin[d].begin();
    int ans = R-L-1;
    cout<<ans<<" ";
}
}

```

Faris Code :

```

#include <bits/stdc++.h>
using namespace std;
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
#define all(v) ((v).begin()), ((v).end())
#define rall(v) ((v).rbegin()), ((v).rend())
#define oo 1e18 + 5
#define MOD 11(1e9 + 7)
#define min3(a, b, c) min(a, min(b, c))
#define max3(a, b, c) max(a, max(b, c))
#define M_PI 3.14159265358979323846
#define int long long
typedef int ll;
typedef vector<ll> vi;
typedef vector<vi> vii;
typedef pair<ll, ll> pi;
typedef vector<pi> vip;
typedef map<ll, ll> mapi;
typedef vector<vip> viip;
typedef tree<pi, null_type, less<pi>, rb_tree_tag,
tree_order_statistics_node_update> ordered_set;
ll gcd(ll a, ll b) { return ((b == 0) ? a : gcd(b, a % b)); }
const int N = 1e6 + 10;
///// Agamista
const int M = 30;
ll ansector[N][M];
ll lvl[N];
vii adj;
vii virtualAdj;
int ans = 0;
vi mp;
void dfs(ll node, ll par)
{
    ansector[node][0] = par;
    lvl[node] = lvl[par] + 1;
    for (int i = 1; i < M; ++i)
    {
        ansector[node][i] = ansector[ansector[node][i - 1]][i - 1];
    }
    for (auto ch : adj[node])
    {
        if (ch == par)
            continue;
        dfs(ch, node);
    }
}

ll findKthAncestor(ll u, ll k)
{
    for (int i = M - 1; i >= 0; --i)
    {

```

```

        if ((1 << i) & k)
            u = ansector[u][i];
    }
    return u;
}

ll LCA(ll u, ll v)
{
    if (lvl[u] < lvl[v])
        swap(u, v);
    u = findKthAncestor(u, lvl[u] - lvl[v]);
    if (u == v)
        return v;

    for (int i = M - 1; i >= 0; --i)
    {
        if (ansector[u][i] == ansector[v][i])
            continue;
        u = ansector[u][i];
        v = ansector[v][i];
    }
    return ansector[u][0];
}

ll dis(ll u, ll v)
{
    return lvl[u] + lvl[v] - 2 * lvl[LCA(u, v)];
}

vi sub(N, 1), in(N);
void euler(ll node, ll par, ll &time)
{
    in[node] = time++;
    for (auto ch : adj[node])
    {
        if (ch == par)
            continue;
        euler(ch, node, time);
        sub[node] += sub[ch];
    }
}

void buildVirtualTree(vi &nodes, map<int, vector<int>> &virtualAdj)
{
    if (nodes.empty())
        return;
    stack<ll> stk;
    stk.push(nodes[0]);

    for (int i = 1; i < nodes.size(); i++)
    {
        ll curr = nodes[i];
        ll lca = LCA(stk.top(), curr);
    }
}

```

```

// Pop nodes that are not ancestors of current node
while (stk.size() > 1 && lvl[lca] < lvl[stk.top()])
{
    ll top = stk.top();
    stk.pop();
    virtualAdj[stk.top()].push_back(top);
}

// If LCA is different from top of stack
if (stk.top() != lca)
{
    ll top = stk.top();
    stk.pop();
    virtualAdj[lca].push_back(top);
    stk.push(lca);
}

stk.push(curr);
}

// Connect remaining nodes in stack
while (stk.size() > 1)
{
    ll top = stk.top();
    stk.pop();
    virtualAdj[stk.top()].push_back(top);
}
}

int rec(int node, int par, map<int,vector<int>> &adj)
{
    ll nc = 0;
    for (auto c : adj[node])
    {
        if (c == par)
            continue;
        int me = rec(c, node, adj);
        if(mp[node])
            ans += me * node;
        ans += (me * nc) * node;
        nc += me;
    }
    nc+=mp[node];
    if(mp[node]){
        ans+=node;
        mp[node]=0;
    }
    return nc;
}

void solve()
{
    ll n;
    cin >> n;

```

```

adj.assign(n + 1, {});
mp.assign(n+1,0);
for (int i = 0; i < n - 1; i++)
{
    ll u, v;
    cin >> u >> v;
    adj[u].push_back(v);
    adj[v].push_back(u);
}
dfs(1, 0);
ll time = 0;
euler(1, -1, time);
ll q;
cin >> q;
while (q--)
{
    ll k;
    cin >> k;
    vi a(k);
    for (int i = 0; i < k; i++){
        cin >> a[i];
        mp[a[i]]++;
    }

    sort(a.begin(), a.end(), [&](ll u, ll v)
        { return in[u] < in[v]; });

    vi allNodes = a;
    for (int i = 0; i < k - 1; i++)
    {
        ll u = a[i];
        ll v = a[(i + 1)];
        ll l = LCA(u, v);
        allNodes.push_back(l);
    }
    sort(allNodes.begin(), allNodes.end(), [&](ll u, ll v)
        { return in[u] < in[v]; });
    allNodes.erase(unique(allNodes.begin(), allNodes.end()), allNodes.end());
    map<int,vector<int>> tmp;
    buildVirtualTree(allNodes, tmp);
    ans = 0;
    rec(allNodes[0], -1, tmp);
    cout << ans << endl;
}
}

signed main()
{
    ios_base::sync_with_stdio(0);
    cin.tie(0);
    cout.tie(0);
    ll tc = 1;
    // cin >> tc;
    while (tc--)

```

```

    {
        solve();
    }
}

```

Number Theory GCDs Sum * GCDs Length :

```

void solve(){
    int n ; cin>>n ;
    int arr[n];
    vi freq(N) , divs(N) , dp(N);
    lp(i,n)cin>>arr[i] , freq[arr[i]]++;
    for (int i = 1; i < N; ++i)
        for (int j = i; j < N; j += i)
            divs[i]+=freq[j];

    int ans = 0 ;
    for (int g = N; g >= 2 ; g--){
        int cur =(divs[g]*fastPowerMod(2 , divs[g]-1 , mod))%mod;
        for (int i = g*2; i < N; i+=g)
        {
            cur = (cur-dp[i]+mod)%mod;
        }
        dp[g] = cur ;
        ans = (ans + (cur*g)%mod)%mod ;
    }
    cout<<ans ln ;
}

```

trie problme :

```

int g = 0 ;
struct Node
{
    map<char,int>mp ;
    int sz = 0 , isEnd = 0;
    pair<int,int>mx = {0 , 0} ;
    int &operator[](char x){
        return mp[x];
    }
};

```

```

struct Trie
{
    vector<Node>tr ;
    int newNode (){
        tr.emplace_back();
        return tr.size()-1 ;
    }
    Trie(){
        tr.clear() ;
        newNode() ;
    }
    void insert(string &s , int i = 0 , int cur = 0 ){
        if(i==s.size()){
            tr[cur].isEnd ++;
            tr[cur].mx = min(tr[cur].mx , {-tr[cur].isEnd , -1});
            return ;
        }
        if(!tr[cur][s[i]]){
            tr[cur][s[i]] = newNode() ;
        }
        int newcur = tr[cur][s[i]];
        tr[cur].sz++;
        insert(s,i+1,newcur);
        tr[cur].mx = min(tr[cur].mx , {tr[newcur].mx.first , s[i]});
    }

    string search (string s){

        int cur = 0 ;
        for(auto ch : s){
            if(tr[cur][ch]==0){
                return "" ;
            }
            cur = tr[cur][ch] ;
        }
        string res = s ;
        int f = 0;
        while (f!=-1)
        {
            f = tr[cur].mx.second ;
            if(f==-1)break;
            cur = tr[cur][f] ;
            res+=f ;
        }
        g = -tr[cur].mx.first ;
        return res ;
    }
};

```

Ternary Search :

```

int mn = 0 , mx = 1e10 ;
while (mx - mn > 3)
{
    int md1 = mn + (mx-mn)/3 ;
    int md2 = mx - (mx-mn)/3 ;
    int c1 = check() , c2 = check() ;
    res = min({res , c1 , c2}) ;
    if(c1 <= c2){
        mx = md2 ;
    }else{
        mn = md1 ;
    }
}

double ternary_search(double l, double r) {
    double eps = 1e-9;           //set the error limit here
    while (r - l > eps) {
        double m1 = l + (r - l) / 3;
        double m2 = r - (r - l) / 3;
        double f1 = f(m1);       //evaluates the function at m1
        double f2 = f(m2);       //evaluates the function at m2
        if (f1 < f2)
            l = m1;
        else
            r = m2;
    }
    return f(l);                 //return the maximum of f(x) in [l, r]
}

```

parall Binary Search

```

int n , m , q; cin>>n>>m>>q;
vi l(q , 0) , r(q , m-1) , res(q , -1);
vector<pair<int,int>>edg , qi;
for(int i = 0 ; i < m ; i++){
    int a , b ; cin>>a>>b;
    edg.push_back({a,b});
}
for(int i = 0 ; i < q ; i++){
    int a , b ; cin>>a>>b;
    qi.push_back({a,b});
}
while(true)
{
    bool f = false ;
    vector<vector<int>>mp(m+5);
    for(int i = 0 ; i < q ; i++){
        if(l[i] <= r[i]){

```



```
        mp[(l[i]+r[i])/2].push_back(i);
        f = true ;
    }
}
if(!f)break;
Dsu d (n+5);
for (int i = 0; i < m; i++)
{
    d.merge(edg[i].first , edg[i].second);
    for(auto x : mp[i]){
        if(d.find(qi[x].first) == d.find(qi[x].second)){
            r[x] = i-1;
            res[x] = i+1;
        }else{
            l[x] = i+1;
        }
    }
}
}
for(auto f : res)cout<<f ln ;
```