




Fantastic Plugins & How to Make Them

About Kerri

- Used PhoneGap for six+ years
- Author of five books about PhoneGap
- Working on several video series about PhoneGap
- IT Consultant for eight years
- Apache Cordova comitter
- @kerrishotts



About Jesse

- PhoneGap Developer since 2008
- Apache Cordova committer
- at Adobe for nearly 6 years now
- @purplecabbage

What is a Cordova Plugin?

noun A mystical collection of machine incantations which grant access to amazing and magical capabilities

ahem...

noun A module consisting of code and settings extending the essential functionality of Cordova with the goal of providing access to device capabilities, enhancing existing capabilities, or improving the developer's workflow

What can plugins do?

- Anything you can do with native code in various contexts:
 - run time
 - build time
 - install time
- Two categories
 - Core — used to be built in
 - Community — people like you!

Plugins at run time

Full access to the native SDK and device features. Some ideas:

- Faster computations (compared to JS)
- Expose native device features
 - push notifications, native social network sharing
- Use native widgets
 - Microsoft ACE
- Quality assurance, logging, etc.
- Analytics

Plugins at build time

Full access to the build-time environment and Cordova project.
Some ideas:

- Transpile ES2015+, TypeScript, etc. to ES5
- Bundle dependencies (webpack, browserify, jspm)
- Pre-process CSS files (SASS, less, auto-prefixer)
- Check code quality (eslint, tslint, jshint)
- Run tests, create code coverage reports

Plugins at install time

Full access to the Cordova project and environment at install time.
Some ideas:

- Could bundle other plugins
- Could configure the project environment
- Or, could provide tests for another plugin...

Plugin-ception 

The Core Plugins

Core Cordova features (used to be built-in)

battery-status	camera	console
contacts	device	device-motion
device-orientation	dialogs	file
file-transfer	geolocation	globalization
inappbrowser	media	media-capture
network-information	splashscreen	statusbar
vibration	whitelist	

Community Plugins

Extensions provided by the community — like you!

Repository	Plugins
https://cordova.apache.org/plugins	~1,960 plugins (– core)
http://www.pluginreg.com	~1,592 plugins (– core)
http://plugins.telerik.com/cordova	~77 plugins

Managing Plugins

or, finding fantastic plugins...

npm

Plugins are typically downloaded from npm:

```
[user@dev] $ cordova plugin add --save cordova-plugin-device

[user@dev] $ cordova plugin ls                # or list
              cordova-plugin-device 1.1.1 "Device"

[user@dev] $ cordova plugin rm --save \
              cordova-plugin-device          # or remove
```

Note: `--save` persists the plugin to `config.xml` so that plugins can be easily restored (done at `prepare` -time)

Github

Plugins can also be installed from a Github repository.

```
[user@dev] $ cordova plugin add --save \
              http://github.com/apache/cordova-plugin-device
[user@dev] $ cordova plugin rm --save cordova-plugin-device
```

Can specify a branch, too (useful for testing pre-release plugins):

```
[user@dev] $ cordova plugin add --save \
              http://github.com/apache/cordova-plugin-device#branch
```

Note: Use the plugin's identifier when removing — not the URL.

Local Filesystem

```
[user@dev] $ cordova plugin add --save [--link] \
              path/to/cordova-plugin-device
```

```
[user@dev] $ cordova plugin rm --save cordova-plugin-device
```

- Use `--link` when developing plugins
 - Changes are reflected automatically — no `rm` & `add` flow
 - Automatically symlinked if a parent (`../`)

Note: Careful with parent plugins and child projects — easy to get circular references in the file system (borks `cp`)

Finding Plugins

- Cordova Plugin Search: <https://cordova.apache.org/plugins>
- npm: <https://www.npmjs.com/search?q=ecosystem:cordova>
- Or, if the CLI is more your thing:

```
[user@dev] $ npm install -g npms-cli
```

```
[user@dev] $ npms search cordova-plugin device --size=5
```

Package
cordova-plugin-device • https://github.com/apache/cordova-plugin-device Cordova Device Plugin updated 2 months ago by shazron

Plugin Autopsy

or, what's inside these things?

ref: cordova-plugin-device

Plugin Structure

```
cordova-plugin-device/      # plugin root
  doc/<locale>              # documentation other than English (convention)
  src/<platform>            # Platform-specific native code
    |  android/
    |    + Device.java      # Native Android code
    |    ios/
    |      | CDVDevice.h    # Native iOS header
    |      + CDVDevice.m    # Native iOS code
    |
  tests/                   # Please add tests!
  types/                   # Types for Typescript
  www/                    # Web assets
  + device.js              # API for JavaScript consumers
  package.json             # npm metadata
  plugin.xml               # plugin metadata and configuration
  README.md                # English documentation
```

(representational only; not every file is included here)

Metadata

All plugins have metadata and settings in `plugin.xml`

- Unique plugin ID for registration, discovery, and management
- Version number, author, repository, etc.
- Supported platforms, engines, OS versions
- Native headers, source files, resources, JavaScript files
- Configuration preferences, permissions
- JavaScript API (if exposed to webview)
- Hook scripts and when to run them

Example Metadata (plugin.xml)

```
<?xml version="1.0" encoding="UTF-8"?>
<plugin xmlns="http://apache.org/cordova/ns/plugins/1.0"
  xmlns:rim="http://www.blackberry.com/ns/widgets"
  xmlns:android="http://schemas.android.com/apk/res/android"
  id="cordova-plugin-device"
  version="1.1.5-dev">
  <name>Device</name>
  <description>Cordova Device Plugin</description>
  <license>Apache 2.0</license>
  <keywords>cordova,device</keywords>
  <repo>https://link/to/git/repository.git</repo>
  <issue>https://link/to/issue/reporter.html</issue>
```

JavaScript API Entry

In cordova-plugin-device's plugin.xml:

```
<js-module src="www/device.js" name="device">  
  <clobbers target="device" />  
</js-module>
```

Examples: Multiple clobbers ¹, runs ², merges ³

-
1. clobbers, in app browser
 2. runs, file transfer
 3. merges, vibration

Indicate Platform Support

Using `<platform>` tags:

```
<platform name="android">
```

...

```
</platform>
```

```
<platform name="ios">
```

...

```
</platform>
```

Specifying headers, frameworks, etc.

```
1  <platform name="android">
2      <source-file src="src/android/Device.java"
3          target-dir="src/org/apache/cordova/
4  </platform>
5  <platform name="ios">
6      <header-file src="src/ios/CDVDevice.h" />
7      <source-file src="src/ios/CDVDevice.m" />
8      <framework src="libz.tbd" />
9  </platform>
```

Note: Can include third-party libraries too. iOS supports Cocoapods too!

Manifest modifications

- `config-file`¹
 - Adds elements to manifest
- `edit-config`²
 - Edits attributes of existing elements

1. android, file transfer; ios, geolocation; windows UAP, geolocation

2. TODO

npm Metadata Example

```
{
  "name": "cordova-plugin-device",
  "author": "Apache Software Foundation",
  "license": "Apache-2.0",
  "version": "1.1.5-dev",
  "description": "Cordova Device Plugin",
  "types": "./types/index.d.ts",
  "cordova": {
    "id": "cordova-plugin-device",
    "platforms": ["android", "ios", "windows", "wp8", ... ]
  },
  "repository": { "type": "git", "url": "https://..." },
  "keywords": ["cordova", "device",
    "ecosystem:cordova", "cordova-ios", "cordova-android",
    ... ],
```

Dependencies

```
<!-- plugin.xml -->
<dependency id="cordova-plugin-device" />
<dependency id="cordova-plugin-console" version="^1.0.0" />
// or in package.json
"engines": {
  "cordovaDependencies": {
    "2.0.0": { //plugin version (applies to any ver 2+)
      "cordova-plugin-console": "> 1.0.0",
      "cordova": "> 1.0.0" // cordova-cli above version 1
    }
  }
}
```

Note: don't forget about XML entities! So `< === <`

Ex 1: engine, in app browser

Ex 2: dependency, file transfer

Creating and Publishing Plugins

or, the art of crafting plugins

€ And getting rich, maybe? €

Or maybe not...

plugman

plugman is a node library that manages plugins in your projects. `cordova-cli`, `phonegap-cli`, etc., use `plugman` internally.

- It can also *create* plugins:

```
[user@dev] $ npm install -g plugman
[user@dev] $ plugman create --name Abracadabra \
                  --plugin_id cordova-plugin-abracadabra \
                  --plugin_version 0.0.1 \
                  --path .
```

- Can pass `--variable-name=value` pair string to define additional data like author, etc.

phonegap-plugin-template

Or, use PhoneGap's plugin template:

<https://github.com/phonegap/phonegap-plugin-template>

```
[user@dev] $ npm install -g \
              https://github.com/phonegap/phonegap-plugin-template

# phonegap-plugin-create path name plugin-id
[user@dev] $ phonegap-plugin-create ./abracadabra Abracadabra \
              cordova-plugin-abracadabra
```

Wiring it all up...


📄 www/<plugin>.js (consumer API)

```
cordova.exec(successFn, failureFn, "PluginName",  
            "pluginMethod", args<Array>);
```

📄 plugin.xml : (class mapping)

```
<feature name="PluginName">  
  <param name="ios-package" value="CDV<PluginClass>" />  
  <param name="onload" value="true" />  
</feature>
```

Wiring it all up... (2)

 `src/ios/CDV<PluginClass>.m` (native code)

```
- (void) <pluginMethod>:(CDVInvokedUrlCommand*)command {  
    // do something useful and optionally  
    // return results across the "bridge"  
}
```

StatusBar Example

 `www/statusbar.js` (consumer API)

```
function setStyleDefault() {  
    cordova.exec(null, null, "StatusBar", "styleDefault", []);  
}
```

 `plugin.xml`

```
<feature name="StatusBar">  
    <param name="ios-package" value="CDVStatusBar" />  
    <param name="onload" value="true" />  
</feature>
```


StatusBar Example (2)

📄 `src/ios/CDVStatusBar.m` (native code)

```
- (void) styleDefault:(CDVInvokedUrlCommand*)command {  
    [self setStyleForStatusBar:UIStatusBarStyleDefault];  
}
```

Remember the API's call to `cordova.exec`?

```
cordova.exec(null, null, "StatusBar", "styleDefault", []);  
"StatusBar"      --> <feature name="StatusBar"> (plugin.xml)  
                  --> <param ... value="CDVStatusBar"/>  
                  --> src/ios/CDVStatusBar.m  
"styleDefault"   --> -styleDefault:command (CDVStatusBar.m)
```

Returning data back to JavaScript

```
// in CDVStatusBar.m
(void)fireTappedEvent {
    if (_eventsCallbackId == nil) { return; }

    NSDictionary* payload = @{@"type": @"tap"};

    CDVPluginResult* result = [CDVPluginResult
        resultWithStatus:CDVCommandStatus_OK
        messageAsDictionary:payload];



    [result setKeepCallbackAsBool:YES]; // default is NO

    [self.commandDelegate sendPluginResult:result
        callbackId:_eventsCallbackId];
}
```

Follow the yellow brick bridge?
or, a look at the code behind the curtain!

Lots of bridges

A bridge is used to cross the gap between the native code context and the web view context.

- iOS
- Android
- Windows is an exception...
 - Careful, the bridge is a **mirage!** 
 - JavaScript is **native** 
 - `cordova.exec` uses a proxy

Publishing your plugin

- If you want to publish to `npm`, you'll need a `package.json`
- `plugman` can do that for you too!

```
[user@dev] $ plugman createpackagejson .  
[user@dev] $ npm publish
```

- Don't panic if the repo doesn't immediately show your plugin
 - wait a while — the underlying index has to catch up

A cool plugin demo

Testing your plugins

or, the art of making sure it works like it should

and improving the lives of developers who use your plugin 😊

Testing plugins

`cordova-mediac` is a test tool designed to run all the core Cordova plugin tests as part of Cordova's continuous integration system

- Tests are written in Jasmine 2.0
- Tests run asynchronously
- Plugins have a dependent test plugin which is installed separately (usually in `/tests` by convention)
- Many of these pieces of `cordova-mediac` are reusable, so Jesse spun them into another purpose-based tool...

cordova-paramedic

n. provides advanced levels of care at the point of illness or injury, including out-of-hospital treatment, and diagnostic services

```
[user@dev] $ | $ npm install -g cordova-paramedic
```

```
[user@dev] $ | $ cordova-paramedic --platform ios --plugin .
```

Repo & docs: <https://github.com/apache/cordova-paramedic>

Automates Jasmine Tests

- Creates a new project (in temporary location)
- Adds the platform specified (`ios` , `android` , `windows` , etc.)
- Installs the `cordova-plugin-test-framework` plugin
- Installs the plugin specified (in `.`) (current working directory)
- Installs the plugin's tests (in `./tests`)
- Sets start page to `cordova-plugin-test-framework` 's test runner
- Creates a local server to listen for results
- Exits with success/fail based on results

Note: Only supports npm-published platforms

How to write tests

- Copy a core plugin's tests – we all do it!
- Create a `tests` folder in your plugin's repository
- Add a `plugin.xml` file (doesn't need to be complex)

Debugging

or, mastering the dark art of reading your
computer's mind

Debugging

- Xcode (macOS) / Safari
 - But not concurrently!
- Android Studio / Google Chrome
- Visual Studio (Windows)

Docs

You should include documentation so that users know how to use your plugin; **good documentation is paramount**

- Look at any of the “core” plugins for best practices
- Convention:
 - English docs in the root `README.md` file
 - Translations in the `docs/` folder

Hooks

noun A piece of code that hooks into a Cordova process in order to perform some action on behalf of the plugin; see [dev guide](#).

Possibilities:

- Create entitlements as needed
- Transform code (transpile, version # replacement, etc.)
- Create launch images and icons
- Check plugin versions and warn if out-of-date

Want to see something [cool](#)?

Some more cool plugin ideas

- Optical Character Recognition using Tesseract
- Game controller support
- Apple Pencil, anyone?
- iOS Storage providers
- Audio/video processing

Tips & Tricks

or, wisdom from those who have gone before

and face-palmed for you in your stead...

JS API

- Promisify your API

```
1  function _promisifyMaybe(fn, thisArg) {
2    if (typeof Promise === "undefined") { return fn.bind(thisArg); }
3    return function _wrapper() {
4      return new Promise(function (resolve, reject) {
5        fn.apply(thisArg ? thisArg : this,
6          [resolve, reject].concat([].slice.call(arguments, 2)));
7      }
8    }
9  }
10 function doSomething(successCB, errorCallback, options) {
11   return (_promisifyMaybe(cordova.exec, cordova)
12     (successCB, errorCallback, "Abracadabra", "doSomething",
13       [arguments.length <= 1 ? successCB : options]));
14 }
```

JS API (2)

- Preprocess arguments in JavaScript
 - convert to appropriate types
 - throw type-mismatch errors, etc.
- Transpile ES2015+ to ES5
 - not all targets understand native ES2015 yet
- Oh, and unless you're creating a polyfill, try sticking to the `cordova.plugins` namespace. `window` gets awfully crowded!

Native

- Return useful error information
- Use background threads!
- Be respectful of other plugins
- Lazy load?
- Init events?

Miscellany

- Don't forget the `browser` platform!
 - Useful when testing on the desktop
 - May need to mock results if no equivalent browser support
- Be kind when using hooks!
 - Your hook runs on your consumer's machine!
 - Don't be evil!
 - `before_prepare` hooks may not always be run when you expect; run the `cordova` command again

Miscellany (2)

- `events.emit("verbose", ...)` and `--verbose` are your friends when troubleshooting hooks
- Likewise, return useful error messages to error callbacks

Homework

- Create a new plugin and publish it to the Cordova plugin repo
- Extend and/or improve a plugin
 - For example, the globalization plugin's API is asynchronous, which is really irritating.
 - All the formatting / globalization information could be determined up-front instead
 - Go for it: <https://github.com/apache/cordova-plugin-globalization>
- The sky's the limit!

Questions?

Thanks!

Jesse (@purplecabbage)

Kerri (@kerrishotts)

<https://github.com/kerrishotts/pgday/2017/fantastic-plugins-and-how-to-make-them>

Based in part on <http://purplecabbage.github.io/slides/pgd16Plugins/index.html>

This slide intentionally left blank