

# AI Overview

MGMT 675: AI-Assisted Financial Analysis



# API Calls

---

# Creating an App that Makes API Calls

- Get an API key from OpenAI or other LLM provider
- Generate code that sends a prompt to an AI and gets a response. API key should be included in code to authorize (for billing).
- Or create an interface that allows the user to formulate a prompt. Your code may expand the prompt to include whatever information you want to provide to the LLM.
- Or send your own prompt and allow users to send prompts.

# Examples

- Julius prompt: build a Streamlit app that scrapes the headlines from *The Guardian* website, sends them to ChatGPT 4o using my API key, and returns a summary of the headlines and an assessment of the sentiment of the headlines.
- After deployment: [Streamlit app with API call built by Julius](#)
- Replit prompt: same as Julius prompt + provide a chat interface that allows the user to ask further questions about the headlines.
- Deployed directly from Replit: [Replit app with API call](#)

# Python code for API call

```
import openai
# [input openai_api_key]
client = openai.OpenAI(api_key=openai_api_key)
prompt = "Here are today's headlines"
# [then include the scraped headlines]
prompt += "Based on these headlines, ..."
response = client.chat.completions.create(
    model="gpt-4o",
    messages=[
        {"role": "system", "content": "You are a
            helpful assistant that analyzes news
            headlines."},
        {"role": "user", "content": prompt}
    ]
)
```

# API-based Apps vs AI Agents

From ChatGPT:

Feature	API-based App	AI Agent
Autonomy	✗ Only reacts	✓ Acts independently
Goal-Oriented	✗ Task-based	✓ Goal-driven
Adaptability	✗ Predefined logic	✓ Can adapt behavior
Tool Use	✓ Manual calls	✓ Chooses tools as needed
Memory	✗ Usually none	✓ May have memory
Intelligence Level	✗ Fixed logic	✓ Planning & reasoning

## **Some Chatbots**

---

- ChatGPT, Gemini, Claude (try ChatGPT Deep Research)
- [Google NotebookLM](#)
  - Notebook = collection of sources (text, images, etc.)
  - Can ask questions about the sources
  - Can create audio ("podcast") from the sources
  - Example: [Stanford AI Report 2025](#)
  - [NotebookLM podcast version](#) also at [this link](#)
- [OpenRouter](#) provides access to many LLMs. Use your own API keys for paid LLMs or use free LLMs.



# Language Models

---

# Tokenization, Embedding, and Prediction

1. Tokenization: break text into tokens (words, characters, or subwords). Example: unhappiness  $\rightarrow$  [un, happy, ness]
2. Embedding: assign each token to a vector (list of numbers)

Tokenization + Embedding  $\rightarrow$  text translated into sequence of vectors


3. Prediction problem: given a sequence of vectors, predict the next vector

Embedding + Prediction optimized jointly by machine learning

## Example: GPT-3

- Tokenization: use 50,257 tokens
- Embedding: each token assigned to a vector of 12,288 numbers.
  - $50,257 \text{ tokens} \times 12,288 \text{ numbers per token} = 617 \text{ million numbers (parameters)}$
- Prediction: Use sequence of 2,048 prior tokens to predict next token.
  - 2,048 tokens is  $2,048 \times 12,288 = 25 \text{ million numbers}$
  - Used to predict next token, which is 12,288 numbers
  - So, predict  $y$  from  $x$  with 25 million  $x$  variables and 12,288  $y$  variables (per observation)

# Summary of GPT-3



# GPT-3.5 Turbo Embeddings

- Can get vector embeddings of tokens from Chat GPT 3.5 Turbo by API calls
- Vectors are 1,536 numbers long
- [Excel file](#) with vector embeddings of king, queen, woman, and man from ChatGPT 3.5 Turbo
- Famous example: can add and subtract vectors and  $\text{king} + \text{woman} - \text{man} \approx \text{queen}$

# Neural Networks (Prediction Model)

---

# History of Neural Networks

- 1943:** McCulloch & Pitts propose a binary threshold model of neurons.
- 1958:** Perceptron introduced by Frank Rosenblatt
- 1986:** Backpropagation popularized by Rumelhart, Hinton, & Williams enables training of multilayer networks.
- 1990s:** Recurrent Neural Networks (RNNs) and Convolutional Neural Networks (CNNs) gain traction.
- 1997:** Long Short-Term Memory (LSTM) addresses RNN vanishing gradient issues (Hochreiter & Schmidhuber).
- 2012:** AlexNet wins ImageNet, marking deep learning's breakthrough.
- 2017:** **Transformers introduced** — Vaswani et al. publish *Attention Is All You Need*, replacing recurrence with self-attention.
- 2020s:** Transformer variants dominate NLP and spread to vision and multi-modal models. GPT = Generative Pre-trained Transformer.

# Multi-Layer Perceptrons

- A multi-layer perceptron (MLP) consists of “neurons” arranged in layers.
- A neuron is a mathematical function. It takes inputs  $x_1, \dots, x_n$ , calculates a function  $y = f(x_1, \dots, x_n)$  and passes  $y$  to the neurons in the next level.
- Standard function (ReLU) for hidden layers is


$$y = \begin{cases} \alpha + \beta_1 x_1 + \dots + \beta_n x_n & \text{if positive} \\ 0 & \text{otherwise} \end{cases}$$

- First layer (input layer) = inputs (features).
- “Hidden layers” take inputs from previous layer and pass output to next layer.
- Last layer (output layer) has one neuron for each output.



# Illustration

Multi-Layer Perceptron with Computation Flow



# Hidden Layer Computations

Inputs  $x_1 = 2.0$ ,  $x_2 = -1.5$

**Neuron 1**  $\alpha = 0.5$ ,  $\beta_1 = 1.2$ ,  $\beta_2 = -2.1$

$$\begin{aligned}h_1 &= \text{ReLU}(0.5 + 1.2 \cdot 2.0 + (-2.1) \cdot (-1.5)) \\&= \text{ReLU}(6.05) = 6.05\end{aligned}$$

**Neuron 2**  $\alpha = -1.0$ ,  $\beta_1 = 0.5$ ,  $\beta_2 = 1.0$

$$\begin{aligned}h_2 &= \text{ReLU}(-1.0 + 0.5 \cdot 2.0 + 1.0 \cdot (-1.5)) \\&= \text{ReLU}(-1.5) = 0\end{aligned}$$

**Neuron 3**  $\alpha = 0.3$ ,  $\beta_1 = -1.5$ ,  $\beta_2 = 0.7$

$$\begin{aligned}h_3 &= \text{ReLU}(0.3 + (-1.5) \cdot 2.0 + 0.7 \cdot (-1.5)) \\&= \text{ReLU}(-3.75) = 0\end{aligned}$$

# Output Computation

$$\alpha = -0.5, \beta_1 = 1.0, \beta_2 = -1.2, \beta_3 = 0.8$$

$$\begin{aligned}\hat{y} &= -0.5 + 1.0 \cdot h_1 + (-1.2) \cdot h_2 + 0.8 \cdot h_3 \\ &= -0.5 + 6.05 + 0 + 0 = \boxed{5.55}\end{aligned}$$