Sleeping Machines — investor pitch

The next general-purpose substrate for machine intelligence.

Sleeping Machines aims to make intelligence composable within **one trainable computing substrate**. Language and reasoning, perception and world models, embodied action, typed tables and interleaved process streams become different forms of experience available to the same learner. The ambition extends through continual learning, communication and self-design to the hardware that executes them.

An observation enters through an interface that respects its meaning: a token, a sensory event, a typed comparison or an action. It becomes an addressed message interacting with persistent memory. Learned delays and temporal races decide which evidence meets and which computation happens. Small messages carry new evidence into deeper state; separate keys and values distinguish where evidence goes from what it says. Counterfactual credit teaches the routes and writes that could have happened.

The larger promise is that these are **reusable learned computations**. Comparison, binding, retention, prediction and planning learned from one form of experience can support another through shared representations and end-to-end credit. Perception can inform reasoning; reasoning can guide action; process traces and tables can contribute to the same world model. Joint training must measure that transfer and the retention of existing skills.

This also connects the learner to its execution. Time performs computation, including useful sleeps; local events can advance it without a mandatory global clock. Inference and learning are designed around the same temporal, addressed substrate. Available memory and skill can grow beyond the activity recruited for one observation, with work tuned from small data and constrained devices to large datasets and datacenters. Candidate discovery and alternative learning work count in that budget.

A revealing proof of the platform: mixed-type tables, token sequences and anonymous event streams learned through the same temporal core, followed by measured skill transfer. The program spans small-data usefulness and large-data scaling.

Progress toward deeper reusable representations. Keyed language development loss improves **5.9572→5.8987→5.8741nats/token** at2/4/8layers on the65528target slice and1.05M-token corpus,one seed and different total work. One pass over4M fresh tokens also favors eight over two layers: **5.8414 versus5.8648**,equal updates,different parameters/work. The earlier native FIT probe gives **1.9258NLL** after readout calibration on the same12FIT prefixes (learnability evidence). Native local grounding improves calibrated root geometry by **34.6%**,while whole-label transfer still selects the acquired actor. The new **8level/32stage** construction keeps exact role-bearing child-memory versions accessible as lower memories evolve;its acquired actor outputs,schedules and parameter gradients match bit-for-bit. A native race head pools the two actual root parts with live credit;**16numerical contracts** pass. These are demonstrated representation/access mechanisms;stable semantic identity and relation transfer are the next learning test. Bound evidence.

Composition scaling now tests data and optimization adequacy. At 128 and 512 additional updates, the native 8-level/32-stage actor reaches 512/512 correct part-identity views on 64 reused DEV scenes (eight known synthetic shapes, common race tape). Whole-object learning is separate:at512updates,legacy-readout DEV NLL0.803995 and broader-TRAIN-readout0.694517 versus saved acquired0.686609;the raw joint head is approximately chance on TRAIN and DEV. The unchanged2048update continuation uses2048unique TRAIN scenes/32geometry-time tapes over64TRAIN arrangements;TEST stays closed.
Source:`investment/composition_scale_milestone_evidence.json`.

Upper sensitivity is acquired;the required relation is not reliably aligned. A frozen audit of eight TRAIN pairs at checkpoints 128/512 finds 51.62× greater root-feature swap sensitivity and 27.73×

greater output contrast, with nonzero upper relation credit. Correct pair rankings are 5/8 then 4/8. This rules out complete upper insensitivity and wholly cancelled credit on these samples;it does not identify a unique cause. Formal analysis shows why separate readable child features can remain insufficient for this balanced whole-label task. Source:`investment/composition_credit_evidence.json`.

Native continuation. First beat the saved dense hybrid with a completely native deep member. An eight-layer, 4.19M-parameter prototype now uses native receiver races and normalized episodic/concept/background causes, with zero SSM, attention or MLP carrier layers. Receiver-local own-write eligibility replaces recurrent BPTT; its exactness is conditional on fixed input messages, routing, timestamps and parameters. Eleven contracts cover local credit, native event/gradient parity, causality and continuation. The real-token gate passes with finite credit at every depth. Packing the same native operations reduces the 32-target optimizer gate from 5.410s to 0.919s; this diagnoses execution, not hardware latency or predictive quality. Persistent indexed episodic history and cause messages into native memories are next, followed by competitive acquisition. Asynchronous optimizer/versioning and changing-parameter credit remain separate integrations. Source: `investment/local_native_language_evidence.json`.

Completed 16M hybrid diagnostic. The four-layer, 3.55M-parameter dense hybrid scores **5.2699 NLL** on 8,192 FineWeb GPT-2 development targets in 1,024-token windows, and **5.172638** on the separate 65,528-target slice. One pass over 16M tokens, one seed; 16-layer endpoint pending. This is the saved accuracy target for the fully native deep model at that data budget, not a native win or public leaderboard result. Source: `investment/depthdata_l4_evidence.json`.

Observed ownership repair,16October. A label-free spatial-support audit finds that **25%** of inferred groups never become pure complete memories under the old dyadic supports,on both128TRAIN and64DEV scenes. The new static observed-ownership candidate composes all pixels of a group in one native part memory before upper composition. Its full32event TRAIN gate produces **8complete parts×4pixels**,retains8levels/32native stages and255394actor parameters,and gives nonzero finite content gradients at every level. Training/evaluation forward equality passes;19combined contracts pass. No optimizer fit,DEV class improvement or TEST result is claimed. Grouping is an explicit TRAIN-fitted static spatial policy;streaming ownership revision and stable semantic identity remain distinct capabilities. Theory;evidence.

Composition engineering milestone. Persistent memories now integrate local evidence and emit composed views through native races. On one paired mechanism fixture with the same acquired parameters, coalescing reduces delivered messages **349→125** and native candidate scores **11,168→4,000**, while timer scores rise **2→188**. A separate repair keeps pixel memories world-indexed and composes upper state in an observed scene frame: pure translation gives exactly identical upper features, without new parameters or sensor replay. Combined translation/timing root-feature displacement falls **0.4162→0.00316** on the controlled fixture. These are mechanism and resource results; prediction quality differs between constructions and complete arithmetic/energy are unaudited. The first synthetic held-out composition fit scored **50% accuracy** and failed its transfer gate. The repaired 128-update model also scores 50% DEV accuracy after TRAIN-only calibration; the coordinate contract passes, but learned part-combination transfer still requires a representation/credit repair. TEST remains closed. Evidence.

Online market forecasting: confirmed on a new month

A preregistered out-of-sample win while every model keeps learning. On Binance BTCUSDT public trades, our native temporal learner, an online LSTM and two online Transformers each adapt their weights after every 32 revealed trades and are scored before any outcome can change them. All model choices were fixed from August evidence and committed before the 1 October data were downloaded; each learner carried its full August memory and optimizer state across the five-week gap.

Model (all learn online)	1 Oct loss, 65,536 trades	25 Aug loss, 65,536 trades	Online arithmetic
Sleeping Machines	**8.0785**	**5.1759**	**8.5 GFLOPs**
LSTM	8.1027	5.1967	9.5 GFLOPs
Transformer, cached history	8.1792	5.2804	124.7 GFLOPs (14.7×)
Transformer, re-encoded history	8.1764	5.2797	7,963 GFLOPs (936×)

Lower loss is better (nats per trade: next-trade timing, aggressor side and price direction). Our model leads in **all 16 of 16** consecutive 4,096-trade windows of the new month, with **14.7× less arithmetic** than the cached Transformer and **16× less retained state** (0.146 MB of weights plus prediction memory versus 2.334 MB). This is the capability a deployed forecaster needs: keep learning from a changing stream at low cost. Single seed; the sealed September test stays unopened until seed replication. Next: return-distribution forecasts of the price itself (10 s, 1 min, 5 min), now in development. No trading-profit or measured chip-energy claim. Source-bound evidence.

Trade-event acquisition now reproduces across three seeds. Native mean development loss is **6.8842**, versus LSTM **6.8996** and Transformer **6.9686**; native leads both references at every paired seed. All nine acquired fits are complete. These are fixed-weight August development results. The October online confirmation above remains single seed. Next: reuse these learners for online August/October replication with unchanged settings and causal updates; October is an already accessed day, so this is replication rather than a new prospective test. Source-bound three-seed evidence.

Industrial fault detection: sealed win on interleaved factory logs

Predictive maintenance on anonymous machine logs. In our FAS benchmark (assembly-line simulator, two interleaved lines of 30 items, no item labels), a failing machine shows only as production steps that slowly take longer. Our model learns each step's duration from normal logs, binds every event to the earlier event it most likely continues through a race of delayed clocks, and keeps a separate running anomaly score per step. The full plan was committed before the test data were generated; each model was scored once.

Detector (2,000 normal + 2,000 faulty runs)	Fault-detection AUROC
Sleeping Machines (three independent fits)	**0.801**
Time-encoded Transformer (three seeds)	0.704
Best of nine classical detectors	0.676
LSTM (three seeds)	0.667

Ahead by 0.097 AUROC (95% interval 0.088 to 0.121), every fit above every reference (wear faults 0.772 vs 0.650; retry faults 0.829 vs 0.758). No item identities are used and the model's knowledge is fixed during scoring. Source-bound evidence.

Language: addressed memory leads

Addressed memory is our strongest language lever. On the same 8,192 FineWeb development targets (GPT-2 tokens, 1,024-token history), our keyed temporal-memory model, whose events write keyed messages that later tokens read directly, scores **5.601 and 5.624 nats/token** (two seeds) against **5.978** for the earlier flagship; removing the keyed read costs 0.10 at 1M tokens. A 6,248-parameter addressed episodic memory with read-time credit lifts the flagship itself to **5.634 (+0.345)**, while an identical plain continuation does not improve (native readout alone: 5.973); the learner's use of history older than 64 tokens rises from 0.004–0.008 to **0.227 nats**, and it learns on its own to discount memories from earlier documents. The same principle, explicit addressed access to the right past events, produced the sealed fault-detection win above. Source-bound evidence.

Continuation uses the memory gains inside the native model. Finish existing hybrid diagnostic acquisitions and reuse their scores as targets. The native eight-layer construction restores sparse receiver writes,computational clocks,counterfactual route credit and local eligibility. Its next admission requires persistent indexed episodic history and complete work accounting. The previous serial native stack failed to compose depth usefully;the new composition gives each layer its own horizontal memory and direct predictive-cause credit.

Price forecasting is in development. Native leads the fixed-window development comparison (29.5089 summed loss versus LSTM 29.6516 and linear Student-t 29.6998). On the corrected full-day online stream it scores 30.6203 versus linear Student-t 30.5936: the classical reference leads overall, while native leads at 10 seconds. Next: causal streaming learning with non-overlapping delayed labels, followed by a preregistered fresh October price test. The confirmed trade-event result above has a different target and scoring protocol.

Learning more efficiently. Sparse counterfactual teaching improves development NLL from **6.62066 to 6.52787 nats/token** while cutting complete CPU training time from **9,129 to 7,734 seconds (15.3%)** at 8.39M GPT-2 FineWeb targets, all core, discovery, backward, replay and optimizer time included. Source-bound evidence.

Forward computation teaches credit — current status and potential

Prospective real-token calibration reduces credit error **98.4% versus static credit and 97.4% versus reference-only credit**, improving all eight fresh TRAIN-tail prefixes. Shared forward-derived geometry tracks alternative parameter and Adam-moment trajectories. A separate matched four-prefix, three-repeat acquisition pipeline is **2.09x faster** than exhaustive alternative learning, with **93.5% fewer supported arithmetic operations**, including context, route discovery and exact factual/reference losses. In a fixed connected 37,377-parameter controller, conditional action-gradient noise is **77.8% lower** than static credit, with exact mean-gradient parity.

Scope: component evidence on a fixed two-layer pretrained native model, 50,257 GPT-2 token classes,64-dimensional lexical learners and65 candidate routes. Accuracy uses eight new48-target prefixes; execution and controller noise use four earlier prefixes. Source pretraining, oracle acquisition and numerical gates are additional. Supported arithmetic omits unsupported work included in wall. Early small route-policy fits have no confirmed held-out prediction gain. Completed evidence and formulas.

The opportunity is to make continual adaptation economical: models that learn as data changes, capable local machines and industrial event systems, and reusable learned credit across the general-purpose substrate. The sparse asynchronous hardware path targets memory, communication and energy budgets. These are conditional platform implications, not measured customer demand or industry-wide savings. The next gate is **better held-out prediction per total learning cost**, followed by larger data/depth and online application confirmation.

Wins and advances at a glance

13 public benchmark wins against the best published single-model results on official dataset/protocol entries. Across these winning entries,53 of61 seed/split scores are ahead;wins compare dataset means,not every individual run. The four added Bosser–Ben Taieb wins are Wikipedia,Github,Stack Overflow and LastFM. Wikipedia/Github also beat stronger composite targets;Stack Overflow/LastFM beat the best single-model totals. B4 uses recorded-data density scoring;these are quality wins,with complete work unaudited. Source-bound headline ledger.

Benchmark	Ours	Best published	At what cost
EasyTPP Taxi (mobility events)	0.525 ± 0.001	0.522 (S2P2, NeurIPS 2025)	1/12 of the leader's parameters and compute; **reproduced independently on separate hardware**
EasyTPP Taobao (shopping)	1.399 ± 0.003	1.318 (IFTPP)	0.92× the leader's compute; largest margin (+0.081)
EasyTPP StackOverflow (Q&A activity)	−2.153 ± 0.005	−2.163 (S2P2)	**matched size and compute**; all 5 seeds ahead
EasyTPP Retweet (social cascades)	−6.326 ± 0.001	−6.348 (NHP)	**1/15** of S2P2's parameters and compute
EasyTPP Amazon (shopping reviews)	0.803 ± 0.001	0.781 (S2P2)	0.29× the leader's compute
P19 ICU sepsis prediction	AUPRC 0.639, AUROC 0.916	0.583 / 0.903 (MTM)	temporal memory adds +0.072 AUPRC on every split beyond summary statistics; reproduced
PAM wearable activity recognition	accuracy 0.978, F1 0.980	0.975 / 0.976 (MTM)	46K parameters vs MTM's 873K
TGB tgbn-trade (temporal graph: node affinity, world trade)	NDCG@10 0.868 ± 0.0005	0.863 (NAVIS, ICLR 2026)	2,107 parameters, 4 CPU-minutes; **a new domain**: interaction graphs, where heuristics beat every temporal GNN
TGB tgbl-wiki (temporal graph: link prediction, Wikipedia edits)	MRR 0.835 ± 0.0003	0.827 (TPNet)	7,995 parameters; exact per-event state; 4.5 ms per query on one CPU thread
B4 Wikipedia,developed	total NLL −258.76 ±37.73 SE	best single −2.67;composite −122.62	Five official splits;beats composite;full work unaudited
B4 Github,developed	total NLL −284.47 ±54.29 SE	best single −269.70;composite −272.90	Five official splits;beats composite;full work unaudited
B4 Stack Overflow,developed	total NLL 11.9956 ±0.6476 SE	best single 12.10;composite 11.90	Five official splits;single-model win,composite missed
B4 LastFM,frozen transfer	total NLL −774.64 ±48.38 SE	best single −697.50;composite −849.65	Five official splits;single-model win,composite missed

Rigor: official scorers,validation selection and once-only test scoring;the original nine-entry record has recording-grid audits. B4 results use recorded-density scoring,with composite and single-model targets distinguished. A one-command kit supports third-party reproduction. **One configuration wins all five:** a single configuration with no per-dataset tuning is ahead of the best published result on all five EasyTPP datasets under a pre-registered protocol (24 of 25 seeds ahead): Taobao 1.397, Taxi 0.526, StackOverflow −2.144, Retweet −6.324, Amazon 0.802.

Advances beyond the leaderboards:

- **Tokenized language:** 6.009 ± 0.010 nats per token vs a Kneser–Ney trigram's 6.537 on GPT-2-tokenized FineWeb (3 seeds); at 4× the data 5.510 vs 6.100, so the lead grows with data.

- **Binding and recall:** associative recall across irregular gaps 97.5% (3 seeds) vs a 14% baseline, 91.6% at twice the training length; **learning through the race alone** (no backpropagation into the network) reaches 77%.

- **Learning without a backward sweep or weight transport:** a race-of-clocks event model learns from each event as it arrives, with exact memory credit carried forward (no stored history). On Taxi development data at the same 20 data passes it scores 0.4805 nats/event vs 0.4557 for backpropagation through time (3 seeds). On Taxi it matches backpropagation run to convergence (0.4774 after 100 passes) with one fifth of the data passes. Across three datasets it leads at equal passes on Taxi (+0.025) and StackOverflow (+0.046) and is level on Amazon (+0.002), while backpropagation run to 100 passes ends ahead on StackOverflow and Amazon. Separate backward weights trained by the forward pass's own updates align to the exact dual (cosine 1.000) and learn as well as shared weights (0.4715 vs 0.4736); fixed random feedback fails (0.17). This is the learning half of clockless hardware.

- **Generative mode:** the same race-of-clocks model samples realistic event streams exactly (no rejection), for simulation, what-if analysis and synthetic data; taxi streams match real timing (gap KS 0.014 vs 0.063 naive) and event-to-event structure (0.024 vs 0.53).

- **Exact training signal and measured speed:** the closed-form likelihood removes the Monte Carlo gradient noise that sampled-intensity models carry (18% relative noise at the common 10-sample setting, measured); a streaming per-event update runs at about 1,500 events per second on one CPU core in plain PyTorch (Taxi; 20.7K multiply-adds per event vs the leader's 250K). A race of clocks provably approximates any continuous inter-event density, confirmed numerically; likelihood saturates once the number of clocks covers the data's gap modes (predicted, then confirmed), so model size follows from the data.

- **Reasoning from few examples:** temporal event chains 99.7% vs Transformers 33–41%; race retrieval 100% at 4× context.

- **Character language:** beats tuned Transformers at equal or lower compute (text8, 10M characters).

- **Learning signal and capacity:** credit to unchosen routes cuts error by 0.14 bits per character for 0.3% more work; doubling memory slots lowers error with the same eight writes per input.

- **Generality:** one shared temporal core serves four event domains; anonymous interleaved process logs (FAS v1) beat six generic detectors across three seeds.

- **Theory:** a race of clocks contains softmax attention and Mamba-style selective state spaces exactly.

New event domains:

- **Temporal Graph Benchmark, node affinity: won** (table). Pre-registered sealed test, 3 seeds: 0.8683 / 0.8674 / 0.8683, every seed above NAVIS's 0.863; persistent forecast 0.855. Validation 0.874 vs 0.860 had predicted it.

- **Temporal Graph Benchmark, link prediction: won** (table). Exact per-event state lifted our model from 0.776 to 0.852 validation MRR (theory note 159 predicted at least +0.03); three pre-registered

sealed seeds score 0.8353 / 0.8350 / 0.8356 on test, every one above TPNet's 0.827, with 7,995 parameters. On tgbl-review a training-free decayed event state already reaches 0.344 validation MRR, above TGN, TGAT and TNCN (0.313–0.325); GraphMixer leads at 0.428.

- **Second neural-TPP benchmark (Bosser & Ben Taieb): four public-reference wins.** Developed Wikipedia total NLL **−258.76 ±37.73 SE** beats composite **−122.62**;developed Github **−284.47 ±54.29 SE** beats composite **−272.90**. Developed Stack Overflow **11.9956 ±0.6476 SE** beats the best single **12.10**,while missing composite11.90. Frozen-transfer LastFM **−774.64 ±48.38 SE** beats best single **−697.50**,while missing composite−849.65. Five official splits,recorded-density scoring;developed variants selected by aggregate validation before once-only TEST. These add four dataset/protocol wins to the original nine. Frozen-configuration composite failures remain separately labelled in the full record. No B4 trainer remains active.

Why the developed models improve. Persistent addressed mark memory is combined with a causal episodic pointer race that can copy a recent event or its observed successor. Numerically stable clock-spread learning and bounded row microbatches preserve training on complete long histories. Earlier completed Github development evidence isolates13.822mark nats/sequence of direct memory-read benefit on28of34DEV sequences,with timing unchanged. Complete recorded-density wins and this mechanism evidence have different scopes. MOOC,MIMIC2 and Retweets remain development targets. Current B4 evidence.

Where we are not yet ahead: large-scale language (our best token model reaches 5.60 nats per token after 4M training tokens on single-thread CPUs; depth scaling is under test), P12 mortality (0.871 vs 0.880 AUROC) and real-world tables.

Evidence anchors for the platform

Token sequences, anonymous interleaved process logs and mixed-type comparisons now learn within the temporal/sparse family. They exercise different information structures through addressed messages, persistent memory, temporal computation and credit to unrealized alternatives. This is evidence for a common computing construction spanning small-data tables, asynchronous analytics and tokenized language.

Evidence front	Completed indication	What it establishes
Public benchmark: timed event data (EasyTPP, ICLR 2024)	**Taobao 1.399 ± 0.003 vs best published 1.318** nats/event (+0.081) at 0.92× the leader's compute; **Taxi**: a 5-seed mixture (0.536) beats every published model at 0.41× S2P2's compute (NeurIPS 2025), and a single model leads S2P2 on the mean (0.525 vs 0.522) at 1/12 of its parameters and compute. **StackOverflow** −2.144 ± 0.004 vs −2.163 (+0.019) at 1.26× S2P2's compute. **Retweet −6.326 ± 0.001 vs best published −6.348** (NHP; S2P2 −6.365) at **1/15 of S2P2's parameters and per-event compute**. Official splits, sealed test, 5 seeds.	**All five datasets won on a public leaderboard of the family's home field, and one model configuration wins all five without per-dataset tuning**, four of them at a fraction of the state of the art's compute; the Taxi win reproduced independently.
Public benchmark: ICU sepsis prediction (P19, PhysioNet 2019)	**AUROC 0.916 ± 0.022, AUPRC 0.639 ± 0.039** vs best published 0.903 / 0.583 (MTM, 2025) on the five official splits; 62,681 parameters. Without its temporal memory the same network scores 0.900 / 0.572 on every split; trees on the same statistics 0.914 / 0.618: the temporal memory carries signal the statistics lack (AUPRC ahead of the trees on every split). Reproduced on separate hardware.	**A second public win, in clinical early warning**, with AUPRC (the clinically relevant metric at 4% prevalence) ahead beyond split spread.
Public benchmark: wearable activity recognition (PAM)	**Accuracy 0.978 ± 0.007, F1 0.980 ± 0.008** vs best published 0.975 / 0.976 (MTM, 2025), five official splits, 46,316 parameters; four of five splits ahead.	**A third public domain won**: wearable sensor streams.
One family across data types	The P19 classifier reuses the event model's temporal memory layer (same code, same size).	Wins on generative event modelling and on sparse clinical classification; the EasyTPP leader S2P2 is shown on one task type. Transfer tests are next (generality plan).
Industrial fault detection (FAS, sealed fresh draw)	**AUROC 0.801 vs Transformer 0.704**, LSTM 0.667, best classical 0.676; every native fit above every reference.	Event binding through time turns better log modelling into earlier fault detection.
Mixed-type tables, small data	**100% accuracy on 256 synthetic DEV rows from 64 FIT rows**,6,370 learned parameters. Numeric, categorical, Boolean and missingness comparisons enter before neural message processing.	The integrated core learns the mixed-type interaction; relabeling, column-order, missing-value semantics and actual alternative-write credit checks pass. Fixed predicates, one seed; learned discovery and real tables versus trees are the next tests.
Online market forecasting (preregistered new-month confirmation)	**8.0785 vs LSTM 8.1027 and Transformers 8.1764–8.1792** nats/trade on 65,536 unseen 1 October trades, every model learning online; leads all 16 of 16 windows at 14.7× less arithmetic than the cached Transformer.	Continual learning from a changing stream, cheaper than attention; choices fixed before the data existed.
Properly tokenized language	The temporal-memory token model with the keyed predecessor read scores **6.009 ± 0.010** nats per token (3 seeds) at 1M GPT-2 tokens of FineWeb vs a Kneser–Ney trigram's 6.537; at 4M tokens **5.510** vs 6.100.	First tokenized-language evidence that persistent memory binds context; the lead grows with data. A published small Transformer under the same protocol is the next reference.

The unifying advantage is the reusable construction: type-respecting comparisons and tokens become events; events recruit meaningful state and teach hard routes through their consequences. Available capacity, selected activity, temporal learning and execution are separate design axes. The larger ambition connects language and reasoning, multimodal world models, embodiment, continual learning, communication, self-design and clockless hardware through this substrate. Joint training with shared parameters must next measure skill transfer and donor-skill retention. These completed instances were trained separately.

What is already shown (language rows single-seed; native compute traced, reference compute shape-estimated):

- **Wins a public leaderboard on its home field:** EasyTPP Taobao (+0.081 nats/event over the best published model at 0.92× the leader's compute), Taxi (beats every published model at 0.41× S2P2's compute) and StackOverflow (+0.019 at 1.26× compute); 5 seeds, sealed test.

- **Wins a public clinical benchmark with the same core:** P19 sepsis prediction, AUPRC 0.639 vs 0.583 for the best published model (MTM, 2025), five official splits. The classifier reuses the event model's temporal memory layer.

- **Beats Transformers at a fraction of their compute.** On 10M characters of text8 the native model reaches 1.888 bpc against the 4-pass Transformer-256×4's 1.908, at 0.40× its training and 0.18× its inference compute, and beats the validation-selected tuned Transformers at both budgets (1.888 vs 1.996; 1.955 vs 2.215). Tuned small LSTMs lead at these budgets by 0.04–0.06 bpc.

- **Counterfactual route credit works:** 2.507 → 2.371 bpc for 0.3% extra training work.

- **Capacity beyond activity:** doubling the receiver pool improves 2.371 → 2.345 bpc at the same selected work.

- **Learned temporal computation:** 99.7–99.9% event-order accuracy from 2,000 examples seen once (Transformers 33–41%); 95.3% on timing-only discrimination where any order-only model is capped at 50%; 100% on unseen modular rules; 100% retrieval at four times the training context.

- **Scales with data and adapts online:** at 90M characters the native model reaches 1.783 bpc and beats a tuned Transformer-256×4 (1.811) at 1.06× its compute, while a tuned Transformer-192×4 (1.704) still leads; online adaptation 3.191 → 3.096 bpc.

- **Hardware economics:** in the cost model, 5.8× fewer bytes moved per character than Transformer-256×4 at better quality (modelled; silicon measurement is a funded milestone).

Typed learning: preserve meaning, then compose evidence

A category label, a temperature, a duration and a missing observation support different operations. Our typed interface applies meaningful comparisons before their outcomes enter addressed messages and persistent neural state. Computational races select evidence; counterfactual consequences teach the routes. Neural sums remain useful once representations share a declared latent space.

The proposed advantage combines tree-compatible conditional decisions with deep temporal memory and a common interface across modalities. Valid changes of units or category labels should preserve the evidence and downstream computation; training requires compatible parameter and optimizer coordinates too. The new theory derives these conditions and retains credit through computational time. **39 mathematical/interface contracts pass.** The integrated synthetic mixed-type fit already reaches 100% on 256 DEV rows from 64 FIT rows with fixed predicates. Learned predicate discovery, real tables versus trees and shared-core skill transfer are the next proofs.

Modern tabular neural models already use typed feature maps; comparison layers and neural/tree hybrids have precedents. Our contribution is the complete temporal/sparse composition and its tested consequences. See typed semantics and race composition.

Paths to revenue. Two entry routes share the core: datacenter AI at lower total cost (models and runtime), and event-native vertical models on existing CPUs and GPUs for interleaved, timestamped logs in industry, IoT, IT operations, security and finance, priced on detection value, the shortest path to revenue. Licensed runtime and accelerator IP and learning-capable event processors for mobile and robotics follow. The largest outcome is ownership of a widely used AI infrastructure layer.

The raise. €3M at €50M priced pre-money, with €100M as a stretch scenario. The 18-month program buys the team, the decisive proofs (race attention against competent Transformers at scale on GPU, the pre-registered FAS v2 home-field benchmark and a real-data track, trained sparse serving), hardware

feasibility on FPGA and neuromorphic silicon, and company-owned IP through patent review and selective filings.

Read the valuation rationale, full investment case, opportunity register and research evidence.