Building initrds in a new way

Zbigniew Jędrzejewski-Szmek



zbyszek@in.waw.pl



FOSDEM 2023, 4,2,2023

(instead of) Intro

(instead of) Intro

see Lennart's

"IMAGE-BASED LINUX AND TPMS

Measured Boot, Protecting Secrets and you"

- SecureBoot signing used to protect code
- "PCR measurements", "boot phases"
- systemd's «credentials» are a mechanism to pass identity information, certificates, key material, passwords, and similar
- "credentials" locked to PCR state
- systemd's «system extensions» are a mechanism to dynamically extend the root fs

local builds pulling in files from host fs,
 ldd to resolve dependencies

- local builds pulling in files from host fs,
 ldd to resolve dependencies
- the packaging layer is duplicated

- local builds pulling in files from host fs,
 ldd to resolve dependencies
- the packaging layer is duplicated
- lots of CPU cycles burnt during each kernel update

- local builds pulling in files from host fs,
 ldd to resolve dependencies
- the packaging layer is duplicated
- lots of CPU cycles burnt during each kernel update
- at runtime: custom logic (e.g. dracut's initqueue)

- local builds pulling in files from host fs,
 ldd to resolve dependencies
- the packaging layer is duplicated
- lots of CPU cycles burnt during each kernel update
- at runtime: custom logic (e.g. dracut's initqueue)
- custom tools (e.g. scripts to bring up LVM, dracut modules)

- local builds pulling in files from host fs,ldd to resolve dependencies
- the packaging layer is duplicated
- lots of CPU cycles burnt during each kernel update
- at runtime: custom logic (e.g. dracut's initqueue)
- custom tools (e.g. scripts to bring up LVM, dracut modules)
- different execution environment

- local builds pulling in files from host fs,ldd to resolve dependencies
- the packaging layer is duplicated
- lots of CPU cycles burnt during each kernel update
- at runtime: custom logic (e.g. dracut's initqueue)
- custom tools (e.g. scripts to bring up LVM, dracut modules)
- different execution environment
- complexity (in particular when dracut is used with systemd)

- local builds pulling in files from host fs,ldd to resolve dependencies
- the packaging layer is duplicated
- lots of CPU cycles burnt during each kernel update
- at runtime: custom logic (e.g. dracut's initqueue)
- custom tools (e.g. scripts to bring up LVM, dracut modules)
- different execution environment
- complexity (in particular when dracut is used with systemd)
- very little sharing of initrd logic between distros

signing of the kernel but not the initrd is a waste of CPU cycles

- signing of the kernel but not the initrd is a waste of CPU cycles
- end-users want kernel+initrd signed by the distro

- signing of the kernel but not the initrd is a waste of CPU cycles
- end-users want kernel+initrd signed by the distro
- the initrd must be built by the distro

- signing of the kernel but not the initrd is a waste of CPU cycles
- end-users want kernel+initrd signed by the distro
- the initrd must be built by the distro
- flexibility & ability to inject local modifications not useful

- signing of the kernel but not the initrd is a waste of CPU cycles
- end-users want kernel+initrd signed by the distro
- the initrd must be built by the distro
- flexibility & ability to inject local modifications not useful
- if we are building in a package builder, let's build directly from distro packages (we could build from files in the fs, but why?)

If we use pre-built images, two ways to deliver differentiated code

If we use pre-built images, two ways to deliver differentiated code

1. initrd variants

If we use pre-built images, two ways to deliver differentiated code

- 1. initrd variants
- 2. systemd-sysexts

If we use UKIs, we need a mechanism to replace config in the initrd

If we use UKIs, we need a mechanism to replace config in the initrd

1. automatic discovery (Discoverable Partitions Spec)

If we use UKIs, we need a mechanism to replace config in the initrd

- 1. automatic discovery (Discoverable Partitions Spec)
- 2. credentials for configuration

If we use UKIs, we need a mechanism to replace config in the initrd

- 1. automatic discovery (Discoverable Partitions Spec)
- 2. credentials for configuration

Easy building of sysexts depends build reproducibility of the initrd

https://github.com/systemd/mkosi

A program that builds "images" from packages (and sources)

- A program that builds "images" from packages (and sources)
- Support for GPT, verity, and signatures → sysexts

- A program that builds "images" from packages (and sources)
- $lue{}$ Support for GPT, verity, and signatures ightarrow sysexts
- Also archives (cpio) → initrd/initramfs

https://github.com/systemd/mkosi-initrd

■ mostly a series of a config files for mkosi

- mostly a series of a config files for mkosi
- list of packages for the "basic" initrd

- mostly a series of a config files for mkosi
- list of packages for the "basic" initrd
- mkosi.finalize to set /etc/initrd-release

- mostly a series of a config files for mkosi
- list of packages for the "basic" initrd
- mkosi.finalize to set /etc/initrd-release
- set of configs for sysexts

- mostly a series of a config files for mkosi
- list of packages for the "basic" initrd
- mkosi.finalize to set /etc/initrd-release
- set of configs for sysexts
- also /usr/lib/kernel/install.d/50-mkosi-initrd.install

- mostly a series of a config files for mkosi
- list of packages for the "basic" initrd
- mkosi.finalize to set /etc/initrd-release
- set of configs for sysexts
- also
 /usr/lib/kernel/install.d/50-mkosi-initrd.install
- hopefully coming soon to a Fedora install near you https://fedoraproject.org/wiki/Changes/mkosi-initrd

■ We get fully functional initrds.

- We get fully functional initrds.
- The initrds are **bigger**.

- We get fully functional initrds.
- The initrds are bigger. Most of the difference is caused by kernel modules.

- We get fully functional initrds.
- The initrds are bigger.
 Most of the difference is caused by kernel modules.
- Only some subset of installations is supported.

■ less things

- less things
- we use package dependency resolution mechanism

- less things
- we use package dependency resolution mechanism
- we let rpm/deb/pacman handle 90% of the installation

- **less** things
- we use package dependency resolution mechanism
- we let rpm/deb/pacman handle 90% of the installation
- we don't pull files from the host

- less things
- we use package dependency resolution mechanism
- we let rpm/deb/pacman handle 90% of the installation
- we don't pull files from the host
- images can be reproducible

- less things
- we use package dependency resolution mechanism
- we let rpm/deb/pacman handle 90% of the installation
- we don't pull files from the host
- images can be reproducible
- images are the same for everyone

- less things
- we use package dependency resolution mechanism
- we let rpm/deb/pacman handle 90% of the installation
- we don't pull files from the host
- images can be reproducible
- images are the same for everyone
- images can be easily signed

- less things
- we use package dependency resolution mechanism
- we let rpm/deb/pacman handle 90% of the installation
- we don't pull files from the host
- images can be reproducible
- images are the same for everyone
- images can be easily signed
- systemd does the heavy lifting in the initrd

systemd was already used in the initrd

- systemd was already used in the initrd
- the first thing systemd does is to set up the environment

- systemd was already used in the initrd
- the first thing systemd does is to set up the environment
- having tools that support running in a custom environment is hence not useful

- systemd was already used in the initrd
- the first thing systemd does is to set up the environment
- having tools that support running in a custom environment is hence not useful
- after removing custom logic we don't need to add anything back

- systemd was already used in the initrd
- the first thing systemd does is to set up the environment
- having tools that support running in a custom environment is hence not useful
- after removing custom logic we don't need to add anything back
- the ecosystem is moving away from scripts towards compiled daemons

- systemd was already used in the initrd
- the first thing systemd does is to set up the environment
- having tools that support running in a custom environment is hence not useful
- after removing custom logic we don't need to add anything back
- the ecosystem is moving away from scripts towards compiled daemons
- most of the code is in shared libraries, which are installed in full because of link dependencies

- systemd was already used in the initrd
- the first thing systemd does is to set up the environment
- having tools that support running in a custom environment is hence not useful
- after removing custom logic we don't need to add anything back
- the ecosystem is moving away from scripts towards compiled daemons
- most of the code is in shared libraries, which are installed in full because of link dependencies
- error handling, timeouts, retries, localized messages, event-driven logic, netlink, D-bus, all are much easier with "real" code

Progress over the last few months

- mkosi-initrd has a growing test suite (booting different storage types)
- mkosi supports builds as an unprivileged user
- systemd is getting new credential features
- systemd has new ukify helper to builds UKIs
- Fedora 38 Change accepted for Unified Kernel Images for VMs
- New kernel package split in Fedora (kernel-modules-core finally)
- GRUB2 might get support for UKIs (https://github.com/osteffenrh/grub2)
- Fedora 39 Change proposal for mkosi-initrd

Links

```
https://github.com/systemd/mkosi
https://github.com/systemd/mkosi-initrd
https://www.freedesktop.org/software/systemd/man/
systemd-sysext.html
https://gitlab.com/cryptsetup/cryptsetup/-/wikis/DMVerity
https://www.kernel.org/doc/html/latest/admin-guide/
device-mapper/verity.html
https://www.kernel.org/doc/html/latest/filesystems/
overlayfs.html
These slides:
https://github.com/keszybz/mkosi-initrd-talk/raw/
main/fosdem2023-buildling-initrds-in-a-new-way.pdf
```

Links

```
https://github.com/systemd/mkosi
https://github.com/systemd/mkosi-initrd
https://www.freedesktop.org/software/systemd/man/
systemd-sysext.html
https://gitlab.com/cryptsetup/cryptsetup/-/wikis/DMVerity
https://www.kernel.org/doc/html/latest/admin-guide/
device-mapper/verity.html
https://www.kernel.org/doc/html/latest/filesystems/
overlayfs.html
These slides:
https://github.com/keszybz/mkosi-initrd-talk/raw/
main/fosdem2023-buildling-initrds-in-a-new-way.pdf
```

QUESTIONS? / EOF