

```
Reply from 10.2.0.101: bytes=32 time<1ms TTL=128
```

```
Ping statistics for 10.2.0.101:
```

```
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
```

```
Approximate round trip times in milli-seconds:
```

```
Minimum = 0ms, Maximum = 0ms, Average = 0ms
```

Un ping IPv6 effettuato da PC-Svi115 con target PC-Svi10 fornisce il seguente output che ne conferma la raggiungibilità:

```
Packet Tracer PC Command Line 1.0
```

```
C:\>ping FC00:1::A
```

```
Pinging FC00:1::A with 32 bytes of data:
```

```
Reply from FC00:1::A: bytes=32 time=1ms TTL=128
```

```
Reply from FC00:1::A: bytes=32 time<1ms TTL=128
```

```
Reply from FC00:1::A: bytes=32 time<1ms TTL=128
```

```
Reply from FC00:1::A: bytes=32 time<1ms TTL=128
```

```
Ping statistics for FC00:1::A:
```

```
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
```

```
Approximate round trip times in milli-seconds:
```

```
Minimum = 0ms, Maximum = 1ms, Average = 0ms
```

Fase 3: verificare la separazione della rete.

Nonostante siano connessi allo stesso switch, un ping effettuato da PC-Svi101 avente come target PC-Mar101 fallisce con il seguente output:

```
C:\>ping 10.2.0.101
```

```
Pinging 10.2.0.101 with 32 bytes of data:
```

```
Request timed out.
```

```
Request timed out.
```

```
Request timed out.
```

```
Request timed out.
```

```
Ping statistics for 10.2.0.101:
```

```
Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),
```

```
Approximate round trip times in milli-seconds:
```

```
Minimum = 0ms, Maximum = 1ms, Average = 0ms
```

Fase 4: configurare l'inter-VLAN routing.

Aggiungere un router Rtr-Corridoio e connetterlo alla porta G0/1 di Sw-Corridoio. Impostare gli indirizzi default gateway (sia IPv4 sia IPv6) su tutti i PC e modificare la configurazione di Sw-Corridoio, da Global Configuration mode:

```
!Impostare a trunk l'interfaccia verso il router
```

```
interface GigabitEthernet 0/1
```

```
switchport mode trunk
```

```
switchport trunk allowed vlan 101,102,103
```

```
exit
```

```
exit
```

```
!Salvare il file di configurazione
```

```
copy running-config startup-config
```