



CANDIDATE
NAME

--

CENTRE
NUMBER

--	--	--	--	--

CANDIDATE
NUMBER

--	--	--	--

0478/23

May/June 2023

1 hour 45 minutes

No additional materials are needed.

- Answer **all** questions.
- Use a black or dark blue pen. You may use an HB pencil for any diagrams or graphs.
- Write your name, centre number and candidate number in the boxes at the top of the page.
- Write your answer to each question in the space provided.
- Do **not** use an erasable pen or correction fluid.
- Do **not** write on any bar codes.
- Calculators must **not** be used in this paper.

- The total mark for this paper is 75.
- The number of marks for each question or part question is shown in brackets [].
- No marks will be awarded for using brand names of software packages or hardware.

This document has **16** pages. Any blank pages are indicated.

- 1 Tick (✓) **one** box to complete the sentence.

A constant

A stores a value that can change at any time during the execution of a program.

☐

B stores a value that cannot change during the execution of a program.

☐

C stores values of multiple data types.

☐

D stores values that must be of the same data type.

☐

[1]

- 2 Explain the purpose of the library routines MOD and RANDOM

MOD

.....

.....

.....

RANDOM

.....

.....

.....

[4]

- 3 Describe what happens when a function is called during the execution of a program.

.....

.....

.....

.....

.....

..... [3]

- 4 (a) Explain why verification checks are used when data is input.

.....

.....

.....

..... [2]

- (b) Give **two** types of verification check and state how each one can be used.

Verification check 1

Use

.....

Verification check 2

Use

..... [4]

5 (a) Four descriptions of validation checks are shown.

Draw **one** line to link each description to the most appropriate check.

Not all checks will be used.

Description	Check
to check that the data entered is an integer	check digit
to check that some data has been entered	format check
to check that the data entered has an appropriate number of characters	length check
to check that an identification number contains no errors	presence check
	type check

[4]

(b) Write an algorithm in pseudocode to make sure that an input for the variable `Length` is between 15 and 35 inclusive. The code must iterate until a valid input has been made and the code must include appropriate messages.

.....

.....

.....

.....

.....

.....

.....

..... [3]

6 An algorithm has been written in pseudocode to allow 100 positive numbers to be input. The total and the average of the numbers are output.

```

01 Counter ← 100
02 Total ← 0
03 WHILE Counter > 100 DO
04     INPUT Number
05     IF Number > 0
06         THEN
07             Total ← Total + Counter
08             Counter ← Counter + 1
09     ENDCASE
10 ENDWHILE
11 OUTPUT "The total value of your numbers is ", Total
12 OUTPUT "The average value of your numbers is ", Total / 100

```

- (a) Identify the **four** errors in the pseudocode and suggest corrections.

Error 1

Correction

.....

Error 2

Correction

.....

Error 3

Correction

.....

Error 4

Correction

.....

[4]

- (b) Describe the changes you should make to the corrected algorithm so that a count-controlled loop is used to allow 100 positive numbers to be input.

You do **not** need to rewrite the algorithm.

.....

.....

.....

.....

.....

.....


.....

.....

.....

..... [5]

- 7 The flowchart represents an algorithm.
An input of -1 will terminate the algorithm.



(a) Complete the trace table for the input data:

5, 50, 52, 555, 57, 500, -1, 5500, 55

[illegible]

[6]

(b) Describe the purpose of the algorithm.

..... [2]

8 Consider the logic expression:

Z is 1 if (**A** = 1 AND **C** = NOT 1) AND (**B** = 1 NOR **C** = 1)

(a) Draw a logic circuit for this logic expression.

Each logic gate must have a maximum of **two** inputs.

Do **not** simplify this logic expression.



[4]

(b) Complete the truth table from the given logic expression.

A	B	C	Working space	Z
0	0	0		
0	0	1		
0	1	0		
0	1	1		
1	0	0		
1	0	1		
1	1	0		
1	1	1		

[4]

9 The variable `Saying` is used to store string data in a program.

(a) Write the pseudocode statement to declare the variable `Saying`

.....
..... [1]

(b) Write the pseudocode statements to:

- allow a string to be input to the variable `Saying`
- store the content of the variable `Saying` in a text file named "`Quotations.txt`"
- make sure the text file is closed at the end of the algorithm.

.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
..... [5]

- 10 A database table called `Site1` stores details of some holiday homes at a holiday park. The database shows the type of home, number of guests, whether it is privately owned and the weekly rate to hire it.

Name	Type	Private	Rate\$	NumberGuest
Bay Lodge	Lodge	NO	1000	10
Bay View	Cabin	NO	400	4
Blue Skies	Cabin	NO	350	4
Cliff View	Cabin	NO	650	6
Coppice Lodge	Lodge	NO	1200	12
Green Lodge	Lodge	NO	1000	8
Henry	Cabin	YES	300	2
Hikers' Rest	Retreat	NO	750	6
Poppy	Cabin	NO	300	2
Summer Joy	Retreat	YES	750	6
Valley View	Cabin	NO	600	6
West Lodge	Lodge	YES	1200	12

- (a) State the number of fields and the number of records in this database table.

Fields

Records [2]

- (b) Describe the purpose of a primary key.

.....

..... [1]

(c) The database uses the data types:

- alphanumeric
- character
- Boolean
- integer
- real
- date/time.

Complete the table to show the most appropriate data type for each field.

Field	Data type
Type	
Private	
Rate\$	
NumberGuest	

[2]

(d) Give the output that would be produced by the structured query language (SQL) statement:

```
SELECT Name, NumberGuest, Rate$
FROM Site1
WHERE NumberGuest >= 10;
```

.....

.....

.....

.....

.....

..... [3]

- 11 A two-dimensional (2D) array `Contacts[]` is used to store names and telephone numbers. All the data is stored as strings. The array must have the capacity to store 100 contacts in the form of:
- column 1 – contact names as: last name, first name
for example: Smith, John
 - column 2 – telephone numbers.

The variable `CurrentSize` shows how many contacts are in the array.

Write a program that meets the following requirements:

- display a menu of choices:
 - enter new contact details
 - display all the contact details
 - delete all the contact details
- validate the menu input
- allow up to a maximum of five new contacts to be added to the array at any one time
- do **not** allow more than 100 contacts in total
- after new contacts have been added, sort the array by contact name, as long as there are at least two contacts in the array
- output the whole of the array
- delete the contents of the array.

You must use pseudocode or program code **and** add comments to explain how your code works.

You do **not** need to declare any arrays, variables or constants; you may assume that this has already been done.

All inputs and outputs must contain suitable messages.

You do **not** need to initialise the data in the array `Contacts[]` and the variable `CurrentSize`

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

BLANK PAGE

Permission to reproduce items where third-party owned material protected by copyright is included has been sought and cleared where possible. Every reasonable effort has been made by the publisher (UCLES) to trace copyright holders, but if any items requiring clearance have unwittingly been included, the publisher will be pleased to make amends at the earliest possible opportunity.

To avoid the issue of disclosure of answer-related information to candidates, all copyright acknowledgements are reproduced online in the Cambridge Assessment International Education Copyright Acknowledgements Booklet. This is produced for each series of examinations and is freely available to download at www.cambridgeinternational.org after the live examination series.

Cambridge Assessment International Education is part of Cambridge Assessment. Cambridge Assessment is the brand name of the University of Cambridge Local Examinations Syndicate (UCLES), which is a department of the University of Cambridge.



Cambridge IGCSE™

COMPUTER SCIENCE

0478/23

Paper 2 Algorithms, Programming and Logic

May/June 2023

MARK SCHEME

Maximum Mark: 50

Published

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge International will not enter into discussions about these mark schemes.

Cambridge International is publishing the mark schemes for the May/June 2023 series for most Cambridge IGCSE, Cambridge International A and AS Level and Cambridge Pre-U components, and some Cambridge O Level components.

PUBLISHED**Generic Marking Principles**

These general marking principles must be applied by all examiners when marking candidate answers. They should be applied alongside the specific content of the mark scheme or generic level descriptors for a question. Each question paper and mark scheme will also comply with these marking principles.

GENERIC MARKING PRINCIPLE 1:

Marks must be awarded in line with:

- the specific content of the mark scheme or the generic level descriptors for the question
- the specific skills defined in the mark scheme or in the generic level descriptors for the question
- the standard of response required by a candidate as exemplified by the standardisation scripts.

GENERIC MARKING PRINCIPLE 2:

Marks awarded are always **whole marks** (not half marks, or other fractions).

GENERIC MARKING PRINCIPLE 3:

Marks must be awarded **positively**:

- marks are awarded for correct/valid answers, as defined in the mark scheme. However, credit is given for valid answers which go beyond the scope of the syllabus and mark scheme, referring to your Team Leader as appropriate
- marks are awarded when candidates clearly demonstrate what they know and can do
- marks are not deducted for errors
- marks are not deducted for omissions
- answers should only be judged on the quality of spelling, punctuation and grammar when these features are specifically assessed by the question as indicated by the mark scheme. The meaning, however, should be unambiguous.

GENERIC MARKING PRINCIPLE 4:

Rules must be applied consistently, e.g. in situations where candidates have not followed instructions or in the application of generic level descriptors.

GENERIC MARKING PRINCIPLE 5:

Marks should be awarded using the full range of marks defined in the mark scheme for the question (however; the use of the full mark range may be limited according to the quality of the candidate responses seen).

GENERIC MARKING PRINCIPLE 6:

Marks awarded are based solely on the requirements as defined in the mark scheme. Marks should not be awarded with grade thresholds or grade descriptors in mind.

Please note the following further points:

The words in **bold** in the mark scheme are important text that needs to be present, or some notion of it needs to be present. It does not have to be the exact word, but something close to the meaning.

If a word is underlined, this **exact** word must be present.

A single forward slash means this is an alternative word. A double forward slash means that this is an alternative mark point.

Ellipsis (...) on the end of one-mark point and the start of the next means that the candidate **cannot** get the second mark point without being awarded the first one. If a mark point has an ellipsis at the beginning, but there is no ellipsis on the mark point before it, then this is just a follow-on sentence and **can** be awarded **without** the previous mark point.

Question	Answer	Marks
1	B	1

Question	Answer	Marks
2	<p>One mark per mark point, max four</p> <p>MOD, max two</p> <ul style="list-style-type: none"> To perform (integer) division when one number is divided by another ... and find the remainder Allow example e.g. $7 \text{ MOD } 2 = 1$ <p>RANDOM, max two</p> <ul style="list-style-type: none"> To generate (pseudo) random numbers ...(usually) within a specified range Allow example e.g. <code>RANDOM() * 10</code> returns a random number between 0 and 10 	4

Question	Answer	Marks
3	<p>One mark per mark point, max three</p> <p>MP1 A call statement is used in order to make use of a function // the function is called using its identifier</p> <p>MP2 Parameters are / may be passed (from the main program) to the function (to be used within the function)</p> <p>MP3 The function performs its task ...</p> <p>MP4 ... and returns a value / values to the main program</p>	3

Question	Answer	Marks
4(a)	<p>One mark per mark point, max two</p> <ul style="list-style-type: none"> To ensure that data has been accurately copied // to ensure that changes have not been made to the values originally intended when data is copied ... from one source to another 	2

Question	Answer	Marks
4(b)	<p>One mark for each appropriate verification check, max two One mark for each correct accompanying use, max two</p> <p>For example:</p> <p>Verification check 1 – Visual check Use – the user looks through the data that has been entered and confirms that no changes have been made.</p> <p>Verification check 2 – Double data entry Use – data is entered twice, the two entries are compared and if they do not match, a re-entry is requested.</p>	4


Question	Answer	Marks												
5(a)	<p>One mark for each correct line.</p> <table><thead><tr><th>Description</th><th>Check</th></tr></thead><tbody><tr><td>to check that the data entered is an integer</td><td>check digit</td></tr><tr><td>to check that some data has been entered</td><td>format check</td></tr><tr><td>to check that the data entered has an appropriate number of characters</td><td>length check</td></tr><tr><td>to check that an identification number contains no errors</td><td>presence check</td></tr><tr><td></td><td>type check</td></tr></tbody></table>	Description	Check	to check that the data entered is an integer	check digit	to check that some data has been entered	format check	to check that the data entered has an appropriate number of characters	length check	to check that an identification number contains no errors	presence check		type check	4
Description	Check													
to check that the data entered is an integer	check digit													
to check that some data has been entered	format check													
to check that the data entered has an appropriate number of characters	length check													
to check that an identification number contains no errors	presence check													
	type check													

Question	Answer	Marks
5(b)	<p>One mark per mark point, max three</p> <ul style="list-style-type: none"> • appropriate REPEAT / WHILE loop begin and end • input of Length • appropriate input prompt / error message • correct loop exit/entry condition / selection <p>Example answers:</p> <p>WHILE Loop</p> <pre> OUTPUT "Enter a number between 15 and 35 inclusive" INPUT Length WHILE Length <15 OR Length > 35 (DO) OUTPUT "Your number must be between 15 and 35 inclusive" INPUT Length ENDWHILE </pre> <p>REPEAT Loop</p> <pre> REPEAT OUTPUT "Enter a number between 15 and 35 inclusive" INPUT Length UNTIL Length >= 15 AND LENGTH <= 35 </pre>	3

Question	Answer	Marks
6(a)	<p>One mark per mark point, max four</p> <ul style="list-style-type: none"> Line 01 / Counter \leftarrow 100 should be Counter \leftarrow 0 Line 03 / While Counter > 100 DO should be While Counter < 100 DO Line 07 / Total \leftarrow Total + Counter should be Total \leftarrow Total + Number Line 09 / ENDCASE should be ENDIF <p>Correct algorithm</p> <pre> 01 Counter \leftarrow 0 02 Total \leftarrow 0 03 WHILE Counter < 100 DO 04 INPUT Number 05 IF Number > 0 06 THEN 07 Total \leftarrow Total + Number 08 Counter \leftarrow Counter + 1 09 ENDIF 10 ENDWHILE 11 OUTPUT "The total value of your numbers is ", Total 12 OUTPUT "The average value of your numbers is ", Total / 100 </pre>	4

Question	Answer	Marks
6(b)	One mark per mark point, max five MP1 replace line 03 MP2 with <code>FOR</code> MP3 ... with limits 0 to 99 / 1 to 100 MP4 replace line 05 to check if <code>Number</code> is not positive MP5 ... (if <code>Number</code> is not positive) insert a validation and re-input routine between lines 06 and 07 ... MP6 ... that will repeat until a positive value is entered MP7 remove the counter update / line 08 MP8 replace line 10 / <code>ENDWHILE</code> with <code>NEXT</code>	5

Question	Answer	Marks																																																																													
7(a)	<p>One mark per mark point, max six</p> <ul style="list-style-type: none">• correct Total column• correct Value column• correct Five1 column• correct Five2 column• correct Ten1 and Ten2 columns• correct OUTPUT column <table><tr><th>Total</th><th>Value</th><th>Five1</th><th>Five2</th><th>Ten1</th><th>Ten2</th><th>OUTPUT</th></tr><tr><td>0</td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td>5</td><td>1</td><td>1</td><td>0</td><td>0.5</td><td>Rejected</td></tr><tr><td></td><td>50</td><td>10</td><td>10</td><td>5</td><td>5</td><td></td></tr><tr><td>50</td><td>52</td><td>10</td><td>10.4</td><td></td><td></td><td>Rejected</td></tr><tr><td></td><td>555</td><td>111</td><td>111</td><td>55</td><td>55.5</td><td>Rejected</td></tr><tr><td></td><td>57</td><td>11</td><td>11.4</td><td></td><td></td><td>Rejected</td></tr><tr><td></td><td>500</td><td>100</td><td>100</td><td>50</td><td>50</td><td></td></tr><tr><td>550</td><td>−1</td><td></td><td></td><td></td><td></td><td>550</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	Total	Value	Five1	Five2	Ten1	Ten2	OUTPUT	0								5	1	1	0	0.5	Rejected		50	10	10	5	5		50	52	10	10.4			Rejected		555	111	111	55	55.5	Rejected		57	11	11.4			Rejected		500	100	100	50	50		550	−1					550															6
Total	Value	Five1	Five2	Ten1	Ten2	OUTPUT																																																																									
0																																																																															
	5	1	1	0	0.5	Rejected																																																																									
	50	10	10	5	5																																																																										
50	52	10	10.4			Rejected																																																																									
	555	111	111	55	55.5	Rejected																																																																									
	57	11	11.4			Rejected																																																																									
	500	100	100	50	50																																																																										
550	−1					550																																																																									
7(b)	<p>One mark per mark point, max two</p> <ul style="list-style-type: none">• to find if an input is divisible by (both 5 and) 10• ... add them together and output the total	2																																																																													

Question	Answer	Marks
8(a)	<p data-bbox="338 215 1205 247">One mark for each correct gate, with the correct input(s) as shown.</p> 	4

Question	Answer	Marks																																				
8(b)	<p>Four marks for eight correct outputs. Three marks for six or seven correct outputs. Two marks for four or five correct outputs. One mark for two or three correct outputs</p> <table><tr><th>A</th><th>B</th><th>C</th><th>Z</th></tr><tr><td>0</td><td>0</td><td>0</td><td>0</td></tr><tr><td>0</td><td>0</td><td>1</td><td>0</td></tr><tr><td>0</td><td>1</td><td>0</td><td>0</td></tr><tr><td>0</td><td>1</td><td>1</td><td>0</td></tr><tr><td>1</td><td>0</td><td>0</td><td>1</td></tr><tr><td>1</td><td>0</td><td>1</td><td>0</td></tr><tr><td>1</td><td>1</td><td>0</td><td>0</td></tr><tr><td>1</td><td>1</td><td>1</td><td>0</td></tr></table>	A	B	C	Z	0	0	0	0	0	0	1	0	0	1	0	0	0	1	1	0	1	0	0	1	1	0	1	0	1	1	0	0	1	1	1	0	4
A	B	C	Z																																			
0	0	0	0																																			
0	0	1	0																																			
0	1	0	0																																			
0	1	1	0																																			
1	0	0	1																																			
1	0	1	0																																			
1	1	0	0																																			
1	1	1	0																																			

Question	Answer	Marks
9(a)	DECLARE Saying : STRING	1

Question	Answer	Marks
9(b)	<p>One mark per mark point, max five</p> <p>MP1 input a string into <code>Saying</code></p> <p>MP2 correct use of <code>OPENFILE</code> to write data</p> <p>MP3 correct use of <code>WRITEFILE</code> to write <code>Saying</code></p> <p>MP4 correct use of <code>CLOSEFILE</code></p> <p>MP5 correct use of filename <code>Quotations.txt</code> throughout</p> <p>For example:</p> <pre>INPUT Saying OPENFILE "Quotations.txt" FOR WRITE WRITEFILE "Quotations.txt", Saying CLOSEFILE "Quotations.txt"</pre>	5

Question	Answer	Marks
10(a)	<p>One mark for each correct answer</p> <p>Fields 5</p> <p>Records 12</p>	2
10(b)	to uniquely identify a record	1

Question	Answer	Marks										
10(c)	<p>Two marks for four correct answers. One mark for two or three correct answers.</p> <table><tr><th>Field</th><th>Data type</th></tr><tr><td>Type</td><td>Alphanumeric</td></tr><tr><td>Private</td><td>Boolean</td></tr><tr><td>Rate\$</td><td>Integer</td></tr><tr><td>NumberGuest</td><td>Integer</td></tr></table>	Field	Data type	Type	Alphanumeric	Private	Boolean	Rate\$	Integer	NumberGuest	Integer	2
Field	Data type											
Type	Alphanumeric											
Private	Boolean											
Rate\$	Integer											
NumberGuest	Integer											
10(d)	<p>One mark per mark point, max three</p> <ul style="list-style-type: none">• data correctly extracted in any two rows• data correctly extracted in third row• data in correct order horizontally and vertically <p>Example answer:</p> <pre>Bay Lodge 10 1000 Coppice Lodge 12 1200 West Lodge 12 1200</pre>	3										

Question	Answer	Marks
11	<p>Read the whole answer:</p> <p>Check if each requirement listed below has been met. Requirements may be met using a suitable built-in function from the programming language used (Python, VB.NET or Java).</p> <p>Mark SEEN on script if requirement met, cross if no attempt seen, NE if partially met (see marked scripts).</p> <p>Use the tables for A02 and A03 below to award a mark in a suitable band using a best fit approach.</p> <p>Then add up the total.</p> <p>Marks are available for:</p> <ul style="list-style-type: none"> • AO2 (maximum 9 marks) • AO3 (maximum 6 marks) <p>Data structures required:</p> <p>The names underlined must match those given in the scenario:</p> <p>Arrays or lists <u>Contacts[]</u></p> <p>Variables <u>CurrentSize</u>, Cont, Choice, NewContacts, Count, Count2, Flag</p> <p>Requirements (techniques):</p> <p>R1 Output menu and input choice, with validation (range check, output with messages, input with prompts).</p> <p>R2 Input number of new entries, within limits, update current size of contacts, input new data and sort the array (range check, totalling, iteration and bubble sort).</p> <p>R3 Output array whole contents and delete contents of array (iteration, output with labelling/messages, array initialisation).</p>	15

Question	Answer	Marks
11	<p>Example 15 mark answer in pseudocode</p> <pre> // meaningful identifiers and appropriate data structures for // all data required DECLARE Contacts : ARRAY[1:100, 1:2] OF STRING DECLARE CurrentSize : INTEGER DECLARE Cont : BOOLEAN DECLARE Choice : INTEGER DECLARE NewContacts : INTEGER DECLARE Count : INTEGER DECLARE Count2 : INTEGER DECLARE Flag : BOOLEAN DECLARE Temp1 : STRING DECLARE Temp2 : STRING // the number of contacts in the array CurrentSize ← 0 // to allow program to continue indefinitely Cont ← TRUE WHILE Cont DO // display menu OUTPUT "Please choose one of the following: " OUTPUT "Press 1 to enter new contacts " OUTPUT "Press 2 to display your contacts " OUTPUT "Press 3 to delete all contacts " INPUT Choice // validate choice as 1, 2 or 3 WHILE Choice = 1 AND CurrentSize = 100 DO OUTPUT "Your contacts are full, please enter 2 or 3" INPUT Choice ENDWHILE WHILE Choice < 1 OR Choice > 3 DO OUTPUT "Incorrect entry - please enter 1, 2, or 3" INPUT Choice ENDWHILE </pre>	

Question	Answer	Marks
11	<pre> // enter new contacts IF Choice = 1 THEN OUTPUT "How many contacts (1 to 5 only)?" INPUT NewContacts // validates new contacts input WHILE NewContacts < 1 OR NewContacts > 5 DO OUTPUT "You may only enter between 1 and 5 contacts. Please try again" INPUT NewContacts ENDWHILE // checks the maximum size is not exceeded WHILE CurrentSize + NewContacts > 100 OUTPUT "Not enough space in your contacts" OUTPUT "The maximum number you may input is ", 100 - CurrentSize INPUT NewContacts ENDWHILE FOR Count ← CurrentSize + 1 TO CurrentSize + NewContacts OUTPUT "Enter the contact name as last name, first name" INPUT Contacts[Count, 1] OUTPUT "Enter the telephone number" INPUT Contacts[Count, 2] NEXT Count CurrentSize ← CurrentSize + NewContacts // bubble sort to sort array if it contains 2 or more contacts IF CurrentSize >= 2 THEN REPEAT Flag ← FALSE FOR Count ← 1 TO CurrentSize-1 IF Contacts[Count + 1, 1] < Contacts[Count, 1] THEN Flag ← TRUE Temp1 ← Contacts[Count, 1] Temp2 ← Contacts[Count, 2] </pre>	

Question	Answer	Marks
11	<pre> Contacts[Count, 1] ← Contacts[Count + 1, 1] Contacts[Count, 2] ← Contacts[Count + 1, 2] Contacts[Count + 1, 1] ← Temp1 Contacts[Count + 1, 2] ← Temp2 ENDIF NEXT Count UNTIL NOT Flag ENDIF ENDIF // display all contacts IF Choice = 2 THEN IF CurrentSize > 0 THEN OUTPUT "Name and Telephone Number" FOR Count ← 1 TO CurrentSize OUTPUT Contacts[Count, 1], " ", Contacts[Count, 2] NEXT Count ENDIF ENDIF // delete all contacts IF Choice = 3 THEN FOR Count ← 1 TO 100 FOR Count2 ← 1 TO 2 Contacts[Count, Count2] ← "" NEXT Count2 NEXT Count ENDIF ENDWHILE </pre>	

Marking Instructions in italics			
AO2: Apply knowledge and understanding of the principles and concepts of computer science to a given context, including the analysis and design of computational or programming problems			
0	1–3	4–6	7–9
No creditable response.	At least one programming technique has been used. <i>Any use of selection, iteration, counting, totalling, input and output.</i>	Some programming techniques used are appropriate to the problem. <i>More than one technique seen applied to the scenario, check the list of techniques needed.</i>	The range of programming techniques used is appropriate to the problem. <i>All criteria stated for the scenario have been covered by the use of appropriate programming techniques, check the list of techniques needed.</i>
	Some data has been stored but not appropriately. <i>Any use of variables or arrays or other language dependent data structures e.g. Python lists.</i>	Some of the data structures chosen are appropriate and store some of the data required. <i>More than one data structure used to store data required by the scenario.</i>	The data structures chosen are appropriate and store all the data required. <i>The data structures used store all the data required by the scenario.</i>

Marking Instructions in <i>italics</i>			
AO3: Provide solutions to problems by: <ul style="list-style-type: none"> • evaluating computer systems • making reasoned judgements • presenting conclusions 			
0	1–2	3–4	5–6
No creditable response.	Program seen without relevant comments.	Program seen with some relevant comment(s).	The program has been fully commented.
	Some identifier names used are appropriate. <i>Some of the data structures used have meaningful names.</i>	The majority of identifiers used are appropriately named. <i>Most of the data structures used have meaningful names.</i>	Suitable identifiers with names meaningful to their purpose have been used throughout. <i>All of the data structures used have meaningful names.</i>
	The solution is illogical.	The solution contains parts that may be illogical.	The program is in a logical order.
	The solution is inaccurate in many places. <i>Solution contains few lines of code with errors that attempt to perform a task given in the scenario.</i>	The solution contains parts that are inaccurate. <i>Solution contains lines of code with some errors that logically perform tasks given in the scenario. Ignore minor syntax errors.</i>	The solution is accurate. <i>Solution logically performs all the tasks given in the scenario. Ignore minor syntax errors.</i>
	The solution attempts at least one of the requirements. <i>Solution contains lines of code that attempt at least one task given in the scenario.</i>	The solution meets most of the requirements. <i>Solution contains lines of code that perform most tasks given in the scenario.</i>	The solution meets all the requirements given in the question. <i>Solution performs all the tasks given in the scenario.</i>