

Lecture 8: Feature Selection and Analysis

COMP90049

Introduction to Machine Learning

Semester 2, 2022

Lida Rashidi, CIS

Copyright @ University of Melbourne 2022. All rights reserved. No part of the publication may be reproduced in any form by print, photoprint, microfilm or any other means without written permission from the author.

Acknowledgement: Jeremy Nicholson, Tim Baldwin & Karin Verspoor



Features in Machine Learning

Where we're at so far

We want to get knowledge out of a data set:

Outlook	Temperature	Humidity	Windy	Play
sunny	hot	high	FALSE	no
sunny	hot	high	TRUE	no
overcast	hot	high	FALSE	yes
rainy	mild	high	FALSE	yes
rainy	cool	normal	FALSE	yes
rainy	cool	normal	TRUE	no
⋮	⋮	⋮	⋮	⋮

We want to get knowledge out of a data set:

- Machine learning
 - supervised machine learning \leftarrow today (mostly)
 - Unsupervised machine learning

How to do (supervised) Machine Learning:

0. Get hired!
1. Pick a feature representation
2. Compile data
3. Pick a (suitable) model
4. Train the model
5. Classify development data, evaluate results
6. Probably: *go to 1.*

Our job as Machine Learning experts:

- Choose a model suitable for classifying the data according to the attributes
- Choose attributes suitable for classifying the data according to the model
 - Inspection
 - Intuition

Our job as Machine Learning experts:

- Choose a model suitable for classifying the data according to the attributes
- Choose attributes suitable for classifying the data according to the model
 - Inspection
 - Intuition
 - Neither possible in practice

Feature Selection

What makes features good?

Lead to better models

- Better performance according to some evaluation metric

Side-goal 1

- Seeing important features can suggest other important features
- Tell us interesting things about the problem

Side-goal 2

- Fewer features \rightarrow smaller models \rightarrow faster answer
 - More accurate answer \gg faster answer



“Wrapper” methods

- Choose subset of attributes that give best performance on the development data
- For example: for the Weather data set:
 - Train model on {Outlook}
 - Train model on {Temperature}
 - ...
 - Train model on {Outlook, Temperature}
 - ...
 - Train model on {Outlook, Temperature, Humidity}
 - ...
 - Train model on {Outlook, Temperature, Humidity, Windy}

“Wrapper” methods

- Choose subset of attributes that give best performance on the development data
- For example: for the Weather data set:
 - Evaluate model on {Outlook}
 - Evaluate model on {Temperature}
 - ...
 - Evaluate model on {Outlook, Temperature}
 - ...
 - Evaluate model on {Outlook, Temperature, Humidity}
 - ...
 - Evaluate model on {Outlook, Temperature, Humidity, Windy}
- Best performance on data set → best feature set



“Wrapper” methods

- Choose subset of attributes that give best performance on the development data
- Advantages:
 - Feature set with optimal performance on development data
- Disadvantages:
 - Takes a **long** time

Aside: how long does the full wrapper method take?

Assume we have a fast method (e.g. Naive Bayes) over a data set of non-trivial size ($\sim 10\text{K}$ instances):

- Assume: train–evaluate cycle takes 10 sec to complete

How many cycles? For m features:

- 2^m subsets = $\frac{2^m}{6}$ minutes
- $m = 10 \rightarrow 3$ hours
- $m = 60 \rightarrow$ heat death of universe

Only practical for very small data sets.



Greedy approach

- Train and evaluate model on each single attribute
- Choose best attribute
- Until convergence:
 - Train and evaluate model on best attribute(s), plus each remaining single attribute
 - Choose best attribute out of the remaining set
- Iterate until performance (e.g. accuracy) stops increasing

Greedy approach

- Bad news:
 - Takes $\frac{1}{2}m^2$ cycles, for m attributes
 - In theory, 386 attributes \rightarrow days
- Good news:
 - In practice, converges much more quickly than this
- Bad news again:
 - Converges to a sub-optimal (and often very bad) solution

“Ablation” approach

- Start with all attributes
- Remove one attribute, train and evaluate model
- Until divergence:
 - From remaining attributes, remove each attribute, train and evaluate model
 - Remove attribute that causes least performance degradation
- Termination condition usually: performance (e.g. accuracy) starts to degrade by more than ϵ

“Ablation” approach

for example:

- Start with all features
 - Train, evaluate model on {Outlook, Temperature, Humidity, Windy}
- Consider feature subsets of size 3:
 - Train, evaluate model on {Outlook, Temperature, Humidity}
 - Train, evaluate model on {Outlook, Temperature, Windy}
 - Train, evaluate model on {Outlook, Humidity, Windy}
 - Train, evaluate model on {Temperature, Humidity, Windy}
- Choose best of previous five (let's say THW):
- Consider feature subsets of size 2:
 - Train, evaluate model on {Temperature, Humidity}
 - Train, evaluate model on {Temperature, Windy}
 - Train, evaluate model on {Humidity, Windy}
- etc...

“Ablation” approach

- Good news:
 - Mostly removes irrelevant attributes (at the start)
- Bad news:
 - Assumes independence of attributes
(Actually, both approaches do this)
 - Takes $O(m^2)$ time; cycles are slower with more attributes
 - Not feasible on non-trivial data sets.

Filtering methods

Intuition: Evaluate the “goodness” of each feature, separate from other features

- Consider each feature separately: linear time in number of attributes
- Possible (but difficult) to control for inter-dependence of features
- Typically most popular strategy

What makes a ~~feature set~~ single feature good?

- Better models!
- Well correlated with class

Toy example

a_1	a_2	c
Y	Y	Y
Y	N	Y
N	Y	N
N	N	N

Which of a_1 , a_2 is good?

Toy example

a_1	a_2	c
Y	Y	Y
Y	N	Y
N	Y	N
N	N	N

a_1 is probably good.

Toy example

a_1	a_2	c
Y	Y	Y
Y	N	Y
N	Y	N
N	N	N

a_2 is probably not good.

Pointwise Mutual Information

Discrepancy between the **observed joint distribution** of two random variables A and C and the expected joint distribution **if A and C were independent**.

Recall independence: $P(C|A) = P(C)$

Pointwise Mutual Information

Discrepancy between the **observed joint distribution** of two random variables A and C and the expected joint distribution **if A and C were independent**.

Recall independence: $P(C|A) = P(C)$

PMI is defined as

$$PMI(A, C) = \log_2 \frac{P(A, C)}{P(A)P(C)}$$

We want to find attributes that are **not** independent of the class.

- If $PMI \gg 0$, attribute and class occur together much more often than randomly.
- If $LHS \sim 0$, attribute and class occur together as often as we would expect from random chance
- If $LHS \ll 0$, attribute and class are negatively correlated. (More on that later!)

Attributes with greatest PMI: best attributes



Toy example, revisited

a_1	a_2	c
Y	Y	Y
Y	N	Y
N	Y	N
N	N	N

Calculate PMI of a_1 , a_2 with respect to c

Toy example, revisited

a_1	a_2	c
Y	Y	Y
Y	N	Y
N	Y	N
N	N	N

$$P(a_1) = \frac{2}{4}$$

$$P(c) = \frac{2}{4}$$

$$P(a_1, c) = \frac{2}{4}$$

Toy example, revisited

a_1	a_2	c
Y	Y	Y
Y	N	Y
N	Y	N
N	N	N

$$P(a_1) = \frac{2}{4}$$

$$P(c) = \frac{2}{4}$$

$$P(a_1, c) = \frac{2}{4}$$

$$\begin{aligned} PMI(a_1, c) &= \log_2 \frac{\frac{1}{2}}{\frac{1}{2} \cdot \frac{1}{2}} \\ &= \log_2(2) = 1 \end{aligned}$$



Toy example, revisited

a_1	a_2	c
Y	Y	Y
Y	N	Y
N	Y	N
N	N	N

$$P(a_2) = \frac{2}{4}$$

$$P(c) = \frac{2}{4}$$

$$P(a_2, c) = \frac{1}{4}$$

Toy example, revisited

a_1	a_2	c
Y	Y	Y
Y	N	Y
N	Y	N
N	N	N

$$P(a_2) = \frac{2}{4}$$

$$P(c) = \frac{2}{4}$$

$$P(a_2, c) = \frac{1}{4}$$

$$\begin{aligned} PMI(a_2, c) &= \log_2 \frac{\frac{1}{4}}{\frac{1}{2} \cdot \frac{1}{2}} \\ &= \log_2(1) = 0 \end{aligned}$$



What makes a single feature good?

- Well correlated with class
 - Knowing a lets us predict c with more confidence
- Reverse correlated with class
 - Knowing \bar{a} lets us predict c with more confidence
- Well correlated (or reverse correlated) with not class
 - Knowing a lets us predict \bar{c} with more confidence
 - Usually not quite as good, but still useful

- Expected value of PMI over all possible events
- For our example: Combine PMI of all possible combinations: a, \bar{a}, c, \bar{c}

Contingency tables: compact representation of these frequency counts

	a	\bar{a}	Total
c	$\sigma(a, c)$	$\sigma(\bar{a}, c)$	$\sigma(c)$
\bar{c}	$\sigma(a, \bar{c})$	$\sigma(\bar{a}, \bar{c})$	$\sigma(\bar{c})$
Total	$\sigma(a)$	$\sigma(\bar{a})$	N

$$P(a, c) = \frac{\sigma(a, c)}{N}, \text{ etc.}$$

Aside: Contingency tables

Contingency tables for toy example:

a_1	$a=Y$	$a=N$	Total
$c=Y$	2	0	2
$c=N$	0	2	2
Total	2	2	4

a_2	$a=Y$	$a=N$	Total
$c=Y$	1	1	2
$c=N$	1	1	2
Total	2	2	4

Combine PMI of all possible combinations: a, \bar{a}, c, \bar{c}

$$MI(A, C) = P(a, c)PMI(a, c) + P(\bar{a}, c)PMI(\bar{a}, c) + \\ P(a, \bar{c})PMI(a, \bar{c}) + P(\bar{a}, \bar{c})PMI(\bar{a}, \bar{c})$$

$$MI(A, C) = P(a, c) \log_2 \frac{P(a, c)}{P(a)P(c)} + P(\bar{a}, c) \log_2 \frac{P(\bar{a}, c)}{P(\bar{a})P(c)} + \\ P(a, \bar{c}) \log_2 \frac{P(a, \bar{c})}{P(a)P(\bar{c})} + P(\bar{a}, \bar{c}) \log_2 \frac{P(\bar{a}, \bar{c})}{P(\bar{a})P(\bar{c})}$$

Combine PMI of all possible combinations: a, \bar{a}, c, \bar{c}

$$MI(A, C) = P(a, c)PMI(a, c) + P(\bar{a}, c)PMI(\bar{a}, c) + \\ P(a, \bar{c})PMI(a, \bar{c}) + P(\bar{a}, \bar{c})PMI(\bar{a}, \bar{c})$$

$$MI(A, C) = P(a, c) \log_2 \frac{P(a, c)}{P(a)P(c)} + P(\bar{a}, c) \log_2 \frac{P(\bar{a}, c)}{P(\bar{a})P(c)} + \\ P(a, \bar{c}) \log_2 \frac{P(a, \bar{c})}{P(a)P(\bar{c})} + P(\bar{a}, \bar{c}) \log_2 \frac{P(\bar{a}, \bar{c})}{P(\bar{a})P(\bar{c})}$$

Often written more compactly as:

$$MI(A, C) = \sum_{i \in \{a, \bar{a}\}} \sum_{j \in \{c, \bar{c}\}} P(i, j) \log_2 \frac{P(i, j)}{P(i)P(j)}$$

We define that $0 \log 0 \equiv 0$.



Mutual Information Example

Contingency Table for attribute a_1

a_1	$a=Y$	$a=N$	Total
$c=Y$	2	0	2
$c=N$	0	2	2
Total	2	2	4

Mutual Information Example

Contingency Table for attribute a_1

a_1	$a=Y$	$a=N$	Total
$c=Y$	2	0	2
$c=N$	0	2	2
Total	2	2	4

$$P(a, c) = \frac{2}{4}; \quad P(a) = \frac{2}{4}; \quad P(c) = \frac{2}{4}; \quad P(a, \bar{c}) = 0$$

$$P(\bar{a}, \bar{c}) = \frac{2}{4}; \quad P(\bar{a}) = \frac{2}{4}; \quad P(\bar{c}) = \frac{2}{4}; \quad P(\bar{a}, c) = 0$$

Contingency Table for attribute a_1

a_1	$a=Y$	$a=N$	Total
$c=Y$	2	0	2
$c=N$	0	2	2
Total	2	2	4

$$P(a, c) = \frac{2}{4}; \quad P(a) = \frac{2}{4}; \quad P(c) = \frac{2}{4}; \quad P(a, \bar{c}) = 0$$
$$P(\bar{a}, \bar{c}) = \frac{2}{4}; \quad P(\bar{a}) = \frac{2}{4}; \quad P(\bar{c}) = \frac{2}{4}; \quad P(\bar{a}, c) = 0$$

$$MI(A_1, C) = P(a_1, c) \log_2 \frac{P(a_1, c)}{P(a_1)P(c)} + P(\bar{a}_1, c) \log_2 \frac{P(\bar{a}_1, c)}{P(\bar{a}_1)P(c)} +$$
$$P(a_1, \bar{c}) \log_2 \frac{P(a_1, \bar{c})}{P(a_1)P(\bar{c})} + P(\bar{a}_1, \bar{c}) \log_2 \frac{P(\bar{a}_1, \bar{c})}{P(\bar{a}_1)P(\bar{c})}$$

Contingency Table for attribute a_1

a_1	$a=Y$	$a=N$	Total
$c=Y$	2	0	2
$c=N$	0	2	2
Total	2	2	4

$$P(a, c) = \frac{2}{4}; \quad P(a) = \frac{2}{4}; \quad P(c) = \frac{2}{4}; \quad P(a, \bar{c}) = 0$$
$$P(\bar{a}, \bar{c}) = \frac{2}{4}; \quad P(\bar{a}) = \frac{2}{4}; \quad P(\bar{c}) = \frac{2}{4}; \quad P(\bar{a}, c) = 0$$

$$\begin{aligned} MI(A_1, C) &= P(a_1, c) \log_2 \frac{P(a_1, c)}{P(a_1)P(c)} + P(\bar{a}_1, c) \log_2 \frac{P(\bar{a}_1, c)}{P(\bar{a}_1)P(c)} + \\ &\quad P(a_1, \bar{c}) \log_2 \frac{P(a_1, \bar{c})}{P(a_1)P(\bar{c})} + P(\bar{a}_1, \bar{c}) \log_2 \frac{P(\bar{a}_1, \bar{c})}{P(\bar{a}_1)P(\bar{c})} \\ &= \frac{1}{2} \log_2 \frac{\frac{1}{2}}{\frac{1}{2} \frac{1}{2}} + 0 \log_2 \frac{0}{\frac{1}{2} \frac{1}{2}} + 0 \log_2 \frac{0}{\frac{1}{2} \frac{1}{2}} + \frac{1}{2} \log_2 \frac{\frac{1}{2}}{\frac{1}{2} \frac{1}{2}} \\ &= \frac{1}{2}(1) + 0 + 0 + \frac{1}{2}(1) = 1 \end{aligned}$$

Contingency Table for attribute a_2

a_2	$a=Y$	$a=N$	Total
$c=Y$	1	1	2
$c=N$	1	1	2
Total	2	2	4

Mutual Information Example continued

Contingency Table for attribute a_2

a_2	$a=Y$	$a=N$	Total
$c=Y$	1	1	2
$c=N$	1	1	2
Total	2	2	4

$$P(a, c) = \frac{1}{4}; \quad P(a) = \frac{2}{4}; \quad P(c) = \frac{2}{4}; \quad P(\bar{a}, c) = \frac{1}{4}$$
$$P(\bar{a}, \bar{c}) = \frac{1}{4}; \quad P(\bar{a}) = \frac{2}{4}; \quad P(\bar{c}) = \frac{2}{4}; \quad P(a, \bar{c}) = \frac{1}{4}$$

Contingency Table for attribute a_2

a_2	$a=Y$	$a=N$	Total
$c=Y$	1	1	2
$c=N$	1	1	2
Total	2	2	4

$$P(a, c) = \frac{1}{4}; \quad P(a) = \frac{2}{4}; \quad P(c) = \frac{2}{4}; \quad P(\bar{a}, c) = \frac{1}{4}$$
$$P(\bar{a}, \bar{c}) = \frac{1}{4}; \quad P(\bar{a}) = \frac{2}{4}; \quad P(\bar{c}) = \frac{2}{4}; \quad P(a, \bar{c}) = \frac{1}{4}$$

$$MI(A_2, C) = P(a_2, c) \log_2 \frac{P(a_2, c)}{P(a_2)P(c)} + P(\bar{a}_2, c) \log_2 \frac{P(\bar{a}_2, c)}{P(\bar{a}_2)P(c)} +$$
$$P(a_2, \bar{c}) \log_2 \frac{P(a_2, \bar{c})}{P(a_2)P(\bar{c})} + P(\bar{a}_2, \bar{c}) \log_2 \frac{P(\bar{a}_2, \bar{c})}{P(\bar{a}_2)P(\bar{c})}$$

Contingency Table for attribute a_2

a_2	$a=Y$	$a=N$	Total
$c=Y$	1	1	2
$c=N$	1	1	2
Total	2	2	4

$$P(a, c) = \frac{1}{4}; \quad P(a) = \frac{2}{4}; \quad P(c) = \frac{2}{4}; \quad P(\bar{a}, c) = \frac{1}{4}$$
$$P(\bar{a}, \bar{c}) = \frac{1}{4}; \quad P(\bar{a}) = \frac{2}{4}; \quad P(\bar{c}) = \frac{2}{4}; \quad P(a, \bar{c}) = \frac{1}{4}$$

$$\begin{aligned} MI(A_2, C) &= P(a_2, c) \log_2 \frac{P(a_2, c)}{P(a_2)P(c)} + P(\bar{a}_2, c) \log_2 \frac{P(\bar{a}_2, c)}{P(\bar{a}_2)P(c)} + \\ &\quad P(a_2, \bar{c}) \log_2 \frac{P(a_2, \bar{c})}{P(a_2)P(\bar{c})} + P(\bar{a}_2, \bar{c}) \log_2 \frac{P(\bar{a}_2, \bar{c})}{P(\bar{a}_2)P(\bar{c})} \\ &= \frac{1}{4} \log_2 \frac{\frac{1}{4}}{\frac{1}{2} \frac{1}{2}} + \frac{1}{4} \log_2 \frac{\frac{1}{4}}{\frac{1}{2} \frac{1}{2}} + \frac{1}{4} \log_2 \frac{\frac{1}{4}}{\frac{1}{2} \frac{1}{2}} + \frac{1}{4} \log_2 \frac{\frac{1}{4}}{\frac{1}{2} \frac{1}{2}} \\ &= \frac{1}{4}(0) + \frac{1}{4}(0) + \frac{1}{4}(0) + \frac{1}{4}(0) = 0 \end{aligned}$$

Similar idea, different solution:

	a	\bar{a}	Total
c	$\sigma(a, c)$	$\sigma(\bar{a}, c)$	$\sigma(c)$
\bar{c}	$\sigma(a, \bar{c})$	$\sigma(\bar{a}, \bar{c})$	$\sigma(\bar{c})$
Total	$\sigma(a)$	$\sigma(\bar{a})$	N

Contingency table (shorthand):

	a	\bar{a}	Total
c	W	X	$W + X$
\bar{c}	Y	Z	$Y + Z$
Total	$W + Y$	$X + Z$	$N = W + X + Y + Z$

If a, c were independent (uncorrelated), what value would you expect in W ?

Denote the expected value as $E(W)$.



If a, c were independent, then $P(a, c) = P(a)P(c)$

$$P(a, c) = P(a)P(c)$$

$$\frac{\sigma(a, c)}{N} = \frac{\sigma(a)}{N} \frac{\sigma(c)}{N}$$

$$\sigma(a, c) = \frac{\sigma(a)\sigma(c)}{N}$$

$$E(W) = \frac{(W + Y)(W + X)}{W + X + Y + Z}$$

Compare the value we actually observed $O(W)$ with the expected value $E(W)$:

- If the **observed value is much greater than the expected value**, a occurs more often with c than we would expect at random — **predictive**
- If the observed value is **much smaller than the expected value**, a occurs less often with c than we would expect at random — **predictive**
- If the **observed value is close to the expected value**, a occurs as often with c as we would expect randomly — **not predictive**

Similarly with X , Y , Z



Actual calculation (to fit to a chi-square distribution)

$$\begin{aligned}\chi^2 &= \frac{(O(W) - E(W))^2}{E(W)} + \frac{(O(X) - E(X))^2}{E(X)} + \\ &\quad \frac{(O(Y) - E(Y))^2}{E(Y)} + \frac{(O(Z) - E(Z))^2}{E(Z)} \\ &= \sum_{i=1}^r \sum_{j=1}^c \frac{(O_{i,j} - E_{i,j})^2}{E_{i,j}}\end{aligned}$$

- i sums over rows and j sums over columns.
- Because the values are squared, χ^2 becomes much greater when $|O - E|$ is large, even if E is also large.

Chi-square Example

Contingency table for toy example (observed values):

a_1	$a=Y$	$a=N$	Total
$c=Y$	2	0	2
$c=N$	0	2	2
Total	2	2	4

Contingency table for toy example (expected values):

a_1	$a=Y$	$a=N$	Total
$c=Y$	1	1	2
$c=N$	1	1	2
Total	2	2	4

Chi-square Example

$$\begin{aligned}\chi^2(A_1, C) &= \frac{(O_{a,c} - E_{a,c})^2}{E_{a,c}} + \frac{(O_{\bar{a},c} - E_{\bar{a},c})^2}{E_{\bar{a},c}} + \\ &\quad \frac{(O_{a,\bar{c}} - E_{a,\bar{c}})^2}{E_{a,\bar{c}}} + \frac{(O_{\bar{a},\bar{c}} - E_{\bar{a},\bar{c}})^2}{E_{\bar{a},\bar{c}}} \\ &= \frac{(2-1)^2}{1} + \frac{(0-1)^2}{1} + \frac{(0-1)^2}{1} + \frac{(2-1)^2}{1} \\ &= 1 + 1 + 1 + 1 = 4\end{aligned}$$

$\chi^2(A_2, C)$ is obviously 0, because all observed values are equal to expected values.

Common Issues

So far, we've only looked at binary (Y/N) attributes:

- Nominal attributes
- Continuous attributes
- Ordinal attributes

Two common strategies

1. Treat as multiple binary attributes:

- e.g. sunny=Y, overcast=N, rainy=N, etc.
- Can just use the formulae as given
- Results often difficult to interpret
 - For example, Outlook=sunny is useful, but Outlook=overcast and Outlook=rainy are not useful... Should we use Outlook?

Two common strategies

1. Treat as multiple binary attributes:

- e.g. sunny=Y, overcast=N, rainy=N, etc.
- Can just use the formulae as given
- Results often difficult to interpret
 - For example, Outlook=sunny is useful, but Outlook=overcast and Outlook=rainy are not useful... Should we use Outlook?

2. Modify contingency tables (and formulae)

	s	o	r
c=Y	U	V	W
c=N	X	Y	Z

Modified MI:

$$\begin{aligned} MI(O, C) &= \sum_{i \in \{s, o, r\}} \sum_{j \in \{c, \bar{c}\}} P(i, j) \log_2 \frac{P(i, j)}{P(i)P(j)} \\ &= P(s, c) \log_2 \frac{P(s, c)}{P(s)P(c)} + P(s, \bar{c}) \log_2 \frac{P(s, \bar{c})}{P(s)P(\bar{c})} + \\ &\quad P(o, c) \log_2 \frac{P(o, c)}{P(o)P(c)} + P(o, \bar{c}) \log_2 \frac{P(o, \bar{c})}{P(o)P(\bar{c})} + \\ &\quad P(r, c) \log_2 \frac{P(r, c)}{P(r)P(c)} + P(r, \bar{c}) \log_2 \frac{P(r, \bar{c})}{P(r)P(\bar{c})} \end{aligned}$$

- Biased towards attributes with many values. (Why?)

Chi-square can be used as normal, with 6 observed/expected values.

- To control for score inflation, we need to consider “number of degrees of freedom”, and then use the significance test explicitly (beyond the scope of this subject)

Continuous attributes

- Usually dealt with by estimating probability based on a Gaussian (normal) distribution
- With a large number of values, most random variables are normally distributed due to the **Central Limit Theorem**
- For small data sets or pathological features, we may need to use binomial/multinomial distributions

All of this is beyond the scope of this subject

Three possibilities, roughly in order of popularity:

1. Treat as binary
 - Particularly appropriate for frequency counts where events are low-frequency (e.g. words in tweets)
2. Treat as continuous
 - The fact that we haven't *seen* any intermediate values is usually not important
 - Does have all of the technical downsides of continuous attributes, however
3. Treat as nominal (i.e. throw away ordering)

Multi-class problems

So far, we've only looked at binary (Y/N) classification tasks.

Multiclass (e.g. LA, NY, C, At, SF) classification tasks are usually much more difficult.



What makes a single feature good?

- Highly correlated with class
- Highly reverse correlated with class
- Highly correlated (or reverse correlated) with not class

... What if there are many classes?

What makes a single feature good?

- Highly correlated with class
- Highly reverse correlated with class
- Highly correlated (or reverse correlated) with not class

... What if there are many classes?

What makes a feature bad?

- Irrelevant
- Correlated with other features
- Good at only predicting one class (but is this truly bad?)

Consider multi-class problem over LA, NY, C, At, SF:

- PMI, MI, χ^2 are all calculated *per-class*
- (Some other feature selection metrics, e.g. Information Gain, work for all classes at once)
- Need to make a point of selecting (hopefully uncorrelated) features for *each* class to give our classifier the best chance of predicting everything correctly.

Multi-class problems

Actual example (MI):

LA	NY	C	At	SF
la	nyc	chicago	atlanta	sf
angeles	york	bears	atl	httpdealnaycom
los	ny	il	ga	francisco
chicago	chicago	httpbitlyczmk	lol	san
hollywood	atlanta	cubs	u	u
atlanta	yankees	la	georgia	lol
lakers	sf	chi	chicago	save

Multi-class problems

Intuitive features:

LA	NY	C	At	SF
la	nyc	chicago	atlanta	sf
angeles	york	bears	atl	httpdealnaycom
los	ny	il	ga	francisco
chicago	chicago	httpbitlyczmk	lol	san
hollywood	atlanta	cubs	u	u
atlanta	yankees	la	georgia	lol
lakers	sf	chi	chicago	save



Multi-class problems

Features for predicting not class (MI):

LA	NY	C	At	SF
la	nyc	chicago	atlanta	sf
angeles	york	bears	atl	httpdealnaycom
los	ny	il	ga	francisco
chicago	chicago	httpbitlyczmk	lol	san
hollywood	atlanta	cubs	u	u
atlanta	yankees	la	georgia	lol
lakers	sf	chi	chicago	save

Multi-class problems

Unintuitive features:

LA	NY	C	At	SF
la	nyc	chicago	atlanta	sf
angeles	york	bears	atl	httpdealnaycom
los	ny	il	ga	francisco
chicago	chicago	httpbitlyczmk	lol	san
hollywood	atlanta	cubs	u	u
atlanta	yankees	la	georgia	lol
lakers	sf	chi	chicago	save



Mutual Information is biased toward rare, uninformative features

- All probabilities: no notion of the raw frequency of events
- If a feature is seen rarely, but always with a given class, it will be seen as “good”
- Best features in the Twitter dataset only had MI of about 0.01 bits; 100th best for a given class had MI of about 0.002 bits

Term Frequency Inverse Document Frequency (TFIDF)

- Common in Natural Language Processing
- Find words that are relevant to a document in a given document collection
- To be relevant, a word should be
 - Frequent enough in the corpus (TF). A word that occurs only 5 times in a corpus of 5,000,000 words is probably not too interesting
 - Special enough (IDF). A word that is very general and occurs in (almost) every document is probably not too interesting

Term Frequency Inverse Document Frequency (TFIDF)

- Common in Natural Language Processing
- Find words that are relevant to a document in a given document collection
- To be relevant, a word should be
 - Frequent enough in the corpus (TF). A word that occurs only 5 times in a corpus of 5,000,000 words is probably not too interesting
 - Special enough (IDF). A word that is very general and occurs in (almost) every document is probably not too interesting

$$tfidf(d, t, D) = tf + idf$$

$$tf = \log(1 + freq(t, d))$$

$$idf = \log\left(\frac{|D|}{count(d \in D : t \in d)}\right)$$

d =document, t =term, D =document collection;

$|D|$ =number of documents in D



And there are many more strategies

https://scikit-learn.org/stable/modules/classes.html#module-sklearn.feature_selection

`sklearn.feature_selection`: Feature Selection

The `sklearn.feature_selection` module implements feature selection algorithms. It currently includes univariate filter selection methods and the recursive feature elimination algorithm.

User guide: See the [Feature selection](#) section for further details.

<code>feature_selection.GenericUnivariateSelect([...])</code>	Univariate feature selector with configurable strategy.
<code>feature_selection.SelectPercentile([...])</code>	Select features according to a percentile of the highest scores.
<code>feature_selection.SelectKBest([score_func, k])</code>	Select features according to the k highest scores.
<code>feature_selection.SelectFpr([score_func, alpha])</code>	Filter: Select the p-values below alpha based on a FPR test.
<code>feature_selection.SelectFdr([score_func, alpha])</code>	Filter: Select the p-values for an estimated false discovery rate
<code>feature_selection.SelectFromModel(estimator, *)</code>	Meta-transformer for selecting features based on importance weights.
<code>feature_selection.SelectFwe([score_func, alpha])</code>	Filter: Select the p-values corresponding to Family-wise error rate
<code>feature_selection.SequentialFeatureSelector(...)</code>	Transformer that performs Sequential Feature Selection.
<code>feature_selection.RFE(estimator, *[, ...])</code>	Feature ranking with recursive feature elimination.
<code>feature_selection.RFECV(estimator, *[, ...])</code>	Feature ranking with recursive feature elimination and cross-validated selection of the best number of features.
<code>feature_selection.VarianceThreshold([threshold])</code>	Feature selector that removes all low-variance features.
<code>feature_selection.chi2(X, y)</code>	Compute chi-squared stats between each non-negative feature and class.
<code>feature_selection.f_classif(X, y)</code>	Compute the ANOVA F-value for the provided sample.
<code>feature_selection.f_regression(X, y, *[, center])</code>	Univariate linear regression tests.
<code>feature_selection.mutual_info_classif(X, y, *)</code>	Estimate mutual information for a discrete target variable.
<code>feature_selection.mutual_info_regression(X, y, *)</code>	Estimate mutual information for a continuous target variable.

So ... is feature selection worth it?

Absolutely!

- Even marginally relevant features usually a vast improvement on an unfiltered data set
- Some models **need** feature selection
 - k-Nearest Neighbours, hugely
 - Naive Bayes, to a lesser extent
- Machine learning experts (us!) need to think about the data!

Today

- Wrappers vs. Filters
- Popular filters: PMI, MI, χ^2 , how should we use them and what are the results going to look like
- Importance of feature selection for different methods (even though it sometimes isn't the solution we were hoping for)

Next week(s):

- Logistic regression
- Perceptron and neural networks
- ...and their respective learning algorithms (iterative optimization)



- Guyon, Isabelle, and Andre Elisseeff. 2003. An introduction to variable and feature selection. *The Journal of Machine Learning Research*. Vol 3, 1157–1182.
- John, George, Ron Kohavi, and Karl Pfleger. 1994. Irrelevant features and the subset selection problem. In *Proceedings of the 11th International Conference on Machine Learning*, 121–9.
- Tan, Pang-Ning, Michael Steinbach, and Vipin Kumar. 2006. *Introduction to Data Mining*. Addison Wesley.
- Witten, Ian, and Eibe Frank. 2005. *Data Mining: Practical Machine Learning Tools and Techniques with Java Implementations*. San Francisco, USA: Morgan Kaufmann.
- Yang, Yiming, Jan Pedersen. 1997. A Comparative Study on Feature Selection in Text Categorization. In *Proceedings of the Fourteenth International Conference on Machine Learning*, 412–20.

