



Create an index pattern

edit

Kibana requires an index pattern to access the Elasticsearch data that you want to explore. An index pattern selects the data to use and allows you to define properties of the fields.

An index pattern can point to a specific index, for example, your log data from yesterday, or all indices that contain your data. It can also point to a [data stream](#) or [index alias](#).

You'll learn how to:

- Create an index pattern
- Explore and configure the data fields
- Set the default index pattern
- Delete an index pattern

Before you begin

edit

- To access **Index Patterns**, you must have the Kibana privilege `Index Pattern Management`. To add the privilege, open the main menu, then click **Stack Management > Roles**.
- If a read-only indicator appears in Kibana, you have insufficient privileges to create or save index patterns. The buttons to create new index patterns or save existing index patterns are not visible. For more information, refer to [Granting access to Kibana](#).

Create an index pattern

edit

If you collected data using one of the Kibana [ingest options](#), uploaded a file, or added sample data, you get an index pattern for free, and can start exploring your data. If you loaded your own data, follow these steps to create an index pattern.

1. Open the main menu, then click to **Stack Management > Index Patterns**.
2. Click **Create index pattern**.

Create index pattern

Kibana uses index patterns to retrieve data from Elasticsearch indices for things like visualizations.

☐ Include system indices

Step 1 of 2: Define index pattern

Index pattern

kibana_sample*

You can use a * as a wildcard in your index pattern.
You can't use spaces or the characters \, /, ?, *, <, >, |.

> Next step

✓ Success! Your index pattern matches 3 indices.

kibana_sample_data_ecommerce

kibana_sample_data_flights

kibana_sample_data_logs

Rows per page: 10

3. Start typing in the **Index pattern** field, and Kibana looks for the names of Elasticsearch indices that match your input.
 - Use a wildcard (*) to match multiple indices. For example, suppose your system creates indices for Apache data using the naming scheme `filebeat-apache-a`, `filebeat-apache-b`, and so on. An index pattern named `filebeat-a` matches a single source, and `filebeat-*` matches multiple data sources. Using a wildcard is the most popular approach.
 - Select multiple indices by entering multiple strings, separated with a comma. Make sure there is no space after the comma. For example, `filebeat-a,filebeat-b` matches two indices, but not other indices you might have afterwards (`filebeat-c`).
 - Use a minus sign (-) to exclude an index, for example, `test*,-test3`.
4. Click **Next step**.
5. If Kibana detects an index with a timestamp, expand the **Time field** menu, and then specify the default field for filtering your data by time.

If your index doesn't have time-based data, or if you don't want to select the default timestamp field, choose **I don't want to use the Time Filter**.

NOTE If you don't set a default time field, you will not be able to use global time filters on your dashboards. This is useful if you have multiple time fields and want to create dashboards that combine visualizations based on different timestamps.

6. Click **Create index pattern**.

Kibana is now configured to use your Elasticsearch data.

7. Select this index pattern when you search and visualize your data.

Create an index pattern for rolled up data

An index pattern can match one rollup index. For a combination rollup index pattern with both raw and rolled up data, use the standard notation:

```
rollup_logstash,kibana_sample_data_logs
```

For an example, refer to [Create and visualize rolled up data](#).

Create an index pattern that searches across clusters

If your Elasticsearch clusters are configured for [cross-cluster search](#), you can create an index pattern to search across the clusters of your choosing. Use the same syntax that you'd use in a raw cross-cluster search request in Elasticsearch:

```
<cluster-names>:<pattern>
```

For example, to query Logstash indices across two Elasticsearch clusters that you set up for cross-cluster search, named `cluster_one` and `cluster_two`, use this for your index pattern:

```
cluster_one:logstash-*,cluster_two:logstash-*
```

You can use wildcards in your cluster names to match any number of clusters. For example, to search Logstash indices across clusters named `cluster_foo`, `cluster_bar`, and so on, create this index pattern:

```
cluster_*:logstash-*
```

To query across all Elasticsearch clusters that have been configured for cross-cluster search, use a standalone wildcard for your cluster name in your index pattern:

```
*:logstash-*
```

Once an index pattern is configured using the cross-cluster search syntax, all searches and aggregations using that index pattern in Kibana take advantage of cross-cluster search.

Explore and configure the data fields

To explore and configure the data fields in your index pattern, open the main menu, then click **Stack Management > Index Patterns**. Each field has a [mapping](#), which indicates the type of data the field contains in Elasticsearch, such as strings or boolean values. The field mapping also determines how you can use the field, such as whether it can be searched or aggregated.

kibana_sample*

Time Filter field name: @timestamp

This page lists every field in the **kibana_sample*** index and the field's associated core type as recorded by Elasticsearch. To change a field type, use the Elasticsearch [Mapping API](#)

Fields (119)

Scripted fields (0)

Source filters (0)

Q Filter

All field types

Name	Type	Format	Searchable	Aggregatable	Excluded
@timestamp	date				
AvgTicketPrice	number				
Cancelled	boolean				
Carrier	string				
Dest	string				
DestAirportID	string				
DestCityName	string				

Format the display of common field types

Whenever possible, Kibana uses the same field type for display as Elasticsearch. However, some field types that Elasticsearch supports are not available in Kibana. Using field formatters, you can manually change the field type in Kibana to display your data the way you prefer to see it, regardless of how it is stored in Elasticsearch.

For example, if you store date values in Elasticsearch, you can use a Kibana field formatter to change the display to mm/dd/yyyy format. Kibana has field formatters for [strings](#), [dates](#), [geopoints](#), and [numbers](#).

A popularity counter keeps track of the fields you use most often. The top five most popular fields and their values are displayed in [Discover](#).

To edit the field format and popularity counter, click the edit icon () in the index pattern detail view.

Edit @timestamp

Type

date

Format (Default: Date)

Date

Formatting allows you to control the way that specific values are displayed. It can also cause values to be completely changed and prevent highlighting in Discover from working.

Moment.js format pattern (Default: MMM D, YYYY @ HH:mm:ss.SSS)

MMM D, YYYY @ HH:mm:ss.SSS

Documentation

Samples

Input	Output
1603720727818	Oct 26, 2020 @ 09:58:47.818
1577854800000	Jan 1, 2020 @ 00:00:00.000
1609477199999	Dec 31, 2020 @ 23:59:59.999

Popularity

0

Save fieldCancel

Refresh the data fields

To pick up newly-added fields, refresh (🔄) the index fields list. This action also resets the Kibana popularity counters for the fields.

edit

Set the default index pattern

The first index pattern you create is automatically designated as the default pattern, but you can set any index pattern as the default. The default index pattern is automatically selected when you first open **Discover** or create a visualization from scratch.

edit

1. In **Index patterns**, click the index pattern name.
2. Click the star icon (★).

Delete an index pattern

This action removes the pattern from the list of saved objects in Kibana. You will not be able to recover field formatters, scripted fields, source filters, and field popularity data associated with the index pattern. Deleting an index pattern does not remove any indices or data documents from Elasticsearch.

edit

Deleting an index pattern breaks all visualizations, saved searches, and other saved objects that reference the pattern.

WARNING

1. In **Index patterns**, click the index pattern name.
2. Click the delete icon (🗑️).

What's next


- Learn about **scripted fields** and how to create data on the fly.


edit


On this page

- [Before you begin](#)
- [Create an index pattern](#)
- [Explore and configure the data fields](#)
- [Set the default index pattern](#)
- [Delete an index pattern](#)
- [What's next](#)

What's New

Elastic Cloud Free Trial

Introducing Elastic Security

Free Elastic Training

Kibana Guide: 7.10 (current) ▾
What is Kibana?
What's new in 7.10
Quick start
Set up
Discover <div>Create an index pattern</div> <div>Set the time filter</div> <div>Search data</div>
Dashboard
Canvas
Maps
Machine learning
Graph
Observability
APM
Elastic Security
Dev Tools
Stack Monitoring
Stack Management
Fleet
Reporting
Alerting and Actions
REST API
Kibana plugins
Accessibility
Breaking Changes
Release Notes

Subscribe to our newsletter

Email address

Sign up

Follow Us

PRODUCTS & SOLUTIONS

- Enterprise Search
- Observability
- Security
- Elastic Stack
- Elasticsearch
- Kibana
- Logstash
- Beats
- Subscriptions
- Pricing

COMPANY

- Careers
- Board of Directors
- Contact

RESOURCES

- Documentation
- What is the ELK Stack?
- What is Elasticsearch?
- Migrating from Splunk
- Compare AWS Elasticsearch
- US Public Sector



[Trademarks](#) | [Terms of Use](#) | [Privacy](#) | [Brand](#) | [Sitemap](#)

Elasticsearch is a trademark of Elasticsearch B.V., registered in the U.S. and in other countries.

Apache, Apache Lucene, Apache Hadoop, Hadoop, HDFS and the yellow elephant logo are trademarks of the Apache Software Foundation in the United States and/or other countries.

