

Installation Guide for Kayak Rack

Preparation:

- Clean the roof and crossbars of your vehicle
- Clean the roof with a soft cleaning cloth
- Wearing gloves to install is highly recommended

⚠ [Safety Warning/Caution]

- Do not load or exceed the designated carrying capacity (70lbs/31.5kg)
- Not recommended for tandem bikes
- Only install onto the vehicle that has crossbars
- Please remove the antenna or any accessories on the roof



Step 1:

- Insert carriage bolts into the kayak rack.
- Place the kayak rack onto the crossbars of your vehicle. Make sure the direction is correct.



Step 2:

- Place the metal brackets under the supporting arms and crossbars.
- Thread the carriage bolts from the bottom of the brackets and tighten the tri-wing nuts. Repeat this step for the other kayak rack.



Step 3:

- [Load your item] Place the kayak evenly and horizontally onto the soft rubber padding of each supporting arm.
- Take the strap and thread it through the kayak seat strap hook.



Step 4:

- Wrap the strap around the kayak and crossbar, tie on the strap to the crossbar.
- Thread the strap through the metal buckle to secure the kayak in place. Pull the straps down firmly.



Step 5:

- Repeat this step for the second carrier. Please always check the kayak rack assembly and straps before transport.

