

SAFETY DATA SHEET

Creation Date 12-Nov-2014

Revision Date 18-Dec-2025

Revision Number 8

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard 2024 (29 CFR 1910.1200)

1. Identification

Product Name Permunt Mounting Media

Cat No. : SP15-100; SP15-500

Synonyms A permanent adhesive for cementing cover glass to microscope slide.

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Emergency Telephone Number

CHEMTREC®, Inside the USA: 800-424-9300
CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous according to [US] OSHA (29 CFR 1910.1200, 2024)

Flammable liquids	Category 2
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Central nervous system (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 2
Target Organs - Neurological effects, Eyes, Ears.	
Aspiration Toxicity	Category 1

Label Elements

Signal Word
Danger

Hazard Statements

Highly flammable liquid and vapor
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye irritation
May cause drowsiness or dizziness
Suspected of damaging the unborn child
May cause damage to organs through prolonged or repeated exposure

**Precautionary Statements****Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wash face, hands and any exposed skin thoroughly after handling
Wear eye/face protection
Do not breathe dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Ground and bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting equipment
Keep cool
Wear protective gloves/protective clothing/eye protection/face protection
Take action to prevent static discharges
Use non-sparking tools

Response

IF exposed or concerned: Get medical attention/advice

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Skin

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
Take off contaminated clothing and wash before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor
Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam to extinguish

Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Hazards classified under paragraph (d)(1)(ii) of 1910.1200**

No information available

WARNING. Reproductive Harm - <https://www.p65warnings.ca.gov/>.

3. Composition/information on Ingredients

Component	CAS No	Weight %
Toluene	108-88-3	55
Polyterpene hydrocarbon resin	68240-09-5	45

4. First-aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Most important symptoms and effects	None reasonably foreseeable. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire
Flash Point	4 °C / 39.2 °F
Method -	No information available
Autoignition Temperature	480 °C / 896 °F
Explosion Limits	
Upper	7.1%
Lower	1.2%
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Keep product and empty container away from heat and sources of ignition. Runoff to sewer may create fire or explosion hazard. Do not allow run-off from fire-fighting to enter drains or water courses. Vapors may travel to source of ignition and flash back. Vapors may accumulate in confined areas (basement, tanks, hopper/tank cars, etc.). Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon oxides.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full

protective gear.

NFPA

Health
3

Flammability
3

Instability
0

Physical hazards
N/A

6. Accidental release measures

Personal Precautions

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and Storage

Handling

Ensure adequate ventilation. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage.

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame. Incompatible Materials. Strong oxidizing agents.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Toluene	TWA: 20 ppm	(Vacated) TWA: 100 ppm (Vacated) TWA: 375 mg/m ³ Ceiling: 300 ppm (Vacated) STEL: 150 ppm (Vacated) STEL: 560 mg/m ³ TWA: 200 ppm	IDLH: 500 ppm REL = 100 ppm (TWA) REL = 375 mg/m ³ (TWA) STEL: 150 ppm STEL: 560 mg/m ³	TWA: 20 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Personal Protective Equipment**Eye/face Protection**

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended Filter type:

Organic gases and vapours filter. Type A. Brown. conforming to EN14387.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance

Physical State

Liquid

Color

Yellow

Odor

aromatic

Odor Threshold

No information available

PropertyValuesRemarks• Method

Melting Point/Range

No data available

Softening Point

No data available

Boiling Point/Range

111 °C / 231.8 °F

@ 760 mmHg

Flash Point

4 °C / 39.2 °F

Method - No information available

Flammability (liquid)

Highly flammable

On basis of test data

Flammability (solid,gas)

Not applicable

Liquid

Explosion Limits

Lower 1.2**Upper** 7.1

Autoignition Temperature

480 °C / 896 °F

Decomposition Temperature

No data available

pH

No information available

Viscosity

No data available

Water Solubility

Insoluble

Solubility in other solvents

No information available

Partition Coefficient (n-octanol/water)

Component

log Pow

Toluene

2.73

Vapor Pressure

No information available

Density / Specific Gravity

No data available

Bulk Density

Not applicable

Liquid

Vapor Density

3.1

(Air = 1.0)

Particle characteristics

Not applicable (liquid)

Other Information

VOC Content(%)

55%

Explosive Properties

Vapors may form explosive mixtures with air

Evaporation Rate

No information available

10. Stability and reactivity

Reactive Hazard

No

Stability

Stable under normal conditions.

Conditions to Avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials

Strong oxidizing agents

Hazardous Decomposition Products Carbon oxides

Hazardous Polymerization

Hazardous polymerization does not occur.

Hazardous Reactions

None under normal processing.

11. Toxicological information

Information on expected route of exposure

Inhalation	Avoid breathing vapors or mists.
Ingestion	May be harmful if swallowed. Potential for aspiration if swallowed. Harmful if swallowed.
Eyes	Avoid contact with eyes. May cause irritation.
Skin	Avoid contact with skin. May cause irritation. Prolonged skin contact may defat the skin and produce dermatitis.

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Toluene	> 5000 mg/kg (Rat)	LD50 = 12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h

Toxicologically Synergistic Products No information available

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;
Respiratory No data available
Skin No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity;

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Toluene	108-88-3	Not listed	Not listed	Not listed	Not listed	Not listed
Polyterpene hydrocarbon resin	68240-09-5	Not listed	Not listed	Not listed	Not listed	Not listed

(g) reproductive toxicity; Category 2

Developmental Effects Possible risk of harm to the unborn child.

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS).

(i) STOT-repeated exposure; Category 2

Target Organs Neuropsychological effects, Eyes, Ears.

(j) aspiration hazard; Category 1

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Other Adverse Effects The toxicological properties have not been fully investigated.

Endocrine Disrupting Properties This product does not contain any known or suspected endocrine disruptors.

12. Ecological information

Ecotoxicity

The product contains following substances which are hazardous for the environment. Contains a substance which is: Toxic to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Toluene	EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: > 433 mg/L, 96h (Pseudokirchneriella subcapitata)	50-70 mg/L LC50 96 h 5-7 mg/L LC50 96 h 15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h	EC50 = 19.7 mg/L 30 min	EC50: = 11.5 mg/L, 48h (Daphnia magna) EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna)

Persistence and Degradability Insoluble in water Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Is not likely mobile in the environment due its low water solubility. Will likely be mobile in the environment due to its volatility.

Component	log Pow
Toluene	2.73

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Toluene - 108-88-3	U220	-

14. Transport information

DOT

UN-No UN1294
 Proper Shipping Name TOLUENE SOLUTION
 Hazard Class 3
 Packing Group II

TDG

UN-No UN1294
 Proper Shipping Name TOLUENE SOLUTION
 Hazard Class 3
 Packing Group II

IATA

UN-No UN1294
 Proper Shipping Name TOLUENE SOLUTION
 Hazard Class 3
 Packing Group II

IMDG/IMO

UN-No UN1294
 Proper Shipping Name TOLUENE SOLUTION
 Hazard Class 3
 Packing Group II

15. Regulatory Information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
-----------	--------	------	---	-----------------------------

Toluene	108-88-3	X	ACTIVE	-
Polyterpene hydrocarbon resin	68240-09-5	X	ACTIVE	XU

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B))

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Not applicable

International Inventories

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Toluene	108-88-3	X	-	203-625-9	X	X	X	X	X	KE-33936
Polyterpene hydrocarbon resin	68240-09-5	X	-	-	X	-		X	X	KE-34432

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS No	Weight %	SARA 313 - Threshold Values %	SARA 313 - Reporting thresholds
Toluene	108-88-3	55	1.0 %	-

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Toluene	X	1000 lb	X	X

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Toluene	X		-

OSHA - Occupational Safety and Health Administration

Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
Toluene	1000 lb	-	1000 lb

			454 kg
--	--	--	--------

California Proposition 65 This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Toluene	108-88-3	Developmental	-	Developmental

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Toluene	X	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y

DOT Marine Pollutant N

DOT Severe Marine Pollutant N

U.S. Department of Homeland Security This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Toluene	108-88-3	-	Use restricted. See entry 48. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-
Polyterpene hydrocarbon resin	68240-09-5	-	-	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Toluene	108-88-3	Listed	Not applicable	Not applicable	Not applicable
Polyterpene hydrocarbon resin	68240-09-5	Not applicable	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Other International Regulations

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Toluene	108-88-3	Not applicable	Not applicable	Not applicable	Annex I - Y42
Polyterpene hydrocarbon resin	68240-09-5	Not applicable	Not applicable	Not applicable	Not applicable

16. Other Information

Prepared By	Product stewardship (Regulatory Affairs) Thermo Fisher Scientific email - begel.sdsdesk@thermofisher.com
Creation Date	12-Nov-2014
Revision Date	18-Dec-2025
Print Date	18-Dec-2025
Revision Summary	Updated to the U.S. Department of Labor's Occupational Safety and Health Administration (OSHA) which published its Final Rule in the Federal Register revising the Hazard Communication Standard (HCS/HazCom), 29 CFR 1910.1200 (2024) (HCS §1910.1200, 2024), May 20, 2024, effective July 19, 2024.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS