

APPENDIX J

CLAREMONT ROAD AND STREET REQUIREMENTS*

The following are, but [are] not limited to, the requirements which must be met prior to submittal to the city for acceptance of new roads and streets.

1. Planning board approvals of:
 - A. All plans, layouts, design and specifications of roads, streets, sidewalks and drainage.
 - B. Where applicable, all plans, layouts, design and specifications of water, sewer and other utilities.
 - C. Other engineering studies which may be required by other city boards or departments.
 - D. Items "A" through "C" shall be prepared and signed by a professional engineer, licensed in the State of New Hampshire.
2. The minimum width of right-of-way shall be fifty (50) feet. A greater width may be required for arterial and collector streets or as required.
3. Bounds will be set at all corners of streets and roadways, intersections, cul-de-sacs, right-of-ways, change of direction and at any other points as deemed necessary to designate street lines. Granite bounds shall be set at important points to preserve essential property information.
4. Except where near future connections may be possible, cul-de-sacs shall not be longer than one thousand (1,000) feet. A turn-

***Editor's note**—Printed herein are the City of Claremont Road and Street Requirements adopted by the Claremont Planning Board on April 17, 1989. Style and capitalization have been made uniform. Obviously misspelled words have been corrected without notation. Words added for clarification have been added in brackets. Amendments have been included and are indicated by a history note immediately following the amended section.

CLAREMONT CODE

around shall be provided at the closed end with the minimum radius of sixty (60) feet from the center to the outside edge of the right-of-way with a paved area of eighty (80) feet in diameter for residential and ninety (90) feet in diameter for commercial/industrial.

5. Stripes on roads, crosswalks, centerline striping or other striping as required shall be as per State of New Hampshire specifications.

6. Street lights shall be installed at all intersections and elsewhere as deemed necessary. Upon acceptance of streets or roads, the city shall assume responsibility for the operation and maintenance of same.

7. No roadside barriers will be allowed within twenty (20) feet of the centerline of the right-of-way. (ie: ledge, trees, signs, etc.)

8. Prior to acceptance, all new roads shall go through one (1) winter cycle. The developer shall be responsible for all maintenance prior to acceptance. Upon acceptance, a two-year maintenance bond shall be posted.

9. Procedure for posting of road bonds:

- A. Prior to start of construction, the developer/contractor shall provide a detailed cost estimate of construction with required plans and specifications as outlined in Item 1.
- B. The city manager's designee shall submit the recommended bond cost to the director of planning and development.
- C. Upon acceptance of the road by the city a two-year maintenance bond shall be posted as follows:
 - 1. No underground utilities—ten (10) percent of the cost of the roadway.
 - 2. With underground utilities—twenty (20) percent of the cost of the roadway.

10. Protection of pavements:

Once the pavement on a highway or sidewalk has been laid, constructed or resurfaced during the first five (5) years of its life, no excavation or pavement cut shall be permitted into that surface

APPENDIX J—ROAD AND STREET REQUIREMENTS

unless the person, firm or corporation wishing to make such excavation or pavement cut first deposits with the public works department a certified check equal to one hundred (100) percent of the city manager's designated agent's estimate of the cost to resurface the original pavement so as to bring the pavement back to the original condition when first paved. Any person, firm or corporation cutting into a resurfaced area which has been laid down less than five (5) years shall be required to resurface on latitudinal cuts one hundred (100) feet both ends of the cut and on longitudinal cuts one hundred (100) feet both ends of the cut for its full width or replace an entire sidewalk panel or panels in such a manner as to blend the shape, texture and color so as to be compatible with the surrounding panels.

11. No driveway shall be located closer than thirty (30) feet from an intersection.

12. Traffic-control signs shall be installed by the developer as per city and state specifications and regulations.

Note: For additional information and guidance reference should be made to the American Association of State Highway and Transportation officials, "A Policy on Geometric Design of Highways and Streets."

Approved by the Claremont Planning Board:

/s/ _____
William Kimball, Chairman
Date: April 7, 1988

