

# Where to put Foreign Keys?

# General Rule to Place Foreign Key

## Connectivity 1:M:

- Enter the primary key from the one side into the many side

## Connectivity 1:1:

- Enter the primary key from the mandatory side into the optional side
- Otherwise – your choice

## Connectivity M:N

- Sources of redundancies
- Need to replace M:N relationships

# Connectivity & Participation – Examples


1:M relationship between Customer and Order  
(order is optional to customer)

Customer		
CustID	CustName	CustPhone
1	John	321
2	Cathy	455
3	Mohammad	788
4	Rupam	745
5	Polash	121

1 side

Order			
OrderID	OrderDate	OrderAmount(\$)	OrderedBy (CustID)
11	21/08/2016	45	1
12	22/08/2016	45	3
13	23/08/2016	48	4
14	24/08/2016	34	1
15	25/08/2016	52	2
16	26/08/2016	78	3

M side (should have FKs)



# Connectivity & Participation – Examples


1:M relationship between Customer and Order  
(order is **mandatory** to customer)

Customer		
CustID	CustName	CustPhone
1	John	321
2	Cathy	455
3	Mohammad	788
4	Rupam	745
5	Polash	121

1 side

Order			
OrderID	OrderDate	OrderAmount(\$)	OrderedBy (CustID)
11	21/08/2016	45	1
12	22/08/2016	45	3
13	23/08/2016	48	4
14	24/08/2016	34	1
15	25/08/2016	52	2
16	26/08/2016	78	3
17	27/08/2016	85	5

M side (should have FKs)



# Connectivity & Participation – Examples


1:1 relationship between Person and License  
License is **optional** to Person

Person		
PersonID	PersonName	PersonPhone
1	John	321
2	Cathy	455
3	Mohammad	788
4	Rupam	745
5	Polash	121
6	Garth	345

1 side

License			
LicenseNum	LicExpiryDate	SpecialCode	BelongsTo (PersonID)
11	21/08/2016	P	1
12	22/08/2016	L	2
13	23/08/2016	F	3
14	24/08/2016	P	4

1 side (FKs are on optional side) → Why?



# Connectivity & Participation – Examples

1:1 relationship between Person and License


License is **optional** to Person

PersonID	PersonName	PersonPhone	LicenseNo
1	John	321	11
2	Cathy	455	12
3	Mohammad	788	13
4	Rupam	745	14
5	Polash	121	NULL
6	Garth	345	NULL

License			
LicenseNum	LiceExpiryDate	SpecialCode	BelongsTo (PersonID)
11	21/08/2016	P	1
12	22/08/2016	L	2
13	23/08/2016	F	3
14	24/08/2016	P	4

“redundant”

Putting FK on the mandatory creates many NULL values



FK: LicenseNo

# Connectivity & Participation – Examples


1:1 relationship between Person and License  
 License is **mandatory** to Person

Person		
PersonID	PersonName	PersonPhone
1	John	321
2	Cathy	455
3	Mohammad	788
4	Rupam	745
5	Polash	121
6	Garth	345

1 side

License			
LicenseNum	LiceExpiryDate	SpecialCode	BelongsTo (PersonID)
11	21/08/2016	P	1
12	22/08/2016	L	2
13	23/08/2016	F	3
14	24/08/2016	P	4
15	25/08/2016	L	5
16	26/08/2016	F	6

1 side (FKs are on right side)



# Connectivity & Participation – Examples


1:1 relationship between Person and License  
 License is **mandatory** to Person

Person			
PersonID	PersonName	PersonPhone	LicNumber
1	John	321	11
2	Cathy	455	12
3	Mohammad	788	13
4	Rupam	745	14
5	Polash	121	15
6	Garth	345	16

1 side (FKs are on left side)

License		
LicenseNum	LiceExpiryDate	SpecialCode
11	21/08/2016	P
12	22/08/2016	L
13	23/08/2016	F
14	24/08/2016	P
15	25/08/2016	L
16	26/08/2016	F

1 side





Thank you