

# Working with Dates and Times in Python

by Dataquest Labs, Inc. - All rights reserved © 2019

## Syntax

---

### IMPORTING MODULES AND DEFINITIONS

- Importing a whole module:

```
import csv  
csv.reader()
```

- Importing a whole module with an alias:

```
import csv as c  
c.reader()
```

- Importing a single definition:

```
from csv import reader  
reader()
```

- Importing multiple definitions:

```
from csv import reader, writer  
reader()  
writer()
```

- Importing all definitions:

```
from csv import *
```

---

### WORKING WITH THE `DATETIME` MODULE

- All examples below presume the following import code:

```
import datetime as dt
```

- Creating datetime.datetime string given a month, year, and day:

```
eg_1 = dt.datetime(1985, 3, 13)
```

- Creating a datetime.datetime object from a string:

```
eg_2 = dt.datetime.strptime("24/12/1984", "%d/%m/%Y")
```

- Converting a datetime.datetime object to a string:

```
dt_object = dt.datetime(1984, 12, 24)
dt_string = dt_object.strftime("%d/%m/%Y")
```

- Instantiating a datetime.time object:

```
eg_3 = datetime.time(hour=0, minute=0, second=0, microsecond=0)
```

- Retrieving a part of a date stored in the datetime.datetime object:

```
eg_1.day
```

- Creating a date from a datetime.datetime object:

```
d2_dt = dt.datetime(1946, 9, 10)
d2 = d2_dt.date()
```

- Creating a datetime.date object from a string:

```
d3_str = "17 February 1963"
d3_dt = dt.datetime.strptime(d3_str, "%d %B %Y")
d3 = d3_dt.date()
```

- Instantiating a datetime.timedelta object:

```
eg_4 = dt.timedelta(weeks=3)
```

- Adding a time period to a datetime.datetime object:

```
d1 = dt.date(1963, 2, 26)
d1_plus_1wk = d1 + dt.timedelta(weeks=1)
```

- Convert integers to objects based on their epoch time value:

```
datetime.datetime.fromtimestamp(345521)
```

## Concepts

- The datetime module contains five classes:
  - `datetime.datetime` — For working with date and time data
  - `datetime.date` — For working with date data only
  - `datetime.time` — For working with time data only
  - `datetime.timedelta` — For representing time periods
  - `datetime.timezone` — For representing a specific time zone

- Time objects behave similarly to datetime objects for the following reasons:
  - They have attributes like `time.hour` and `time.second` that you can use to access individual time components.
  - They have a `time.strftime()` method, which you can use to create a formatted string representation of the object.
- The timedelta type represents a period of time, e.g. 30 minutes or two days.
- Epoch time represents time as an integer, counting the number of seconds since midnight on January 1, 1970. Epoch time is the default on the majority of the world's servers, which makes it an important time format to know and understand.
- Common format codes when working with `datetime.datetime.strptime`:

Strftime Code	Meaning	Examples
<code>%d</code>	Day of the month as a zero-padded number <sup>1</sup>	<code>04</code>
<code>%A</code>	Day of the week as a word <sup>2</sup>	<code>Monday</code>
<code>%m</code>	Month as a zero-padded number <sup>1</sup>	<code>09</code>
<code>%Y</code>	Year as a four-digit number	<code>1901</code>
<code>%y</code>	Year as a two-digit number with zero-padding <sup>1, 3</sup>	<code>01</code> (2001) <code>88</code> (1988)
<code>%B</code>	Month as a word <sup>2</sup>	<code>September</code>
<code>%H</code>	Hour in 24 hour time as zero-padded number <sup>1</sup>	<code>05</code> (5am) <code>15</code> (3pm)
<code>%p</code>	AM or PM <sup>2</sup>	<code>AM</code>
<code>%I</code>	Hour in 12 hour time as zero-padded number <sup>1</sup>	<code>05</code> (5am, or 5pm if AM/PM indicates otherwise)
<code>%M</code>	Minute as a zero-padded number <sup>1</sup>	<code>07</code>

1. The `strptime` parser will parse non-zero padded numbers without raising an error.

2. Date parts containing words will be interpreted using the locale settings on your computer, so `strptime` won't be able to parse 'febrero' (february in Spanish) if your locale is set to an english language locale.

3. Year values from 00-68 will be interpreted as 2000-2068, with values 70-99 interpreted as 1970-1999.

- Operations between timedelta, datetime, date, and time objects:

		Resultant
--	--	-----------

Operation	Explanation		Resultant Type
Epoch Time:			
<code>Epoch Time - datetime</code>	<b>Date/Time in UTC</b>	Calculate the time between two specific dates/times	timedelta
<code>0 - datetime</code>	Midnight	January 1, 1970	
<code>timedelta 1</code>	One second	Subtract a time period from a date or time. after midnight, January 1, 1970	datetime
<code>datetime + timedelta 60</code>	One minute	Add a time period to a date or time. after midnight, January 1, 1970	datetime
<code>timedelta 3600</code>	One hour	Add two periods of time together	timedelta
<code>timedelta 86400 - timedelta</code>	Midnight	Calculate the difference between two time periods. January 2, 1970	timedelta
<code>timedelta / integer</code>	Divide a time period by a number.		timedelta
<code>timedelta * integer</code>	Multiply a time period by a number.		timedelta

## Resources

- [Python Documentation - Datetime module](#)
- [Python Documentation: Strftime/Strptime Codes](#)
- [strftime.org](#)
- [Wikipedia - Epoch time](#)

