

# Data Cleaning Basics



by Dataquest Labs, Inc. - All rights reserved © 2019

## Syntax

---

### READING A CSV IN WITH A SPECIFIC ENCODING

- Reading in a CSV file using Latin encoding:

```
laptops = pd.read_csv('laptops.csv', encoding='Latin-1')
```

- Reading in a CSV file using UTF-8:

```
laptops = pd.read_csv('laptops.csv', encoding='UTF-8')
```

- Reading in a CSV file using Windows-1251:

```
laptops = pd.read_csv('laptops.csv', encoding='Windows-1251')
```

---

### MODIFYING COLUMNS IN A DATAFRAME

- Renaming An Existing Column:

```
laptops.rename(columns={'MANufacturer' : 'manufacturer'}, inplace=True)
```

- Converting A String Column To Float:

```
laptops["screen_size"] = laptops["screen_size"].str.replace(' ','').astype(float)
```

- Converting A String Column To Integer:

```
laptops["ram"] = laptops["ram"].str.replace('GB','')  
laptops["ram"] = laptops["ram"].astype(int)
```

---

### STRING COLUMN OPERATIONS

- Extracting Values From The Beginning Of Strings:

```
laptops["gpu_manufacturer"] = (laptops["gpu"]  
                               .str.split(n=1,expand=True)  
                               .iloc[:,0]  
                               )
```

- Extracting Values From The End Of Strings:

```
laptops["cpu_speed_ghz"] = (laptops["cpu"]  
                            .str.replace("GHz", "")  
                            .str.rsplit(n=1, expand=True)  
                            .iloc[:, 1]  
                            .astype(float)  
                            )
```

- Reordering Columns And Exporting Cleaned Data:

```
specific_order = ['manufacturer', 'model_name', 'category', 'screen_size_inches',  
                  'screen', 'cpu', 'cpu_manufacturer', 'cpu_speed', 'ram_gb',  
                  'storage_1_type', 'storage_1_capacity_gb', 'storage_2_type',  
                  'storage_2_capacity_gb', 'gpu', 'gpu_manufacturer', 'os',  
                  'os_version', 'weight_kg', 'price_euros']  
  
reordered_df = laptops[specific_order]  
  
reordered_df.to_csv("laptops_cleaned.csv", index=False)
```

---

## FIXING VALUES

- Replacing Values Using A Mapping Dictionary:

```
mapping_dict = {  
    'Android': 'Android',  
    'Chrome OS': 'Chrome OS',  
    'Linux': 'Linux',  
    'Mac OS': 'macOS',  
    'No OS': 'No OS',  
    'Windows': 'Windows',  
    'macOS': 'macOS'  
}  
  
laptops["os"] = laptops["os"].map(mapping_dict)
```

- Dropping Missing Values:

```
laptops_no_null_rows = laptops.dropna(axis=0)
```

- Filling Missing Values:

```
laptops.loc[laptops["os"] == "No OS", "os_version"] = "No OS"
```

## Concepts

- Computers, at their lowest levels, can only understand binary. Encodings are systems for representing all other values in binary so a computer can work with them. The first standard was ASCII, which specified 128 characters. Other encodings popped up to support other languages, like Latin-1 and UTF-8. UTF-8 is the most common encoding and is very friendly to work with in Python 3.
- When converting text data to numeric data, we usually follow the following steps:
  - Explore the data in the column.
  - Identify patterns and special cases.
  - Remove non-digit characters.
  - Convert the column to a numeric dtype.
  - Rename column if required.

## Resources

- [Python Encodings](#)
- [Indexing and Selecting Data](#)



Takeaways by Dataquest Labs, Inc. - All rights reserved © 2019