



Geometry Representation

Introduction to Computer Graphics
Yu-Ting Wu

1

1


Define the 3D World

2

2

Description of the 3D World


- 3D coordinate systems



3

3

Points in 3D




4

4


Vector in 3D Space

- Use to represent direction (e.g., movement) in the 3D world



5



Triangles in 3D



6

Triangle Mesh


- We can define the geometry of an object by specifying the coordinates of the vertices and their adjacencies



7


Triangle Mesh (cont.)

- Using more triangles can lead to higher-quality meshes
 - However, takes more time to render



8

Scene Built with Triangle Mesh




9

9

Surface Normal


- A **surface normal** is a vector that is **perpendicular** to a surface at a particular position
- Represent the orientation of the face
- The length of a normal should be equal to **1**



10

10

Point, Triangle, and Surface Normal




11

11

Vertex Normal

- Compute by **averaging** the surface normals of the faces that contain that vertex
- Can achieve much **smooth** shading than using triangle normals



12

12

3D Model Format

- A model is often stored in a file
- Common file format includes
 - **Wavefront (*.obj)**
 - Polygon file format (*.ply)
 - **Filmbox (*.fbx)**
 - MAX (*.max)
 - Digital Asset Exchange File (*.dae)
 - STereoLithography (*.stl)

13


Example: Wavefront OBJ File Format

- cube.obj




14

Example: Wavefront OBJ File Format (cont.)







15

Example: Wavefront OBJ File Format (cont.)



16




Transformation

21

21

World Space and World Coordinate

- Objects are defined in **object space individually**
- When building a scene, each object is transformed to a **global** and **unique** space called **world space**
- The transform is called **world transform**




22

22

World Space and World Coordinate (cont.)

- Advantages for using "transformation"
 - **Reuse model**: design a model and use it in several scenes
 - **Memory saving**: store a 4x4 matrix instead of duplication of the entire models



23

23

Common Transformations

- Translation
- Scaling
- Rotation

24


24

2D Translation

- Given a point $p(x, y)$ and a translation offset $T(t_x, t_y)$, the new point $p'(x', y')$ after translation is $p' = p + T$

$$x' = x + t_x$$

$$y' = y + t_y$$



- Can be represented as Matrix-vector multiplication

$$\begin{bmatrix} x' \\ y' \\ 1 \end{bmatrix} = \begin{bmatrix} 1 & 0 & t_x \\ 0 & 1 & t_y \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$


25

2D Scaling

- Given a point $p(x, y)$ and a scaling factor $S(s_x, s_y)$, the new point $p'(x', y')$ after scaling is $p' = S p$

$$x' = x * s_x$$

$$y' = y * s_y$$




- Matrix-vector multiplication

$$\begin{bmatrix} x' \\ y' \\ 1 \end{bmatrix} = \begin{bmatrix} s_x & 0 & 0 \\ 0 & s_y & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$


26

2D Rotation


- Given a point $p(x, y)$, rotate it with respect to the **origin** by θ and get the new point $p'(x', y')$ after rotation



- First we define



$\theta > 0$: rotate
counterclockwise



$\theta < 0$: rotate
clockwise


27

2D Rotation (cont.)

- Given a point $p(x, y)$, rotate it with respect to the **origin** by θ and get the new point $p'(x', y')$ after rotation

$$x = r \cos(\phi) \quad y = r \sin(\phi)$$

$$x' = r \cos(\phi + \theta) \quad y' = r \sin(\phi + \theta)$$



$$x' = r \cos(\phi + \theta)$$

$$= r \cos(\phi) \cos(\theta) - r \sin(\phi) \sin(\theta)$$

$$= x \cos(\theta) - y \sin(\theta)$$

$$y' = r \sin(\phi + \theta)$$

$$= x \sin(\phi) \cos(\theta) + r \cos(\phi) \sin(\theta)$$


$$= y \cos(\theta) + x \sin(\theta)$$

28

2D Rotation (cont.)

- Given a point $p(x, y)$, rotate it with respect to the **origin** by θ and get the new point $p'(x', y')$ after rotation

$$\begin{aligned}x' &= r\cos(\phi + \theta) \\ &= x\cos(\theta) - y\sin(\theta) \\ y' &= r\sin(\phi + \theta) \\ &= y\cos(\theta) + x\sin(\theta)\end{aligned}$$



- Matrix-vector multiplication

$$\begin{bmatrix} x' \\ y' \\ 1 \end{bmatrix} = \begin{bmatrix} \cos(\theta) & -\sin(\theta) & 0 \\ \sin(\theta) & \cos(\theta) & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$

29

29

2D Translation, Scaling, and Rotation

- Translation $\begin{bmatrix} x' \\ y' \\ 1 \end{bmatrix} = \begin{bmatrix} 1 & 0 & t_x \\ 0 & 1 & t_y \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$
- Scaling $\begin{bmatrix} x' \\ y' \\ 1 \end{bmatrix} = \begin{bmatrix} s_x & 0 & 0 \\ 0 & s_y & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$
- Rotation $\begin{bmatrix} x' \\ y' \\ 1 \end{bmatrix} = \begin{bmatrix} \cos(\theta) & -\sin(\theta) & 0 \\ \sin(\theta) & \cos(\theta) & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$
- Using a 3x3 matrix allows us to perform all transformations using matrix/vector multiplications
 - We can also **pre-multiply (concatenate)** all the matrices

30

30

Homogeneous Coordinate

- We call the $(x, y, 1)$ representation the **homogeneous coordinate** for (x, y)

$$\begin{bmatrix} x' \\ y' \\ w \end{bmatrix} = \begin{bmatrix} a & b & c \\ d & e & f \\ g & h & i \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$

- If w is not equal to 1, to make the transformed coordinate also homogeneous, we need to divide the x and y components by w


$$x' = x'/w \quad y' = y'/w \quad w = 1$$

31

31

Revisit 2D Scaling

- The standard scaling matrix will only anchor at $(0, 0)$




- What if we want the object to be scaled w.r.t its center?

32

32

Revisit 2D Scaling (cont.)

- Scaling about an arbitrary pivot point $Q(q_x, q_y)$
 - Translate the objects so that Q will coincide with the origin: $T(-q_x, -q_y)$
 - Scale the object: $S(s_x, s_y)$
 - Translate the object back: $T(q_x, q_y)$
- The final scaling matrix can be written as $T(q)S(s)T(-q)$ Concatenation of matrices




33

33

Revisit 2D Rotation

- The standard rotation matrix is used to rotate about the origin (0, 0)




- What if we want the object to be rotated w.r.t a specific pivot?

34

34

Revisit 2D Rotation (cont.)

- Rotate about an arbitrary pivot point $Q(q_x, q_y)$ by θ
 - Translate the objects so that Q will coincide with the origin: $T(-q_x, -q_y)$
 - Rotate the object: $R(\theta)$
 - Translate the object back: $T(q_x, q_y)$
- The final rotation matrix can be written as $T(q)R(\theta)T(-q)$



35

35

Translation (3D) and Scaling (3D)

- A 3D transformation is represented as a **4x4 matrix**, with **homogeneous coordinate**

$$\begin{array}{ll}
 \text{translation} & \begin{bmatrix} 1 & 0 & t_x \\ 0 & 1 & t_y \\ 0 & 0 & 1 \end{bmatrix} \rightarrow \begin{bmatrix} 1 & 0 & 0 & t_x \\ 0 & 1 & 0 & t_y \\ 0 & 0 & 1 & t_z \\ 0 & 0 & 0 & 1 \end{bmatrix} \\
 \text{scaling} & \begin{bmatrix} s_x & 0 & 0 \\ 0 & s_y & 0 \\ 0 & 0 & 1 \end{bmatrix} \rightarrow \begin{bmatrix} s_x & 0 & 0 & 0 \\ 0 & s_y & 0 & 0 \\ 0 & 0 & s_z & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}
 \end{array}$$

2D 3D

36

36

Rotation (3D)

	rotation w.r.t x-axis	$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & \cos\theta & -\sin\theta & 0 \\ 0 & \sin\theta & \cos\theta & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$
$\begin{bmatrix} \cos(\theta) & -\sin(\theta) & 0 \\ \sin(\theta) & \cos(\theta) & 0 \\ 0 & 0 & 1 \end{bmatrix}$	rotation w.r.t y-axis	$\begin{bmatrix} \cos\theta & 0 & \sin\theta & 0 \\ 0 & 1 & 0 & 0 \\ -\sin\theta & 0 & \cos\theta & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$
	rotation w.r.t z-axis	$\begin{bmatrix} \cos\theta & -\sin\theta & 0 & 0 \\ \sin\theta & \cos\theta & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$

2D 3D

37

37

3D Transformation


- Practice
 - Scale w.r.t a given pivot point
 - Rotate w.r.t a given pivot point

38

38

Spoiler

- There are other spaces
- We will introduce camera space, clip space, and NDC in the next slides



39

39

Any Questions?

40

40