



Operating Systems

Introduction to Computer

Yu-Ting Wu

(with some slides borrowed from Prof. Tian-Li Yu)

1

1

Outline

- What is an operating system
- The history of operating systems
- Operating system architecture
- Coordinating the machine's activities
- Handling competition among processes
- Security

2

2

Outline

- What is an operating system
- The history of operating systems
- Operating system architecture
- Coordinating the machine's activities
- Handling competition among processes
- Security

3

3

What is an Operating System


- An operating system (OS) is a **software program** that acts as an **intermediary** between a user and the computer hardware
 - Execute user programs
 - Make the computer system convenient to use
 - Such that users can focus on their problems
 - Use the computer hardware in an efficient manner

4

4

What is an Operating System (cont.)

- An operating system (OS) can be considered as a government or environment provider



5

Features of Operating Systems

- User view: varies by the types of the computers



6

Features of Operating Systems (cont.)

- System view: a resource allocator and control program

- Resource allocator**

- CPU time
- Memory space
- File storage
- I/O devices

- Control program**

- Control execution of user programs
- Prevent errors and misuse

7

Examples of Operating Systems

- | | |
|-----------|--------------------|
| • Windows | • Apple iOS |
| • UNIX | • Windows phone |
| • Mac OS | • BlackBerry OS |
| • Solaris | • Nokia Symbian OS |
| • Linux | • Google Android |

8

Free and Open-Source OSes

- OS with available source
 - Otherwise: closed-source OS. E.g., MS Windows, iOS
- Examples: GNU/Linux, BSD, UNIX, etc.
- Arguably issues on bugs, security, support

9

9

Outline

- What is an operating system
- The history of operating systems
- Operating system architecture
- Coordinating the machine's activities
- Handling competition among processes
- Security

10

10

History of Operating Systems


- Batch processing (job queue)
- Interactive and (real-time) processing
- Multi-tasking and time-sharing and
- Multiprocessor machines
- Embedded Systems (specific devices)

11

11

Batching Process

- Each program is called a "job"
 - Feed by computer operators
- First-in, first-out (FIFO)



12

12

Batching Process (cont.)




Punch card operator

13

13

Interactive Processing

- OS with remote terminals




14

14

Interactive Processing (cont.)

- Terminals



15

15

Real-Time Processing

- Real-time OS has well-defined fixed time constraints
 - **Hard real-time system**
 - Processing **must** be done within the constraint
 - Correct operation only if constraints met
 - **Soft real-time system**
 - Missing a timing is serious but does not necessarily result in failure (ex: multimedia)
- Real-time means **on time!** (not fast)

16

16

Multi-Tasking

- Before multi-tasking, one job at a time
- Example: MS DOS



17

17

Multi-Tasking (cont.)


- A single user cannot always keep CPU and I/O devices busy
 - E.g., humans and disk I/O are too slow compared to CPU and memory
 - Put multiple programs in memory
 - OS organizes jobs so that the CPU always has one to execute
 - When a job has to wait (e.g., for I/O), OS **switches to another job**
- ➔ Increase CPU utilization
- ➔ Need job and CPU scheduling

18

18

Multi-Tasking with Time-Sharing

- CPU switches jobs frequently so that users can interact with each job while it is running
 - Only **one** (per core) task is being executed at any given time
 - A logical extension of multi-tasking
 - **Interactivity!**
 - Response time should be less than 1 sec.




19

19

Context Switch

- Kernel saves the state of the old process and loads the saved state for the new process
- Context switch time is **purely overhead**
- Switch time (about 1 ~ 1000 ms) depends on hardware




20


20

Multiprocessor

- More than one processor in close communication sharing bus, memory, and peripheral devices



- The recent trend: from a fast single processor to lots of processors
 - **Multiple cores** over a single chip



21

21

Outline

- What is an operating system
- The history of operating systems
- Operating system architecture
- Coordinating the machine's activities
- Handling competition among processes
- Security

22

22


Software Classification

- **Application software**
 - Performs specific tasks for users (productivity, games, software development)
- **System software**
 - Provides infrastructure for application software
 - Consists of operating system and utility software

23

23

Software Classification (cont.)



24

24

Operating System Components

• User interface:


• Communicates with users

- Text-based (Shell)
- Graphical user interface (GUI)

• Kernel:

• Performs basic required functions


- File manager
- Device drivers
- Memory manager
- Scheduler
- Dispatcher



25

25

Operating System Components (cont.)



26

26

User Interface: Shell


```
1. root@r6181-d5-us01:~ (ssh)
x root@r6181-d5-us01:~ (ssh) x ssh x root@r6181-d5-us01:~ (ssh)
Last login: Thu Jul 14 08:47:01 on tty002
[MacPro:~ pab$ ssh root@r6181-d5-us01]
root@r6181-d5-us01's password:
Last login: Thu Jul 14 06:01:11 2016 from 172.16.16.162
[root@r6181-d5-us01:~]# uptime
06:57:48 up 16 days, 10:52, 3 users, load average: 129.52, 80.33, 56.55
[root@r6181-d5-us01:~]# df -kh
Filesystem      Size  Used Avail Use% Mounted on
/dev/mapper/vg_ks-lv_root
127G  520K 127G   1% /dev/shm
477M  71M 381M  16% /boot
1.0T  480K 545G   0% /dssd_xfs
tcp://192.168.150.1:3334/orangefs
12T  5.7T  6.4T  47% /mnt/orangefs
/dev/gpfs-test
22T  1.1T 22T   5% /mnt/gpfs
[root@r6181-d5-us01:~]# ps aux | sort -nrk 3,3 | head -n 5
root  97653 11.2  6.6 42665344 17520636 ?   S-dl  Jul13 166:23 /usr/lpp/mmfs/bin/mmfsd
root  69849  6.6  0.0  0  0 ?   S   Jul12 181:54 [vpthread-1-1]
root  69850  6.4  0.0  0  0 ?   S   Jul12 177:42 [vpthread-1-2]
root  3829  3.0  0.0  0  0 ?   S   Jun27 730:04 [rp_thread 7:0]
root  3826  3.0  0.0  0  0 ?   S   Jun27 728:00 [rp_thread 6:0]
[root@r6181-d5-us01:~]# ls -l /usr/lpp/mmfs/bin/mmfsd
-r-x----- 1 root root 28667161 Jun  3 2015 /usr/lpp/mmfs/bin/mmfsd
[root@r6181-d5-us01:~]#
```

Bourne Shell (default shell of UNIX ver. 7)

27

27

User Interface: GUI



Mac OS X GUI

28

28

29

30


31

31

32

Kernel: Memory Manager

- Allocating space in the main memory
- Contiguous allocation: fixed-partition allocation**
 - Each process loads into one partition of fixed-size
 - Degree of multi-programming** is bounded by the number of partitions
 - Result in **internal fragmentation**
 - Memory that is internal to a partition but is not being used




33

33

Kernel: Memory Manager (cont.)

- Allocating space in the main memory
- Contiguous allocation: variable-size partition**




- When a process arrives, it is allocated a hole **large enough** to accommodate it
- Result in **external fragmentation**

34

34

Kernel: Memory Manager (cont.)

- Non-contiguous allocation: paging**



35

35

Kernel: Memory Manager (cont.)

- Paging**
 - Divide **physical memory** into fixed-size blocks called **frames**
 - Divide **logical address** space into blocks of the **same size** called **pages**
 - To run a program of n pages, need to find n free frames and load the program
 - Must keep track of free frames**
 - Set up a **page table** to translate logical to physical addresses


36

36

Kernel: Memory Manager

• Virtual memory

- A process can be swapped out of memory to a **backing store**, and later brought back into memory for continuous execution



37

37

Kernel: Memory Manager

• Virtual memory


- To run an **extremely large process**
 - Logical address space can be much larger than physical address space
- To increase **CPU/resource utilization**
 - Higher degree of multi-tasking
 - Avoid putting rarely used data and codes in memory
- To **launch** programs **faster**
 - Less I/O would be needed to load or swap

38

38

Bootstrapping / Booting

- **Boot loader**: program in ROM (read-only memory)
 - Run by the CPU when power is turned on
 - Transfers operating system from mass storage to main memory
 - Executes jump to the operating system



39

39

Bootstrapping / Booting (cont.)

BOOTSTRAPS



40

40

Outline

- What is an operating system
- The history of operating systems
- Operating system architecture
- Coordinating the machine's activities
- Handling competition among processes
- Security

41

Coordinating the Machine's Activities

- An operating system coordinates the execution of application software, utility software, and units within the operating system itself


Processes

名稱	PID	狀態	使用者名稱	CPU	記憶體 (使用中的私人工作集)	UAC 權限
AsusLinkHear.exe	3628	執行中	SYSTEM	00	784 K	不允許
AsusLinkRemote.exe	5016	執行中	SYSTEM	00	1,052 K	不允許
AsusOptimization.exe	4552	執行中	SYSTEM	00	696 K	不允許
AsusOptimizationStartupTask.exe	8876	執行中	user	00	536 K	已停用
AsusSoftwareManager.exe	5100	執行中	SYSTEM	00	1,776 K	不允許
AsusSoftwareManagerAgent.exe	4592	執行中	user	00	3,064 K	不允許
AsusSwitch.exe	5092	執行中	SYSTEM	00	492 K	不允許
AsusSystemAnalysis.exe	7644	執行中	SYSTEM	00	1,320 K	不允許
AsusSystemDiagnosis.exe	5116	執行中	SYSTEM	00	232 K	不允許
asus_framework.exe	8000	執行中	user	00	14,152 K	不允許
asus_framework.exe	12444	執行中	user	00	584 K	不允許
asus_framework.exe	14756	執行中	user	00	20,512 K	不允許
asusFramework.exe	4008	執行中	SYSTEM	00	92 K	不允許
audiodg.exe	4536	執行中	LOCAL SE...	00	25,212 K	不允許
Canva.exe	16180	執行中	user	00	304 K	已停用
Canva.exe	2032	執行中	user	00	96 K	已停用
chrome.exe	16312	執行中	user	00	196,584 K	已停用
chrome.exe	15868	執行中	user	00	632 K	已停用

42

The Concept of a Process


- **Process**
 - The activity of executing a program
- **Process state**
 - Current status of the activity
 - Program counter
 - General purpose registers
 - Related portion of main memory
 - Managed by a process table (**Process Control Block, PCB**)
 - Save/load during a **context switch**







43

Process Administration

- **Scheduler**
 - Maintain the process table
 - Introduce new processes
 - Remove completed processes
 - Decide whether a process is ready or waiting
- **Dispatcher**
 - Really execute the program
 - Control the allocation of time slices to the processes
 - Switch processes (**context switch**)



44



45

46

47

48

Outline

- What is an operating system
- The history of operating systems
- Operating system architecture
- Coordinating the machine's activities
- Handling competition among processes
- Security

49

49

Data Consistency

- **Concurrent access** to **shared data** may result in **data inconsistency**
- Maintaining data consistency requires a mechanism to ensure the **orderly execution** of cooperating processes

50

50

Example: Consumer & Producer Problem

- **Producer** process produces information that is consumed by a **Consumer** process, both operating on a fixed-size buffer

```

/* Producer */
while (true) {
    // produce an item in next produced.
    while (counter == BUFFER_SIZE);
    // do nothing.
    buffer[in] = next_produced;
    in = (in + 1) % BUFFER_SIZE;
    counter++;
}

/* Consumer */
while (true) {
    while (counter == 0);
    // do nothing.
    next_consumed = buffer[out];
    out = (out + 1) % BUFFER_SIZE;
    counter--;
    // consume the item in next consumed.
}

```

51

51

Concurrent Operations on Counter

- The statement "counter++" may be implemented in machine language as

```

move R1, counter
add R1, 1
move counter, R1

```

- The statement "counter--" may be implemented as

```

move R2, counter
sub R2, 1
move counter, R2

```

52

52

Instruction Interleaving

- Assume the counter is initially 5. One interleaving of statement is

```

producer: move R1, counter    → R1 = 5
producer: add R1, 1           → R1 = 6
context switch
consumer: move R2, counter    → R2 = 5
consumer: sub R2, 1           → R2 = 4
context switch
producer: move counter, R1    → counter = 6
context switch
consumer: move counter, R2    → counter = 4

```

53

Handling Competition among Processes

• Critical Region

- A **protocol** for processes to cooperate
- A group of instructions that should be executed by only one process at a time

• Mutual exclusion

- Requirement that **only one** process at a time be allowed to execute a critical region

```

do {
    entry section → get entry permission
    critical section → modified shared data
    exit section → release entry permission
    remainder section
} while (1);

```

54

53

54

Semaphore

- A tool to generalize the synchronization problem
 - Can be achieved by hardware or software solutions
- Hardware support: **atomic instructions** (uninterruptible)

```

bool TestAndSet (bool &lock) {
    bool value = lock;
    lock = true;
    return value;
}
// execute atomically:
// return the value of "lock" and set "lock" to true

shared data: bool lock; // initially lock = false
// P0
do {
    while (TestAndSet (lock));
    critical section
    lock = false;
    remainder section
} while (1);

// P1
do {
    while (TestAndSet (lock));
    critical section
    lock = false;
    remainder section
} while (1);

```

55

Deadlock

- Processes block each other from continuing because each is waiting for a resource that is allocated to another
- Example
 - 2 processes
 - P₁ holds resource B and waits for resource A
 - P₂ holds resource A and waits for resource B

56

55

56

Deadlock (cont.)


- Conditions required for deadlock
 - Competition for non-sharable resources (**mutual exclusion**)
 - Only one process at a time can use a resource
 - Resources requested on a partial basis (**hold and wait**)
 - A process holding some resources and is waiting for another resource
 - An allocated resource can not be forcibly retrieved (**no preemption**)
 - A resource can be only released by a process **voluntarily**
 - **Circular wait**
 - There exists a set $\{P_0, P_1, \dots, P_n\}$ of waiting processes such that $P_0 \rightarrow P_1 \rightarrow P_2 \rightarrow \dots \rightarrow P_n \rightarrow P_0$

57

57

Deadlock (cont.)

- Dining-philosophers problem



58

58

Handling Deadlocks

- Ensure the system will **never** enter a deadlock state
 - **Deadlock prevention**: ensure that at least one of the **four necessary conditions** cannot hold
 - **Deadlock avoidance**: **dynamically** examines the resource-allocation state before allocation
- Allow to **enter a deadlock state** and then **recover**
 - **Deadlock detection**
 - **Deadlock recovery**
- **Ignore the problem** and pretend that deadlocks never occur in the system
 - **Used by most operating systems, including UNIX**

59

59

Deadlock v.s. Starvation

- **Starvation**
 - Process cannot get the resources needed for a long time because the resources are being allocated to other processes
- **Aging**
 - Add an aging factor to the priority of each request

60

60

Outline

- What is an operating system
- The history of operating systems
- Operating system architecture
- Coordinating the machine's activities
- Handling competition among processes
- Security

61

61

Security

- **Goals**
 - Prevent error and misuse
 - Resources are only allowed to be accessed by authorized processes
- **Attacks from outside**
 - Problems
 - Insecure passwords and **bad habits**
 - Sniffing software
 - Virus, worms, Trojan horses
 - Counter measures
 - Auditing software (record and analyze activities)
 - Antivirus software

62

62

Security (cont.)

- **Attacks from within**
 - Problem
 - Process that gains access to memory outside its designated area
 - Counter measures
 - Control process activities via **privilege levels** and **privileged instructions**

63

63

Any Questions?

64

64