



Geometry Representation

Introduction to Computer Graphics
Yu-Ting Wu

1

1


Define the 3D World

2

2

Description of the 3D World


- 3D coordinate systems



3

3

Points in 3D




4

4


Vector in 3D Space

- Use to represent direction (e.g., movement) in the 3D world



5



Triangles in 3D



6

Triangle Mesh


- We can define the geometry of an object by specifying the coordinates of the vertices and their adjacencies



7

Triangle Mesh (cont.)

- Using more triangles can lead to higher-quality meshes
 - However, takes more time to render



8


Scene Built with Triangle Mesh



9


Surface Normal

- A **surface normal** is a vector that is **perpendicular** to a surface at a particular position
- Represent the orientation of the face



10


Point, Triangle, and Surface Normal



11

Vertex Normal

- Compute by **averaging** the surface normals of the faces that contain that vertex
- Can achieve much **smooth** shading than using triangle normals



12

3D Model Format

- A model is often stored in a file
- Common file format includes
 - Wavefront (*.obj)
 - Polygon file format (*.ply)
 - Filmbox (*.fbx)
 - MAX (*.max)
 - Digital Asset Exchange File (*.dae)
 - STereoLithography (*.stl)

13


Example: Wavefront OBJ File Format

- cube.obj




14

Example: Wavefront OBJ File Format (cont.)






15

Example: Wavefront OBJ File Format (cont.)




16



World Space and World Coordinate

- Objects are defined in **object space individually**
- When building a scene, each object is transformed to a **global** and **unique** space called **world space**
- The transform is called **world transform**



21

21

World Space and World Coordinate (cont.)

- Advantages for using "transformation"
 - **Reuse model**: design a model and use it in several scenes
 - **Memory saving**: store a 4x4 matrix instead of duplication of the entire models



22

22

Common Transformations

- Translation
- Scaling
- Rotation


23

23

2D Translation

- Given a point $p(x, y)$ and a translation offset $T(t_x, t_y)$, the new point $p'(x', y')$ after translation is $p' = p + T$

$$\begin{aligned} x' &= x + t_x \\ y' &= y + t_y \end{aligned}$$



- **Can be represented as** Matrix-vector multiplication

$$\begin{bmatrix} x' \\ y' \\ 1 \end{bmatrix} = \begin{bmatrix} 1 & 0 & t_x \\ 0 & 1 & t_y \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$

24

24

2D Scaling


- Given a point $p(x, y)$ and a scaling factor $S(s_x, s_y)$, the new point $p'(x', y')$ after scaling is $p' = S p$

$$x' = x * s_x$$

$$y' = y * s_y$$

- Matrix-vector multiplication

$$\begin{bmatrix} x' \\ y' \\ 1 \end{bmatrix} = \begin{bmatrix} s_x & 0 & 0 \\ 0 & s_y & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$




25


25

2D Rotation


- Given a point $p(x, y)$, rotate it with respect to the **origin** by θ and get the new point $p'(x', y')$ after rotation



- First we define



$\theta > 0$: rotate
counterclockwise



$\theta < 0$: rotate
clockwise

26

26

2D Rotation (cont.)

- Given a point $p(x, y)$, rotate it with respect to the **origin** by θ and get the new point $p'(x', y')$ after rotation

$$x = r \cos(\phi) \quad y = r \sin(\phi)$$

$$x' = r \cos(\phi + \theta) \quad y' = r \sin(\phi + \theta)$$

$$x' = r \cos(\phi + \theta)$$


$$= r \cos(\phi) \cos(\theta) - r \sin(\phi) \sin(\theta)$$

$$= x \cos(\theta) - y \sin(\theta)$$

$$y' = r \sin(\phi + \theta)$$

$$= x \sin(\phi) \cos(\theta) + r \cos(\phi) \sin(\theta)$$

$$= y \cos(\theta) + x \sin(\theta)$$



27

27

2D Rotation (cont.)


- Given a point $p(x, y)$, rotate it with respect to the **origin** by θ and get the new point $p'(x', y')$ after rotation

$$x' = r \cos(\phi + \theta)$$

$$= x \cos(\theta) - y \sin(\theta)$$

$$y' = r \sin(\phi + \theta)$$

$$= y \cos(\theta) + x \sin(\theta)$$



- Matrix-vector multiplication

$$\begin{bmatrix} x' \\ y' \\ 1 \end{bmatrix} = \begin{bmatrix} \cos(\theta) & -\sin(\theta) & 0 \\ \sin(\theta) & \cos(\theta) & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$

28

28

2D Translation, Scaling, and Rotation


- Translation $\begin{bmatrix} x' \\ y' \\ 1 \end{bmatrix} = \begin{bmatrix} 1 & 0 & t_x \\ 0 & 1 & t_y \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$
- Scaling $\begin{bmatrix} x' \\ y' \\ 1 \end{bmatrix} = \begin{bmatrix} s_x & 0 & 0 \\ 0 & s_y & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$
- Rotation $\begin{bmatrix} x' \\ y' \\ 1 \end{bmatrix} = \begin{bmatrix} \cos(\theta) & -\sin(\theta) & 0 \\ \sin(\theta) & \cos(\theta) & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$
- Using a 3x3 matrix allows us to perform all transformations using matrix/vector multiplications
 - We can also **pre-multiply (concatenate)** all the matrices
- We call the $(x, y, 1)$ representation the **homogeneous coordinate** for (x, y)

29

29

Revisit 2D Scaling

- The standard scaling matrix will only anchor at $(0, 0)$




- What if we want the object to be scaled w.r.t its center?

30

30

Revisit 2D Scaling (cont.)

- Scaling about an arbitrary pivot point $Q(q_x, q_y)$
 - Translate the objects so that Q will coincide with the origin: $T(-q_x, -q_y)$
 - Scale the object: $S(s_x, s_y)$
 - Translate the object back: $T(q_x, q_y)$
- The final scaling matrix can be written as $T(q)S(s)T(-q)$ Concatenation of matrices




31

31

Revisit 2D Rotation

- The standard rotation matrix is used to rotate about the origin $(0, 0)$



- What if we want the object to be rotated w.r.t a specific pivot?

32

32

Revisit 2D Rotation (cont.)

- Rotate about an arbitrary pivot point $Q(q_x, q_y)$ by θ
 - Translate the objects so that Q will coincide with the origin: $T(-q_x, -q_y)$
 - Rotate the object: $R(\theta)$
 - Translate the object back: $T(q_x, q_y)$
- The final rotation matrix can be written as $T(q)R(\theta)T(-q)$



33

33

Translation (3D) and Scaling (3D)

- A 3D transformation is represented as a **4x4 matrix**, with **homogeneous coordinate**

$$\begin{array}{lcl} \text{translation} & \begin{bmatrix} 1 & 0 & t_x \\ 0 & 1 & t_y \\ 0 & 0 & 1 \end{bmatrix} & \rightarrow \begin{bmatrix} 1 & 0 & 0 & t_x \\ 0 & 1 & 0 & t_y \\ 0 & 0 & 1 & t_z \\ 0 & 0 & 0 & 1 \end{bmatrix} \\ \\ \text{scaling} & \begin{bmatrix} s_x & 0 & 0 \\ 0 & s_y & 0 \\ 0 & 0 & 1 \end{bmatrix} & \rightarrow \begin{bmatrix} s_x & 0 & 0 & 0 \\ 0 & s_y & 0 & 0 \\ 0 & 0 & s_z & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \\ & \text{2D} & \text{3D} \end{array}$$

34

34

Rotation (3D)

$$\begin{array}{lcl} & \text{rotation w.r.t} & \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & \cos\theta & -\sin\theta & 0 \\ 0 & \sin\theta & \cos\theta & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \\ & \text{x-axis} & \\ \begin{bmatrix} \cos(\theta) & -\sin(\theta) & 0 \\ \sin(\theta) & \cos(\theta) & 0 \\ 0 & 0 & 1 \end{bmatrix} & \text{rotation w.r.t} & \begin{bmatrix} \cos\theta & 0 & \sin\theta & 0 \\ 0 & 1 & 0 & 0 \\ -\sin\theta & 0 & \cos\theta & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \\ & \text{y-axis} & \\ & \text{rotation w.r.t} & \begin{bmatrix} \cos\theta & -\sin\theta & 0 & 0 \\ \sin\theta & \cos\theta & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix} \\ & \text{z-axis} & \end{array}$$

2D 3D

35

35

3D Transformation


- Practice
 - Scale w.r.t a given pivot point
 - Rotate w.r.t a given pivot point

36

36

Spoiler

- There are other spaces
- We will introduce camera space, clip space, and NDC in the next slides



37

37

Any Questions?

38

38